

---

# Fermipy Documentation

*Release 0.19.0+dirty*

**Matthew Wood**

**Mar 25, 2020**



---

## Contents

---

<b>1</b>	<b>Introduction</b>	<b>1</b>
1.1	Getting Help . . . . .	1
1.2	Acknowledging Fermipy . . . . .	1
1.3	Documentation Contents . . . . .	2
1.3.1	Installation . . . . .	2
1.3.2	Quickstart Guide . . . . .	7
1.3.3	Configuration . . . . .	13
1.3.4	Output File . . . . .	25
1.3.5	ROI Optimization and Fitting . . . . .	28
1.3.6	Customizing the Model . . . . .	30
1.3.7	Developer Notes . . . . .	33
1.3.8	Advanced Analysis Methods . . . . .	33
1.3.9	Validation Tools . . . . .	58
1.3.10	fermipy package . . . . .	58
1.3.11	fermipy.jobs subpackage . . . . .	114
1.3.12	fermipy.diffuse subpackage . . . . .	154
1.3.13	Changelog . . . . .	200
<b>2</b>	<b>Indices and tables</b>	<b>207</b>
	<b>Python Module Index</b>	<b>209</b>
	<b>Index</b>	<b>211</b>



# CHAPTER 1

---

## Introduction

---

This is the Fermipy documentation page. Fermipy is a python package that facilitates analysis of data from the Large Area Telescope (LAT) with the [Fermi Science Tools](#). For more information about the Fermi mission and the LAT instrument please refer to the [Fermi Science Support Center](#).

The Fermipy package is built on the pyLikelihood interface of the Fermi Science Tools and provides a set of high-level tools for performing common analysis tasks:

- Data and model preparation with the gt-tools (gtselect, gtmktime, etc.).
- Extracting a spectral energy distribution (SED) of a source.
- Generating TS and residual maps for a region of interest.
- Finding new source candidates.
- Localizing a source or fitting its spatial extension.

Fermipy uses a configuration-file driven workflow in which the analysis parameters (data selection, IRFs, and ROI model) are defined in a YAML configuration file. Analysis is executed through a python script that calls the methods of *GTAnalysis* to perform different analysis operations.

For instructions on installing Fermipy see the [Installation](#) page. For a short introduction to using Fermipy see the [Quickstart Guide](#).

## 1.1 Getting Help

If you have questions about using Fermipy please open a [GitHub Issue](#) or email the [Fermipy developers](#).

## 1.2 Acknowledging Fermipy

To acknowledge Fermipy in a publication please cite [Wood et al. 2017](#).

## 1.3 Documentation Contents

### 1.3.1 Installation

---

**Note:** From version 0.19.0 fermipy is only compatible with fermitools version 1.2.23 or later. If you are using an earlier version, you will need to download and install the latest version from the [FSSC](#).

---

These instructions assume that you already have a local installation of the fermitools. For more information about installing and setting up the fermitools see *Installing the fermitools*. For we currently recommend following the *Installing Anaconda Python* instructions. However the *Installing with pip* instructions should also work. The *Installing with Docker* instructions can be used to install the fermitools on OSX and Linux machines that are new enough to support Docker. To install the development version of Fermipy follow the *Installing From Source* instructions.

#### The condainstall.sh script

The recommended way to install fermipy and the fermitools is by using the condainstall.sh script included in the package. This script properly handles a rather complicated set of interdependencies between fermipy, the fermitools and packages they depend on.

```
$ curl -OL https://raw.githubusercontent.com/fermiPy/fermipy/master/condainstall.sh
$ export CONDA_PATH=<path to your conda installation>
$ source condainstall.sh
```

This script optionally uses a number of other environmental variables to control how the installation is set up. The important ones and their default values are listed below. Unless you want to override some of these values you can leave them as is:

```
$ export PYTHON_VERSION=2.7
$ export CONDA_DEPS="scipy matplotlib pyyaml numpy astropy gammapy healpy"
$ # This should point at your conda installation, or at the place you would like to
  ↪install conda
$ export CONDA_PATH="$HOME/miniconda"
$ # This is the name that will be given to the conda environment created for fermipy
$ export FERMIPY_CONDA_ENV="fermipy"
$ # This is the command used to install the fermitools.
$ # Set it to an empty string if you do not want to install the fermitools
$ # of if you have already installed them.
$ export ST_INSTALL="conda install -y --name $FERMIPY_CONDA_ENV $FERMI_CONDA_CHANNELS_
  ↪-c $CONDA_CHANNELS fermitools"
$ # This is the command used install fermipy.
$ # If you want to install for source or use a different version of
$ # fermipy you should change this
$ export INSTALL_CMD="conda install -y --name $FERMIPY_CONDA_ENV -c $CONDA_CHANNELS_
  ↪fermipy"
```

#### Installing the fermitools

---

**Note:** If you used the condainstall.sh script, it should have already installed the fermitools. This example is if you want to install the fermitools without using that script.

---

The fermitools are a prerequisite for fermipy. The following example illustrates how the fermitools in an existing anaconda installation.

```
$ conda create --name fermipy -y python=$PYTHON_VERSION
$ conda activate fermipy
$ conda install -y --name fermipy -c conda-forge/label/cf201901 -c
fermi -c conda-forge fermitools"
```

More information about installing the fermitools is available on the [FSSC software page](#). More information about setting up an anaconda installation is included in the [Installing Anaconda Python](#) instructions below.

## The diffuse emission models

Starting with fermipy version 0.19.0, we are using the diffuse and isotropic emission model from the fermitools-data package rather than including them in fermipy. However, for working on older analyses created with earlier version of fermipy you can set the FERMI\_DIFFUSE\_DIR environmental variable to point at a directory that include the version of the models that you wish to use.

## Installing with pip

These instructions cover installation with the pip package management tool. This will install fermipy and its dependencies into the conda distribution that contains the fermitools. We will assume that you have installed the fermitools in a conda environment called “fermi”. First verify that you’ve installed from the fermitools

```
$ conda activate fermi
$ which girfs
```

If this doesn’t point to the girfs in your fermitools install then the fermitools are not properly set up.

Until the fermitools moves to python 3, we recommend making sure that this environment includes python and pip

```
$ conda activate fermi
$ which girfs
$ which pip
```

Both the girfs and pip should point to the versions installed in the fermi environment.

Because of some issues with the dependencies in fermitools and gammapy we recommend installing the dependencies using conda.

```
$ conda install -n fermi -y -c conda-forge scipy matplotlib pyyaml numpy astropy_
↳gammapy healpy
$ pip install fermipy
```

To run the ipython notebook examples you will also need to install jupyter notebook:

```
$ pip install jupyter
```

Finally, check that fermipy imports:

```
$ python
Python 2.7.8 (default, Aug 20 2015, 11:36:15)
[GCC 4.2.1 Compatible Apple LLVM 6.0 (clang-600.0.56)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>> from fermipy.gtanalysis import GTAnalysis
>>> help(GTAnalysis)
```

## Installing Anaconda Python

These instructions cover how to use fermipy with a new or existing anaconda python installation.

If you do not have an anaconda installation, the `condainstall.sh` script can be used to create a minimal anaconda installation from scratch. First download and source the `condainstall.sh` script from the fermipy repository:

```
$ curl -OL https://raw.githubusercontent.com/fermiPy/fermipy/master/condainstall.sh
$ source condainstall.sh
```

If you do not already have anaconda python installed on your system this script will create a new installation under `$HOME/miniconda`. If you already have anaconda installed and the `conda` command is in your path the script will use your existing installation.

## Installing with Docker

---

**Note:** This method for installing the STs is currently experimental and has not been fully tested on all operating systems. If you encounter issues please try either the pip- or anaconda-based installation instructions.

---

Docker is a virtualization tool that can be used to deploy software in portable containers that can be run on any operating system that supports Docker. Before following these instruction you should first install docker on your machine following the [installation instructions](#) for your operating system. Docker is currently supported on the following operating systems:

- macOS 10.10.3 Yosemite or later
- Ubuntu Precise 12.04 or later
- Debian 8.0 or later
- RHEL7 or later
- Windows 10 or later

Note that Docker is not supported by RHEL6 or its variants (CentOS6, Scientific Linux 6).

These instructions describe how to create a docker-based ST installation that comes preinstalled with anaconda python and fermipy. The installation is fully contained in a docker image that is roughly 2GB in size. To see a list of the available images go to the [fermipy Docker Hub page](#). Images are tagged with the release version of the STs that was used to build the image (e.g. 11-05-00). The *latest* tag points to the image for the most recent ST release.

To install the *latest* image first download the image file:

```
$ docker pull fermipy/fermipy
```

Now switch to the directory where you plan to run your analysis and execute the following command to launch a docker container instance:

```
$ docker run -it --rm -p 8888:8888 -v $PWD:/workdir -w /workdir fermipy/fermipy
```

This will start an ipython notebook server that will be attached to port 8888. Once you start the server it will print a URL that you can use to connect to it with the web browser on your host machine. The `-v $PWD:/workdir` argument mounts the current directory to the working area of the container. Additional directories may be mounted by adding more volume arguments `-v` with host and container paths separated by a colon.

The same docker image may be used to launch python, ipython, or a bash shell by passing the command as an argument to `docker run`:



```
$ docker run -it --rm -v $PWD:/workdir -w /workdir fermipy/fermipy ipython
$ docker run -it --rm -v $PWD:/workdir -w /workdir fermipy/fermipy python
$ docker run -it --rm -v $PWD:/workdir -w /workdir fermipy/fermipy /bin/bash
```

By default interactive graphics will not be enabled. The following commands can be used to enable X11 forwarding for interactive graphics on an OSX machine. This requires you to have installed XQuartz 2.7.10 or later. First enable remote connections by default and start the X server:

```
$ defaults write org.macosforge.xquartz.X11 nolisten_tcp -boolean false
$ open -a XQuartz
```

Now check that the X server is running and listening on port 6000:

```
$ lsof -i :6000
```

If you don't see X11 listening on port 6000 then try restarting XQuartz.

Once you have XQuartz configured you can enable forwarding by setting DISPLAY environment variable to the IP address of the host machine:

```
$ export HOST_IP=`ifconfig en0 | grep "inet " | cut -d " " -f2`
$ xhost +local:
$ docker run -it --rm -e DISPLAY=$HOST_IP:0 -v $PWD:/workdir -w /workdir fermipy_
→ipython
```

## Installing From Source

The instructions describe how to install development versions of Fermipy from source code. Before installing a development version we recommend first installing a tagged release following the [Installing with pip](#) or [Installing Anaconda Python](#) instructions above.

```
$ git clone https://github.com/fermiPy/fermipy.git
$ cd fermipy
$ export INSTALL_CMD=" "
$ source condainstall.sh
$ # Consider using python setup.py develop
$ # if you are doing active development
$ python setup.py install
```

## Upgrading

By default installing fermipy with pip or conda will get the latest tagged released available on the [PyPi](#) package repository. You can check your currently installed version of fermipy with pip show:

```
$ pip show fermipy
```

or conda info:

```
$ conda info fermipy
```

To upgrade your fermipy installation to the latest version run the pip installation command with --upgrade --no-deps (remember to also include the --user option if you're running at SLAC):

```
$ pip install fermipy --upgrade --no-deps
Collecting fermipy
Installing collected packages: fermipy
  Found existing installation: fermipy 0.6.6
    Uninstalling fermipy-0.6.6:
      Successfully uninstalled fermipy-0.6.6
Successfully installed fermipy-0.6.7
```

If you installed fermipy with conda the equivalent command is:

```
$ conda update fermipy
```

### Developer Installation

These instructions describe how to install fermipy from its git source code repository using the `setup.py` script. Installing from source can be useful if you want to make your own modifications to the fermipy source code. Note that non-developers are recommended to install a tagged release of fermipy following the [Installing with pip](#) or [Installing Anaconda Python](#) instructions above.

First clone the fermipy git repository and cd to the root directory of the repository:

```
$ git clone https://github.com/fermiPy/fermipy.git
$ cd fermipy
$ export INSTALL_CMD=" "
$ source condainstall.sh
```

To install the latest commit in the master branch run `setup.py install` from the root directory:

```
# Install the latest commit
$ git checkout master
$ python setup.py install --user
```

A useful option if you are doing active code development is to install your working copy of the package. This will create an installation in your python distribution that is linked to the copy of the code in your local repository. This allows you to run with any local modifications without having to reinstall the package each time you make a change. To install your working copy of fermipy run with the `develop` argument:

```
# Install a link to your source code installation
$ python setup.py develop --user
```

You can later remove the link to your working copy by running the same command with the `--uninstall` flag:

```
# Install a link to your source code installation
$ python setup.py develop --user --uninstall
```

Specific release tags can be installed by running `git checkout` before running the installation command:

```
# Checkout a specific release tag
$ git checkout X.X.X
$ python setup.py install --user
```

To see the list of available release tags run `git tag`.

## Issues

If you get an error about importing matplotlib (specifically something about the macosx backend) you might change your default backend to get it working. The [customizing matplotlib page](#) details the instructions to modify your default matplotlibrc file (you can pick GTK or WX as an alternative). Specifically the TkAgg and macosx backends currently do not work on OSX if you upgrade matplotlib to the version required by fermipy. To get around this issue you can switch to the Agg backend at runtime before importing fermipy:

```
>>> import matplotlib
>>> matplotlib.use('Agg')
```

However note that this backend does not support interactive plotting.

If you are running OSX El Capitan or newer you may see errors like the following:

```
dyld: Library not loaded
```

In this case you will need to disable the System Integrity Protections (SIP). See [here](#) for instructions on disabling SIP on your machine.

In some cases the setup.py script will fail to properly install the fermipy package dependencies. If installation fails you can try running a forced upgrade of these packages with `pip install --upgrade:`

```
$ pip install --upgrade --user numpy matplotlib scipy astropy pyyaml healpy wcsaxes,
↪ipython jupyter
```

## 1.3.2 Quickstart Guide

This page walks through the steps to setup and perform a basic spectral analysis of a source. For additional fermipy tutorials see the [IPython Notebook Tutorials](#). To more easily follow along with this example a directory containing pre-generated input files (FT1, source maps, etc.) is available from the following link:

```
$ curl -OL https://raw.githubusercontent.com/fermiPy/fermipy-extras/master/data/
↪mkn421.tar.gz
$ tar xzf mkn421.tar.gz
$ cd mkn421
```

## Creating a Configuration File

The first step is to compose a configuration file that defines the data selection and analysis parameters. Complete documentation on the configuration file and available options is given in the [Configuration](#) page. fermiPy uses the [YAML format](#) for its configuration files. The configuration file has a hierarchical organization that groups related parameters into separate dictionaries. In this example we will compose a configuration file for a SOURCE-class analysis of Markarian 421 with FRONT+BACK event types (evtype=3):

```
data:
  evfile : ft1.lst
  scfile : ft2.fits
  ltcube : ltcube.fits

binning:
  roiwidth : 10.0
  binsz : 0.1
  binsperdec : 8
```

(continues on next page)

(continued from previous page)

```

selection :
  emin : 100
  emax : 316227.76
  zmax : 90
  evclass : 128
  evtype : 3
  tmin : 239557414
  tmax : 428903014
  filter : null
  target : 'mkn421'

gtlike:
  edisp : True
  irfs : 'P8R2_SOURCE_V6'
  edisp_disable : ['isodiff', 'galdiff']

model:
  src_roiwidth : 15.0
  galdiff : '$FERMI_DIFFUSE_DIR/gll_iem_v06.fits'
  isodiff : 'iso_P8R2_SOURCE_V6_v06.txt'
  catalogs : ['3FGL']

```

The *data* section defines the input data set and spacecraft file for the analysis. Here *evfile* points to a list of FT1 files that encompass the chosen ROI, energy range, and time selection. The parameters in the *binning* section define the dimensions of the ROI and the spatial and energy bin size. The *selection* section defines parameters related to the data selection (energy range, zmax cut, and event class/type). The *target* parameter in this section defines the ROI center to have the same coordinates as the given source. The *model* section defines parameters related to the ROI model definition (diffuse templates, point sources).

Fermipy gives the user the option to combine multiple data selections into a joint likelihood with the *components* section. The components section contains a list of dictionaries with the same hierarchy as the root analysis configuration. Each element of the list defines the analysis parameters for an independent sub-selection of the data. Any parameters not defined within the component dictionary default to the value defined in the root configuration. The following example shows the *components* section that could be appended to the previous configuration to define a joint analysis with four PSF event types:

```

components:
- { selection : { evtype : 4 } } # PSF0
- { selection : { evtype : 8 } } # PSF1
- { selection : { evtype : 16 } } # PSF2
- { selection : { evtype : 32 } } # PSF3

```

Any configuration parameter can be changed with this mechanism. The following example is a configuration in which a different zmax selection and isotropic template is used for each of the four PSF event types:

```

components:
- model: {isodiff: isotropic_source_psf0_4years_P8V3.txt}
  selection: {evtype: 4, zmax: 70}
- model: {isodiff: isotropic_source_psf1_4years_P8V3.txt}
  selection: {evtype: 8, zmax: 75}
- model: {isodiff: isotropic_source_psf2_4years_P8V3.txt}
  selection: {evtype: 16, zmax: 85}
- model: {isodiff: isotropic_source_psf3_4years_P8V3.txt}
  selection: {evtype: 32, zmax: 90}

```

## Creating an Analysis Script

Once the configuration file has been composed, the analysis is executed by creating an instance of *GTAnalysis* with the configuration file as its argument and calling its analysis methods. *GTAnalysis* serves as a wrapper over the underlying *pyLikelihood* classes and provides methods to fix/free parameters, add/remove sources from the model, and perform a fit to the ROI. For a complete documentation of the available methods you can refer to the *fermipy package* page.

In the following python examples we show how to initialize and run a basic analysis of a source. First we instantiate a *GTAnalysis* object with the path to the configuration file and run *setup()*.

```
from fermipy.gtanalysis import GTAnalysis

gta = GTAnalysis('config.yaml', logging={'verbosity' : 3})
gta.setup()
```

The *setup()* method performs the data preparation and response calculations needed for the analysis (selecting the data, creating counts and exposure maps, etc.). Depending on the data selection and binning of the analysis this will often be the slowest step in the analysis sequence. The output of *setup()* is cached in the analysis working directory so subsequent calls to *setup()* will run much faster.

Before running any other analysis methods it is recommended to first run *optimize()*:

```
gta.optimize()
```

This will loop over all model components in the ROI and fit their normalization and spectral shape parameters. This method also computes the TS of all sources which can be useful for identifying weak sources that could be fixed or removed from the model. We can check the results of the optimization step by calling *print\_roi()*:

```
gta.print_roi()
```

By default all models parameters are initially fixed. The *free\_source()* and *free\_sources()* methods can be used to free or fix parameters of the model. In the following example we free the normalization of catalog sources within 3 deg of the ROI center and free the galactic and isotropic components by name.

```
# Free Normalization of all Sources within 3 deg of ROI center
gta.free_sources(distance=3.0, pars='norm')

# Free all parameters of isotropic and galactic diffuse components
gta.free_source('galdiff')
gta.free_source('isodiff')
```

The *minmax\_ts* and *minmax\_npred* arguments to *free\_sources()* can be used to free or fixed sources on the basis of their current TS or Npred values:

```
# Free sources with TS > 10
gta.free_sources(minmax_ts=[10, None], pars='norm')

# Fix sources with TS < 10
gta.free_sources(minmax_ts=[None, 10], free=False, pars='norm')

# Fix sources with 10 < Npred < 100
gta.free_sources(minmax_npred=[10, 100], free=False, pars='norm')
```

When passing a source name argument both case and whitespace are ignored. When using a FITS catalog file a source can also be referred to by any of its associations. When using the 3FGL catalog, the following calls are equivalent ways of freeing the parameters of Mkn 421:

```
# These calls are equivalent
gta.free_source('mkn421')
gta.free_source('Mkn 421')
gta.free_source('3FGL J1104.4+3812')
gta.free_source('3fglj1104.4+3812')
```

After freeing parameters of the model we can execute a fit by calling `fit()`. This will maximize the likelihood with respect to the model parameters that are currently free.

```
gta.fit()
```

After the fitting is complete we can write the current state of the model with `write_roi`:

```
gta.write_roi('fit_model')
```

This will write several output files including an XML model file and an ROI dictionary file. The names of all output files will be prepended with the `prefix` argument to `write_roi()`.

Once we have optimized our model for the ROI we can use the `residmap()` and `tmap()` methods to assess the fit quality and look for new sources.

```
# Dictionary defining the spatial/spectral parameters of the test source
model = {'SpatialModel' : 'PointSource', 'Index' : 2.0,
        'SpectrumType' : 'PowerLaw'}

# Both methods return a dictionary with the maps
m0 = gta.residmap('fit_model', model=model, make_plots=True)
m1 = gta.tmap('fit_model', model=model, make_plots=True)
```

More documentation on these methods is available in the [TS Map](#) and [Residual Map](#) pages.

By default, calls to `fit()` will execute a global spectral fit over the entire energy range of the analysis. To extract a bin-by-bin flux spectrum (i.e. a SED) you can call `sed()` method with the name of the source:

```
gta.sed('mkn421', make_plots=True)
```

More information about `sed()` method can be found in the [SED Analysis](#) page.

## Extracting Analysis Results

Results of the analysis can be extracted from the dictionary file written by `write_roi()`. This method writes information about the current state of the analysis to a python dictionary. More documentation on the contents of the output file are available in the [Output File](#) page.

By default the output dictionary is written to a file in the `numpy format` and can be loaded from a python session after your analysis is complete. The following demonstrates how to load the analysis dictionary that was written to `fit_model.npy` in the Mkn421 analysis example:

```
>>> # Load analysis dictionary from a npy file
>>> import np
>>> c = np.load('fit_model.npy').flat[0]
>>> list(c.keys())
['roi', 'config', 'sources', 'version']
```

The output dictionary contains the following top-level elements:

Table 1: File Dictionary

Key	Description
roi	<code>dict</code> A dictionary containing information about the ROI as a whole.
sources	<code>dict</code> A dictionary containing information about individual sources in the model (diffuse and point-like). Each element of this dictionary maps to a single source in the ROI model.
config	<code>dict</code> The configuration dictionary of the <i>GTAnalysis</i> instance.
version	<code>str</code> The version of the Fermipy package that was used to run the analysis. This is automatically generated from the git release tag.

Each source dictionary collects the properties of the given source (TS, NPred, best-fit parameters, etc.) computed up to that point in the analysis.

```
>>> list(c['sources'].keys())
['3FGL J1032.7+3735',
 '3FGL J1033.2+4116',
 ...
 '3FGL J1145.8+4425',
 'galdiff',
 'isodiff']
>>> c['sources']['3FGL J1104.4+3812']['ts']
87455.9709683
>>> c['sources']['3FGL J1104.4+3812']['npred']
31583.7166495
```

Information about individual sources in the ROI is also saved to a catalog FITS file with the same string prefix as the dictionary file. This file can be loaded with the `astropy.io.fits` or `astropy.table.Table` interface:

```
>>> # Load the source catalog file
>>> from astropy.table import Table
>>> tab = Table.read('fit_model.fits')
>>> tab[['name', 'class', 'ts', 'npred', 'flux']]
      name      class      ts      npred      flux [2]
                                1 / (cm2 s)
-----
↪-----
3FGL J1104.4+3812    BLL    87455.9709683  31583.7166495  2.20746290445e-07 .. 1.
↪67062058528e-09
3FGL J1109.6+3734    bll     42.34511826  93.7971922425   5.90635786943e-10 .. 3.
↪6620894143e-10
...
3FGL J1136.4+3405    fsrq    4.78089819776  261.427034151   1.86805869704e-08 .. 8.
↪62638727067e-09
3FGL J1145.8+4425    fsrq    3.78006883967  237.525501441   7.25611442299e-08 .. 3.
↪77056557247e-08
```

The FITS file contains columns for all scalar and vector elements of the source dictionary. Spectral fit parameters are contained in the `param_names`, `param_values`, and `param_errors` columns:

```
>>> tab[['param_names', 'param_values', 'param_errors']][0]
<Row 0 of table
  values=(['Prefactor', 'Index', 'Scale', '', '', ''],
          [2.1301351784512767e-11, -1.7716399431228638, 1187.1300048828125, nan, nan,
↪nan],
          [1.6126233510314277e-13, nan, nan, nan, nan, nan])
  dtype=(['param_names', 'S32', (6,)],
```

(continues on next page)

(continued from previous page)

```
('param_values', '>f8', (6,)),  
( 'param_errors', '>f8', (6,))]>
```

## Reloading from a Previous State

One can reload an analysis instance that was saved with `write_roi()` by calling either the `create()` or `load_roi()` methods. The `create()` method can be used to construct an entirely new instance of `GTAnalysis` from a previously saved results file:

```
from fermipy.gtanalysis import GTAnalysis  
gta = GTAnalysis.create('fit_model.npy')  
  
# Continue running analysis starting from the previously saved  
# state  
gta.fit()
```

where the argument is the path to an output file produced with `write_roi()`. This function will instantiate a new analysis object, run the `setup()` method, and load the state of the model parameters at the time that `write_roi()` was called.

The `load_roi()` method can be used to reload a previous state of the analysis to an existing instance of `GTAnalysis`.

```
from fermipy.gtanalysis import GTAnalysis  
  
gta = GTAnalysis('config.yaml')  
gta.setup()  
  
gta.write_roi('prefit_model')  
  
# Fit a source  
gta.free_source('mkn421')  
gta.fit()  
  
# Restore the analysis to its prior state before the fit of mkn421  
# was executed  
gta.load_roi('prefit_model')
```

Using `load_roi()` is generally faster than `create()` when an analysis instance already exists.

## IPython Notebook Tutorials

Additional tutorials with more detailed examples are available as IPython notebooks in the `notebooks` directory of the `fermipy-extra` repository. These notebooks can be browsed as [static web pages](#) or run interactively by downloading the `fermipy-extra` repository and running `jupyter notebook` in the `notebooks` directory:

```
$ git clone https://github.com/fermiPy/fermipy-extra.git  
$ cd fermipy-extra/notebooks  
$ jupyter notebook index.ipynb
```

Note that this will require you to have both `ipython` and `jupyter` installed in your python environment. These can be installed in a conda- or pip-based installation as follows:



```
# Install with conda
$ conda install ipython jupyter

# Install with pip
$ pip install ipython jupyter
```

One can also run the notebooks from a docker container following the *Installing with Docker* instructions:

```
$ git clone https://github.com/fermiPy/fermipy-extra.git
$ cd fermipy-extra
$ docker pull fermipy/fermipy
$ docker run -it --rm -p 8888:8888 -v $PWD:/workdir -w /workdir fermipy/fermipy
```

After launching the notebook server, paste the URL that appears into your web browser and navigate to the *notebooks* directory.

### 1.3.3 Configuration

This page describes the configuration management scheme used within the Fermipy package and documents the configuration parameters that can be set in the configuration file.

#### Class Configuration

Classes in the Fermipy package own a configuration state dictionary that is initialized when the class instance is created. Elements of the configuration dictionary can be scalars (str, int, float) or dictionaries containing groups of parameters. The settings in this dictionary are used to control the runtime behavior of the class.

When creating a class instance, the configuration is initialized by passing either a configuration dictionary or configuration file path to the class constructor. Keyword arguments can be passed to the constructor to override configuration parameters in the input dictionary. In the following example the *config* dictionary defines values for the parameters *emin* and *emax*. By passing a dictionary for the *selection* keyword argument, the value of *emax* in the keyword argument (10000) overrides the value of *emax* in the input dictionary.

```
config = {
    'selection' : { 'emin' : 100,
                   'emax' : 1000 }
}

gta = GTAnalysis(config, selection={'emax' : 10000})
```

The first argument can also be the path to a YAML configuration file rather than a dictionary:

```
gta = GTAnalysis('config.yaml', selection={'emax' : 10000})
```

#### Configuration File

Fermipy uses **YAML** files to read and write its configuration in a persistent format. The configuration file has a hierarchical structure that groups parameters into dictionaries that are keyed to a section name (*data*, *binning*, etc.).

Listing 1: Sample Configuration

```

data:
  evfile : ft1.lst
  scfile : ft2.fits
  ltcube : ltcube.fits

binning:
  roiwidth : 10.0
  binsz : 0.1
  binsperdec : 8

selection :
  emin : 100
  emax : 316227.76
  zmax : 90
  evclass : 128
  evtype : 3
  tmin : 239557414
  tmax : 428903014
  filter : null
  target : 'mkn421'

gtlike:
  edisp : True
  edisp_bins : -1
  irfs : 'P8R3_SOURCE_V2'
  edisp_disable : ['isodiff', 'galdiff']

model:
  src_roiwidth : 15.0
  galdiff : '$FERMI_DIFFUSE_DIR/gll_iem_v07.fits'
  isodiff : 'iso_P8R3_SOURCE_V2_v1.txt'
  catalogs : ['4FGL']

```

The configuration file has the same structure as the configuration dictionary such that one can read/write configurations using the load/dump methods of the yaml module :

```

import yaml
# Load a configuration
config = yaml.load(open('config.yaml'))
# Update a parameter and write a new configuration
config['selection']['emin'] = 1000.
yaml.dump(config, open('new_config.yaml', 'w'))

```

Most of the configuration parameters are optional and if not set explicitly in the configuration file will be set to a default value. The parameters that can be set in each section are described below.

## binning

Options in the *binning* section control the spatial and spectral binning of the data.

Listing 2: Sample *binning* Configuration

```

binning:

```

(continues on next page)

(continued from previous page)

```
# Binning
roiwidth : 10.0
npix      : null
binsz     : 0.1 # spatial bin size in deg
binsperdec : 8  # nb energy bins per decade
projtype  : WCS
```

Table 2: *binning* Options

Option	Default	Description
binsperdec	8	Number of energy bins per decade.
binsz	0.1	Spatial bin size in degrees.
coordsys	CEL	Coordinate system of the spatial projection (CEL or GAL).
enumbins	None	Number of energy bins. If none this will be inferred from energy range and binsperdec parameter.
hpx_ebin	True	Include energy binning
hpx_order	10	Order of the map (int between 0 and 12, included)
hpx_ordering_scheme	RING	HEALPix Ordering Scheme
npix	None	Number of pixels along the x and y dimension (tuple) for WCS mode. If none then this will be set from roiwidth and binsz.
proj	AIT	Spatial projection for WCS mode.
projtype	WCS	Projection mode (WCS or HPX).
roiwidth	10.0	Width of the ROI in degrees. The number of pixels in each spatial dimension will be set from roiwidth / binsz (rounded up) if not specified using npix.

## components

The *components* section can be used to define analysis configurations for independent subselections of the data. Each subselection will have its own binned likelihood instance that is combined in a global likelihood function for the ROI (implemented with the SummedLikelihood class in pyLikelihood). The *components* section is optional and when set to null (the default) only a single likelihood component will be created with the parameters of the root analysis configuration.

The component section is defined as a list of dictionaries where each element sets analysis parameters for a different subcomponent of the analysis. The component configurations follow the same structure and accept the same parameters as the root analysis configuration. Parameters not defined in a given element will default to the values set in the root analysis configuration.

The following example illustrates how to define a Front/Back analysis with two components. Files associated to each component will be given a suffix according to their order in the list (e.g. file\_00.fits, file\_01.fits, etc.).

```
# Component section for Front/Back analysis
- { selection : { evtype : 1 } } # Front
- { selection : { evtype : 2 } } # Back
```

## data

The *data* section defines the input data files for the analysis (FT1, FT2, and livetime cube). evfile and scfile can either be individual files or group of files. The optional ltcube option can be used to choose a pre-generated livetime cube. If ltcube is null a livetime cube will be generated at runtime with gtltcube.

Listing 3: Sample *data* Configuration

```
data :  
  evfile : ft1.lst  
  scfile : ft2.fits  
  ltcube : null
```

Table 3: *data* Options

Option	Default	Description
cacheft1	True	Cache FT1 files when performing binned analysis. If false then only the counts cube is retained.
evfile	None	Path to FT1 file or list of FT1 files.
ltcube	None	Path to livetime cube. If none a livetime cube will be generated with <code>gtmktime</code> .
scfile	None	Path to FT2 (spacecraft) file.

## extension

The options in *extension* control the default behavior of the *extension* method. For more information about using this method see the [Extension Fitting](#) page.

Table 4: *extension* Options

Option	Default	Description
fit_ebin	False	Perform a fit for the angular extension in each analysis energy bin.
fit_posi	False	Perform a simultaneous fit to the source position and extension.
fix_shape	False	Fix spectral shape parameters of the source of interest. If True then only the normalization parameter will be fit.
free_background	False	Leave background parameters free when performing the fit. If True then any parameters that are currently free in the model will be fit simultaneously with the source of interest.
free_rad	None	Free normalizations of background sources within this angular distance in degrees from the source of interest. If None then no sources will be freed.
make_plots	False	Generate diagnostic plots.
make_tsm	True	Make a TS map for the source of interest.
psf_scaling	None	Tuple of two vectors (logE,f) defining an energy-dependent PSF scaling function that will be applied when building spatial models for the source of interest. The tuple (logE,f) defines the fractional corrections f at the sequence of energies logE = log10(E/MeV) where f=0 corresponds to no correction. The correction function f(E) is evaluated by linearly interpolating the fractional correction factors f in log(E). The corrected PSF is given by $P'(x;E) = P(x/(1+f(E));E)$ where x is the angular separation.
save_model	False	Save model counts cubes for the best-fit model of extension.
spatial	RadialGauss	Spatial model that will be used to test the source extension. The spatial scale parameter of the model will be set such that the 68% containment radius of the model is equal to the width parameter.
sqrt_ts_thresh	None	Threshold on sqrt(TS_ext) that will be applied when update is True. If None then no threshold is applied.
tsmap_fit	tsmap	Set the method for generating the TS map. Valid options are tsmap or tscube.
update	False	Update this source with the best-fit model for spatial extension if TS_ext > tsext_threshold.
width	None	Sequence of values in degrees for the likelihood scan over spatial extension (68% containment radius). If this argument is None then the scan points will be determined from width_min/width_max/width_nstep.
width_max	0	Maximum value in degrees for the likelihood scan over spatial extent.
width_min	0.01	Minimum value in degrees for the likelihood scan over spatial extent.
width_nstep	20	Number of scan points between width_min and width_max. Scan points will be spaced evenly on a logarithmic scale between width_min and width_max.
write_fits	True	Write the output to a FITS file.
write_numpy	True	Write the output dictionary to a numpy file.

## fileio

The *fileio* section collects options related to file bookkeeping. The *outdir* option sets the root directory of the analysis instance where all output files will be written. If *outdir* is null then the output directory will be automatically set to the directory in which the configuration file is located. Enabling the *usescratch* option will stage all output data files to a temporary scratch directory created under *scratchdir*.

Listing 4: Sample *fileio* Configuration

```
fileio:
  outdir : null
  logfile : null
  usescratch : False
  scratchdir : '/scratch'
```

Table 5: *fileio* Options

Option	Default	Description
logfile	None	Path to log file. If None then log will be written to fermipy.log.
outdir	None	Path of the output directory. If none this will default to the directory containing the configuration file.
outdir_regex	None	String file storing the output directory that match at least one of the regular expressions in this list. This option only takes effect when <code>usescratch</code> is True.
savefits	True	Save intermediate FITS files.
scratchdir	scratch	Path to the scratch directory. If <code>usescratch</code> is True then a temporary working directory will be created under this directory.
usescratch	False	Run analysis in a temporary working directory under <code>scratchdir</code> .
workdir	None	Path to the working directory.
workdir_regex	None	String file storing the working directory that match at least one of the regular expressions in this list. This option only takes effect when <code>usescratch</code> is True.

## gtlike

Options in the *gtlike* section control the setup of the likelihood analysis include the IRF name (`irfs`). The `edisp_bin` option has been recently added to implement the latest handling of the energy dispersion (see [FSSC](#) for further details).

Table 6: *gtlike* Options

Option	Default	Description
bexpmap	None	
bexpmap_name	None	Set the baseline all-sky expoure map file. This will be used to generate a scaled source map.
bexpmap_dir	None	
bexpmap_base	None	Set the baseline ROI expoure map file. This will be used to generate a scaled source map.
convolve	True	
edisp	True	Enable the correction for energy dispersion.
edisp_bins	20	Number of bins to use for energy correction.
edisp_disable	None	Provide a list of sources for which the edisp correction should be disabled.
expscale	None	Exposure correction that is applied to all sources in the analysis component. This correction is superseded by <code>src_expscale</code> if it is defined for a source.
irfs	None	Set the IRF string.
llscan_npts	20	Number of evaluation points to use when performing a likelihood scan.
minbinsz	0.05	Set the minimum bin size used for resampling diffuse maps.
resample	True	
rfactor	2	
src_expscale	None	Dictionary of exposure corrections for individual sources keyed to source name. The exposure for a given source will be scaled by this value. A value of 1.0 corresponds to the nominal exposure.
srcmap	None	Set the source maps file. When defined this file will be used instead of the local source maps file.
srcmap_base	None	Set the baseline source maps file. This will be used to generate a scaled source map.
use_external_srcmap	False	Use an external precomputed source map file.
use_scaled_srcmap	False	Generate source map by scaling an external srcmap file.
wmap	None	Likelihood weights map.

## lightcurve

The options in *lightcurve* control the default behavior of the *lightcurve* method. For more information about using this method see the [Light Curves](#) page.

Table 7: *lightcurve* Options

Option	Default	Description
<code>binsz</code>	86400.0	Set the lightcurve bin size in seconds.
<code>free_background</code>	False	Leave background parameters free when performing the fit. If True then any parameters that are currently free in the model will be fit simultaneously with the source of interest.
<code>free_parameters</code>	None	Set the parameters of the source of interest that will be re-fit in each time bin. If this list is empty then all parameters will be freed.
<code>free_radius</code>	None	Free normalizations of background sources within this angular distance in degrees from the source of interest. If None then no sources will be freed.
<code>free_sources</code>	None	List of sources to be freed. These sources will be added to the list of sources satisfying the <code>free_radius</code> selection.
<code>make_plots</code>	False	Generate diagnostic plots.
<code>max_free_sources</code>	5	Maximum number of sources that will be fit simultaneously with the source of interest.
<code>multithread</code>	False	Split the calculation across number of processes set by <code>nthread</code> option.
<code>nbins</code>	None	Set the number of lightcurve bins. The total time range will be evenly split into this number of time bins.
<code>nthread</code>	None	Number of processes to create when <code>multithread</code> is True. If None then one process will be created for each available core.
<code>outdir</code>	None	Store all data in this directory (e.g. “30days”). If None then use current directory.
<code>save_bin_tables</code>	True	Save analysis directories for individual time bins. If False then only the analysis results table will be saved.
<code>shape_ts_threshold</code>	16.0	Set the TS threshold at which shape parameters of sources will be freed. If a source is detected with TS less than this value then its shape parameters will be fixed to values derived from the analysis of the full time range.
<code>systematic</code>	0.02	Systematic correction factor for TS: $\text{subscript:var}$ . See Sect. 3.6 in 2FGL for details.
<code>time_bin_edges</code>	None	Set the lightcurve bin edge sequence in MET. This option takes precedence over <code>binsz</code> and <code>nbins</code> .
<code>use_localcube</code>	True	Generate a fast LT cube.
<code>use_scaled_source_maps</code>	False	Generate approximate source maps for each time bin by scaling the current source maps by the exposure ratio with respect to that time bin.
<code>write_fits</code>	True	Write the output to a FITS file.
<code>write_numpy</code>	True	Write the output dictionary to a numpy file.

## model

The *model* section collects options that control the inclusion of point-source and diffuse components in the model. `galdiff` and `isodiff` set the templates for the Galactic IEM and isotropic diffuse respectively. `catalogs` defines a list of catalogs that will be merged to form a master analysis catalog from which sources will be drawn. Valid entries in this list can be FITS files or XML model files. `sources` can be used to insert additional point-source or extended components beyond those defined in the master catalog. `src_radius` and `src_roiwidth` set the maximum distance from the ROI center at which sources in the master catalog will be included in the ROI model.

Listing 5: Sample *model* Configuration

```
model :
```

(continues on next page)

(continued from previous page)

```

# Diffuse components
galdiff : '$FERMI_DIR/refdata/fermi/galdiffuse/gll_iem_v06.fits'
isodiff : '$FERMI_DIR/refdata/fermi/galdiffuse/iso_P8R2_SOURCE_V6_v06.txt'

# List of catalogs to be used in the model.
catalogs :
- '3FGL'
- 'extra_sources.xml'

sources :
- { 'name' : 'SourceA', 'ra' : 60.0, 'dec' : 30.0, 'SpectrumType' : PowerLaw }
- { 'name' : 'SourceB', 'ra' : 58.0, 'dec' : 35.0, 'SpectrumType' : PowerLaw }

# Include catalog sources within this distance from the ROI center
src_radius : null

# Include catalog sources within a box of width roisrc.
src_roiwidth : 15.0

```

Table 8: *model* Options

Option	Default	Description
assoc_xmatch	[3FGL, 4FGL]	Choose a set of association columns on which to cross-match catalogs.
catalogs	None	
diffuse	None	
diffuse_	None	
diffuse_	None	
extdir	None	Set a directory that will be searched for extended source FITS templates. Template files in this directory will take precedence over catalog source templates with the same name.
extract	False	Extract a copy of all mapcube components centered on the ROI.
galdiff	None	Set the path to one or more galactic IEM mapcubes. A separate component will be generated for each item in this list.
isodiff	None	Set the path to one or more isotropic templates. A separate component will be generated for each item in this list.
limbdiff	None	
merge_sources	True	Merge properties of sources that appear in multiple source catalogs. If merge_sources=false then subsequent sources with the same name will be ignored.
sources	None	
src_radius	None	Radius of circular region in degrees centered on the ROI that selects sources for inclusion in the model. If this parameter is none then no selection is applied. This selection is ORed with the src_roiwidth selection.
src_radius_roi	None	Half-width of src_roiwidth selection. This parameter can be used in lieu of src_roiwidth.
src_roiwidth	None	Width of square region in degrees centered on the ROI that selects sources for inclusion in the model. If this parameter is none then no selection is applied. This selection will be ORed with the src_radius selection.



## optimizer

Table 9: *optimizer* Options

Option	Default	Description
init_lambda	0.001	Initial value of damping parameter for step size calculation when using the NEWTON fitter. A value of zero disables damping.
max_iter	100	Maximum number of iterations for the Newtons method fitter.
min_fit_quality	2	Set the minimum fit quality.
optimizer	MINUIT	Set the optimization algorithm to use when maximizing the likelihood function.
retries	3	Set the number of times to retry the fit when the fit quality is less than min_fit_quality.
tol	0.001	Set the optimizer tolerance.
verbosity	0	

## plotting

Table 10: *plotting* Options

Option	Default	Description
catalogs	None	
cmap	magma	Set the colormap for 2D plots.
cmap_res	RdBu_r	Set the colormap for 2D residual plots.
figsize	[8.0, 6.0]	Set the default figure size.
format	png	
graticule_radii	None	Define a list of radii at which circular graticules will be drawn.
interact	False	Enable interactive mode. If True then plots will be drawn after each plotting command.
label_thresh	0.0	Threshold for labeling sources in sky maps. If None then no sources will be labeled.
loge_bound	None	

## residmap

The options in *residmap* control the default behavior of the *residmap* method. For more information about using this method see the *Residual Map* page.

Table 11: *residmap* Options

Option	Default	Description
exclude	None	List of sources that will be removed from the model when computing the residual map.
loge_bound	None	Restrict the analysis to an energy range (emin,emax) in log10(E/MeV) that is a subset of the analysis energy range. By default the full analysis energy range will be used. If either emin/emax are None then only an upper/lower bound on the energy range will be applied.
make_plots	False	Generate diagnostic plots.
model	None	Dictionary defining the spatial/spectral properties of the test source. If model is None the test source will be a PointSource with an Index 2 power-law spectrum.
use_weighted	False	Used weighted version of maps in making plots.
write_fits	True	Write the output to a FITS file.
write_numpy	True	Write the output dictionary to a numpy file.

## roiopt

The options in *roiopt* control the default behavior of the *optimize* method. For more information about using this method see the [ROI Optimization and Fitting](#) page.

Table 12: *roiopt* Options

Option	Default	Description
max_free_sources	5	Maximum number of sources that will be fit simultaneously in the first optimization step.
npred_frac	0.95	
npred_thresh	1.0	Threshold
shape_ts_thresh	25.0	Threshold on source TS used for determining the sources that will be fit in the third optimization step.
skip	None	List of str source names to skip while optimizing.

## sed

The options in *sed* control the default behavior of the *sed* method. For more information about using this method see the [SED Analysis](#) page.

Table 13: *sed* Options

Option	Default	Description
bin_index	2.0	Spectral index that will be use when fitting the energy distribution within an energy bin.
cov_scale	1.0	Scale factor that sets the strength of the prior on nuisance parameters that are free. Setting this to None disables the prior.
free_background	False	Leave background parameters free when performing the fit. If True then any parameters that are currently free in the model will be fit simultaneously with the source of interest.
free_params	None	Set the parameters of the source of interest that will be freed when performing the global fit. By default all parameters will be freed.
free_rad	None	Free normalizations of background sources within this angular distance in degrees from the source of interest. If None then no sources will be freed.
make_plots	False	Generate diagnostic plots.
ul_confidence	0.95	Confidence level for flux upper limit.
use_local_index	False	Use a power-law approximation to the shape of the global spectrum in each bin. If this is false then a constant index set to <i>bin_index</i> will be used.
write_fits	True	Write the output to a FITS file.
write_numpy	True	Write the output dictionary to a numpy file.

## selection

The *selection* section collects parameters related to the data selection and target definition. The majority of the parameters in this section are arguments to *gtselect* and *gtmktime*. The ROI center can be set with the *target* parameter by providing the name of a source defined in one of the input catalogs (defined in the *model* section). Alternatively the ROI center can be defined by giving explicit sky coordinates with *ra* and *dec* or *glon* and *glat*.

```
selection:

# gtselect parameters
emin      : 100
emax      : 100000
zmax      : 90
```

(continues on next page)

(continued from previous page)

```

evclass : 128
evtype  : 3
tmin    : 239557414
tmax    : 428903014

# gtmktime parameters
filter : 'DATA_QUAL>0 && LAT_CONFIG==1'
roicut : 'no'

# Set the ROI center to the coordinates of this source
target : 'mkn421'

```

Table 14: *selection Options*

Option	Default	Description
convtype	None	Conversion type selection.
dec	None	
emax	None	Maximum Energy (MeV)
emin	None	Minimum Energy (MeV)
evclass	None	Event class selection.
evtype	None	Event type selection.
filter	None	Filter string for gtmktime selection.
glat	None	
glon	None	
logemax	None	Maximum Energy (log10(MeV))
logemin	None	Minimum Energy (log10(MeV))
phasemax	None	Maximum pulsar phase
phasemin	None	Minimum pulsar phase
ra	None	
radius	None	Radius of data selection. If none this will be automatically set from the ROI size.
roicut	no	
target	None	Choose an object on which to center the ROI. This option takes precedence over ra/dec or glon/glat.
tmax	None	Maximum time (MET).
tmin	None	Minimum time (MET).
zmax	None	Maximum zenith angle.

## sourcefind

The options in *sourcefind* control the default behavior of the *find\_sources* method. For more information about using this method see the *Source Finding* page.

Table 15: *sourcefind* Options

Option	Default	Description
<code>free_parameters</code>	<code>None</code>	
<code>max_iter</code>	5	Maximum number of source finding iterations. The source finder will continue adding sources until no additional peaks are found or the number of iterations exceeds this number.
<code>min_separation</code>	1.0	Minimum separation in degrees between sources detected in each iteration. The source finder will look for the maximum peak in the TS map within a circular region of this radius.
<code>model</code>	<code>None</code>	Dictionary defining the spatial/spectral properties of the test source. If model is <code>None</code> the test source will be a <code>PointSource</code> with an Index 2 power-law spectrum.
<code>multithread</code>	<code>False</code>	Split the calculation across number of processes set by <code>nthread</code> option.
<code>nthread</code>	<code>None</code>	Number of processes to create when <code>multithread</code> is <code>True</code> . If <code>None</code> then one process will be created for each available core.
<code>sources_per_iter</code>	4	Maximum number of sources that will be added in each iteration. If the number of detected peaks in a given iteration is larger than this number, only the N peaks with the largest TS will be used as seeds for the current iteration.
<code>sqrt_ts_threshold</code>	5.0	Source threshold in $\sqrt{\text{TS}}$ . Only peaks with $\sqrt{\text{TS}}$ exceeding this threshold will be used as seeds for new sources.
<code>tmap_fitmap</code>	<code>tmap</code>	Set the method for generating the TS map. Valid options are <code>tmap</code> or <code>tscube</code> .

## tmap

The options in *tmap* control the default behavior of the *tmap* method. For more information about using this method see the [TS Map](#) page.

Table 16: *tmap* Options

Option	Default	Description
<code>exclude</code>	<code>None</code>	List of sources that will be removed from the model when computing the TS map.
<code>loge_bounds</code>	<code>None</code>	Restrict the analysis to an energy range ( <code>emin,emax</code> ) in $\log_{10}(\text{E/MeV})$ that is a subset of the analysis energy range. By default the full analysis energy range will be used. If either <code>emin/emax</code> are <code>None</code> then only an upper/lower bound on the energy range will be applied.
<code>make_plots</code>	<code>False</code>	Generate diagnostic plots.
<code>max_kernel_radius</code>	3.0	Set the maximum radius of the test source kernel. Using a smaller value will speed up the TS calculation at the loss of accuracy.
<code>model</code>	<code>None</code>	Dictionary defining the spatial/spectral properties of the test source. If model is <code>None</code> the test source will be a <code>PointSource</code> with an Index 2 power-law spectrum.
<code>multithread</code>	<code>False</code>	Split the calculation across number of processes set by <code>nthread</code> option.
<code>nthread</code>	<code>None</code>	Number of processes to create when <code>multithread</code> is <code>True</code> . If <code>None</code> then one process will be created for each available core.
<code>write_fits</code>	<code>True</code>	Write the output to a FITS file.
<code>write_numpy</code>	<code>True</code>	Write the output dictionary to a numpy file.

## tscube

The options in *tscube* control the default behavior of the *tscube* method. For more information about using this method see the [TS Cube](#) page.

Table 17: *tscube* Options

Option	Default	Description
cov_scale	1.0	Scale factor to apply to broadband fitting cov. matrix in bin-by-bin fits ( < 0 -> fixed )
cov_scale	1.0	Scale factor to apply to global fitting cov. matrix in broadband fits. ( < 0 -> no prior )
do_sed	True	Compute the energy bin-by-bin fits
exclude	None	List of sources that will be removed from the model when computing the TS map.
init_lambda	0.0	Initial value of damping parameter for newton step size calculation. A value of zero disables damping.
max_iter	30	Maximum number of iterations for the Newtons method fitter.
model	None	Dictionary defining the spatial/spectral properties of the test source. If model is None the test source will be a PointSource with an Index 2 power-law spectrum.
nnorm	10	Number of points in the likelihood v. normalization scan
norm_sigma	5.0	Number of sigma to use for the scan range
remake_test_source	False	If true, recomputes the test source image (otherwise just shifts it)
st_scan_level	1	Level to which to do ST-based fitting (for testing)
tol	0.001	Criteria for fit convergence (estimated vertical distance to min < tol )
tol_type	0	Absolute (0) or relative (1) criteria for convergence.

### 1.3.4 Output File

The current state of the ROI can be written at any point by calling `write_roi`.

```
>>> gta.write_roi('output.npy')
```

The output file will contain all information about the state of the ROI as calculated up to that point in the analysis including model parameters and measured source characteristics (flux, TS, NPred). An XML model file will also be saved for each analysis component.

The output file can be read with `load`:

```
>>> o = np.load('output.npy').flat[0]
>>> print(o.keys())
['roi', 'config', 'sources', 'version']
```

The output file is organized in four top-level of dictionaries:

Table 18: File Dictionary

Key	Type	Description
roi	dict	A dictionary containing information about the ROI as a whole.
sources	dict	A dictionary containing information about individual sources in the model (diffuse and point-like). Each element of this dictionary maps to a single source in the ROI model.
config	dict	The configuration dictionary of the <i>GTAnalysis</i> instance.
version	str	The version of the Fermipy package that was used to run the analysis. This is automatically generated from the git release tag.

### ROI Dictionary

#### Source Dictionary

The `sources` dictionary contains one element per source keyed to the source name. The following table lists the elements of the source dictionary and their descriptions.

Table 19: Source Dictionary

Key	Type	Description
name	str	Name of the source.
SourceName		Name of the source.
SpatialModel		Spatial model.
SpatialWidth	float	Spatial size parameter.
SpatialType		Spatial type string. This corresponds to the type attribute of the spatialModel component in the XML model.
SourceType		Source type string (PointSource or DiffuseSource).
SpectrumType		Spectrum type string. This corresponds to the type attribute of the spectrum component in the XML model (e.g. PowerLaw, LogParabola, etc.).
Spatial_Filename		Path to spatial template associated to this source.
Spectrum_Filename		Path to file associated to the spectral model of this source.
correlation	dict	Dictionary of correlation coefficients.
model_counts	ndarray	Vector of predicted counts for this source in each analysis energy bin.
model_counts_wt	ndarray	Vector of predicted counts for this source in each analysis energy bin.
sed	dict	Output of SED analysis. See <a href="#">SED Analysis</a> for more information.
ra	float	Right ascension of the source (deg).
dec	float	Declination of the source (deg).
glon	float	Galactic longitude of the source (deg).
glat	float	Galactic latitude of the source (deg).
ra_err	float	Std. deviation of positional uncertainty in right ascension (deg).
dec_err	float	Std. deviation of positional uncertainty in declination (deg).
glon_err	float	Std. deviation of positional uncertainty in galactic longitude (deg).
glat_err	float	Std. deviation of positional uncertainty in galactic latitude (deg).
pos_err	float	1-sigma positional uncertainty (deg).
pos_r68	float	68% positional uncertainty (deg).
pos_r95	float	95% positional uncertainty (deg).
pos_r99	float	99% positional uncertainty (deg).
pos_err_semajor	float	1-sigma uncertainty (deg) along major axis of uncertainty ellipse.
pos_err_seminor	float	1-sigma uncertainty (deg) along minor axis of uncertainty ellipse.
pos_angle	float	Position angle of uncertainty ellipse with respect to major axis.
pos_gal_cov	ndarray	Covariance matrix of positional uncertainties in local projection in galactic coordinates.
pos_gal_cor	ndarray	Correlation matrix of positional uncertainties in local projection in galactic coordinates.
pos_cel_cov	ndarray	Covariance matrix of positional uncertainties in local projection in celestial coordinates.
pos_cel_cor	ndarray	Correlation matrix of positional uncertainties in local projection in celestial coordinates.
offset_ra	float	Right ascension offset from ROI center in local celestial projection (deg).
offset_dec	float	Declination offset from ROI center in local celestial projection (deg).
offset_glon	float	Galactic longitude offset from ROI center in local galactic projection (deg).
offset_glat	float	Galactic latitude offset from ROI center in local galactic projection (deg).
offset_r68edge	float	Distance from the edge of the ROI (deg). Negative (positive) values indicate locations inside (outside) the ROI.
offset	float	Angular offset from ROI center (deg).
param_names	ndarray	Names of spectral parameters.
param_values	ndarray	Spectral parameter values.
param_errors	ndarray	Spectral parameters errors.
ts	float	Source test statistic.
loglike	float	Log-likelihood of the model evaluated at the best-fit normalization of the source.
loglike_scan	ndarray	Log-likelihood values for scan of source normalization.
dloglike_scan	ndarray	Delta Log-likelihood values for scan of source normalization.

Continued on next page

Table 19 – continued from previous page

Key	Type	Description
<code>eflux_scan</code>	<code>ndarray</code>	Energy flux values for scan of source normalization.
<code>flux_scan</code>	<code>ndarray</code>	Flux values for scan of source normalization.
<code>norm_scan</code>	<code>ndarray</code>	Normalization parameters values for scan of source normalization.
<code>npred</code>	<code>float</code>	Number of predicted counts from this source integrated over the analysis energy range.
<code>npred_wt</code>	<code>float</code>	Number of predicted counts from this source integrated over the analysis energy range.
<code>pivot_energy</code>	<code>float</code>	Decorrelation energy in MeV.
<code>flux</code>	<code>float</code>	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
<code>flux100</code>	<code>float</code>	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
<code>flux1000</code>	<code>float</code>	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
<code>flux10000</code>	<code>float</code>	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
<code>flux_err</code>	<code>float</code>	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
<code>flux100_err</code>	<code>float</code>	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
<code>flux1000_err</code>	<code>float</code>	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
<code>flux10000_err</code>	<code>float</code>	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
<code>flux_ul95</code>	<code>float</code>	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
<code>flux100_ul95</code>	<code>float</code>	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
<code>flux1000_ul95</code>	<code>float</code>	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
<code>flux10000_ul95</code>	<code>float</code>	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
<code>eflux</code>	<code>float</code>	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
<code>eflux100</code>	<code>float</code>	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
<code>eflux1000</code>	<code>float</code>	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
<code>eflux10000</code>	<code>float</code>	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
<code>eflux_err</code>	<code>float</code>	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
<code>eflux100_err</code>	<code>float</code>	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
<code>eflux1000_err</code>	<code>float</code>	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
<code>eflux10000_err</code>	<code>float</code>	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
<code>eflux_ul95</code>	<code>float</code>	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
<code>eflux100_ul95</code>	<code>float</code>	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
<code>eflux1000_ul95</code>	<code>float</code>	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
<code>eflux10000_ul95</code>	<code>float</code>	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
<code>dnde</code>	<code>float</code>	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at the pivot energy.
<code>dnde100</code>	<code>float</code>	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 100 MeV.
<code>dnde1000</code>	<code>float</code>	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 1 GeV.
<code>dnde10000</code>	<code>float</code>	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 10 GeV.
<code>dnde_err</code>	<code>float</code>	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at the pivot energy.
<code>dnde100_err</code>	<code>float</code>	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 100 MeV.
<code>dnde1000_err</code>	<code>float</code>	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 1 GeV.
<code>dnde10000_err</code>	<code>float</code>	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 10 GeV.
<code>dnde_index</code>	<code>float</code>	Logarithmic slope of the differential photon spectrum evaluated at the pivot energy.
<code>dnde100_index</code>	<code>float</code>	Logarithmic slope of the differential photon spectrum evaluated at 100 MeV.
<code>dnde1000_index</code>	<code>float</code>	Logarithmic slope of the differential photon spectrum evaluated at 1 GeV.
<code>dnde10000_index</code>	<code>float</code>	Logarithmic slope of the differential photon spectrum evaluated at 10 GeV.

### 1.3.5 ROI Optimization and Fitting

Source fitting with fermipy is generally performed with the `optimize` and `fit` methods.

#### Fitting

`fit` is a wrapper on the pyLikelihood fit method and performs a likelihood fit of all free parameters of the model. This method can be used to manually optimize of the model by calling it after freeing one or more source parameters. The following example demonstrates the commands that would be used to fit the normalizations of all sources within 3 deg of the ROI center:

```
>>> gta.free_sources(distance=2.0, pars='norm')
>>> gta.print_params(True)
```

idx	parname	value	error	min	max	scale	free
3FGL J1104.4+3812							
18	Prefactor	1.77	0	1e-05	100	1e-11	*
3FGL J1109.6+3734							
24	Prefactor	0.33	0	1e-05	100	1e-14	*
galdiff							
52	Prefactor	1	0	0.1	10	1	*
isodiff							
55	Normalization	1	0	0.001	1e+03	1	*

```
>>> o = gta.fit()
2016-04-19 14:07:55 INFO GTAnalysis.fit(): Starting fit.
2016-04-19 14:08:56 INFO GTAnalysis.fit(): Fit returned successfully.
2016-04-19 14:08:56 INFO GTAnalysis.fit(): Fit Quality: 3 LogLike: -77279.869
↪DeltaLogLike: 501.128
>>> gta.print_params(True)
```

idx	parname	value	error	min	max	scale	free
3FGL J1104.4+3812							
18	Prefactor	2.13	0.0161	1e-05	100	1e-11	*
3FGL J1109.6+3734							
24	Prefactor	0.342	0.0904	1e-05	100	1e-14	*
galdiff							
52	Prefactor	0.897	0.0231	0.1	10	1	*
isodiff							
55	Normalization	1.15	0.016	0.001	1e+03	1	*

By default `fit` will repeat the fit until a fit quality of 3 is obtained. After the fit returns all sources with free parameters will have their properties (flux, TS, NPred, etc.) updated in the `ROIModel` instance. The return value of the method is a dictionary containing the following diagnostic information about the fit:



Table 20: *fit* Output Dictionary

Key	Type	Description
<code>fit_quality</code>	<code>int</code>	Fit quality parameter for MINUIT and NEWMINUIT optimizers (3 - Full accurate covariance matrix, 2 - Full matrix, but forced positive-definite (i.e. not accurate), 1 - Diagonal approximation only, not accurate, 0 - Error matrix not calculated at all)
<code>errors</code>	<code>ndarray</code>	Vector of parameter errors (unscaled).
<code>loglike</code>	<code>float</code>	Post-fit log-likelihood value.
<code>correlation</code>	<code>ndarray</code>	Correlation matrix between free parameters of the fit.
<code>config</code>	<code>dict</code>	Copy of input configuration to this method.
<code>values</code>	<code>ndarray</code>	Vector of best-fit parameter values (unscaled).
<code>dloglike</code>	<code>float</code>	Improvement in log-likelihood value.
<code>fit_status</code>	<code>int</code>	Optimizer return code (0 = ok).
<code>covariance</code>	<code>ndarray</code>	Covariance matrix between free parameters of the fit.
<code>edm</code>	<code>float</code>	Estimated distance to maximum of log-likelihood function.

The *fit* also accepts keyword arguments which can be used to configure its behavior at runtime:

```
>>> o = gta.fit(min_fit_quality=2, optimizer='NEWMINUIT', reoptimize=True)
```

## Reference/API

`GTAnalysis.fit(update=True, **kwargs)`

Run the likelihood optimization. This will execute a fit of all parameters that are currently free in the model and update the characteristics of the corresponding model components (TS, npred, etc.). The fit will be repeated `N` times (set with the `retries` parameter) until a fit quality greater than or equal to `min_fit_quality` and a fit status code of 0 is obtained. If the fit does not succeed after `N` retries then all parameter values will be reverted to their state prior to the execution of the fit.

### Parameters

- **update** (*bool*) – Update the model dictionary for all sources with free parameters.
- **tol** (*float*) – Set the optimizer tolerance.
- **verbosity** (*int*) – Set the optimizer output level.
- **optimizer** (*str*) – Set the likelihood optimizer (e.g. MINUIT or NEWMINUIT).
- **retries** (*int*) – Set the number of times to rerun the fit when the fit quality is < 3.
- **min\_fit\_quality** (*int*) – Set the minimum fit quality. If the fit quality is smaller than this value then all model parameters will be restored to their values prior to the fit.
- **reoptimize** (*bool*) – Refit background sources when updating source properties (TS and likelihood profiles).

**Returns** `fit` – Dictionary containing diagnostic information from the fit (fit quality, parameter covariances, etc.).

**Return type** `dict`

## ROI Optimization

The *optimize* method performs an automatic optimization of the ROI by fitting all sources with an iterative strategy.

```
>>> o = gta.optimize()
```

It is generally good practice to run this method once at the start of your analysis to ensure that all parameters are close to their global likelihood maxima.

Table 21: *optimization* Output Dictionary

Key	Type	Description
loglike1	float	Post-optimization log-likelihood value.
loglike0	float	Pre-optimization log-likelihood value.
config	dict	Copy of input configuration to this method.
dloglike	float	Improvement in log-likelihood value.

## Reference/API

GTAnalysis.**optimize** (\*\*kwargs)

Iteratively optimize the ROI model. The optimization is performed in three sequential steps:

- Free the normalization of the N largest components (as determined from NPred) that contain a fraction `npred_frac` of the total predicted counts in the model and perform a simultaneous fit of the normalization parameters of these components.
- Individually fit the normalizations of all sources that were not included in the first step in order of their `npred` values. Skip any sources that have `NPred < npred_threshold`.
- Individually fit the shape and normalization parameters of all sources with `TS > shape_ts_threshold` where TS is determined from the first two steps of the ROI optimization.

To ensure that the model is fully optimized this method can be run multiple times.

### Parameters

- **npred\_frac** (*float*) – Threshold on the fractional number of counts in the N largest components in the ROI. This parameter determines the set of sources that are fit in the first optimization step.
- **npred\_threshold** (*float*) – Threshold on the minimum number of counts of individual sources. This parameter determines the sources that are fit in the second optimization step.
- **shape\_ts\_threshold** (*float*) – Threshold on source TS used for determining the sources that will be fit in the third optimization step.
- **max\_free\_sources** (*int*) – Maximum number of sources that will be fit simultaneously in the first optimization step.
- **skip** (*list*) – List of str source names to skip while optimizing.
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

## 1.3.6 Customizing the Model

The ROIModel class is responsible for managing the source and diffuse components in the ROI. Configuration of the model is controlled with the *model* block of YAML configuration file.

## Configuring Diffuse Components

The simplest configuration uses a single file for the galactic and isotropic diffuse components. By default the galactic diffuse and isotropic components will be named *galdiff* and *isodiff* respectively. An alias for each component will also be created with the name of the mapcube or file spectrum. For instance the galactic diffuse can be referred to as *galdiff* or *gll\_iem\_v06* in the following example.

```
model:
  src_roiwidth : 10.0
  galdiff      : '$FERMI_DIFFUSE_DIR/gll_iem_v06.fits'
  isodiff      : '$FERMI_DIFFUSE_DIR/isotropic_source_4years_P8V3.txt'
  catalogs    : ['gll_psc_v14.fit']
```

To define two or more galactic diffuse components you can optionally define the *galdiff* and *isodiff* parameters as lists. A separate component will be generated for each element in the list with the name *galdiffXX* or *isodiffXX* where *XX* is an integer position in the list.

```
model:
  galdiff :
    - '$FERMI_DIFFUSE_DIR/diffuse_component0.fits'
    - '$FERMI_DIFFUSE_DIR/diffuse_component1.fits'
```

To explicitly set the name of a component you can define any element as a dictionary containing *name* and *file* fields:

```
model:
  galdiff :
    - { 'name' : 'component0', 'file' : '$FERMI_DIFFUSE_DIR/diffuse_component0.fits' }
    - { 'name' : 'component1', 'file' : '$FERMI_DIFFUSE_DIR/diffuse_component1.fits' }
```

## Configuring Source Components

The list of sources for inclusion in the ROI model is set by defining a list of catalogs with the *catalogs* parameter. Catalog files can be in either XML or FITS format. Sources from the catalogs in this list that satisfy either the *src\_roiwidth* or *src\_radius* selections are added to the ROI model. If a source is defined in multiple catalogs the source definition from the last file in the catalogs list takes precedence.

```
model:
  src_radius: 5.0
  src_roiwidth: 10.0
  catalogs :
    - 'gll_psc_v16.fit'
    - 'extra_sources.xml'
```

Individual sources can also be defined within the configuration file with the *sources* parameter. This parameter contains a list of dictionaries that defines the spatial and spectral parameters of each source. The keys of the source dictionary map to the spectral and spatial source properties as they would be defined in the XML model file.

```
model:
  sources :
    - { name: 'SourceA', glon : 120.0, glat : -3.0,
        SpectrumType : 'PowerLaw', Index : 2.0, Scale : 1000, Prefactor : !!float 1e-11,
        SpatialModel: 'PointSource' }
    - { name: 'SourceB', glon : 122.0, glat : -3.0,
        SpectrumType : 'LogParabola', norm : !!float 1E-11, Scale : 1000, beta : 0.0,
        SpatialModel: 'PointSource' }
```

For parameters defined as scalars, the scale and value properties will be assigned automatically from the input value. To set these manually a parameter can also be initialized with a dictionary that explicitly sets the value and scale properties:

```
model:
  sources :
    - { name: 'SourceA', glon : 120.0, glat : -3.0,
        SpectrumType : 'PowerLaw', Index : 2.0, Scale : 1000,
        Prefactor : { value : 1.0, scale : !!float 1e-11, free : '0' },
        SpatialModel: 'PointSource' }
```

## Spatial Models

Fermipy supports four spatial models which are defined with the `SpatialModel` property:

- `PointSource` : A point source (`SkyDirFunction`).
- `RadialGaussian` : A symmetric 2D Gaussian with width parameter ‘Sigma’.
- `RadialDisk` : A symmetric 2D Disk with radius ‘Radius’.
- `SpatialMap` : An arbitrary 2D shape with morphology defined by a FITS template.

The spatial extension of `RadialDisk` and `RadialGaussian` can be controlled with the `SpatialWidth` parameter which sets the 68% containment radius in degrees. Note for ST releases prior to 11-01-01, `RadialDisk` and `RadialGaussian` sources will be represented with the `SpatialMap` type.

```
model:
  sources :
    - { name: 'PointSource', glon : 120.0, glat : 0.0,
        SpectrumType : 'PowerLaw', Index : 2.0, Scale : 1000, Prefactor : !!float 1e-11,
        SpatialModel: 'PointSource' }
    - { name: 'DiskSource', glon : 120.0, glat : 0.0,
        SpectrumType : 'PowerLaw', Index : 2.0, Scale : 1000, Prefactor : !!float 1e-11,
        SpatialModel: 'RadialDisk', SpatialWidth: 1.0 }
    - { name: 'GaussSource', glon : 120.0, glat : 0.0,
        SpectrumType : 'PowerLaw', Index : 2.0, Scale : 1000, Prefactor : !!float 1e-11,
        SpatialModel: 'RadialGaussian', SpatialWidth: 1.0 }
    - { name: 'MapSource', glon : 120.0, glat : 0.0,
        SpectrumType : 'PowerLaw', Index : 2.0, Scale : 1000, Prefactor : !!float 1e-11,
        SpatialModel: 'SpatialMap', Spatial_Filename : 'template.fits' }
```

## Editing the Model at Runtime

The model can be manually editing at runtime with the `add_source()` and `delete_source()` methods. Sources can be added either before or after calling `setup()` as shown in the following example.

```
from fermipy.gtanalysis import GTAnalysis

gta = GTAnalysis('config.yaml', logging={'verbosity' : 3})

# Remove isodiff from the model
gta.delete_source('isodiff')

# Add SourceA to the model
gta.add_source('SourceA', { 'glon' : 120.0, 'glat' : -3.0,
```

(continues on next page)

(continued from previous page)

```

        'SpectrumType' : 'PowerLaw', 'Index' : 2.0,
        'Scale' : 1000, 'Prefactor' : 1e-11,
        'SpatialModel' : 'PointSource' })

gta.setup()

# Add SourceB to the model
gta.add_source('SourceB',{ 'glon' : 121.0, 'glat' : -2.0,
        'SpectrumType' : 'PowerLaw', 'Index' : 2.0,
        'Scale' : 1000, 'Prefactor' : 1e-11,
        'SpatialModel' : 'PointSource' })

```

Sources added before calling `setup()` will be appended to the XML model definition. Sources added after calling `setup()` will be created dynamically through the `pyLikelihood` object creation mechanism.

### 1.3.7 Developer Notes

#### Creating a New Release

The following are steps for creating a new release:

1. Update the Changelog page (in `docs/changelog.rst`) with notes for the release and commit those changes.
2. Update documentation tables by running `make_tables.py` inside the `docs` subdirectory and commit any resulting changes to the configuration table files under `docs/config`.
3. Checkout `master` and ensure that you have pulled all commits from origin.
4. Create the release tag and push it to GitHub.

```

$ git tag -a XX.YY.ZZ -m ""
$ git push --tags

```

5. Upload the release to pypi.

```
$ python setup.py sdist upload -r pypi
```

6. Create a new release on conda-forge by opening a PR on the [fermipy-feedstock](#) repo. There is a fork of `fermipy-feedstock` in the `fermipy` organization that you can use for this purpose. Edit `recipe/meta.yaml` by entering the new package version and updating the sha256 hash to the value copied from the [pypi download](#) page. Update the package dependencies as necessary in the `run` section of `requirements`. Verify that `entry_points` contains the desired set of command-line scripts. Generally this section should match the contents `entry_points` in `setup.py`. Before merging the PR confirm that all tests have successfully passed.

### 1.3.8 Advanced Analysis Methods

This page documents some of the more advanced methods and features available in Fermipy:

- **TS Map**: Generate a test statistic (TS) map for a new source centered at each spatial bin in the ROI.
- **TS Cube**: Generate a TS map using the `gttscube` ST application. In addition to generating a TS map this method can also extract a test source likelihood profile as a function of energy and position over the whole ROI.
- **Residual Map**: Generate a residual map by evaluating the difference between smoothed data and model maps (residual) at each spatial bin in the ROI.

- *Source Finding*: Find new sources using an iterative source-finding algorithm. Adds new sources to the ROI by looking for peaks in the TS map.
- *SED Analysis*: Extract the spectral energy distribution of a source with the `sed` method. This method fits the source amplitude in a sequence of energy bins.
- *Light Curves*: Extract the lightcurve of a source with the `lightcurve` method. This method fits the source amplitude in a sequence of time bins.
- *Extension Fitting*: Fit the angular extension of a source with the `extension` method.
- *Source Localization*: Find the best-fit position of a source with the `localize` method.
- *Phased Analysis*: Instructions for performing a phased-selected analysis.
- *Sensitivity Tools*: Scripts and classes for estimating sensitivity.

## SED Analysis

The `sed()` method computes a spectral energy distribution (SED) by performing independent fits for the flux normalization of a source in bins of energy. The normalization in each bin is fit using a power-law spectral parameterization with a fixed index. The value of this index can be set with the `bin_index` parameter or allowed to vary over the energy range according to the local slope of the global spectral model (with the `use_local_index` parameter).

The `free_background`, `free_radius`, and `cov_scale` parameters control how nuisance parameters are dealt with in the fit. By default the method will fix the parameters of background components ROI when fitting the source normalization in each energy bin (`free_background=False`). Setting `free_background=True` will profile the normalizations of all background components that were free when the method was executed. In order to minimize overfitting, background normalization parameters are constrained with priors taken from the global fit. The strength of the priors is controlled with the `cov_scale` parameter. A larger (smaller) value of `cov_scale` applies a weaker (stronger) constraint on the background amplitude. Setting `cov_scale=None` performs an unconstrained fit without priors.

## Examples

The `sed()` method is executed by passing the name of a source in the ROI as a single argument. Additional keyword argument can also be provided to override the default configuration of the method:

```
# Run analysis with default energy binning
sed = gta.sed('sourceA')

# Override the energy binning and the assumed power-law index
# within the bin
sed = gta.sed('sourceA', loge_bins=[2.0,2.5,3.0,3.5,4.0,4.5,5.0], bin_index=2.3)

# Profile background normalization parameters with prior scale of 5.0
sed = gta.sed('sourceA', free_background=True, cov_scale=5.0)
```

By default the method will use the energy bins of the underlying analysis. The `loge_bins` keyword argument can be used to override the default binning with the restriction that the SED energy bins must align with the analysis bins. The bins used in the analysis can be found with `gta.log_energies`. For example if in the analysis 8 energy bins per decade are considered and you want to make the SED in 4 bins per decade you can specify `loge_bins=gta.log_energies[::2]`.

The return value of `sed()` is a dictionary with the results of the analysis. The following example shows how to extract values from the output dictionary and load the SED data from the output FITS file:

```
# Get the sed results from the return argument
sed = gta.sed('sourceA', outfile='sed.fits')

# Print the SED flux values
print(sed['flux'])

# Reload the SED table from the output FITS file
from astropy.table import Table
sed_tab = Table.read('sed.fits')
```

The contents of the FITS file and output dictionary are documented in *SED FITS File* and *SED Dictionary*.

## SED FITS File

The following table describes the contents of the FITS file written by `sed()`. The SED HDU uses that data format specification for SEDs documented [here](#).

Table 22: `sed` Output Dictionary

HDU	Column Name	Description
SED	e_min	Lower edges of SED energy bins (MeV).
SED	e_ref	Upper edges of SED energy bins (MeV).
SED	e_max	Centers of SED energy bins (MeV).
SED	ref_dnde	Differential flux of the reference model evaluated at the lower bin edge ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
SED	ref_dnde	Differential flux of the reference model evaluated at the upper bin edge ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
SED	ref_flux	Flux of the reference model in each bin ( $\text{cm}^{-2} \text{s}^{-1}$ ).
SED	ref_eflu	Energy flux of the reference model in each bin ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ).
SED	ref_dnde	Differential flux of the reference model evaluated at the bin center ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
SED	ref_npre	Number of predicted counts in the reference model in each bin.
SED	norm	Normalization in each bin in units of the reference model.
SED	norm_err	Symmetric error on the normalization in each bin in units of the reference model.
SED	norm_err	Lower 1-sigma error on the normalization in each bin in units of the reference model.
SED	norm_err	Upper 1-sigma error on the normalization in each bin in units of the reference model.
SED	norm_UL	Upper limit on the normalization in each bin in units of the reference model.
SED	loglike	Log-likelihood value of the model for the best-fit amplitude.
SED	norm_sca	Array of NxM normalization values for the profile likelihood scan in N energy bins and M scan points. A row-wise multiplication with any of <code>ref</code> columns can be used to convert this matrix to the respective unit.
SED	dloglike	Array of NxM delta-loglikelihood values for the profile likelihood scan in N energy bins and M scan points.
MODEL	Ebary	Energies at which the spectral band is evaluated (MeV).
MODEL	Ebary	Central value of spectral band ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
MODEL	Ebary_lo	Lower 1-sigma bound of spectral band ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
MODEL	Ebary_hi	Upper 1-sigma bound of spectral band ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
MODEL	Ebary_err	Symmetric error of spectral band ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
MODEL	Ebary_fer	Fractional width of spectral band.
PARAMS	name	Name of the parameter.
PARAMS	value	Value of the parameter.
PARAMS	error	1-sigma parameter error (nan indicates that the parameter was not included in the fit).
PARAMS	covarian	Covariance matrix among free parameters.
PARAMS	correlat	Correlation matrix among free parameters.



## SED Dictionary

The following table describes the contents of the `sed()` output dictionary:

Table 23: `sed` Output Dictionary

Key	Type	Description
<code>loge_min</code>	<code>ndarray</code>	Lower edges of SED energy bins ( $\log_{10}(E/\text{MeV})$ ).
<code>loge_max</code>	<code>ndarray</code>	Upper edges of SED energy bins ( $\log_{10}(E/\text{MeV})$ ).
<code>loge_ctr</code>	<code>ndarray</code>	Centers of SED energy bins ( $\log_{10}(E/\text{MeV})$ ).
<code>loge_ref</code>	<code>ndarray</code>	Reference energies of SED energy bins ( $\log_{10}(E/\text{MeV})$ ).
<code>e_min</code>	<code>ndarray</code>	Lower edges of SED energy bins (MeV).
<code>e_max</code>	<code>ndarray</code>	Upper edges of SED energy bins (MeV).
<code>e_ctr</code>	<code>ndarray</code>	Centers of SED energy bins (MeV).
<code>e_ref</code>	<code>ndarray</code>	Reference energies of SED energy bins (MeV).
<code>ref_flux</code>	<code>ndarray</code>	Flux of the reference model in each bin ( $\text{cm}^{-2} \text{s}^{-1}$ ).
<code>ref_eflux</code>	<code>ndarray</code>	Energy flux of the reference model in each bin ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ).
<code>ref_dnde</code>	<code>ndarray</code>	Differential flux of the reference model evaluated at the bin center ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
<code>ref_dnde_min</code>	<code>ndarray</code>	Differential flux of the reference model evaluated at the lower bin edge ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
<code>ref_dnde_max</code>	<code>ndarray</code>	Differential flux of the reference model evaluated at the upper bin edge ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
<code>ref_e2dnde</code>	<code>ndarray</code>	$E^2$ x the differential flux of the reference model evaluated at the bin center ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ).
<code>ref_npred</code>	<code>ndarray</code>	Number of predicted counts in the reference model in each bin.
<code>norm</code>	<code>ndarray</code>	Normalization in each bin in units of the reference model.
<code>flux</code>	<code>ndarray</code>	Flux in each bin ( $\text{cm}^{-2} \text{s}^{-1}$ ).
<code>eflux</code>	<code>ndarray</code>	Energy flux in each bin ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ).
<code>dnde</code>	<code>ndarray</code>	Differential flux in each bin ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ).
<code>e2dnde</code>	<code>ndarray</code>	$E^2$ x the differential flux in each bin ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ).
<code>dnde_err</code>	<code>ndarray</code>	1-sigma error on dnde evaluated from likelihood curvature.
<code>dnde_err_low</code>	<code>ndarray</code>	Lower 1-sigma error on dnde evaluated from the profile likelihood (MINOS errors).
<code>dnde_err_high</code>	<code>ndarray</code>	Upper 1-sigma error on dnde evaluated from the profile likelihood (MINOS errors).
<code>dnde_ul_95</code>	<code>ndarray</code>	95% CL upper limit on dnde evaluated from the profile likelihood (MINOS errors).
<code>dnde_ul</code>	<code>ndarray</code>	Upper limit on dnde evaluated from the profile likelihood using a <code>CL = ul_confidence</code> .
<code>e2dnde_err</code>	<code>ndarray</code>	1-sigma error on e2dnde evaluated from likelihood curvature.
<code>e2dnde_err_low</code>	<code>ndarray</code>	Lower 1-sigma error on e2dnde evaluated from the profile likelihood (MINOS errors).
<code>e2dnde_err_high</code>	<code>ndarray</code>	Upper 1-sigma error on e2dnde evaluated from the profile likelihood (MINOS errors).
<code>e2dnde_ul_95</code>	<code>ndarray</code>	95% CL upper limit on e2dnde evaluated from the profile likelihood (MINOS errors).
<code>e2dnde_ul</code>	<code>ndarray</code>	Upper limit on e2dnde evaluated from the profile likelihood using a <code>CL = ul_confidence</code> .
<code>ts</code>	<code>ndarray</code>	Test statistic.
<code>loglike</code>	<code>ndarray</code>	Log-likelihood of model for the best-fit amplitude.
<code>npred</code>	<code>ndarray</code>	Number of model counts.
<code>fit_quality</code>	<code>ndarray</code>	Fit quality parameter for MINUIT and NEWMINUIT optimizers (3 - Full accurate covariance matrix, 2 - Full matrix, but forced positive-definite (i.e. not accurate), 1 - Diagonal approximation only, not accurate, 0 - Error matrix not calculated at all).
<code>fit_status</code>	<code>ndarray</code>	Fit status parameter (0=ok).
<code>index</code>	<code>ndarray</code>	Spectral index of the power-law model used to fit this bin.
<code>norm_scan</code>	<code>ndarray</code>	Array of NxM normalization values for the profile likelihood scan in N energy bins and M scan points. A row-wise multiplication with any of <code>ref</code> columns can be used to convert this matrix to the respective unit.
<code>dloglik_scan</code>	<code>ndarray</code>	Array of NxM delta-loglikelihood values for the profile likelihood scan in N energy bins and M scan points.

Continued on next page



Table 23 – continued from previous page

Key	Type	Description
loglike_scan	ndarray	Array of NxM loglikelihood values for the profile likelihood scan in N energy bins and M scan points.
param_covariance	ndarray	Covariance matrix for the best-fit spectral parameters of the source.
param_names	ndarray	Array of names for the parameters in the global spectral parameterization of this source.
param_values	ndarray	Array of parameter values.
param_errors	ndarray	Array of parameter errors.
model_flux	dict	Dictionary containing the differential flux uncertainty band of the best-fit global spectral parameterization for the source.
config	dict	Copy of input configuration to this method.

## Configuration

The default configuration of the method is controlled with the `sed` section of the configuration file. The default configuration can be overridden by passing the option as a `kwargs` argument to the method.

Table 24: `sed` Options

Option	Default	Description
bin_index	20	Spectral index that will be use when fitting the energy distribution within an energy bin.
cov_scale	1.0	Scale factor that sets the strength of the prior on nuisance parameters that are free. Setting this to None disables the prior.
free_background	False	Leave background parameters free when performing the fit. If True then any parameters that are currently free in the model will be fit simultaneously with the source of interest.
free_parameters	None	Set the parameters of the source of interest that will be freed when performing the global fit. By default all parameters will be freed.
free_radius	None	Free normalizations of background sources within this angular distance in degrees from the source of interest. If None then no sources will be freed.
make_plots	False	Generate diagnostic plots.
ul_confidence	0.95	Confidence level for flux upper limit.
use_local_index	False	Use a power-law approximation to the shape of the global spectrum in each bin. If this is false then a constant index set to <code>bin_index</code> will be used.
write_fits	True	Write the output to a FITS file.
write_numpy	True	Write the output dictionary to a numpy file.

## Reference/API

`GTAnalysis.sed(name, **kwargs)`

Generate a spectral energy distribution (SED) for a source. This function will fit the normalization of the source in each energy bin. By default the SED will be generated with the analysis energy bins but a custom binning can be defined with the `log_e_bins` parameter.

### Parameters

- **name** (`str`) – Source name.
- **prefix** (`str`) – Optional string that will be prepended to all output files (FITS and rendered images).
- **log\_e\_bins** (`ndarray`) – Sequence of energies in  $\log_{10}(E/\text{MeV})$  defining the edges of the energy bins. If this argument is None then the analysis energy bins will be used. The energies in this sequence must align with the bin edges of the underlying analysis instance.

- **{options}** –
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** *sed* – Dictionary containing output of the SED analysis.

**Return type** *dict*

## Light Curves

*lightcurve()* fits the characteristics of a source (flux, TS, etc.) in a sequence of time bins. This method uses the data selection and model of a baseline analysis (e.g. the full mission) and is therefore restricted to analyzing time bins that are encompassed by the time selection of the baseline analysis. In general when using this method it is recommended to use a baseline time selection of at least several years or more to ensure the best characterization of background sources in the ROI.

When fitting a time bin the method will initialize the model to the current parameters of the baseline analysis. The parameters to be refit in each time bin may be controlled with *free\_background*, *free\_sources*, *free\_radius*, *free\_params*, and *shape\_ts\_threshold* options.

## Examples

```
# Generate a lightcurve with two bins
lc = gta.lightcurve('sourceA', nbins=2)

# Generate a lightcurve with 1-week binning
lc = gta.lightcurve('sourceA', binsz=86400.*7.0)

# Generate a lightcurve freeing sources within 3 deg of the source
# of interest
lc = gta.lightcurve('sourceA', binsz=86400.*7.0, free_radius=3.0)

# Generate a lightcurve with arbitrary MET binning
lc = gta.lightcurve('sourceA', time_bins=[239557414, 242187214, 250076614],
                    free_radius=3.0)
```

## Optimizing Computation Speed

By default the *lightcurve* method will run an end-to-end analysis in each time bin using the same processing steps as the baseline analysis. Depending on the data selection and ROI size each time bin may take 10-15 minutes to process. There are several options which can be used to reduce the *lightcurve* computation time. The *multithread* option splits the analysis of time bins across multiple cores:

```
# Split lightcurve across all available cores
lc = gta.lightcurve('sourceA', nbins=2, multithread=True)

# split lightcurve across 2 cores
lc = gta.lightcurve('sourceA', nbins=2, multithread=True, nthread=2)
```

Note that when using the *multithread* option in a computing cluster environment one should reserve the appropriate number of cores when submitting the job.

The *use\_scaled\_srcmap* option generates an approximate source map for each time bin by scaling the source map of the baseline analysis by the relative exposure.

```
# Enable scaled source map
lc = gta.lightcurve('sourceA', nbins=2, use_scaled_srcmap=True)
```

Enabling this option can speed up the lightcurve calculation by at least a factor of 2 or 3 at the cost of slightly reduced accuracy in the model evaluation. For point-source analysis on medium to long timescales (days to years) the additional systematic uncertainty incurred by using scaled source maps should be no more than 1-2%. For analysis of diffuse sources or short time scales (< day) one should verify the systematic uncertainty is less than the systematic uncertainty of the IRFs.

## Output

The following tables describe the contents of the method output:

Table 25: *lightcurve* Output

Key	Type	Description
name	str	Name of Source,
tmin	ndarray	Lower edge of time bin in MET.
tmax	ndarray	Upper edge of time bin in MET.
fit_success	bool	Did the likelihood fit converge? True if yes.
config	dict	Copy of the input configuration to this method.
ts_var	float	TS of variability. Should be distributed as $\chi^2$ with $n - 1$ degrees of freedom, where $n$ is the number of time bins.

Table 26: *lightcurve* Source Output

Key	Type	Description
param_names	ndarray	Names of spectral parameters.
param_values	ndarray	Spectral parameter values.
param_errors	ndarray	Spectral parameters errors.
ts	float	Source test statistic.
loglike	float	Log-likelihood of the model evaluated at the best-fit normalization of the source.
loglike_scan	ndarray	Log-likelihood values for scan of source normalization.
dloglike_scan	ndarray	Delta Log-likelihood values for scan of source normalization.
eflux_scan	ndarray	Energy flux values for scan of source normalization.
flux_scan	ndarray	Flux values for scan of source normalization.
norm_scan	ndarray	Normalization parameters values for scan of source normalization.
npred	float	Number of predicted counts from this source integrated over the analysis energy range.
npred_wt	float	Number of predicted counts from this source integrated over the analysis energy range.
pivot_energy	float	Decorrelation energy in MeV.
flux	float	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
flux100	float	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
flux1000	float	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
flux10000	float	Photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
flux_err	float	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
flux100_err	float	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
flux1000_err	float	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
flux10000_err	float	Photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
flux_ul95	float	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
flux100_ul95	float	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
flux1000_ul95	float	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.

Continued on next page

Table 26 – continued from previous page

Key	Type	Description
flux100001_u195	float	95% CL upper limit on the photon flux ( $\text{cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
eflux	float	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
eflux1000float	float	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
eflux1000float	float	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
eflux1000float	float	Energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
eflux_errfloat	float	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
eflux1000_errfloat	float	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
eflux1000_errfloat	float	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
eflux10000_errfloat	float	Energy flux uncertainty ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
eflux_u195float	float	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated over analysis energy range
eflux1000_u195float	float	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 100 MeV to 316 GeV.
eflux1000_u195float	float	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 1 GeV to 316 GeV.
eflux10000_u195float	float	95% CL upper limit on the energy flux ( $\text{MeV cm}^{-2} \text{s}^{-1}$ ) integrated from 10 GeV to 316 GeV.
dnde	float	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at the pivot energy.
dnde1000float	float	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 100 MeV.
dnde1000float	float	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 1 GeV.
dnde1000float	float	Differential photon flux ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 10 GeV.
dnde_errfloat	float	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at the pivot energy.
dnde1000_errfloat	float	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 100 MeV.
dnde1000_errfloat	float	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 1 GeV.
dnde1000_errfloat	float	Differential photon flux uncertainty ( $\text{cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$ ) evaluated at 10 GeV.
dnde_indexfloat	float	Logarithmic slope of the differential photon spectrum evaluated at the pivot energy.
dnde1000_indexfloat	float	Logarithmic slope of the differential photon spectrum evaluated at 100 MeV.
dnde1000_indexfloat	float	Logarithmic slope of the differential photon spectrum evaluated at 1 GeV.
dnde1000_indexfloat	float	Logarithmic slope of the differential photon spectrum evaluated at 10 GeV.

## Reference/API

GTAnalysis.**lightcurve** (*name*, *\*\*kwargs*)

Generate a lightcurve for the named source. The function will complete the basic analysis steps for each bin and perform a likelihood fit for each bin. Extracted values (along with errors) are Integral Flux, spectral model, Spectral index, TS value, pred. # of photons. Note: successful calculation of TS:subscript:var requires at least one free background parameter and a previously optimized ROI model.

### Parameters

- **name** (*str*) – source name
- **{options}** –

**Returns** **LightCurve** – Dictionary containing output of the LC analysis

**Return type** **dict**

## Extension Fitting

The `extension()` method executes a source extension analysis for a given source by computing a likelihood ratio test with respect to the no-extension (point-source) hypothesis and a best-fit model for extension. The best-fit extension is found by performing a likelihood profile scan over the source width (68% containment) and fitting for the extension that maximizes the model likelihood. Currently this method supports two models for extension: a 2D Gaussian (*RadialGaussian*) or a 2D disk (*RadialDisk*).

At runtime the default settings for the extension analysis can be overridden by passing one or more *kwargs* when executing `extension()`:

```
# Run extension fit of sourceA with default settings
>>> gta.extension('sourceA')

# Override default spatial model
>>> gta.extension('sourceA', spatial_model='RadialDisk')
```

By default the method will fix all background parameters before performing the extension fit. One can leave background parameters free by setting `free_background=True`:

```
# Free a nearby source that maybe be partially degenerate with the
# source of interest. The normalization of SourceB will be refit
# when testing the extension of sourceA
gta.free_norm('sourceB')
gta.extension('sourceA', free_background=True)

# Fix all background parameters when testing the extension
# of sourceA
gta.extension('sourceA', free_background=False)

# Free normalizations of sources within 2 degrees of sourceA
gta.extension('sourceA', free_radius=2.0)
```

The results of the extension analysis are written to a dictionary which is the return value of the extension method.

```
ext = gta.extension('sourceA', write_npy=True, write_fits=True)
```

The contents of the output dictionary are given in the following table:

Table 27: *extension* Output Dictionary

Key	Type	Description
name	str	Name of source.
file	str	Name of output FITS file.
config	dict	Copy of the input configuration to this method.
width	ndarray	Vector of width (intrinsic 68% containment radius) values (deg).
dloglik	ndarray	Delta-log-likelihood values for each point in the profile likelihood scan.
loglike	ndarray	Log-likelihood values for each point in the scan over the spatial extension.
loglike_ptsrc	float	Log-Likelihood value of the best-fit point-source model.
loglike_extsrc	float	Log-Likelihood of the best-fit extended source model.
loglike_fitinit	float	Log-Likelihood of model before extension fit.
loglike_fitset	float	Log-Likelihood of model after initial spectral fit.
ext	float	Best-fit extension (68% containment radius) (deg).
ext_err_hfloat	float	Upper (1-sigma) error on the best-fit extension (deg).
ext_err_lfloat	float	Lower (1-sigma) error on the best-fit extension (deg).
ext_err_float	float	Symmetric (1-sigma) error on the best-fit extension (deg).

Continued on next page

Table 27 – continued from previous page

Key	Type	Description
ext_ul95	float	95% CL upper limit on the spatial extension (deg).
ts_ext	float	Test statistic for the extension hypothesis.
ebin_e_min	ndarray	
ebin_e_center	ndarray	
ebin_e_max	ndarray	
ebin_ext	ndarray	Best-fit extension as measured in each energy bin (intrinsic 68% containment radius) (deg).
ebin_ext_err	ndarray	Symmetric (1-sigma) error on best-fit extension in each energy bin (deg).
ebin_ext_err_upper	ndarray	Upper (1-sigma) error on best-fit extension in each energy bin (deg).
ebin_ext_err_lower	ndarray	Lower (1-sigma) error on best-fit extension in each energy bin (deg).
ebin_ext_ul95	ndarray	95% CL upper limit on best-fit extension in each energy bin (deg).
ebin_ts_ext	ndarray	Test statistic for extension hypothesis in each energy bin.
ebin_dloglike	ndarray	Delta-log-likelihood values for scan over the spatial extension in each energy bin.
ebin_loglike	ndarray	Log-likelihood values for scan over the spatial extension in each energy bin.
ebin_loglike_pt	ndarray	Log-Likelihood value of the best-fit point-source model in each energy bin.
ebin_loglike_ext	ndarray	Log-Likelihood value of the best-fit extended source model in each energy bin.
ra	float	Right ascension of best-fit position (deg).
dec	float	Declination of best-fit position (deg).
glon	float	Galactic Longitude of best-fit position (deg).
glat	float	Galactic Latitude of best-fit position (deg).
ra_err	float	Std. deviation of positional uncertainty in right ascension (deg).
dec_err	float	Std. deviation of positional uncertainty in declination (deg).
glon_err	float	Std. deviation of positional uncertainty in galactic longitude (deg).
glat_err	float	Std. deviation of positional uncertainty in galactic latitude (deg).
pos_offset	float	Angular offset (deg) between the old and new (localized) source positions.
pos_err	float	1-sigma positional uncertainty (deg).
pos_r68	float	68% positional uncertainty (deg).
pos_r95	float	95% positional uncertainty (deg).
pos_r99	float	99% positional uncertainty (deg).
pos_err_semajor	float	1-sigma uncertainty (deg) along major axis of uncertainty ellipse.
pos_err_seminor	float	1-sigma uncertainty (deg) along minor axis of uncertainty ellipse.
pos_angle	float	Position angle of uncertainty ellipse with respect to major axis.
tmap	Map	
ptsrc_tmap	Map	
ptsrc_srm	Map	
ptsrc_bkg	Map	
ext_tot	Map	
ext_src	Map	
ext_bkg	Map	
source_fit	dict	Dictionary with parameters of the best-fit extended source model.

## Configuration

The default configuration of the method is controlled with the *extension* section of the configuration file. The default configuration can be overridden by passing the option as a *kwargs* argument to the method.

Table 28: *extension* Options

Option	Default	Description
fit_ebin	False	Perform a fit for the angular extension in each analysis energy bin.
fit_position	False	Perform a simultaneous fit to the source position and extension.
fix_shape	False	Fix spectral shape parameters of the source of interest. If True then only the normalization parameter will be fit.
free_background	False	Leave background parameters free when performing the fit. If True then any parameters that are currently free in the model will be fit simultaneously with the source of interest.
free_radius	None	Free normalizations of background sources within this angular distance in degrees from the source of interest. If None then no sources will be freed.
make_plots	False	Generate diagnostic plots.
make_tsm	True	Make a TS map for the source of interest.
psf_scaling	None	Tuple of two vectors (logE,f) defining an energy-dependent PSF scaling function that will be applied when building spatial models for the source of interest. The tuple (logE,f) defines the fractional corrections f at the sequence of energies logE = log10(E/MeV) where f=0 corresponds to no correction. The correction function f(E) is evaluated by linearly interpolating the fractional correction factors f in log(E). The corrected PSF is given by $P'(x;E) = P(x/(1+f(E));E)$ where x is the angular separation.
save_model	False	Save model counts cubes for the best-fit model of extension.
spatial_model	RadialGauss	Spatial model that will be used to test the source extension. The spatial scale parameter of the model will be set such that the 68% containment radius of the model is equal to the width parameter.
sqrt_ts_threshold	None	Threshold on sqrt(TS_ext) that will be applied when update is True. If None then no threshold is applied.
tsmap_fit	tsmap	Set the method for generating the TS map. Valid options are tsmap or tscube.
update	False	Update this source with the best-fit model for spatial extension if TS_ext > tsext_threshold.
width	None	Sequence of values in degrees for the likelihood scan over spatial extension (68% containment radius). If this argument is None then the scan points will be determined from width_min/width_max/width_nstep.
width_max	0	Maximum value in degrees for the likelihood scan over spatial extent.
width_min	0.01	Minimum value in degrees for the likelihood scan over spatial extent.
width_nstep	20	Number of scan points between width_min and width_max. Scan points will be spaced evenly on a logarithmic scale between width_min and width_max.
write_fits	True	Write the output to a FITS file.
write_numpy	True	Write the output dictionary to a numpy file.

## Reference/API

GTAnalysis.**extension** (*name*, *\*\*kwargs*)

Test this source for spatial extension with the likelihood ratio method (TS\_ext). This method will substitute an extended spatial model for the given source and perform a one-dimensional scan of the spatial extension parameter over the range specified with the width parameters. The 1-D profile likelihood is then used to compute the best-fit value, upper limit, and TS for extension. The nuisance parameters that will be simultaneously fit when performing the spatial scan can be controlled with the `fix_shape`, `free_background`, and `free_radius` options. By default the position of the source will be fixed to its current position. A simultaneous fit to position and extension can be performed by setting `fit_position` to True.

### Parameters

- **name** (*str*) – Source name.
- **{options}** –



- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** **extension** – Dictionary containing results of the extension analysis. The same dictionary is also saved to the dictionary of this source under ‘extension’.

**Return type** *dict*

## TS Map

*tsmap()* generates a test statistic (TS) map for an additional source component centered at each spatial bin in the ROI. The methodology is similar to that of the *gttsmap* ST application but with the following approximations:

- Evaluation of the likelihood is limited to pixels in the vicinity of the test source position.
- The background model is fixed when fitting the test source amplitude.

*TS Cube* is a related method that can also be used to generate TS maps as well as cubes (TS vs. position and energy).

For each spatial bin the method calculates the maximum likelihood test statistic given by

$$\text{TS} = 2 \sum_k \ln L(\mu, \theta | n_k) - \ln L(0, \theta | n_k)$$

where the summation index  $k$  runs over both spatial and energy bins,  $\mu$  is the test source normalization parameter, and  $\theta$  represents the parameters of the background model. The likelihood fitting implementation used by *tsmap()* only fits the test source normalization ( $\mu$ ). Shape parameters of the test source and parameters of background components are fixed to their current values.

## Examples

The spatial and spectral properties of the convolution kernel are defined with the *model* dictionary argument. The *model* dictionary format is the same as accepted by *add\_source()*.

```
# Generate TS map for a power-law point source with Index=2.0
model = {'Index' : 2.0, 'SpatialModel' : 'PointSource'}
maps = gta.tsmap('fit1', model=model)

# Generate TS map for a power-law point source with Index=2.0 and
# restricting the analysis to E > 3.16 GeV
model = {'Index' : 2.0, 'SpatialModel' : 'PointSource'}
maps = gta.tsmap('fit1_emin35', model=model, erange=[3.5, None])

# Generate TS maps for a power-law point source with Index=1.5, 2.0, and 2.5
model={'SpatialModel' : 'PointSource'}
maps = []
for index in [1.5, 2.0, 2.5]:
    model['Index'] = index
    maps += [gta.tsmap('fit1', model=model)]
```

The *multithread* option can be enabled to split the calculation across all available cores:

```
maps = gta.tsmap('fit1', model=model, multithread=True)
```

Note that care should be taken when using this option in an environment where the number of cores per process is restricted such as a batch farm.

*tsmap()* returns a *maps* dictionary containing *Map* representations of the TS and predicted counts (NPred) of the best-fit test source at each position.



```
model = {'Index' : 2.0, 'SpatialModel' : 'PointSource'}
maps = gta.tsmap('fit1',model=model)
print('TS at Pixel (50,50): ',maps['ts'].counts[50,50])
```

The contents of the output dictionary are given in the following table.

Key	Type	Description
amplitude	<a href="#">Map</a>	Best-fit test source amplitude expressed in terms of the spectral prefactor.
npred	<a href="#">Map</a>	Best-fit test source amplitude expressed in terms of the total model counts (Npred).
ts	<a href="#">Map</a>	Test source TS (twice the logLike difference between null and alternate hypothes).
sqrt_ts	<a href="#">Map</a>	Square-root of the test source TS.
file	str	Path to a FITS file containing the maps (TS, etc.) generated by this method.
src_dict	dict	Dictionary defining the properties of the test source.


The `write_fits` and `write_npy` options can be used to write the output to a FITS or numpy file. All output files are prepended with the `prefix` argument.

Diagnostic plots can be generated by setting `make_plots=True` or by passing the output dictionary to `make_residmap_plots`:

```
maps = gta.tsmap('fit1',model=model, make_plots=True)
gta.plotter.make_tsmap_plots(maps, roi=gta.roi)
```

This will generate the following plots:

- `tsmap_sqrt_ts`: Map of  $\sqrt{\text{TS}}$  values. The color map is truncated at 5 sigma with isocontours at 2 sigma intervals indicating values above this threshold.
- `tsmap_npred`: Map of best-fit source amplitude in counts.
- `tsmap_ts_hist`: Histogram of TS values for all points in the map. Overplotted is the reference distribution for chi-squared with one degree of freedom (expectation from Chernoff's theorem).



## Configuration

The default configuration of the method is controlled with the `tsmap` section of the configuration file. The default configuration can be overridden by passing the option as a `kwargs` argument to the method.

Table 29: *tmap* Options

Option	Default	Description
<code>exclude</code>	None	List of sources that will be removed from the model when computing the TS map.
<code>loge_bound</code>	None	Restrict the analysis to an energy range ( <code>emin,emax</code> ) in $\log_{10}(E/\text{MeV})$ that is a subset of the analysis energy range. By default the full analysis energy range will be used. If either <code>emin/emax</code> are None then only an upper/lower bound on the energy range will be applied.
<code>make_plots</code>	False	Generate diagnostic plots.
<code>max_kernel_radius</code>	2.0	Set the maximum radius of the test source kernel. Using a smaller value will speed up the TS calculation at the loss of accuracy.
<code>model</code>	None	Dictionary defining the spatial/spectral properties of the test source. If <code>model</code> is None the test source will be a <code>PointSource</code> with an Index 2 power-law spectrum.
<code>multithread</code>	False	Split the calculation across number of processes set by <code>nthread</code> option.
<code>nthread</code>	None	Number of processes to create when <code>multithread</code> is True. If None then one process will be created for each available core.
<code>write_fits</code>	True	Write the output to a FITS file.
<code>write_numpy</code>	True	Write the output dictionary to a numpy file.

## Reference/API

`GTAnalysis.tmap` (*prefix*=", \*\*kwargs)

Generate a spatial TS map for a source component with properties defined by the `model` argument. The TS map will have the same geometry as the ROI. The output of this method is a dictionary containing [Map](#) objects with the TS and amplitude of the best-fit test source. By default this method will also save maps to FITS files and render them as image files.

This method uses a simplified likelihood fitting implementation that only fits for the normalization of the test source. Before running this method it is recommended to first optimize the ROI model (e.g. by running `optimize()`).

### Parameters

- **prefix** (*str*) – Optional string that will be prepended to all output files.
- **{options}** –

**Returns** `tmap` – A dictionary containing the [Map](#) objects for TS and source amplitude.

**Return type** `dict`

## TS Cube

**Warning:** This method requires Fermi Science Tools version 11-04-00 or later.

`tscube()` can be used generate both test statistic (TS) maps and bin-by-bin scans of the test source likelihood as a function of spatial pixel and energy bin (likelihood cubes). The implementation is based on the `gttscube` ST application which uses an efficient newton optimization algorithm for fitting the test source at each pixel in the ROI.

The TS map output has the same format as TS maps produced by `tmap()` (see [TS Map](#) for further details). However while `tmap()` fixes the background model, `tscube()` can also fit background normalization parameters when scanning the test source likelihood. This method makes no approximations in the evaluation of the likelihood and may be somewhat slower than `tmap()` depending on the ROI dimensions and energy bounds.

For each spatial bin the method calculates the maximum likelihood test statistic given by

$$TS = 2 \sum_k \ln L(\mu, \hat{\theta}|n_k) - \ln L(0, \hat{\theta}|n_k)$$

where the summation index  $k$  runs over both spatial and energy bins,  $\mu$  is the test source normalization parameter, and  $\theta$  represents the parameters of the background model. Normalization parameters of the background model are refit at every test source position if they are free in the model. All other spectral parameters (indices etc.) are kept fixed.

## Examples

The method is executed by providing a `model` dictionary argument that defines the spectrum and spatial morphology of the test source:

```
# Generate TS cube for a power-law point source with Index=2.0
model = {'Index' : 2.0, 'SpatialModel' : 'PointSource'}
cube = gta.tscube('fit1', model=model)

# Generate TS cube for a power-law point source with Index=2.0 and
# restricting the analysis to E > 3.16 GeV
model = {'Index' : 2.0, 'SpatialModel' : 'PointSource'}
cube = gta.tscube('fit1_emin35', model=model, erange=[3.5, None])

# Generate TS cubes for a power-law point source with Index=1.5, 2.0, and 2.5
model={'SpatialModel' : 'PointSource'}
cubes = []
for index in [1.5, 2.0, 2.5]:
    model['Index'] = index
    cubes += [gta.tsmap('fit1', model=model)]
```

In addition to generating a TS map, this method can also extract a test source likelihood profile as a function of energy at every position in the ROI (likelihood cube). This information is saved to the `SCANDATA` HDU of the output FITS file:

```
from astropy.table import Table
cube = gta.tscube('fit1', model=model, do_sed=True)
tab_scan = Table.read(cube['file'], 'SCANDATA')
tab_ebounds = Table.read(cube['file'], 'EBOUNDS')

eflux_scan = tab_ebounds['REF_EFLUX'][None, :, None] * tab_scan['norm_scan']

# Plot likelihood for pixel 400 and energy bin 2
plt.plot(eflux_scan[400, 2], tab_scan['dloglike_scan'][400, 2])
```

The likelihood profile cube can be used to evaluate the likelihood for a test source with an arbitrary spectral model at any position in the ROI. The `TSCube` and `CastroData` classes can be used to analyze a TS cube:

```
from fermipy.castro import TSCube
tscube = TSCube.create_from_fits('tscube.fits')
cd = tscube.castroData_from_ipix(400)

# Fit the likelihoods at pixel 400 with different spectral models
cd.test_spectra()
```

## Configuration

The default configuration of the method is controlled with the `tscube` section of the configuration file. The default configuration can be overridden by passing the option as a `kwargs` argument to the method.

Table 30: `tscube` Options

Option	Default	Description
<code>cov_scale</code>	1.0	Scale factor to apply to broadband fitting cov. matrix in bin-by-bin fits ( $< 0 \rightarrow$ fixed )
<code>cov_scale_bb</code>	1.0	Scale factor to apply to global fitting cov. matrix in broadband fits. ( $< 0 \rightarrow$ no prior )
<code>do_sed</code>	True	Compute the energy bin-by-bin fits
<code>exclude</code>	None	List of sources that will be removed from the model when computing the TS map.
<code>init_lambda</code>	0	Initial value of damping parameter for newton step size calculation. A value of zero disables damping.
<code>max_iter</code>	30	Maximum number of iterations for the Newtons method fitter.
<code>model</code>	None	Dictionary defining the spatial/spectral properties of the test source. If model is None the test source will be a PointSource with an Index 2 power-law spectrum.
<code>nnorm</code>	10	Number of points in the likelihood v. normalization scan
<code>norm_sigma</code>	5.0	Number of sigma to use for the scan range
<code>remake_test_source</code>	False	If true, recomputes the test source image (otherwise just shifts it)
<code>st_scan_level</code>	0	Level to which to do ST-based fitting (for testing)
<code>tol</code>	0.001	Critetia for fit convergence (estimated vertical distance to min $< tol$ )
<code>tol_type</code>	0	Absoulte (0) or relative (1) criteria for convergence.

## Reference/API

`GTAnalysis.tscube` (*prefix*=", \*\*kwargs)

Generate a spatial TS map for a source component with properties defined by the `model` argument. This method uses the `gttscube` ST application for source fitting and will simultaneously fit the test source normalization as well as the normalizations of any background components that are currently free. The output of this method is a dictionary containing `Map` objects with the TS and amplitude of the best-fit test source. By default this method will also save maps to FITS files and render them as image files.

### Parameters

- **prefix** (*str*) – Optional string that will be prepended to all output files (FITS and rendered images).
- **model** (*dict*) – Dictionary defining the properties of the test source.
- **do\_sed** (*bool*) – Compute the energy bin-by-bin fits.
- **nnorm** (*int*) – Number of points in the likelihood v. normalization scan.
- **norm\_sigma** (*float*) – Number of sigma to use for the scan range.
- **tol** (*float*) – Critetia for fit convergence (estimated vertical distance to min  $< tol$  ).
- **tol\_type** (*int*) – Absoulte (0) or relative (1) criteria for convergence.
- **max\_iter** (*int*) – Maximum number of iterations for the Newton’s method fitter
- **remake\_test\_source** (*bool*) – If true, recomputes the test source image (otherwise just shifts it)
- **st\_scan\_level** (*int*) –
- **make\_plots** (*bool*) – Write image files.

- **write\_fits** (*bool*) – Write a FITS file with the results of the analysis.

**Returns** **maps** – A dictionary containing the *Map* objects for TS and source amplitude.

**Return type** *dict*

## Residual Map

*residmap()* calculates the residual between smoothed data and model maps. Whereas a TS map is only sensitive to positive deviations with respect to the model, *residmap()* is sensitive to both positive and negative residuals and therefore can be useful for assessing the model goodness-of-fit. The significance of the data/model residual at map position  $(i, j)$  is given by

$$\sigma_{ij}^2 = 2\text{sgn}(\tilde{n}_{ij} - \tilde{m}_{ij}) (\ln L_P(\tilde{n}_{ij}, \tilde{n}_{ij}) - \ln L_P(\tilde{n}_{ij}, \tilde{m}_{ij}))$$

$$\text{with } \tilde{m}_{ij} = \sum_k (m_k * f_k)_{ij} \quad \tilde{n}_{ij} = \sum_k (n_k * f_k)_{ij} \quad \ln L_P(n, m) = n \ln(m) - m$$

where  $n_k$  and  $m_k$  are the data and model maps at energy plane  $k$  and  $f_k$  is the convolution kernel. The convolution kernel is proportional to the counts expectation at a given pixel and normalized such that

$$f_{ijk} = s_{ijk} \left( \sum_{ijk} s_{ijk}^2 \right)^{-1}$$

where  $s$  is the expectation counts cube for a pure signal normalized to one.

## Examples

The spatial and spectral properties of the convolution kernel are defined with the *model* dictionary argument. All source models are supported as well as a gaussian kernel (defined by setting *SpatialModel* to *Gaussian*).

```
# Generate residual map for a Gaussian kernel with Index=2.0 and
# radius (R_68) of 0.3 degrees
model = {'Index' : 2.0,
        'SpatialModel' : 'Gaussian', 'SpatialWidth' : 0.3 }
maps = gta.residmap('fit1', model=model)

# Generate residual map for a power-law point source with Index=2.0 for
# E > 3.16 GeV
model = {'Index' : 2.0, 'SpatialModel' : 'PointSource'}
maps = gta.residmap('fit1_emin35', model=model, loge_bounds=[3.5, None])

# Generate residual maps for a power-law point source with Index=1.5, 2.0, and 2.5
model={'SpatialModel' : 'PointSource'}
maps = []
for index in [1.5, 2.0, 2.5]:
    model['Index'] = index
    maps += [gta.residmap('fit1', model=model)]
```

*residmap()* returns a *maps* dictionary containing *Map* representations of the residual significance and amplitude as well as the smoothed data and model maps. The contents of the output dictionary are described in the following table.

Key	Type	Description
sigma	<a href="#">Map</a>	Residual significance in sigma.
excess	<a href="#">Map</a>	Residual amplitude in counts.
data	<a href="#">Map</a>	Smoothed counts map.
model	<a href="#">Map</a>	Smoothed model map.
files	dict	File paths of the FITS image files generated by this method.
src_dict	dict	Source dictionary with the properties of the convolution kernel.


The `write_fits` and `write_numpy` options can be used to write the output to a FITS or numpy file. All output files are prepended with the `prefix` argument.

Diagnostic plots can be generated by setting `make_plots=True` or by passing the output dictionary to `make_residmap_plots`:

```
maps = gta.residmap('fit1', model=model, make_plots=True)
gta.plotter.make_residmap_plots(maps, roi=gta.roi)
```

This will generate the following plots:

- `residmap_excess`: Smoothed excess map (data-model).
- `residmap_data`: Smoothed data map.
- `residmap_model`: Smoothed model map.
- `residmap_sigma`: Map of residual significance. The color map is truncated at -5 and 5 sigma with labeled isocontours at 2 sigma intervals indicating values outside of this range.
- `residmap_sigma_hist`: Histogram of significance values for all points in the map. Overplotted are distributions for the best-fit Gaussian and a unit Gaussian.



## Configuration

The default configuration of the method is controlled with the `residmap` section of the configuration file. The default configuration can be overridden by passing the option as a `kwargs` argument to the method.

Table 31: *residmap* Options

Option	Default	Description
<code>exclude</code>	None	List of sources that will be removed from the model when computing the residual map.
<code>loge_bound</code>	None	Restrict the analysis to an energy range ( <code>emin,emax</code> ) in $\log_{10}(E/\text{MeV})$ that is a subset of the analysis energy range. By default the full analysis energy range will be used. If either <code>emin/emax</code> are None then only an upper/lower bound on the energy range will be applied.
<code>make_plots</code>	False	Generate diagnostic plots.
<code>model</code>	None	Dictionary defining the spatial/spectral properties of the test source. If <code>model</code> is None the test source will be a <code>PointSource</code> with an Index 2 power-law spectrum.
<code>use_weighted</code>	False	Used weighted version of maps in making plots.
<code>write_fits</code>	True	Write the output to a FITS file.
<code>write_numpy</code>	True	Write the output dictionary to a numpy file.

## Reference/API

`GTAnalysis.residmap` (*prefix*=", \*\*kwargs)

Generate 2-D spatial residual maps using the current ROI model and the convolution kernel defined with the `model` argument.

### Parameters

- **prefix** (*str*) – String that will be prefixed to the output residual map files.
- **{options}** –

**Returns** `maps` – A dictionary containing the `Map` objects for the residual significance and amplitude.

**Return type** `dict`

## Source Finding

`find_sources()` is an iterative source-finding algorithm that uses peak detection on a TS map to find new source candidates. The procedure for adding new sources at each iteration is as follows:

- Generate a TS map for the test source model defined with the `model` argument.
- Identify peaks with  $\text{sqrt}(\text{TS}) > \text{sqrt\_ts\_threshold}$  and an angular distance of at least `min_separation` from a higher amplitude peak in the map.
- Order the peaks by TS and add a source at each peak starting from the highest TS peak. Set the source position by fitting a 2D parabola to the log-likelihood surface around the peak maximum. After adding each source, re-fit its spectral parameters.
- Add sources at the N highest peaks up to `N = sources_per_iter`.

Source finding is repeated up to `max_iter` iterations or until no peaks are found in a given iteration. Sources found by the method are added to the model and given designations `PS JXXXX.X+XXXX` according to their position in celestial coordinates.

## Examples

```
model = {'Index' : 2.0, 'SpatialModel' : 'PointSource'}
srcs = gta.find_sources(model=model, sqrt_ts_threshold=5.0,
                        min_separation=0.5)
```

The method for generating the TS maps can be controlled with the `tmap_fitter` option. TS maps can be generated with either `tmap()` or `tscube()`.

## Reference/API

`GTAnalysis.find_sources` (*prefix=""*, *\*\*kwargs*)

An iterative source-finding algorithm that uses likelihood ratio (TS) maps of the region of interest to find new sources. After each iteration a new TS map is generated incorporating sources found in the previous iteration. The method stops when the number of iterations exceeds `max_iter` or no sources exceeding `sqrts_threshold` are found.

### Parameters

- `{options}` –
- `tmap` (*dict*) – Keyword arguments dictionary for `tmap` method.
- `tscube` (*dict*) – Keyword arguments dictionary for `tscube` method.

### Returns

- `peaks` (*list*) – List of peak objects.
- `sources` (*list*) – List of source objects.

## Source Localization

The `localize()` method can be used to spatially localize a source. Localization is performed by scanning the likelihood surface in source position in a local patch around the nominal source position. The fit to the source position proceeds in two iterations:

- **TS Map Scan:** Obtain a first estimate of the source position by generating a likelihood map of the region using the `tmap` method. In this step all background parameters are fixed to their nominal values. The size of the search region used for this step is set with the `dtheta_max` parameter.
- **Likelihood Scan:** Refine the position of the source by performing a scan of the likelihood surface in a box centered on the best-fit position found in the first iteration. The size of the search region is set to encompass the 99% positional uncertainty contour. This method uses a full likelihood fit at each point in the likelihood scan and will re-fit all free parameters of the model.

If a peak is found in the search region and the positional fit succeeds, the method will update the position of the source in the model to the new best-fit position.


## Examples

The localization method is executed by passing the name of a source as its argument. The method returns a python dictionary with the best-fit source position and localization errors and also saves the same information to FITS and numpy files.

```
>>> loc = gta.localize('3FGL J1722.7+6104', make_plots=True)
>>> print(loc['ra'], loc['dec'], loc['pos_r68'], loc['pos_r95'])
(260.53164555483784, 61.04493807148745, 0.14384100879403075, 0.23213050350030126)
```

When running with `make_plots=True` the method will save a diagnostic plot to the working directory with a visualization of the localization contours. The green and white contours show the uncertainty ellipse derived from the first and second iterations of the positional scan.





The default configuration for the localization analysis can be overridden by supplying one or more *kwargs*:

```
# Localize the source and update its properties in the model
# with the localized position
>>> o = gta.extension('3FGL J1722.7+6104', update=True)
```

By default all background parameters will be fixed when the positional fit is performed. One can choose to free background parameters with the `free_background` and `free_radius` options:

```
# Free a nearby source that may be partially degenerate with the
# source of interest
gta.free_norm('sourceB')
gta.localize('3FGL J1722.7+6104', free_background=True)

# Free normalizations of background sources within a certain
# distance of the source of interest
gta.localize('3FGL J1722.7+6104', free_radius=1.0)
```

The contents of the output dictionary are described in the following table:

Table 32: *localize* Output

Key	Type	Description
name	str	Name of source.
file	str	Name of output FITS file.
config	dict	Copy of the input configuration to this method.
ra	float	Right ascension of best-fit position (deg).
dec	float	Declination of best-fit position (deg).
glon	float	Galactic Longitude of best-fit position (deg).
glat	float	Galactic Latitude of best-fit position (deg).
xpix	float	Longitude pixel coordinate of best-fit position.
ypix	float	Latitude pixel coordinate of best-fit position.
deltax	float	Longitude offset from old position (deg).
deltay	float	Latitude offset from old position (deg).
skydir	SkyCoord	
ra_preloc	float	Right ascension of pre-localization position (deg).
dec_preloc	float	Declination of pre-localization position (deg).

Continued on next page

Table 32 – continued from previous page

Key	Type	Description
glon_preflcat		Galactic Longitude of pre-localization position (deg).
glat_preflcat		Galactic Latitude of pre-localization position (deg).
ra_err	float	Std. deviation of positional uncertainty in right ascension (deg).
dec_err	float	Std. deviation of positional uncertainty in declination (deg).
glon_err	float	Std. deviation of positional uncertainty in galactic longitude (deg).
glat_err	float	Std. deviation of positional uncertainty in galactic latitude (deg).
pos_offs	float	Angular offset (deg) between the old and new (localized) source positions.
pos_err	float	1-sigma positional uncertainty (deg).
pos_r68	float	68% positional uncertainty (deg).
pos_r95	float	95% positional uncertainty (deg).
pos_r99	float	99% positional uncertainty (deg).
pos_err_semimaj	float	1-sigma uncertainty (deg) along major axis of uncertainty ellipse.
pos_err_semimin	float	1-sigma uncertainty (deg) along minor axis of uncertainty ellipse.
pos_angle	float	Position angle of uncertainty ellipse with respect to major axis.
pos_ecc1	float	Eccentricity of uncertainty ellipse defined as $\sqrt{1-b^2/a^2}$ .
pos_ecc2	float	Eccentricity of uncertainty ellipse defined as $\sqrt{a^2/b^2-1}$ .
pos_gal_cov	ndarray	Covariance matrix of positional uncertainties in local projection in galactic coordinates.
pos_gal_cor	ndarray	Correlation matrix of positional uncertainties in local projection in galactic coordinates.
pos_cel_cov	ndarray	Covariance matrix of positional uncertainties in local projection in celestial coordinates.
pos_cel_cor	ndarray	Correlation matrix of positional uncertainties in local projection in celestial coordinates.
tmap	Map	
tmap_peak	Map	
loglike_fit	float	Log-Likelihood of model before localization.
loglike_base	float	Log-Likelihood of model after initial spectral fit.
loglike_flcat	float	Log-Likelihood of model after localization.
dloglike	float	Difference in log-likelihood before and after localization.
fit_success	bool	
fit_inbounds	bool	
fit_init	dict	
fit_scandict	dict	

## Configuration

Table 33: *localize* Options

Option	Default	Description
dtheta_max	0.5	Half-width of the search region in degrees used for the first pass of the localization search.
fix_shape	False	Fix spectral shape parameters of the source of interest. If True then only the normalization parameter will be fit.
free_background	False	Leave background parameters free when performing the fit. If True then any parameters that are currently free in the model will be fit simultaneously with the source of interest.
free_radius	None	Free normalizations of background sources within this angular distance in degrees from the source of interest. If None then no sources will be freed.
make_plots	False	Generate diagnostic plots.
nstep	5	Number of steps in longitude/latitude that will be taken when refining the source position. The bounds of the scan range are set to the 99% positional uncertainty as determined from the TS map peak fit. The total number of sampling points will be nstep**2.
tmap_fit	tmap	Set the method for generating the TS map. Valid options are tmap or tscube.
update	True	Update the source model with the best-fit position.
write_fit	True	Write the output to a FITS file.
write_numpy	True	Write the output dictionary to a numpy file.

## Reference/API

GTAnalysis.**localize** (*name*, **\*\*kwargs**)

Find the best-fit position of a source. Localization is performed in two steps. First a TS map is computed centered on the source with half-width set by `dtheta_max`. A fit is then performed to the maximum TS peak in this map. The source position is then further refined by scanning the likelihood in the vicinity of the peak found in the first step. The size of the scan region is set to encompass the 99% positional uncertainty contour as determined from the peak fit.

### Parameters

- **name** (*str*) – Source name.
- **{options}** –
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** **localize** – Dictionary containing results of the localization analysis.

**Return type** *dict*

## Phased Analysis

Fermipy provides several options to support analysis with selections on pulsar phase. The following examples assume that you already have a phased FT1 file that contains a PULSE\_PHASE column with the pulsar phase for each event.

The following examples illustrates the settings for the *gtlike* and *selection* sections of the configuration file that would be used for a single-component ON- or OFF-phase analysis:

```
selection :
  emin : 100
  emax : 316227.76
  zmax : 90
  evclass : 128
```

(continues on next page)

(continued from previous page)

```

evtype : 3
tmin   : 239557414
tmax   : 428903014
target : '3FGL J0534.5+2201p'
phasemin : 0.68
phasemax : 1.00

gtlike :
  edisp : True
  irfs : 'P8R2_SOURCE_V6'
  edisp_disable : ['isodiff', 'galdiff']
  expscale : 0.32

```

The `gtlike.expscale` parameter defines the correction that should be applied to the nominal exposure to account for the phase selection defined by `selection.phasemin` and `selection.phasemax`. Normally this should be set to the size of the phase selection interval.

To perform a joint analysis of multiple phase selections you can use the *components* section to define separate ON- and OFF-phase components:

```

components:
- selection : {phasemin : 0.68, phasemax: 1.0}
  gtlike    : {expscale : 0.32, src_expscale : {'3FGL J0534.5+2201p':0.0}}
- selection : {phasemin : 0.0 , phasemax: 0.68}
  gtlike     : {expscale : 0.68, src_expscale : {'3FGL J0534.5+2201p':1.0}}

```

The `src_expscale` parameter can be used to define an exposure correction for individual sources. In this example it is used to zero the pulsar component for the OFF-phase selection.

## Sensitivity Tools

The `fermipy-flux-sensitivity` script calculates the LAT flux threshold for a gamma-ray source in bins of energy (differential sensitivity) and integrated over the full LAT energy range (integral sensitivity). The source flux threshold is the flux at which the median TS of a source (twice the likelihood ratio of the best-fit model with and without the source) equals a certain value. Primary inputs to this script are the livetime cube (output of `gtlrcube`) and the model cube for the galactic diffuse background. The `obs_time_yr` option can be used to rescale the livetime cube to a shorter or longer observation time.

```

$ fermipy-flux-sensitivity --glon=30 --glat=30 --output=lat_sensitivity.fits \
--lrcube=lrcube.fits --galdiff=gll_iem_v06.fits --event_class=P8R2_SOURCE_V6 \
--ts_thresh=25.0 --min_counts=10.0

```

If no livetime cube is provided then the sensitivity will be computed assuming an “ideal” survey-mode operation with uniform exposure over the whole sky and no Earth obscuration or deadtime. By default the flux sensitivity will be calculated for a TS threshold of 25 and at least 3 counts.

A map of sensitivity with WCS or HEALPix pixelization can be generated by setting the `map_type` argument to either `wcs` or `hpx`:

```

# Generate a WCS sensitivity map of 50 x 50 deg centered at (glon, glat) = (30, 30)
$ fermipy-flux-sensitivity --glon=30 --glat=30 --output=lat_sensitivity_map.fits \
--lrcube=lrcube.fits --galdiff=gll_iem_v06.fits --event_class=P8R2_SOURCE_V6 \
--map_type=wcs --wcs_npix=100 --wcs_cdelt=0.5 --wcs_proj=AIT

# Generate a HPX sensitivity map of nside=16

```

(continues on next page)

(continued from previous page)

```
$ fermipy-flux-sensitivity --output=lat_sensitivity_map.fits \
--ltcube=ltcube.fits --galdiff=gll_iem_v06.fits --event_class=P8R2_SOURCE_V6 \
--map_type=hpx --hpx_nside=16
```

The integral and differential sensitivity maps will be written to the MAP\_INT\_FLUX and MAP\_DIFF\_FLUX extensions respectively.

By default the flux sensitivity will be computed for a point-source morphology. The assumed source morphology can be changed with the `spatial_model` and `spatial_size` parameters:

It is possible to choose among PowerLaw, LogParabola and PLSuperExpCutoff SED shapes using the option `sedshape`.

```
# Generate the sensitivity to a source with a 2D gaussian morphology
# and a 68% containment radius of 1 deg located at longitude 30deg and
# latitude 30 deg and with a PLSuperExpCutoff SED with index 2.0 and
# cutoff energy 10 GeV
$ fermipy-flux-sensitivity --output=lat_sensitivity_map.fits \
--ltcube=ltcube.fits --galdiff=gll_iem_v06.fits --event_class=P8R2_SOURCE_V6 \
--spatial_model=RadialGaussian --spatial_size=1.0 --glon=30 --glat=30
--sedshape=PLSuperExpCutoff --index=2.0 --cutoff=1e4

# Generate the sensitivity map in healpix with nside 128 of a point source with
# LogParabola SED and with spectral index 2.0 and curvature index beta=0.50
# between 1 and 10 GeV
$ fermipy-flux-sensitivity --output=lat_sensitivity_map.fits \
--ltcube=ltcube.fits --galdiff=gll_iem_v06.fits --event_class=P8R2_SOURCE_V6 \
--spatial_model=PointSource --sedshape=LogParabola --index=2.0 --beta=0.50 \
--hpx_nside=128 --map_type=hpx --emin=1000 --emax=10000
```

The output FITS file set with the `output` option contains the following tables. Note that MAP tables are only generated when the `map_type` argument is set.

- **DIFF\_FLUX** : Differential flux sensitivity for a gamma-ray source at sky position set by `glon` and `glat`.
- **INT\_FLUX** : Integral flux sensitivity evaluated for PowerLaw sources with spectral indices between 1.0 and 5.0 at sky position set by `glon` and `glat`. Columns starting with `ebin` contain the source amplitude vs. energy bin.
- **MAP\_DIFF\_FLUX** : Sky cube with differential flux threshold vs. sky position and energy.
- **MAP\_DIFF\_NPRED** : Sky cube with counts amplitude (NPred) of a source at the detection threshold vs. position and energy.
- **MAP\_INT\_FLUX** : Sky map with integral flux threshold vs. sky position. Integral sensitivity will be computed for a PowerLaw source with index equal to the `index` parameter.
- **MAP\_INT\_NPRED** : Sky map with counts amplitude (NPred) of a source at the detection threshold vs. sky position.

The output file can be read using the `Table` module:

```
from astropy.table import Table

tab = Table.read('lat_sensitivity.fits', 'DIFF_FLUX')
print(tab['e_min'], tab['e_max'], tab['flux'])
tab = Table.read('lat_sensitivity.fits', 'INT_FLUX')
print(tab['index'], tab['flux'])
```

### 1.3.9 Validation Tools

This page documents LAT validation tools.

#### Merit Skimmer

The `fermipy-merit-skimmer` script can be used to create skimmed Merit files (either MC or data) and serves as a replacement for the web-based merit skimmer tool. The script accepts as input a sequence of Merit file paths or lists of Merit file paths which can be either local (nfs) or xrootd.

```
$ fermipy-merit-skimmer merit_list.txt --output=merit.root --selection='FswGamFilter' \
↪ \
--aliases=aliases.yaml

$ fermipy-merit-skimmer merit_list.txt --output=merit-clean.root \
--selection='FswGamFilter && CLEAN' --aliases=EvtClassDefs_P8R2.xml
```

where `merit_list.txt` is a text file with one path per line. The `--selection` option sets the selection that will be applied when filtering events in each file. The `--output` option sets the path to the output merit file. The `--aliases` option can be used to load an alias file (set of key/value cut expression pairs). This option can accept either a YAML alias file or an XML event class definition file. The following illustrates the YAML alias file format:

```
FswGamFilter : FswGamState == 0
TracksCutFilter : FswGamState == 0 && TkrNumTracks > 0
CalEnergyFilter : FswGamState == 0 && CalEnergyRaw > 0
```

One can restrict the set of output branches with the `--branches` option which accepts an alias file or a YAML file containing a list of branch names. In the former case all branch names used in the given alias set will be extracted and added to the list of output branches.

```
$ fermipy-merit-skimmer merit_list.txt --output=merit.root --selection='FswGamFilter' \
↪ \
--aliases=EvtClassDefs_P8R2.xml --branches=EvtClassDefs_P8R2.xml
```

One can split the skimming task into separate batch jobs by running with the `--batch` option. This will subdivide task into N jobs when N is the number of files in the list divided by `--files_per_job`. The name of the output ROOT file of each job will be appended with the index of the job in the sequence (e.g. `skim_000.root`, `skim_001.root`, etc.). The `--time` and `--resources` options can be used to set the LSF wallclock time and resource flags.

```
$ fermipy-merit-skimmer merit_list.txt --output=merit.root --selection='SOURCE && \
↪ FRONT' \
--branches=EvtClassDefs_P8R2.xml --files_per_job=1000 --batch --aliases=EvtClassDefs_
↪ P8R2.xml
```

When skimming MC files it can be useful to extract the `jobinfo` for tracking the number of thrown events. The `--extra_trees` option can be used to copy one or more trees to the output file in addition to the Merit Tuple:

```
$ fermipy-merit-skimmer merit_list.txt --output=merit.root --extra_trees=jobinfo
```

### 1.3.10 fermipy package

**fermipy.config module****class** fermipy.config.ConfigManagerBases: `object`**classmethod** `create` (*configfile*)

Create a configuration dictionary from a yaml config file. This function will first populate the dictionary with defaults taken from pre-defined configuration files. The configuration dictionary is then updated with the user-defined configuration file. Any settings defined by the user will take precedence over the default settings.

**static** `load` (*path*)**class** fermipy.config.ConfigSchema (*options=None, \*\*kwargs*)Bases: `object`

Class encapsulating a configuration schema.

**add\_option** (*name, default\_value, helpstr="", otype=None*)**add\_section** (*name, section*)**create\_config** (*config=None, validate=True, \*\*kwargs*)**items** ()**class** fermipy.config.Configurable (*config, \*\*kwargs*)Bases: `object`

The base class provides common facilities like loading and saving configuration state.

**config**

Return the configuration dictionary of this class.

**configdir****configure** (*config, \*\*kwargs*)**classmethod** `get_config` ()

Return a default configuration dictionary for this class.

**print\_config** (*logger, loglevel=None*)**schema**

Return the configuration schema of this class.

**write\_config** (*outfile*)

Write the configuration dictionary to an output file.

fermipy.config.**cast\_config** (*config, defaults*)fermipy.config.**create\_default\_config** (*schema*)

Create a configuration dictionary from a schema dictionary. The schema defines the valid configuration keys and their default values. Each element of `schema` should be a tuple/list containing (default value,docstring,type) or a dict containing a nested schema.

fermipy.config.**update\_from\_schema** (*cfg, cfgin, schema*)

Update configuration dictionary `cfg` with the contents of `cfgin` using the `schema` dictionary to determine the valid input keys.

**Parameters**

- **cfg** (*dict*) – Configuration dictionary to be updated.
- **cfgin** (*dict*) – New configuration dictionary that will be merged with `cfg`.

- **schema** (*dict*) – Configuration schema defining the valid configuration keys and their types.

**Returns** *cfgout*

**Return type** *dict*

`fermipy.config.validate_config(config, defaults, section=None)`

`fermipy.config.validate_from_schema(cfg, schema, section=None)`

`fermipy.config.validate_option(opt_name, opt_val, schema_type)`

## fermipy.defaults module

`fermipy.defaults.make_attrs_class(typename, d)`

`fermipy.defaults.make_default_dict(d)`

`fermipy.defaults.make_default_tuple(d)`

## fermipy.gtanalysis module

**class** `fermipy.gtanalysis.GTAnalysis` (*config, roi=None, \*\*kwargs*)

Bases: `fermipy.config.Configurable`, `fermipy.sed.SEDGenerator`, `fermipy.residmap.ResidMapGenerator`, `fermipy.tsmap.TSMapGenerator`, `fermipy.tsmap.TSCubeGenerator`, `fermipy.sourcefind.SourceFind`, `fermipy.extension.ExtensionFit`, `fermipy.lightcurve.LightCurve`

High-level analysis interface that manages a set of analysis component objects. Most of the functionality of the Fermipy package is provided through the methods of this class. The class constructor accepts a dictionary that defines the configuration for the analysis. Keyword arguments to the constructor can be used to override parameters in the configuration dictionary.

**add\_gauss\_prior** (*name, parName, mean, sigma*)

**add\_source** (*name, src\_dict, free=None, init\_source=True, save\_source\_maps=True, use\_pylike=True, use\_single\_psf=False, \*\*kwargs*)

Add a source to the ROI model. This function may be called either before or after `setup`.

### Parameters

- **name** (*str*) – Source name.
- **src\_dict** (dict or *Source* object) – Dictionary or source object defining the source properties (coordinates, spectral parameters, etc.).
- **free** (*bool*) – Initialize the source with a free normalization parameter.
- **use\_pylike** (*bool*) – Create source maps with pyLikelihood.
- **use\_single\_psf** (*bool*) – Use the PSF model calculated for the ROI center. If false then a new model will be generated using the position of the source.

**add\_sources\_from\_roi** (*names, roi, free=False, \*\*kwargs*)

Add multiple sources to the current ROI model copied from another ROI model.

### Parameters

- **names** (*list*) – List of str source names to add.
- **roi** (*ROIModel* object) – The roi model from which to add sources.



- **free** (*bool*) – Initialize the source with a free normalization paramter.

**bowtie** (*name*, *fd=None*, *loge=None*)

Generate a spectral uncertainty band (bowtie) for the given source. This will create an uncertainty band on the differential flux as a function of energy by propagating the errors on the global fit parameters. Note that this band only reflects the uncertainty for parameters that are currently free in the model.

#### Parameters

- **name** (*str*) – Source name.
- **fd** (*FluxDensity*) – Flux density object. If this parameter is None then one will be created.
- **loge** (*array-like*) – Sequence of energies in log10(E/MeV) at which the flux band will be evaluated.

**cleanup** ()

**clone** (*config*, *\*\*kwargs*)

Make a clone of this analysis instance.

**components**

Return the list of analysis components.

**compute\_drm** (*edisp\_bins=1*, *overwrite=False*)

Run the gtdrm app

**compute\_psf** (*overwrite=False*)

Run the gtpsf app

**compute\_srcprob** (*xmlfile=None*, *overwrite=False*)

Run the gtsrcprob app with the current model or a user provided xmlfile

**config**

Return the configuration dictionary of this class.

**configdir**

**configure** (*config*, *\*\*kwargs*)

**constrain\_norms** (*srcNames*, *cov\_scale=1.0*)

Constrain the normalizations of one or more sources by adding gaussian priors with sigma equal to the parameter error times a scaling factor.

**counts\_map** ()

Return a [Map](#) representation of the counts map.

**Returns map**

**Return type** [Map](#)

**classmethod create** (*infile*, *config=None*, *params=None*, *mask=None*)

Create a new instance of GTAnalysis from an analysis output file generated with `write_roi`. By default the new instance will inherit the configuration of the saved analysis instance. The configuration may be overridden by passing a configuration file path with the `config` argument.

#### Parameters

- **infile** (*str*) – Path to the ROI results file.
- **config** (*str*) – Path to a configuration file. This will override the configuration in the ROI results file.
- **params** (*str*) – Path to a yaml file with updated parameter values

- **mask** (*str*) – Path to a fits file with an updated mask

**create\_roi\_table** ()

**curvature** (*name*, *\*\*kwargs*)

Test whether a source shows spectral curvature by comparing the likelihood ratio of PowerLaw and Log-Parabola spectral models.

**Parameters** *name* (*str*) – Source name.

**defaults** = {'binning': {'binsperdec': (8, 'Number of energy bins per decade.', <class

**delete\_source** (*name*, *save\_template=True*, *delete\_source\_map=False*, *build\_fixed\_wts=True*, *\*\*kwargs*)

Delete a source from the ROI model.

**Parameters**

- **name** (*str*) – Source name.
- **save\_template** (*bool*) – Keep the SpatialMap FITS template associated with this source.
- **delete\_source\_map** (*bool*) – Delete the source map associated with this source from the source maps file.

**Returns** *src* – The deleted source object.

**Return type** *Model*

**delete\_sources** (*cuts=None*, *distance=None*, *skydir=None*, *minmax\_ts=None*, *minmax\_npred=None*, *exclude=None*, *square=False*, *names=None*)

Delete sources in the ROI model satisfying the given selection criteria.

**Parameters**

- **cuts** (*dict*) – Dictionary of [min,max] selections on source properties.
- **distance** (*float*) – Cut on angular distance from *skydir*. If None then no selection will be applied.
- **skydir** (*SkyCoord*) – Reference sky coordinate for *distance* selection. If None then the distance selection will be applied with respect to the ROI center.
- **minmax\_ts** (*list*) – Select sources that have TS in the range [min,max]. If either min or max are None then only a lower (upper) bound will be applied. If this parameter is none no selection will be applied.
- **minmax\_npred** (*list*) – Select sources that have npred in the range [min,max]. If either min or max are None then only a lower (upper) bound will be applied. If this parameter is none no selection will be applied.
- **square** (*bool*) – Switch between applying a circular or square (ROI-like) selection on the maximum projected distance from the ROI center.
- **names** (*list*) – Select sources matching a name in this list.

**Returns** *srcs* – A list of *Model* objects.

**Return type** *list*

**delete\_workdir** ()

**energies**

Return the energy bin edges in MeV.

**enumbins**

Return the number of energy bins.

**extension** (*name*, *\*\*kwargs*)

Test this source for spatial extension with the likelihood ratio method (TS\_ext). This method will substitute an extended spatial model for the given source and perform a one-dimensional scan of the spatial extension parameter over the range specified with the width parameters. The 1-D profile likelihood is then used to compute the best-fit value, upper limit, and TS for extension. The nuisance parameters that will be simultaneously fit when performing the spatial scan can be controlled with the `fix_shape`, `free_background`, and `free_radius` options. By default the position of the source will be fixed to its current position. A simultaneous fit to position and extension can be performed by setting `fit_position` to True.

**Parameters**

- **name** (*str*) – Source name.
- **{options}** –
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** **extension** – Dictionary containing results of the extension analysis. The same dictionary is also saved to the dictionary of this source under ‘extension’.

**Return type** *dict*

**files****find\_sources** (*prefix*=”, *\*\*kwargs*)

An iterative source-finding algorithm that uses likelihood ratio (TS) maps of the region of interest to find new sources. After each iteration a new TS map is generated incorporating sources found in the previous iteration. The method stops when the number of iterations exceeds `max_iter` or no sources exceeding `sqrt_ts_threshold` are found.

**Parameters**

- **{options}** –
- **tmap** (*dict*) – Keyword arguments dictionary for tmap method.
- **tscube** (*dict*) – Keyword arguments dictionary for tscube method.

**Returns**

- **peaks** (*list*) – List of peak objects.
- **sources** (*list*) – List of source objects.

**fit** (*update*=True, *\*\*kwargs*)

Run the likelihood optimization. This will execute a fit of all parameters that are currently free in the model and update the characteristics of the corresponding model components (TS, npred, etc.). The fit will be repeated N times (set with the `retries` parameter) until a fit quality greater than or equal to `min_fit_quality` and a fit status code of 0 is obtained. If the fit does not succeed after N retries then all parameter values will be reverted to their state prior to the execution of the fit.

**Parameters**

- **update** (*bool*) – Update the model dictionary for all sources with free parameters.
- **tol** (*float*) – Set the optimizer tolerance.
- **verbosity** (*int*) – Set the optimizer output level.
- **optimizer** (*str*) – Set the likelihood optimizer (e.g. MINUIT or NEWMINUIT).

- **retries** (*int*) – Set the number of times to rerun the fit when the fit quality is  $< 3$ .
- **min\_fit\_quality** (*int*) – Set the minimum fit quality. If the fit quality is smaller than this value then all model parameters will be restored to their values prior to the fit.
- **reoptimize** (*bool*) – Refit background sources when updating source properties (TS and likelihood profiles).

**Returns** **fit** – Dictionary containing diagnostic information from the fit (fit quality, parameter covariances, etc.).

**Return type** **dict**

**fit\_correlation**()

**free\_index** (*name*, *free=True*, *\*\*kwargs*)

Free/Fix index of a source.

**Parameters**

- **name** (*str*) – Source name.
- **free** (*bool*) – Choose whether to free (*free=True*) or fix (*free=False*).

**free\_norm** (*name*, *free=True*, *\*\*kwargs*)

Free/Fix normalization of a source.

**Parameters**

- **name** (*str*) – Source name.
- **free** (*bool*) – Choose whether to free (*free=True*) or fix (*free=False*).

**free\_parameter** (*name*, *par*, *free=True*)

Free/Fix a parameter of a source by name.

**Parameters**

- **name** (*str*) – Source name.
- **par** (*str*) – Parameter name.

**free\_shape** (*name*, *free=True*, *\*\*kwargs*)

Free/Fix shape parameters of a source.

**Parameters**

- **name** (*str*) – Source name.
- **free** (*bool*) – Choose whether to free (*free=True*) or fix (*free=False*).

**free\_source** (*name*, *free=True*, *pars=None*, *\*\*kwargs*)

Free/Fix parameters of a source.

**Parameters**

- **name** (*str*) – Source name.
- **free** (*bool*) – Choose whether to free (*free=True*) or fix (*free=False*) source parameters.
- **pars** (*list*) – Set a list of parameters to be freed/fixed for this source. If none then all source parameters will be freed/fixed with the exception of those defined in the *skip\_pars* list.

**free\_sources** (*free=True*, *pars=None*, *cuts=None*, *distance=None*, *skydir=None*, *minmax\_ts=None*, *minmax\_npred=None*, *exclude=None*, *square=False*, *\*\*kwargs*)

Free or fix sources in the ROI model satisfying the given selection. When multiple selections are defined,

the selected sources will be those satisfying the logical AND of all selections (e.g. `distance < X && minmax_ts[0] < ts < minmax_ts[1] && ...`).

#### Parameters

- **free** (*bool*) – Choose whether to free (`free=True`) or fix (`free=False`) source parameters.
- **pars** (*list*) – Set a list of parameters to be freed/fixed for each source. If none then all source parameters will be freed/fixed. If `pars='norm'` then only normalization parameters will be freed.
- **cuts** (*dict*) – Dictionary of [min,max] selections on source properties.
- **distance** (*float*) – Cut on angular distance from `skydir`. If None then no selection will be applied.
- **skydir** (*SkyCoord*) – Reference sky coordinate for `distance` selection. If None then the distance selection will be applied with respect to the ROI center.
- **minmax\_ts** (*list*) – Free sources that have TS in the range [min,max]. If either min or max are None then only a lower (upper) bound will be applied. If this parameter is none no selection will be applied.
- **minmax\_npred** (*list*) – Free sources that have npred in the range [min,max]. If either min or max are None then only a lower (upper) bound will be applied. If this parameter is none no selection will be applied.
- **exclude** (*list*) – Names of sources that will be excluded from the selection.
- **square** (*bool*) – Switch between applying a circular or square (ROI-like) selection on the maximum projected distance from the ROI center.

**Returns** `srcs` – A list of *Model* objects.

**Return type** *list*

**free\_sources\_by\_name** (*names, free=True, pars=None, \*\*kwargs*)

Free all sources with names matching *names*.

#### Parameters

- **names** (*list*) – List of source names.
- **free** (*bool*) – Choose whether to free (`free=True`) or fix (`free=False`) source parameters.
- **pars** (*list*) – Set a list of parameters to be freed/fixed for each source. If none then all source parameters will be freed/fixed. If `pars='norm'` then only normalization parameters will be freed.

**Returns** `srcs` – A list of *Model* objects.

**Return type** *list*

**generate\_model** (*model\_name=None*)

Generate model maps for all components. *model\_name* should be a unique identifier for the model. If *model\_name* is None then the model maps will be generated using the current parameters of the ROI.

**geom**

ROI geometry.

**classmethod** `get_config()`

Return a default configuration dictionary for this class.

`get_free_param_vector()`

`get_free_source_params(name)`

**get\_norm** (*name*)

**get\_params** (*freeonly=False*)

**get\_source\_dnde** (*name*)

Return differential flux distribution of a source. For sources with FileFunction spectral type this returns the internal differential flux array.

**Returns**

- **loge** (*ndarray*) – Array of energies at which the differential flux is evaluated ( $\log_{10}(E/\text{MeV})$ ).
- **dnde** (*ndarray*) – Array of differential flux values ( $\text{cm}^{-2} \text{ s}^{-1} \text{ MeV}^{-1}$ ) evaluated at energies in **loge**.

**get\_source\_name** (*name*)

Return the name of a source as it is defined in the pyLikelihood model object.

**get\_source\_params** (*name*)

**get\_sources** (*cuts=None, distance=None, skydir=None, minmax\_ts=None, minmax\_npred=None, exclude=None, square=False*)

Retrieve list of sources in the ROI satisfying the given selections.

**Returns** *srcs* – A list of *Model* objects.

**Return type** *list*

**get\_src\_model** (*name, paramsonly=False, reoptimize=False, npts=None, \*\*kwargs*)

Compose a dictionary for a source with the current best-fit parameters.

**Parameters**

- **name** (*str*) –
- **paramsonly** (*bool*) – Skip computing TS and likelihood profile.
- **reoptimize** (*bool*) – Re-fit background parameters in likelihood scan.
- **npts** (*int*) – Number of points for likelihood scan.

**Returns** *src\_dict*

**Return type** *dict*

**lightcurve** (*name, \*\*kwargs*)

Generate a lightcurve for the named source. The function will complete the basic analysis steps for each bin and perform a likelihood fit for each bin. Extracted values (along with errors) are Integral Flux, spectral model, Spectral index, TS value, pred. # of photons. Note: successful calculation of `TS:subscript:var` requires at least one free background parameter and a previously optimized ROI model.

**Parameters**

- **name** (*str*) – source name
- **{options}** –

**Returns** *LightCurve* – Dictionary containing output of the LC analysis

**Return type** *dict*

**like**

Return the global likelihood object.

**load\_parameters\_from\_yaml** (*yamlfile, update\_sources=False*)

Load model parameters from yaml

Parameters **yamfile** (*str*) – Name of the input yaml file.

**load\_roi** (*infile*, *reload\_sources=False*, *params=None*, *mask=None*)

This function reloads the analysis state from a previously saved instance generated with `write_roi`.

**Parameters**

- **infile** (*str*) –
- **reload\_sources** (*bool*) – Regenerate source maps for non-diffuse sources.
- **params** (*str*) – Path to a yaml file with updated parameter values
- **mask** (*str*) – Path to a fits file with an updated mask

**load\_xml** (*xmlfile*)

Load model definition from XML.

Parameters **xmlfile** (*str*) – Name of the input XML file.

**localize** (*name*, *\*\*kwargs*)

Find the best-fit position of a source. Localization is performed in two steps. First a TS map is computed centered on the source with half-width set by `dtheta_max`. A fit is then performed to the maximum TS peak in this map. The source position is then further refined by scanning the likelihood in the vicinity of the peak found in the first step. The size of the scan region is set to encompass the 99% positional uncertainty contour as determined from the peak fit.

**Parameters**

- **name** (*str*) – Source name.
- **{options}** –
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** **localize** – Dictionary containing results of the localization analysis.

**Return type** `dict`

**lock\_parameter** (*name*, *par*, *lock=True*)

Set parameter to locked/unlocked state. A locked parameter will be ignored when running methods that free/fix sources or parameters.

**Parameters**

- **name** (*str*) – Source name.
- **par** (*str*) – Parameter name.
- **lock** (*bool*) – Set parameter to locked (True) or unlocked (False) state.

**lock\_source** (*name*, *lock=True*)

Set all parameters of a source to a locked/unlocked state. Locked parameters will be ignored when running methods that free/fix sources or parameters.

**Parameters**

- **name** (*str*) – Source name.
- **lock** (*bool*) – Set source parameters to locked (True) or unlocked (False) state.

**log\_energies**

Return the energy bin edges in  $\log_{10}(E/\text{MeV})$ .

**loge\_bounds**

Current analysis energy bounds in  $\log_{10}(E/\text{MeV})$ .

**logger**

Return the default loglevel.

**loglevel**

Return the default loglevel.

**make\_plots** (*prefix*, *mcube\_map=None*, *\*\*kwargs*)

Make diagnostic plots using the current ROI model.

**make\_template** (*src*)**model\_counts\_map** (*name=None*, *exclude=None*, *use\_mask=False*)

Return the model counts map for a single source, a list of sources, or for the sum of all sources in the ROI. The exclude parameter can be used to exclude one or more components when generating the model map.

**Parameters**

- **name** (*str* or *list of str*) – Parameter controlling the set of sources for which the model counts map will be calculated. If name=None the model map will be generated for all sources in the ROI.
- **exclude** (*str* or *list of str*) – List of sources that will be excluded when calculating the model map.
- **use\_mask** (*bool*) – Parameter that specifies in the model counts map should include mask pixels (i.e., ones whose weights are  $\leq 0$ )

**Returns map**

Return type Map

**model\_counts\_spectrum** (*name*, *logemin=None*, *logemax=None*, *summed=False*, *weighted=False*)

Return the predicted number of model counts versus energy for a given source and energy range. If summed=True return the counts spectrum summed over all components otherwise return a list of model spectra. If weighted=True return the weighted version of the counts spectrum

**npix**

Return the number of energy bins.

**optimize** (*\*\*kwargs*)

Iteratively optimize the ROI model. The optimization is performed in three sequential steps:

- Free the normalization of the N largest components (as determined from NPred) that contain a fraction npred\_frac of the total predicted counts in the model and perform a simultaneous fit of the normalization parameters of these components.
- Individually fit the normalizations of all sources that were not included in the first step in order of their npred values. Skip any sources that have NPred < npred\_threshold.
- Individually fit the shape and normalization parameters of all sources with TS > shape\_ts\_threshold where TS is determined from the first two steps of the ROI optimization.

To ensure that the model is fully optimized this method can be run multiple times.

**Parameters**

- **npred\_frac** (*float*) – Threshold on the fractional number of counts in the N largest components in the ROI. This parameter determines the set of sources that are fit in the first optimization step.
- **npred\_threshold** (*float*) – Threshold on the minimum number of counts of individual sources. This parameter determines the sources that are fit in the second optimization step.



- **shape\_ts\_threshold** (*float*) – Threshold on source TS used for determining the sources that will be fit in the third optimization step.
- **max\_free\_sources** (*int*) – Maximum number of sources that will be fit simultaneously in the first optimization step.
- **skip** (*list*) – List of str source names to skip while optimizing.
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**outdir**

Return the analysis output directory.

**plotter**

Return the plotter instance.

**print\_config** (*logger, loglevel=None*)

**print\_model** (*loglevel=20*)

**print\_params** (*allpars=False, loglevel=20*)

Print information about the model parameters (values, errors, bounds, scale).

**print\_roi** (*loglevel=20*)

Print information about the spectral and spatial properties of the ROI (sources, diffuse components).

**profile** (*name, parName, logemin=None, logemax=None, reoptimize=False, xvals=None, npts=None, savestate=True, \*\*kwargs*)

Profile the likelihood for the given source and parameter.

**Parameters**

- **name** (*str*) – Source name.
- **parName** (*str*) – Parameter name.
- **reoptimize** (*bool*) – Re-fit nuisance parameters at each step in the scan. Note that enabling this option will only re-fit parameters that were free when the method was executed.

**Returns Inlprofile** – Dictionary containing results of likelihood scan.

**Return type** *dict*

**profile\_norm** (*name, logemin=None, logemax=None, reoptimize=False, xvals=None, npts=None, fix\_shape=True, savestate=True, \*\*kwargs*)

Profile the normalization of a source.

**Parameters**

- **name** (*str*) – Source name.
- **reoptimize** (*bool*) – Re-optimize free parameters in the model at each point in the profile likelihood scan.

**projtype**

Return the type of projection to use

**reload\_source** (*name, init\_source=True*)

Delete and reload a source in the model. This will update the spatial model of this source to the one defined in the XML model.

**reload\_sources** (*names, init\_source=True*)

**remove\_prior** (*name, parName*)

**remove\_priors** ()

Clear all priors.

**residmap** (*prefix*="", *\*\*kwargs*)

Generate 2-D spatial residual maps using the current ROI model and the convolution kernel defined with the `model` argument.

**Parameters**

- **prefix** (*str*) – String that will be prefixed to the output residual map files.
- **{options}** –

**Returns** **maps** – A dictionary containing the Map objects for the residual significance and amplitude.

**Return type** `dict`

**roi**

Return the ROI object.

**scale\_parameter** (*name*, *par*, *scale*)

**schema**

Return the configuration schema of this class.

**sed** (*name*, *\*\*kwargs*)

Generate a spectral energy distribution (SED) for a source. This function will fit the normalization of the source in each energy bin. By default the SED will be generated with the analysis energy bins but a custom binning can be defined with the `log_e_bins` parameter.

**Parameters**

- **name** (*str*) – Source name.
- **prefix** (*str*) – Optional string that will be prepended to all output files (FITS and rendered images).
- **log\_e\_bins** (*ndarray*) – Sequence of energies in  $\log_{10}(E/\text{MeV})$  defining the edges of the energy bins. If this argument is `None` then the analysis energy bins will be used. The energies in this sequence must align with the bin edges of the underlying analysis instance.
- **{options}** –
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** **sed** – Dictionary containing output of the SED analysis.

**Return type** `dict`

**set\_edisp\_flag** (*name*, *flag=True*)

Enable or disable the energy dispersion correction for the given source.

**set\_energy\_range** (*logemin*, *logemax*)

Set the energy bounds of the analysis. This restricts the evaluation of the likelihood to the data that falls in this range. Input values will be rounded to the closest bin edge value. If either argument is `None` then the lower or upper bound of the analysis instance will be used.

**Parameters**

- **logemin** (*float*) – Lower energy bound in  $\log_{10}(E/\text{MeV})$ .
- **logemax** (*float*) – Upper energy bound in  $\log_{10}(E/\text{MeV})$ .

**Returns** **eminmax** – Minimum and maximum energy in  $\log_{10}(E/\text{MeV})$ .

Return type array

**set\_free\_param\_vector** (*free*)

**set\_log\_level** (*level*)

**set\_norm** (*name*, *value*, *update\_source=True*)

**set\_norm\_bounds** (*name*, *bounds*)

**set\_norm\_scale** (*name*, *value*)

**set\_parameter** (*name*, *par*, *value*, *true\_value=True*, *scale=None*, *bounds=None*, *error=None*, *update\_source=True*)

Update the value of a parameter. Parameter bounds will automatically be adjusted to encompass the new parameter value.

#### Parameters

- **name** (*str*) – Source name.
- **par** (*str*) – Parameter name.
- **value** (*float*) – Parameter value. By default this argument should be the unscaled (True) parameter value.
- **scale** (*float*) – Parameter scale (optional). Value argument is interpreted with respect to the scale parameter if it is provided.
- **error** (*float*) – Parameter error (optional). By default this argument should be the unscaled (True) parameter value.
- **update\_source** (*bool*) – Update the source dictionary for the object.

**set\_parameter\_bounds** (*name*, *par*, *bounds*)

Set the bounds on the scaled value of a parameter.

#### Parameters

- **name** (*str*) – Source name.
- **par** (*str*) – Parameter name.
- **bounds** (*list*) – Upper and lower bound.

**set\_parameter\_error** (*name*, *par*, *error*)

Set the error on the value of a parameter.

#### Parameters

- **name** (*str*) – Source name.
- **par** (*str*) – Parameter name.
- **error** (*float*) – The value for the parameter error

**set\_parameter\_scale** (*name*, *par*, *scale*)

Update the scale of a parameter while keeping its value constant.

**set\_random\_seed** (*seed*)

Set the seed for the random number generator

**set\_source\_dnde** (*name*, *dnde*, *update\_source=True*)

Set the differential flux distribution of a source with the FileFunction spectral type.

#### Parameters

- **name** (*str*) – Source name.

- **dnde** (*ndarray*) – Array of differential flux values ( $\text{cm}^{-2} \text{ s}^{-1} \text{ MeV}^{-1}$ ).

**set\_source\_morphology** (*name*, *\*\*kwargs*)

Set the spatial model of a source.

#### Parameters

- **name** (*str*) – Source name.
- **spatial\_model** (*str*) – Spatial model name (PointSource, RadialGaussian, etc.).
- **spatial\_pars** (*dict*) – Dictionary of spatial parameters (optional).
- **use\_cache** (*bool*) – Generate the spatial model by interpolating the cached source map.
- **use\_pylike** (*bool*) –

**set\_source\_spectrum** (*name*, *spectrum\_type*='PowerLaw', *spectrum\_pars*=None, *update\_source*=True)

Set the spectral model of a source. This function can be used to change the spectral type of a source or modify its spectral parameters. If called with *spectrum\_type*='FileFunction' and *spectrum\_pars*=None, the source spectrum will be replaced with a FileFunction with the same differential flux distribution as the original spectrum.

#### Parameters

- **name** (*str*) – Source name.
- **spectrum\_type** (*str*) – Spectrum type (PowerLaw, etc.).
- **spectrum\_pars** (*dict*) – Dictionary of spectral parameters (optional).
- **update\_source** (*bool*) – Recompute all source characteristics (flux, TS, NPred) using the new spectral model of the source.

**set\_weights\_map** (*wmap*, *update\_roi*=True)

**setup** (*init\_sources*=True, *overwrite*=False, *\*\*kwargs*)

Run pre-processing for each analysis component and construct a joint likelihood object. This function performs the following tasks: data selection (gtselect, gtmktime), data binning (gtbin), and model generation (gtexpcube2, gtsrcmaps).

#### Parameters

- **init\_sources** (*bool*) – Choose whether to compute properties (flux, TS, etc.) for individual sources.
- **overwrite** (*bool*) – Run all pre-processing steps even if the output file of that step is present in the working directory. By default this function will skip any steps for which the output file already exists.

**simulate\_roi** (*name*=None, *randomize*=True, *restore*=False)

Generate a simulation of the ROI using the current best-fit model and replace the data counts cube with this simulation. The simulation is created by generating an array of Poisson random numbers with expectation values drawn from the model cube of the binned analysis instance. This function will update the counts cube both in memory and in the source map file. The counts cube can be restored to its original state by calling this method with *restore* = True.

#### Parameters

- **name** (*str*) – Name of the model component to be simulated. If None then the whole ROI will be simulated.
- **restore** (*bool*) – Restore the data counts cube to its original state.

**simulate\_source** (*src\_dict=None*)

Inject simulated source counts into the data.

**Parameters** **src\_dict** (*dict*) – Dictionary defining the spatial and spectral properties of the source that will be injected.

**stage\_input** ()

Copy input files to working directory.

**stage\_output** ()

Copy data products to final output directory.

**tmax**

Return the MET time for the end of the observation.

**tmin**

Return the MET time for the start of the observation.

**tscube** (*prefix=*”, *\*\*kwargs*)

Generate a spatial TS map for a source component with properties defined by the `model` argument. This method uses the `gttscube` ST application for source fitting and will simultaneously fit the test source normalization as well as the normalizations of any background components that are currently free. The output of this method is a dictionary containing *Map* objects with the TS and amplitude of the best-fit test source. By default this method will also save maps to FITS files and render them as image files.

#### Parameters

- **prefix** (*str*) – Optional string that will be prepended to all output files (FITS and rendered images).
- **model** (*dict*) – Dictionary defining the properties of the test source.
- **do\_sed** (*bool*) – Compute the energy bin-by-bin fits.
- **nnorm** (*int*) – Number of points in the likelihood v. normalization scan.
- **norm\_sigma** (*float*) – Number of sigma to use for the scan range.
- **tol** (*float*) – Criteria for fit convergence (estimated vertical distance to min < tol).
- **tol\_type** (*int*) – Absolute (0) or relative (1) criteria for convergence.
- **max\_iter** (*int*) – Maximum number of iterations for the Newton’s method fitter
- **remake\_test\_source** (*bool*) – If true, recomputes the test source image (otherwise just shifts it)
- **st\_scan\_level** (*int*) –
- **make\_plots** (*bool*) – Write image files.
- **write\_fits** (*bool*) – Write a FITS file with the results of the analysis.

**Returns** **maps** – A dictionary containing the *Map* objects for TS and source amplitude.

**Return type** *dict*

**tmap** (*prefix=*”, *\*\*kwargs*)

Generate a spatial TS map for a source component with properties defined by the `model` argument. The TS map will have the same geometry as the ROI. The output of this method is a dictionary containing *Map* objects with the TS and amplitude of the best-fit test source. By default this method will also save maps to FITS files and render them as image files.

This method uses a simplified likelihood fitting implementation that only fits for the normalization of the test source. Before running this method it is recommended to first optimize the ROI model (e.g. by running `optimize()`).

**Parameters**

- **prefix** (*str*) – Optional string that will be prepended to all output files.
- **{options}** –

**Returns** `tmap` – A dictionary containing the `Map` objects for TS and source amplitude.

**Return type** `dict`

**unzero\_source** (*name*, *\*\*kwargs*)

**update\_source** (*name*, *paramsonly=False*, *reoptimize=False*, *\*\*kwargs*)

Update the dictionary for this source.

**Parameters**

- **name** (*str*) –
- **paramsonly** (*bool*) –
- **reoptimize** (*bool*) – Re-fit background parameters in likelihood scan.

**weight\_map** ()

Return a `Map` representation of the weights map.

**Returns** `map`

**Return type** `Map`

**workdir**

Return the analysis working directory.

**write\_config** (*outfile*)

Write the configuration dictionary to an output file.

**write\_fits** (*fitsfile*)

**write\_model\_map** (*model\_name*, *name=None*)

Save the counts model map to a FITS file.

**Parameters**

- **model\_name** (*str*) – String that will be append to the name of the output file.
- **name** (*str*) – Name of the component.

**write\_roi** (*outfile=None*, *save\_model\_map=False*, *\*\*kwargs*)

Write current state of the analysis to a file. This method writes an XML model definition, a ROI dictionary, and a FITS source catalog file. A previously saved analysis state can be reloaded from the ROI dictionary file with the `load_roi` method.

**Parameters**

- **outfile** (*str*) – String prefix of the output files. The extension of this string will be stripped when generating the XML, YAML and npy filenames.
- **make\_plots** (*bool*) – Generate diagnostic plots.
- **save\_model\_map** (*bool*) – Save the current counts model to a FITS file.

**write\_weight\_map** (*model\_name*)

Save the counts model map to a FITS file.

Parameters **model\_name** (*str*) – String that will be append to the name of the output file.

**write\_xml** (*xmlfile*)

Save current model definition as XML file.

Parameters **xmlfile** (*str*) – Name of the output XML file.

**zero\_source** (*name*, *\*\*kwargs*)

## fermipy.logger module

**class** fermipy.logger.Logger

Bases: *object*

This class provides helper functions which facilitate creating instances of the built-in logger class.

**static configure** (*name*, *logfile*, *loglevel=10*)

Create a python logger instance and configure it.

Parameters

- **name** (*str*) – Logger name.
- **logfile** (*str*) – Path to the log file.
- **loglevel** (*int*) – Default log level for STDOUT.

**static setup** (*config=None*, *logfile=None*)

This method sets up the default configuration of the logger. Once this method is called all subsequent instances Logger instances will inherit this configuration.

**class** fermipy.logger.StreamLogger (*name='stdout'*, *logfile=None*, *quiet=True*)

Bases: *object*

File-like object to log stdout/stderr using the *logging* module.

**close** ()

**flush** ()

**write** (*msg*, *level=10*)

fermipy.logger.log\_level (*level*)

This is a function that returns a python like level from a HEASOFT like level.

## fermipy.roi\_model module

**class** fermipy.roi\_model.CompositeSource (*name*, *data*)

Bases: *fermipy.roi\_model.Model*

**diffuse**

**nested\_sources**

**write\_xml** (*root*)

**class** fermipy.roi\_model.IsoSource (*name*, *data*)

Bases: *fermipy.roi\_model.Model*

**diffuse**

**filefunction**

**write\_xml** (*root*, *\*\*kwargs*)

```
class fermipy.roi_model.MapCubeSource (name, data)
```

```
    Bases: fermipy.roi_model.Model
```

```
    diffuse
```

```
    mapcube
```

```
    write_xml (root, **kwargs)
```

```
class fermipy.roi_model.Model (name, data)
```

```
    Bases: object
```

Base class for point-like and diffuse source components. This class is a container for spectral and spatial parameters as well as other source properties such as TS, Npred, and location within the ROI.

```
    add_name (name)
```

```
    add_to_table (tab)
```

```
    assoc
```

```
    check_cuts (cuts)
```

```
    static create_from_dict (src_dict, roi_skydir=None, rescale=False)
```

```
    data
```

```
    get_catalog_dict ()
```

```
    get_norm ()
```

```
    is_free
```

```
        returns True if any of the spectral model parameters is set to free, else False
```

```
    items ()
```

```
    name
```

```
    names
```

```
    params
```

```
    psf_scale_fn
```

```
    set_name (name, names=None)
```

```
    set_psf_scale_fn (fn)
```

```
    set_spectral_pars (spectral_pars)
```

```
    spatial_pars
```

```
    spectral_pars
```

```
    update_data (d)
```

```
    update_from_source (src)
```

```
    update_spectral_pars (spectral_pars)
```

```
class fermipy.roi_model.ROIModel (config=None, **kwargs)
```

```
    Bases: fermipy.config.Configurable
```

This class is responsible for managing the ROI model (both sources and diffuse components). Source catalogs can be read from either FITS or XML files. Individual components are represented by instances of *Model* and can be accessed by name using the bracket operator.

- Create an ROI with all 3FGL sources and print a summary of its contents:



```
>>> skydir = astropy.coordinates.SkyCoord(0.0,0.0,unit='deg')
>>> roi = ROIModel({'catalogs' : ['3FGL'],'src_roiwidth' : 10.0},
↳skydir=skydir)
>>> print(roi)
name           SpatialModel  SpectrumType  offset  ts
↳ npred
-----
↳ -----
3FGL J2357.3-0150  PointSource  PowerLaw      1.956   nan
↳ 0.0
3FGL J0006.2+0135  PointSource  PowerLaw      2.232   nan
↳ 0.0
3FGL J0016.3-0013  PointSource  PowerLaw      4.084   nan
↳ 0.0
3FGL J0014.3-0455  PointSource  PowerLaw      6.085   nan
↳ 0.0
```

- Print a summary of an individual source

```
>>> print(roi['3FGL J0006.2+0135'])
Name           : 3FGL J0006.2+0135
Associations   : ['3FGL J0006.2+0135']
RA/DEC         :      1.572/      1.585
GLON/GLAT      :      100.400/     -59.297
TS             : nan
Npred          : nan
Flux           :      nan +/-      nan
EnergyFlux     :      nan +/-      nan
SpatialModel   : PointSource
SpectrumType   : PowerLaw
Spectral Parameters
Index          :      -2 +/-      nan
Scale          :      1000 +/-      nan
Prefactor      :      1e-12 +/-      nan
```

- Get the SkyCoord for a source

```
>>> dir = roi['SourceA'].skydir
```

- Loop over all sources and print their names

```
>>> for s in roi.sources: print(s.name)
3FGL J2357.3-0150
3FGL J0006.2+0135
3FGL J0016.3-0013
3FGL J0014.3-0455
```

**clear()**

Clear the contents of the ROI.

**copy\_source(name)**

**classmethod create(selection, config, \*\*kwargs)**

Create an ROIModel instance.

**create\_diffuse\_srcs(config)**

**classmethod** `create_from_position` (*skydir*, *config*, *\*\*kwargs*)

Create an ROIModel instance centered on a sky direction.

**Parameters**

- **skydir** (*SkyCoord*) – Sky direction on which the ROI will be centered.
- **config** (*dict*) – Model configuration dictionary.

**classmethod** `create_from_roi_data` (*datafile*)

Create an ROI model.

**classmethod** `create_from_source` (*name*, *config*, *\*\*kwargs*)

Create an ROI centered on the given source.

**create\_param\_table** ()

**classmethod** `create_roi_from_ft1` (*ft1file*, *config*)

Create an ROI model by extracting the sources coordinates form an FT1 file.

**create\_source** (*name*, *src\_dict*, *build\_index=True*, *merge\_sources=True*, *rescale=True*)

Add a new source to the ROI model from a dictionary or an existing source object.

**Parameters**

- **name** (*str*) –
- **src\_dict** (dict or *Source*) –

**Returns** *src*

**Return type** *Source*

**create\_source\_table** ()

**create\_table** (*names=None*)

Create an astropy Table object with the contents of the ROI model.

**defaults** = {'assoc\_xmatch\_columns': (['3FGL\_Name'], 'Choose a set of association columns')}

**delete\_sources** (*srcs*)

**diffuse\_sources**

**extdir**

**geom**

**get\_nearby\_sources** (*name*, *distance*, *min\_dist=None*, *square=False*)

**get\_source\_by\_name** (*name*)

Return a single source in the ROI with the given name. The input name string can match any of the strings in the names property of the source object. Case and whitespace are ignored when matching name strings. If no sources are found or multiple sources then an exception is thrown.

**Parameters** **name** (*str*) – Name string.

**Returns** *srcs* – A source object.

**Return type** *Model*

**get\_sources** (*skydir=None*, *distance=None*, *cuts=None*, *minmax\_ts=None*, *minmax\_npred=None*, *exclude=None*, *square=False*, *coordsys='CEL'*, *names=None*)

Retrieve list of source objects satisfying the following selections:

- Angular separation from **skydir** or ROI center (if **skydir** is None) less than **distance**.
- Cuts on source properties defined in **cuts** list.

- TS and Npred in range specified by `minmax_ts` and `minmax_npred`.
- Name matching a value in `names`

Sources can be excluded from the selection by adding their name to the `exclude` list.

**Returns** `srcs` – List of source objects.

**Return type** `list`

**get\_sources\_by\_name** (*name*)

Return a list of sources in the ROI matching the given name. The input name string can match any of the strings in the `names` property of the source object. Case and whitespace are ignored when matching name strings.

**Parameters** `name` (*str*) –

**Returns** `srcs` – A list of `Model` objects.

**Return type** `list`

**get\_sources\_by\_position** (*skydir*, *dist*, *min\_dist=None*, *square=False*, *coordsys='CEL'*)

Retrieve sources within a certain angular distance of a sky coordinate. This function supports two types of geometric selections: circular (`square=False`) and square (`square=True`). The circular selection finds all sources with a given angular distance of the target position. The square selection finds sources within an ROI-like region of size  $R \times R$  where  $R = 2 \times \text{dist}$ .

**Parameters**

- **skydir** (*SkyCoord*) – Sky direction with respect to which the selection will be applied.
- **dist** (*float*) – Maximum distance in degrees from the sky coordinate.
- **square** (*bool*) – Choose whether to apply a circular or square selection.
- **coordsys** (*str*) – Coordinate system to use when applying a selection with `square=True`.

**get\_sources\_by\_property** (*pname*, *pmin*, *pmax=None*)

**has\_source** (*name*)

**load** (*\*\*kwargs*)

Load both point source and diffuse components.

**load\_diffuse\_srcs** ()

**load\_existing\_catalog** (*cat*, *\*\*kwargs*)

Load sources from an existing catalog object.

**Parameters** `cat` (*Catalog*) – Catalog object.

**load\_fits\_catalog** (*name*, *\*\*kwargs*)

Load sources from a FITS catalog file.

**Parameters** `name` (*str*) – Catalog name or path to a catalog FITS file.

**load\_source** (*src*, *build\_index=True*, *merge\_sources=True*, *\*\*kwargs*)

Load a single source.

**Parameters**

- **src** (*Source*) – Source object that will be added to the ROI.
- **merge\_sources** (*bool*) – When a source matches an existing source in the model update that source with the properties of the new source.

- **build\_index** (*bool*) – Re-make the source index after loading this source.

**load\_sources** (*sources*)

Delete all sources in the ROI and load the input source list.

**load\_xml** (*xmlfile*, *\*\*kwargs*)

Load sources from an XML file.

**match\_source** (*src*)

Look for source or sources in the model that match the given source. Sources are matched by name and any association columns defined in the `assoc_xmatch_columns` parameter.

**point\_sources**

**set\_geom** (*geom*)

**skydir**

Return the sky direction corresponding to the center of the ROI.

**sources**

**src\_name\_cols** = ['Source\_Name', 'ASSOC', 'ASSOC1', 'ASSOC2', 'ASSOC\_GAM', '1FHL\_Name',

**to\_ds9** (*free='box'*, *fixed='cross'*, *frame='fk5'*, *color='green'*, *header=True*)

Returns a list of ds9 region definitions :param free: one of the supported ds9 point symbols, used for free sources, see here: <http://ds9.si.edu/doc/ref/region.html> :type free: bool :param fixed: as free but for fixed sources :type fixed: bool :param frame: typically fk5, more to be implemented :type frame: str :param color: color used for symbols (only ds9 compatible colors) :type color: str :param header: if True, will prepend a global header line. :type header: bool

**Returns** **lines** – list of regions (and header if requested)

**Return type** **list**

**write\_ds9region** (*region*, *\*args*, *\*\*kwargs*)

Create a ds9 compatible region file from the ROI.

It calls the `to_ds9` method and write the result to the region file. Only the file name is required. All other parameters will be forwarded to the `to_ds9` method, see the documentation of that method for all accepted parameters and options. :param region: name of the region file (string) :type region: str

**write\_fits** (*fitsfile*)

Write the ROI model to a FITS file.

**write\_xml** (*xmlfile*, *config=None*)

Save the ROI model as an XML file.

**class** `fermipy.roi_model.Source` (*name*, *data*, *radec=None*)

Bases: `fermipy.roi_model.Model`

Class representation of a source (non-diffuse) model component. A source object serves as a container for the properties of that source (position, spatial/spectral parameters, TS, etc.) as derived in the current analysis. Most properties of a source object can be accessed with the bracket operator:

# Return the TS of this source >>> `src['ts']`

# Get a skycoord representation of the source position >>> `src.skydir`

**associations**

**classmethod** **create\_from\_dict** (*src\_dict*, *roi\_skydir=None*, *rescale=False*)

Create a source object from a python dictionary.

**Parameters** **src\_dict** (*dict*) – Dictionary defining the properties of the source.

**static create\_from\_xml** (*root*, *extdir=None*)

Create a Source object from an XML node.

**Parameters**

- **root** (*Element*) – XML node containing the source.
- **extdir** (*str*) – Path to the extended source archive.

**classmethod create\_from\_xmlfile** (*xmlfile*, *extdir=None*)

Create a Source object from an XML file.

**Parameters**

- **xmlfile** (*str*) – Path to XML file.
- **extdir** (*str*) – Path to the extended source archive.

**data**

**diffuse**

**extended**

**radec**

**separation** (*src*)

**set\_position** (*skydir*)

Set the position of the source.

**Parameters skydir** (*SkyCoord*) –

**set\_radec** (*ra*, *dec*)

**set\_roi\_direction** (*roidir*)

**set\_roi\_geom** (*geom*)

**set\_spatial\_model** (*spatial\_model*, *spatial\_pars*)

**skydir**

Return a SkyCoord representation of the source position.

**Returns skydir**

**Return type** *SkyCoord*

**update\_data** (*d*)

**write\_xml** (*root*)

Write this source to an XML node.

**fermipy.roi\_model.create\_source\_table** (*scan\_shape*)

Create an empty source table.

**Returns tab**

**Return type** *Table*

**fermipy.roi\_model.get\_dist\_to\_edge** (*skydir*, *lon*, *lat*, *width*, *coordsys='CEL'*)

**fermipy.roi\_model.get\_linear\_dist** (*skydir*, *lon*, *lat*, *coordsys='CEL'*)

**fermipy.roi\_model.get\_skydir\_distance\_mask** (*src\_skydir*, *skydir*, *dist*, *min\_dist=None*,  
*square=False*, *coordsys='CEL'*)

Retrieve sources within a certain angular distance of an (ra,dec) coordinate. This function supports two types of geometric selections: circular (*square=False*) and square (*square=True*). The circular selection finds all sources

with a given angular distance of the target position. The square selection finds sources within an ROI-like region of size  $R \times R$  where  $R = 2 \times \text{dist}$ .

#### Parameters

- **src\_skydir** (*SkyCoord*) – Array of sky directions.
- **skydir** (*SkyCoord*) – Sky direction with respect to which the selection will be applied.
- **dist** (*float*) – Maximum distance in degrees from the sky coordinate.
- **square** (*bool*) – Choose whether to apply a circular or square selection.
- **coordsys** (*str*) – Coordinate system to use when applying a selection with square=True.

`fermipy.roi_model.get_true_params_dict(pars_dict)`

`fermipy.roi_model.spatial_pars_from_catalog(cat)`

`fermipy.roi_model.spectral_pars_from_catalog(cat)`

Create spectral parameters from 3FGL catalog columns.

### fermipy.utils module

`fermipy.utils.angle_to_cartesian(lon, lat)`

Convert spherical coordinates to cartesian unit vectors.

`fermipy.utils.apply_minmax_selection(val, val_minmax)`

`fermipy.utils.arg_to_list(arg)`

`fermipy.utils.center_to_edge(center)`

`fermipy.utils.collect_dirs(path, max_depth=1, followlinks=True)`

Recursively find directories under the given path.

`fermipy.utils.convolve2d_disk(fn, r, sig, nstep=200)`

Evaluate the convolution  $f'(r) = f(r) * g(r)$  where  $f(r)$  is azimuthally symmetric function in two dimensions and  $g$  is a step function given by:

$$g(r) = H(1-r/s)$$

#### Parameters

- **fn** (*function*) – Input function that takes a single radial coordinate parameter.
- **r** (*ndarray*) – Array of points at which the convolution is to be evaluated.
- **sig** (*float*) – Radius parameter of the step function.
- **nstep** (*int*) – Number of sampling point for numeric integration.

`fermipy.utils.convolve2d_gauss(fn, r, sig, nstep=200)`

Evaluate the convolution  $f'(r) = f(r) * g(r)$  where  $f(r)$  is azimuthally symmetric function in two dimensions and  $g$  is a 2D gaussian with standard deviation  $s$  given by:

$$g(r) = 1/(2*\pi*s^2) \text{Exp}[-r^2/(2*s^2)]$$

#### Parameters

- **fn** (*function*) – Input function that takes a single radial coordinate parameter.
- **r** (*ndarray*) – Array of points at which the convolution is to be evaluated.
- **sig** (*float*) – Width parameter of the gaussian.
- **nstep** (*int*) – Number of sampling point for numeric integration.

`fermipy.utils.cov_to_correlation(cov)`

Compute the correlation matrix given the covariance matrix.

**Parameters** `cov` (`ndarray`) – N x N matrix of covariances among N parameters.

**Returns** `corr` – N x N matrix of correlations among N parameters.

**Return type** `ndarray`

`fermipy.utils.create_dict(d0, **kwargs)`

`fermipy.utils.create_hpx_disk_region_string(skyDir, coordsys, radius, inclusive=0)`

`fermipy.utils.create_kernel_function_lookup(psf, fn, sigma, egy, dtheta, psf_scale_fn)`

`fermipy.utils.create_model_name(src)`

Generate a name for a source object given its spatial/spectral properties.

**Parameters** `src` (`Source`) – A source object.

**Returns** `name` – A source name.

**Return type** `str`

`fermipy.utils.create_radial_spline(psf, fn, sigma, egy, dtheta, psf_scale_fn)`

`fermipy.utils.create_source_name(skydir, floor=True, prefix='PS')`

`fermipy.utils.create_xml_element(root, name, attrib)`

`fermipy.utils.dot_prod(xyz0, xyz1)`

Compute the dot product between two cartesian vectors where the second dimension contains the vector components.

`fermipy.utils.edge_to_center(edges)`

`fermipy.utils.edge_to_width(edges)`

`fermipy.utils.ellipse_to_cov(sigma_maj, sigma_min, theta)`

Compute the covariance matrix in two variables x and y given the std. deviation along the semi-major and semi-minor axes and the rotation angle of the error ellipse.

**Parameters**

- `sigma_maj` (`float`) – Std. deviation along major axis of error ellipse.
- `sigma_min` (`float`) – Std. deviation along minor axis of error ellipse.
- `theta` (`float`) – Rotation angle in radians from x-axis to ellipse major axis.

`fermipy.utils.eq2gal(ra, dec)`

`fermipy.utils.eval_radial_kernel(psf, fn, sigma, idx, dtheta, psf_scale_fn)`

`fermipy.utils.extend_array(edges, binsz, lo, hi)`

Extend an array to encompass lo and hi values.

`fermipy.utils.find_function_root(fn, x0, xb, delta=0.0, bounds=None)`

Find the root of a function: f(x)+delta in the interval encompassed by x0 and xb.

**Parameters**

- `fn` (`function`) – Python function.
- `x0` (`float`) – Fixed bound for the root search. This will either be used as the lower or upper bound depending on the relative value of xb.

- **xb** (*float*) – Upper or lower bound for the root search. If a root is not found in the interval  $[x_0, x_b]/[x_b, x_0]$  this value will be increased/decreased until a change in sign is found.

`fermipy.utils.find_rows_by_string(tab, names, colnames=['assoc'])`

Find the rows in a table `tab` that match at least one of the strings in `names`. This method ignores whitespace and case when matching strings.

#### Parameters

- **tab** (*astropy.table.Table*) – Table that will be searched.
- **names** (*list*) – List of strings.
- **colname** (*str*) – Name of the table column that will be searched for matching string.

**Returns** `mask` – Boolean mask for rows with matching strings.

**Return type** *ndarray*

`fermipy.utils.fit_parabola(z, ix, iy, dpix=3, zmin=None)`

Fit a parabola to a 2D numpy array. This function will fit a parabola with the functional form described in [parabola](#) to a 2D slice of the input array `z`. The fit region encompasses pixels that are within `dpix` of the pixel coordinate `(iz, iy)` OR that have a value relative to the peak value greater than `zmin`.

#### Parameters

- **z** (*ndarray*) –
- **ix** (*int*) – X index of center pixel of fit region in array `z`.
- **iy** (*int*) – Y index of center pixel of fit region in array `z`.
- **dpix** (*int*) – Max distance from center pixel of fit region.
- **zmin** (*float*) –

`fermipy.utils.fits_rearray_to_dict(table)`

Convert a FITS rearray to a python dictionary.

`fermipy.utils.format_filename(outdir, basename, prefix=None, extension=None)`

`fermipy.utils.gal2eq(l, b)`

`fermipy.utils.get_bounded_slice(idx, dpix, shape)`

`fermipy.utils.get_parameter_limits(xval, loglike, cl_limit=0.95, cl_err=0.68269, tol=0.01, bounds=None)`

Compute upper/lower limits, peak position, and 1-sigma errors from a 1-D likelihood function. This function uses the delta-loglikelihood method to evaluate parameter limits by searching for the point at which the change in the log-likelihood value with respect to the maximum equals a specific value. A cubic spline fit to the log-likelihood values is used to improve the accuracy of the calculation.

#### Parameters

- **xval** (*ndarray*) – Array of parameter values.
- **loglike** (*ndarray*) – Array of log-likelihood values.
- **cl\_limit** (*float*) – Confidence level to use for limit calculation.
- **cl\_err** (*float*) – Confidence level to use for two-sided confidence interval calculation.
- **tol** (*float*) – Absolute precision of likelihood values.

#### Returns

- **x0** (*float*) – Coordinate at maximum of likelihood function.



- **err\_lo** (*float*) – Lower error for two-sided confidence interval with CL `cl_err`. Corresponds to point ( $x < x_0$ ) at which the log-likelihood falls by a given value with respect to the maximum (0.5 for 1 sigma). Set to nan if the change in the log-likelihood function at the lower bound of the `xval` input array is less than the value for the given CL.
- **err\_hi** (*float*) – Upper error for two-sided confidence interval with CL `cl_err`. Corresponds to point ( $x > x_0$ ) at which the log-likelihood falls by a given value with respect to the maximum (0.5 for 1 sigma). Set to nan if the change in the log-likelihood function at the upper bound of the `xval` input array is less than the value for the given CL.
- **err** (*float*) – Symmetric 1-sigma error. Average of `err_lo` and `err_hi` if both are defined.
- **ll** (*float*) – Lower limit evaluated at confidence level `cl_limit`.
- **ul** (*float*) – Upper limit evaluated at confidence level `cl_limit`.
- **lnlmax** (*float*) – Log-likelihood value at `x0`.

`fermipy.utils.get_region_mask` (*z*, *delta*, *xy=None*)

Get mask of connected region within delta of max(*z*).

`fermipy.utils.init_matplotlib_backend` (*backend=None*)

This function initializes the matplotlib backend. When no DISPLAY is available the backend is automatically set to 'Agg'.

**Parameters** `backend` (*str*) – matplotlib backend name.

`fermipy.utils.interpolate_function_min` (*x*, *y*)

`fermipy.utils.is_fits_file` (*path*)

`fermipy.utils.isstr` (*s*)

String instance testing method that works under both Python 2.X and 3.X. Returns true if the input is a string.

`fermipy.utils.join_strings` (*strings*, *sep=' '*)

`fermipy.utils.load_data` (*infile*, *workdir=None*)

Load python data structure from either a YAML or numpy file.

`fermipy.utils.load_npy` (*infile*)

`fermipy.utils.load_xml_elements` (*root*, *path*)

`fermipy.utils.load_yaml` (*infile*, *\*\*kwargs*)

`fermipy.utils.lonlat_to_xyz` (*lon*, *lat*)

`fermipy.utils.make_cdisk_kernel` (*psf*, *sigma*, *npix*, *cdelt*, *xpix*, *ypix*, *psf\_scale\_fn=None*, *normalize=False*)

Make a kernel for a PSF-convolved 2D disk.

#### Parameters

- **psf** (PSFModel) –
- **sigma** (*float*) – 68% containment radius in degrees.

`fermipy.utils.make_cgauss_kernel` (*psf*, *sigma*, *npix*, *cdelt*, *xpix*, *ypix*, *psf\_scale\_fn=None*, *normalize=False*)

Make a kernel for a PSF-convolved 2D gaussian.

#### Parameters

- **psf** (PSFModel) –
- **sigma** (*float*) – 68% containment radius in degrees.

`fermipy.utils.make_disk_kernel (radius, npix=501, cdelt=0.01, xpix=None, ypix=None)`  
 Make kernel for a 2D disk.

**Parameters** `radius (float)` – Disk radius in deg.

`fermipy.utils.make_gaussian_kernel (sigma, npix=501, cdelt=0.01, xpix=None, ypix=None)`  
 Make kernel for a 2D gaussian.

**Parameters** `sigma (float)` – Standard deviation in degrees.

`fermipy.utils.make_pixel_distance (shape, xpix=None, ypix=None)`  
 Fill a 2D array with dimensions `shape` with the distance of each pixel from a reference direction (`xpix,ypix`) in pixel coordinates. Pixel coordinates are defined such that (0,0) is located at the center of the corner pixel.

`fermipy.utils.make_psf_kernel (psf, npix, cdelt, xpix, ypix, psf_scale_fn=None, normalize=False)`  
 Generate a kernel for a point-source.

**Parameters**

- **psf** (PSFModel) –
- **npix** (*int*) – Number of pixels in X and Y dimensions.
- **cdelt** (*float*) – Pixel size in degrees.

`fermipy.utils.make_radial_kernel (psf, fn, sigma, npix, cdelt, xpix, ypix, psf_scale_fn=None, normalize=False, klims=None, sparse=False)`  
 Make a kernel for a general radially symmetric 2D function.

**Parameters**

- **psf** (PSFModel) –
- **fn** (*callable*) – Function that evaluates the kernel at a radial coordinate `r`.
- **sigma** (*float*) – 68% containment radius in degrees.

`fermipy.utils.match_regex_list (patterns, string)`  
 Perform a regex match of a string against a list of patterns. Returns true if the string matches at least one pattern in the list.

`fermipy.utils.memoize (obj)`

`fermipy.utils.merge_dict (d0, d1, add_new_keys=False, append_arrays=False)`  
 Recursively merge the contents of python dictionary `d0` with the contents of another python dictionary, `d1`.

**Parameters**

- **d0** (*dict*) – The input dictionary.
- **d1** (*dict*) – Dictionary to be merged with the input dictionary.
- **add\_new\_keys** (*str*) – Do not skip keys that only exist in `d1`.
- **append\_arrays** (*bool*) – If an element is a numpy array set the value of that element by concatenating the two arrays.

`fermipy.utils.merge_list_of_dicts (listofdicts)`

`fermipy.utils.met_to_mjd (time)`  
 “Convert mission elapsed time to mean julian date.

`fermipy.utils.mkdir (dir)`

`fermipy.utils.onesided_cl_to_dlnl (cl)`  
 Compute the delta-loglikelihood values that corresponds to an upper limit of the given confidence level.

**Parameters** `cl (float)` – Confidence level.

**Returns** `dlnl` – Delta-loglikelihood value with respect to the maximum of the likelihood function.

**Return type** `float`

`fermipy.utils.onesided_dlnl_to_cl(dlnl)`

Compute the confidence level that corresponds to an upper limit with a given change in the loglikelihood value.

**Parameters** `dlnl` (`float`) – Delta-loglikelihood value with respect to the maximum of the likelihood function.

**Returns** `cl` – Confidence level.

**Return type** `float`

`fermipy.utils.overlap_slices(large_array_shape, small_array_shape, position)`

Modified version of `overlap_slices`.

Get slices for the overlapping part of a small and a large array.

Given a certain position of the center of the small array, with respect to the large array, tuples of slices are returned which can be used to extract, add or subtract the small array at the given position. This function takes care of the correct behavior at the boundaries, where the small array is cut off appropriately.

**Parameters**

- **large\_array\_shape** (`tuple`) – Shape of the large array.
- **small\_array\_shape** (`tuple`) – Shape of the small array.
- **position** (`tuple`) – Position of the small array's center, with respect to the large array. Coordinates should be in the same order as the array shape.

**Returns**

- **slices\_large** (`tuple of slices`) – Slices in all directions for the large array, such that `large_array[slices_large]` extracts the region of the large array that overlaps with the small array.
- **slices\_small** (`slice`) – Slices in all directions for the small array, such that `small_array[slices_small]` extracts the region that is inside the large array.

`fermipy.utils.parabola(xy, amplitude, x0, y0, sx, sy, theta)`

Evaluate a 2D parabola given by:

$$f(x,y) = f_0 - (1/2) * \text{delta}^T * R * \text{Sigma} * R^T * \text{delta}$$

where

$$\text{delta} = [(x - x_0), (y - y_0)]$$

and `R` is the matrix for a 2D rotation by angle `theta` and `Sigma` is the covariance matrix:

$$\text{Sigma} = [[1/\text{sigma\_x}^2, 0], [0, 1/\text{sigma\_y}^2]]$$

**Parameters**

- **xy** (`tuple`) – Tuple containing `x` and `y` arrays for the values at which the parabola will be evaluated.
- **amplitude** (`float`) – Constant offset value.
- **x0** (`float`) – Centroid in `x` coordinate.
- **y0** (`float`) – Centroid in `y` coordinate.
- **sx** (`float`) – Standard deviation along first axis (`x`-axis when `theta=0`).

- **sy** (*float*) – Standard deviation along second axis (y-axis when theta=0).
- **theta** (*float*) – Rotation angle in radians.

**Returns** **vals** – Values of the parabola evaluated at the points defined in the *xy* input tuple.

**Return type** *ndarray*

`fermipy.utils.path_to_xmlpath(path)`

`fermipy.utils.poly_to_parabola(coeff)`

`fermipy.utils.prettify_xml(elem)`

Return a pretty-printed XML string for the Element.

`fermipy.utils.project(lon0, lat0, lon1, lat1)`

This function performs a stereographic projection on the unit vector (lon1,lat1) with the pole defined at the reference unit vector (lon0,lat0).

`fermipy.utils.rebin_map(k, nebin, npix, rebin)`

`fermipy.utils.resolve_file_path(path, **kwargs)`

`fermipy.utils.resolve_file_path_list(pathlist, workdir, prefix="", randomize=False)`

Resolve the path of each file name in the file *pathlist* and write the updated paths to a new file.

`fermipy.utils.resolve_path(path, workdir=None)`

`fermipy.utils.scale_parameter(p)`

`fermipy.utils.separation_cos_angle(lon0, lat0, lon1, lat1)`

Evaluate the cosine of the angular separation between two direction vectors.

`fermipy.utils.split_bin_edges(edges, npts=2)`

Subdivide an array of bins by splitting each bin into *npts* subintervals.

#### Parameters

- **edges** (*ndarray*) – Bin edge array.
- **npts** (*int*) – Number of intervals into which each bin will be subdivided.

**Returns** **edges** – Subdivided bin edge array.

**Return type** *ndarray*

`fermipy.utils.strip_suffix(filename, suffix)`

`fermipy.utils.sum_bins(x, dim, npts)`

`fermipy.utils.tolist(x)`

convenience function that takes in a nested structure of lists and dictionaries and converts everything to its base objects. This is useful for dumping a file to yaml.

(a) numpy arrays into python lists

```
>>> type(tolist(np.asarray(123))) == int
True
>>> tolist(np.asarray([1,2,3])) == [1,2,3]
True
```

(b) numpy strings into python strings.

```
>>> tolist([np.asarray('cat')]) == ['cat']
True
```

(c) an ordered dict to a dict

```
>>> ordered=OrderedDict(a=1, b=2)
>>> type(tolist(ordered)) == dict
True
```

(d) converts unicode to regular strings

```
>>> type(u'a') == str
False
>>> type(tolist(u'a')) == str
True
```

(e) converts numbers & bools in strings to real representation, (i.e. '123' -> 123)

```
>>> type(tolist(np.asarray('123')) == int
True
>>> type(tolist('123')) == int
True
>>> tolist('False') == False
True
```

`fermipy.utils.twosided_cl_to_dlnl(cl)`

Compute the delta-loglikelihood value that corresponds to a two-sided interval of the given confidence level.

**Parameters** `cl` (*float*) – Confidence level.

**Returns** `dlnl` – Delta-loglikelihood value with respect to the maximum of the likelihood function.

**Return type** *float*

`fermipy.utils.twosided_dlnl_to_cl(dlnl)`

Compute the confidence level that corresponds to a two-sided interval with a given change in the loglikelihood value.

**Parameters** `dlnl` (*float*) – Delta-loglikelihood value with respect to the maximum of the likelihood function.

**Returns** `cl` – Confidence level.

**Return type** *float*

`fermipy.utils.unicode_representer(dumper, uni)`

`fermipy.utils.unicode_to_str(args)`

`fermipy.utils.update_bounds(val, bounds)`

`fermipy.utils.update_keys(input_dict, key_map)`

`fermipy.utils.val_to_bin(edges, x)`

Convert axis coordinate to bin index.

`fermipy.utils.val_to_bin_bounded(edges, x)`

Convert axis coordinate to bin index.

`fermipy.utils.val_to_edge(edges, x)`

Convert axis coordinate to bin index.

`fermipy.utils.val_to_pix(center, x)`

`fermipy.utils.write_yaml(o, outfile, **kwargs)`

`fermipy.utils.xmlpath_to_path(path)`

```
fermipy.utils.xyz_to_lonlat(*args)
```

## fermipy.plotting module

```
class fermipy.plotting.AnalysisPlotter(config, **kwargs)
```

Bases: `fermipy.config.Configurable`

```
defaults = {'catalogs': (None, '', <class 'list'>), 'cmap': ('magma', 'Set the color
```

```
make_extension_plots(ext, roi=None, **kwargs)
```

```
make_localization_plots(loc, roi=None, **kwargs)
```

```
make_residmap_plots(maps, roi=None, **kwargs)
```

Make plots from the output of `residmap`.

### Parameters

- **maps** (*dict*) – Output dictionary of `residmap`.
- **roi** (*ROIModel*) – ROI Model object. Generate markers at the positions of the sources in this ROI.
- **zoom** (*float*) – Crop the image by this factor. If None then no crop is applied.

```
make_roi_plots(gta, mcube_tot, **kwargs)
```

Make various diagnostic plots for the 1D and 2D counts/model distributions.

**Parameters** **prefix** (*str*) – Prefix that will be appended to all filenames.

```
make_sed_plots(sed, **kwargs)
```

```
make_tsmmap_plots(maps, roi=None, **kwargs)
```

Make plots from the output of `tsmap` or `tscube`. This method generates a 2D sky map for the best-fit test source in sqrt(TS) and Npred.

### Parameters

- **maps** (*dict*) – Output dictionary of `tsmap` or `tscube`.
- **roi** (*ROIModel*) – ROI Model object. Generate markers at the positions of the sources in this ROI.
- **zoom** (*float*) – Crop the image by this factor. If None then no crop is applied.

```
run(gta, mcube_map, **kwargs)
```

Make all plots.

```
class fermipy.plotting.ExtensionPlotter(src, roi, suffix, workdir, loge_bounds=None)
```

Bases: `object`

```
plot(iaxis)
```

```
class fermipy.plotting.ImagePlotter(img, mapping=None)
```

Bases: `object`

```
geom
```

```
plot(subplot=111, cmap='magma', **kwargs)
```

```
projtype
```

```
class fermipy.plotting.ROIPlotter(data_map, hpx2wcs=None, **kwargs)
```

Bases: `fermipy.config.Configurable`

```
classmethod create_from_fits(fitsfile, roi, **kwargs)
```

```

data
defaults = {'catalogs': (None, '', <class 'list'>), 'cmap': ('ds9_b', '', <class 'st.
draw_circle(radius, **kwargs)

geom
static get_data_projection(data_map, axes, iaxis, xmin=-1, xmax=1, loge_bounds=None)

map
plot(**kwargs)
plot_catalog(catalog)
plot_projection(iaxis, **kwargs)
plot_roi(roi, **kwargs)
plot_sources(skydir, labels, plot_kwargs, text_kwargs, **kwargs)

proj
projtype
static setup_projection_axis(iaxis, loge_bounds=None)
zoom(zoom)

class fermipy.plotting.SEDPlotter(sed)
Bases: object
static get_ylimits(sed)
plot(showlnl=False, **kwargs)
static plot_flux_points(sed, **kwargs)
static plot_lnlscan(sed, **kwargs)
static plot_model(model_flux, **kwargs)
static plot_resid(src, model_flux, **kwargs)
static plot_sed(sed, showlnl=False, **kwargs)
    Render a plot of a spectral energy distribution.

    Parameters
    • showlnl (bool) – Overlay a map of the delta-loglikelihood values vs. flux in each
      energy bin.
    • cmap (str) – Colormap that will be used for the delta-loglikelihood map.
    • llhcut (float) – Minimum delta-loglikelihood value.
    • ul_ts_threshold (float) – TS threshold that determines whether the MLE or UL
      is plotted in each energy bin.

sed
fermipy.plotting.annotate(**kwargs)
fermipy.plotting.annotate_name(data, xy=(0.05, 0.93), **kwargs)
fermipy.plotting.get_xerr(sed)
fermipy.plotting.load_bluered_cmap()

```

```
fermipy.plotting.load_ds9_cmap()
fermipy.plotting.make_counts_spectrum_plot(o, roi, energies, imfile, **kwargs)
fermipy.plotting.make_cube_slice(map_in, loge_bounds)
    Extract a slice from a map cube object.
fermipy.plotting.plot_error_ellipse(fit, xy, cdelt, **kwargs)
fermipy.plotting.plot_markers(lon, lat, **kwargs)
fermipy.plotting.truncate_colormap(cmap, minval=0.0, maxval=1.0, n=256)
    Function that extracts a subset of a colormap.
```

## fermipy.sed module

Utilities for dealing with SEDs

Many parts of this code are taken from `dsphs/like/lnlfn.py` by Matthew Wood <mdwood@slac.stanford.edu>  
 Alex Drlica-Wagner <kadrlica@slac.stanford.edu>

```
class fermipy.sed.SEDGenerator
```

Bases: `object`

Mixin class that provides SED functionality to `GTAnalysis`.

```
sed(name, **kwargs)
```

Generate a spectral energy distribution (SED) for a source. This function will fit the normalization of the source in each energy bin. By default the SED will be generated with the analysis energy bins but a custom binning can be defined with the `loge_bins` parameter.

### Parameters

- **name** (*str*) – Source name.
- **prefix** (*str*) – Optional string that will be prepended to all output files (FITS and rendered images).
- **loge\_bins** (*ndarray*) – Sequence of energies in  $\log_{10}(E/\text{MeV})$  defining the edges of the energy bins. If this argument is `None` then the analysis energy bins will be used. The energies in this sequence must align with the bin edges of the underlying analysis instance.
- **{options}** –
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** `sed` – Dictionary containing output of the SED analysis.

**Return type** `dict`

## fermipy.sourcefind module

```
class fermipy.sourcefind.SourceFind
```

Bases: `object`

Mixin class which provides source-finding functionality to `GTAnalysis`.

```
find_sources(prefix="", **kwargs)
```

An iterative source-finding algorithm that uses likelihood ratio (TS) maps of the region of interest to find new sources. After each iteration a new TS map is generated incorporating sources found in the previous iteration. The method stops when the number of iterations exceeds `max_iter` or no sources exceeding `sqrt_ts_threshold` are found.



**Parameters**

- **{options}** –
- **tmap** (*dict*) – Keyword arguments dictionary for tmap method.
- **tscube** (*dict*) – Keyword arguments dictionary for tscube method.

**Returns**

- **peaks** (*list*) – List of peak objects.
- **sources** (*list*) – List of source objects.

**localize** (*name*, *\*\*kwargs*)

Find the best-fit position of a source. Localization is performed in two steps. First a TS map is computed centered on the source with half-width set by `dtheta_max`. A fit is then performed to the maximum TS peak in this map. The source position is then further refined by scanning the likelihood in the vicinity of the peak found in the first step. The size of the scan region is set to encompass the 99% positional uncertainty contour as determined from the peak fit.

**Parameters**

- **name** (*str*) – Source name.
- **{options}** –
- **optimizer** (*dict*) – Dictionary that overrides the default optimizer settings.

**Returns** **localize** – Dictionary containing results of the localization analysis.

**Return type** *dict*

**fermipy.spectrum module**

**class** `fermipy.spectrum.DMFitFunction` (*params*, *chan='bb'*, *jfactor=1e+19*, *tablepath=None*, *dfactor=1e+17*)

Bases: `fermipy.spectrum.SpectralFunction`

Class that evaluates the spectrum for a DM particle of a given mass, channel, cross section, and J-factor. The parameterization is given by:

$$F(x) = 1 / (8 * \pi) * (1/\text{mass}^2) * \text{sigmav} * J * dN/dE(E, \text{mass}, i)$$

where the `params` array should be defined with:

- `params[0]` : sigmav (or tau for decay)
- `params[1]` : mass

Note that this class assumes that mass and J-factor are provided in units of GeV and GeV<sup>2</sup> cm<sup>-5</sup> while energies are defined in MeV.

For decay the D-factor is in uits of GeV cm<sup>-2</sup> s

**ann\_channel\_names**

**chan**

Return the channel string.

**chan\_code**

Return the channel code.

**channel\_index\_mapping** = {1: 8, 2: 6, 3: 3, 4: 1, 5: 2, 6: 7, 7: 4, 8: 5, 9: 0}

**channel\_name\_mapping** = {1: ['e+e-', 'ee'], 2: ['mu+mu-', 'mumu', 'musrc'], 3: ['tau

```
channel_rev_map = {'W+W-': 7, 'W+W-_decay': 107, 'ZZ': 8, 'ZZ_decay': 108, 'bb': 4, 'bb_decay': 109, 'tt': 5, 'tt_decay': 110}
channel_shortcode_mapping = {1: 'ee', 2: 'mumu', 3: 'tautau', 4: 'bb', 5: 'tt', 6: 'tau+tau-'}
static channels()
    Return all available DMFit channel strings
decay
    Return True if this is a decay spectrum
decay_channel_names
static nparam()
set_channel(chan)
class fermipy.spectrum.LogParabola (params=None, scale=1.0, extra_params=None)
    Bases: fermipy.spectrum.SpectralFunction
    Class that evaluates a function with the parameterization:

$$F(x) = p_0 * (x/x_s)^{(p_1 - p_2 * \log(x/x_s))}$$

    where  $x_s$  is a scale parameter. The params array should be defined with:


- params[0] : Prefactor ( $p_0$ )
- params[1] : Index ( $p_1$ )
- params[2] : Curvature ( $p_2$ )


static nparam()
class fermipy.spectrum.PLExpCutoff (params=None, scale=1.0, extra_params=None)
    Bases: fermipy.spectrum.SpectralFunction
    Class that evaluates a function with the parameterization:

$$F(x) = p_0 * (x/x_s)^{(p_1)} * \exp(-x/p_2)$$

    where  $x_s$  is the scale parameter. The params array should be defined with:


- params[0] : Prefactor ( $p_0$ )
- params[1] : Index ( $p_1$ )
- params[2] : Cutoff ( $p_2$ )


static log_to_params(params)
static nparam()
static params_to_log(params)
class fermipy.spectrum.PLSuperExpCutoff (params=None, scale=1.0, extra_params=None)
    Bases: fermipy.spectrum.SpectralFunction
    Class that evaluates a function with the parameterization:

$$F(x) = p_0 * (x/x_s)^{(p_1)} * \exp(-(x/p_2)^{p_3})$$

    where  $x_s$  is the scale parameter. The params array should be defined with:


- params[0] : Prefactor ( $p_0$ )
- params[1] : Index1 ( $p_1$ )
- params[2] : Curvature ( $p_2$ )
- params[3] : Index2 ( $p_3$ )

```

```

    static log_to_params (params)

    static nparam ()

    static params_to_log (params)

```

**class** fermipy.spectrum.**PowerLaw** (params=None, scale=1.0, extra\_params=None)  
 Bases: [fermipy.spectrum.SpectralFunction](#)

Class that evaluates a power-law function with the parameterization:

$$F(x) = p_0 * (x/x_s)^{p_1}$$

where  $x_s$  is the scale parameter. The `params` array should be defined with:

- `params[0]` : Prefactor ( $p_0$ )
- `params[1]` : Index ( $p_1$ )

```

    classmethod eval_eflux (emin, emax, params, scale=1.0, extra_params=None)

    static eval_flux (emin, emax, params, scale=1.0, extra_params=None)

    classmethod eval_norm (scale, index, emin, emax, flux)

    static nparam ()

```

**class** fermipy.spectrum.**SEDEFfluxFunc** (sfn, emin, emax)  
 Bases: [fermipy.spectrum.SEDFunc](#)

Func that computes the energy flux of a source in a pre-defined sequence of energy bins.

**class** fermipy.spectrum.**SEDfluxFunc** (sfn, emin, emax)  
 Bases: [fermipy.spectrum.SEDFunc](#)

Func that computes the flux of a source in a pre-defined sequence of energy bins.

**class** fermipy.spectrum.**SEDFunc** (sfn, emin, emax)  
 Bases: `object`

Func object that wraps a [SpectralFunction](#) and computes the normalization of the model in a sequence of SED energy bins. The evaluation method of this class accepts a single vector for the parameters of the model. This class serves as an object that can be passed to likelihood optimizers.

```

    emax

    emin

    params

    scale

    spectral_fn

```

**class** fermipy.spectrum.**SpectralFunction** (params, scale=1.0, extra\_params=None)  
 Bases: `object`

Base class for spectral models. Spectral models inheriting from this class should implement at a minimum an `_eval_dnde` method which evaluates the differential flux at a given energy.

```

    classmethod create_eflux_func (emin, emax, params=None, scale=1.0, extra_params=None)

    classmethod create_flux_func (emin, emax, params=None, scale=1.0, extra_params=None)

    classmethod create_from_eflux (params, emin, emax, eflux, scale=1.0)

```

Create a spectral function instance given its energy flux.

**classmethod** **create\_from\_flux** (*params, emin, emax, flux, scale=1.0*)  
Create a spectral function instance given its flux.

**classmethod** **create\_func** (*spec\_type, func\_type, emin, emax, params=None, scale=1.0, extra\_params=None*)

**dnde** (*x, params=None*)  
Evaluate differential flux.

**dnde\_deriv** (*x, params=None*)  
Evaluate derivative of the differential flux with respect to E.

**e2dnde** (*x, params=None*)  
Evaluate  $E^2$  times differential flux.

**e2dnde\_deriv** (*x, params=None*)  
Evaluate derivative of  $E^2$  times differential flux with respect to E.

**ednde** (*x, params=None*)  
Evaluate  $E$  times differential flux.

**ednde\_deriv** (*x, params=None*)  
Evaluate derivative of  $E$  times differential flux with respect to E.

**eflux** (*emin, emax, params=None*)  
Evaluate the integral energy flux.

**classmethod** **eval\_dnde** (*x, params, scale=1.0, extra\_params=None*)

**classmethod** **eval\_dnde\_deriv** (*x, params, scale=1.0, extra\_params=None*)

**classmethod** **eval\_e2dnde** (*x, params, scale=1.0, extra\_params=None*)

**classmethod** **eval\_e2dnde\_deriv** (*x, params, scale=1.0, extra\_params=None*)

**classmethod** **eval\_ednde** (*x, params, scale=1.0, extra\_params=None*)

**classmethod** **eval\_ednde\_deriv** (*x, params, scale=1.0, extra\_params=None*)

**classmethod** **eval\_eflux** (*emin, emax, params, scale=1.0, extra\_params=None*)

**classmethod** **eval\_flux** (*emin, emax, params, scale=1.0, extra\_params=None*)

**extra\_params**  
Dictionary containing additional parameters needed for evaluation of the function.

**flux** (*emin, emax, params=None*)  
Evaluate the integral flux.

**log\_params**  
Return transformed parameter vector in which norm and scale parameters are converted to log10.

**params**  
Return parameter vector of the function.

**scale**

`fermipy.spectrum.cast_args(x)`

`fermipy.spectrum.cast_params(params)`

## fermipy.skymap module

**class** `fermipy.skymap.HpxMap` (*counts, hpx*)  
Bases: `fermipy.skymap.Map_Base`

Representation of a 2D or 3D counts map using HEALPix.

**convert\_to\_cached\_wcs** (*hpx\_in*, *sum\_ebins=False*, *normalize=True*)

Make a WCS object and convert HEALPix data into WCS projection

#### Parameters

- **hpx\_in** (*ndarray*) – HEALPix input data
- **sum\_ebins** (*bool*) – sum energy bins over energy bins before reprojecting
- **normalize** (*bool*) – True -> preserve integral by splitting HEALPix values between bins
- (**WCS object**, **np.ndarray()** with **reprojected data**) (*returns*) –

**classmethod create\_from\_fits** (*fitsfile*, *\*\*kwargs*)

**classmethod create\_from\_hdu** (*hdu*, *ebins*)

Creates and returns an HpxMap object from a FITS HDU.

*hdu* : The FITS ebins : Energy bin edges [optional]

**classmethod create\_from\_hdulist** (*hdulist*, *\*\*kwargs*)

Creates and returns an HpxMap object from a FITS HDUList

*extname* : The name of the HDU with the map data ebounds : The name of the HDU with the energy bin data

**create\_image\_hdu** (*name=None*, *\*\*kwargs*)

**expanded\_counts\_map** ()

return the full counts map

**explicit\_counts\_map** (*pixels=None*)

return a counts map with explicit index scheme

**Parameters pixels** (*np.ndarray* or *None*) – If set, grab only those pixels. If none, grab only non-zero pixels

**get\_map\_values** (*lons*, *lats*, *ibin=None*)

Return the indices in the flat array corresponding to a set of coordinates

#### Parameters

- **lons** (*array-like*) – ‘Longitudes’ (RA or GLON)
- **lats** (*array-like*) – ‘Latitudes’ (DEC or GLAT)
- **ibin** (*int* or *array-like*) – Extract data only for a given energy bin. None -> extract data for all bins

**Returns vals** – Values of pixels in the flattened map, np.nan used to flag coords outside of map

**Return type** *numpy.ndarray((n))*

**get\_pixel\_indices** (*lats*, *lons*)

Return the indices in the flat array corresponding to a set of coordinates

**get\_pixel\_skydirs** ()

Get a list of sky coordinates for the centers of every pixel.

#### hpx

**interpolate** (*lon*, *lat*, *egy=None*, *interp\_log=True*)

Interpolate map values.

Parameters **interp\_log** (*bool*) – Interpolate the z-coordinate in logspace.

**make\_wcs\_from\_hpx** (*sum\_ebins=False, proj='CAR', oversample=2, normalize=True*)

Make a WCS object and convert HEALPix data into WCS projection

NOTE: this re-calculates the mapping, if you have already calculated the mapping it is much faster to use `convert_to_cached_wcs()` instead

#### Parameters

- **sum\_ebins** (*bool*) – sum energy bins over energy bins before reprojecting
- **proj** (*str*) – WCS-projection
- **oversample** (*int*) – Oversampling factor for WCS map
- **normalize** (*bool*) – True -> preserve integral by splitting HEALPix values between bins
- (**WCS object, np.ndarray() with reprojected data**) (*returns*) –

**sparse\_counts\_map** ()

return a counts map with sparse index scheme

**sum\_over\_energy** ()

Reduce a counts cube to a counts map

**swap\_scheme** ()

**ud\_grade** (*order, preserve\_counts=False*)

**class** `fermipy.skymap.Map` (*counts, wcs, ebins=None*)

Bases: `fermipy.skymap.Map_Base`

Representation of a 2D or 3D counts map using WCS.

**classmethod** **create** (*skydir, cdelt, npix, coordsys='CEL', projection='AIT', ebins=None, differential=False*)

**classmethod** **create\_from\_fits** (*fitsfile, \*\*kwargs*)

**classmethod** **create\_from\_hdu** (*hdu, wcs*)

**create\_image\_hdu** (*name=None, \*\*kwargs*)

**create\_primary\_hdu** ()

**get\_map\_values** (*lons, lats, ibin=None*)

Return the map values corresponding to a set of coordinates.

#### Parameters

- **lons** (*array-like*) – ‘Longitudes’ (RA or GLON)
- **lats** (*array-like*) – ‘Latitudes’ (DEC or GLAT)
- **ibin** (*int or array-like*) – Extract data only for a given energy bin. None -> extract data for all bins

**Returns** **vals** – Values of pixels in the flattened map, np.nan used to flag coords outside of map

**Return type** `numpy.ndarray((n))`

**get\_pixel\_indices** (*lons, lats, ibin=None*)

Return the indices in the flat array corresponding to a set of coordinates

#### Parameters

- **lons** (*array-like*) – ‘Longitudes’ (RA or GLON)

- **lats** (*array-like*) – ‘Latitudes’ (DEC or GLAT)
- **ibin** (*int or array-like*) – Extract data only for a given energy bin. None -> extract data for all energy bins.

**Returns** **pixcrd** – Pixel indices along each dimension of the map.

**Return type** **list**

**get\_pixel\_skydirs** ()

Get a list of sky coordinates for the centers of every pixel.

**interpolate** (*lon, lat, egy=None*)

Return the interpolated map values corresponding to a set of coordinates.

**interpolate\_at\_skydir** (*skydir*)

**ipix\_swap\_axes** (*ipix, colwise=False*)

Return the transposed pixel index from the pixel xy coordinates

if colwise is True (False) this assumes the original index was in column wise scheme

**ipix\_to\_ypix** (*ipix, colwise=False*)

Return array multi-dimensional pixel indices from flattened index.

**Parameters** **colwise** (*bool*) – Use column-wise pixel indexing.

**npix**

**pix\_center**

Return the ROI center in pixel coordinates.

**pix\_size**

Return the pixel size along the two image dimensions.

**skydir**

Return the sky coordinate of the image center.

**sum\_over\_energy** ()

Reduce a 3D counts cube to a 2D counts map

**wcs**

**width**

Return the dimensions of the image.

**ypix\_to\_ipix** (*ypix, colwise=False*)

Return the flattened pixel indices from an array multi-dimensional pixel indices.

**Parameters**

- **ypix** (*list*) – List of pixel indices in the order (LON,LAT,ENERGY).
- **colwise** (*bool*) – Use column-wise pixel indexing.

**class** `fermipy.skymap.Map_Base` (*counts*)

Bases: `object`

Abstract representation of a 2D or 3D counts map.

**counts**

**data**

**get\_map\_values** (*lons, lats, ibin=None*)

Return the map values corresponding to a set of coordinates.

**get\_pixel\_indices** (*lats, lons*)

Return the indices in the flat array corresponding to a set of coordinates

**get\_pixel\_skydirs** ()

Get a list of sky coordinates for the centers of every pixel.

**interpolate** (*lon, lat, egy=None*)

Return the interpolated map values corresponding to a set of coordinates.

**sum\_over\_energy** ()

Reduce a counts cube to a counts map by summing over the energy planes

`fermipy.skymap.coadd_maps` (*geom, maps, preserve\_counts=True*)

Coadd a sequence of Map objects.

`fermipy.skymap.make_coadd_hpx` (*maps, hpx, shape, preserve\_counts=True*)

`fermipy.skymap.make_coadd_map` (*maps, proj, shape, preserve\_counts=True*)

`fermipy.skymap.make_coadd_wcs` (*maps, wcs, shape*)

`fermipy.skymap.read_map_from_fits` (*fitsfile, extname=None*)

## fermipy.castro module

Utilities for dealing with ‘castro data’, i.e., 2D table of likelihood values.

Castro data can be tabulated in terms of a variety of variables. The most common example is probably a simple SED, where we have the likelihood as a function of Energy and Energy Flux.

However, we could easily convert to the likelihood as a function of other variables, such as the Flux normalization and the spectral index, or the mass and cross-section of a putative dark matter particle.

**class** `fermipy.castro.CastroData` (*norm\_vals, nll\_vals, refSpec, norm\_type*)

Bases: `fermipy.castro.CastroData_Base`

This class wraps the data needed to make a “Castro” plot, namely the log-likelihood as a function of normalization for a series of energy bins.

**classmethod** `create_from_fits` (*fitsfile, norm\_type='eflux', hdu\_scan='SCANDATA',  
hdu\_energies='EBOUNDS', irow=None*)

Create a CastroData object from a tscube FITS file.

### Parameters

- **fitsfile** (*str*) – Name of the fits file
- **norm\_type** (*str*) – Type of normalization to use. Valid options are:
  - `norm` : Normalization w.r.t. to test source
  - `flux` : Flux of the test source (  $\text{ph cm}^{-2} \text{ s}^{-1}$  )
  - `eflux` : Energy Flux of the test source (  $\text{MeV cm}^{-2} \text{ s}^{-1}$  )
  - `npred` : Number of predicted photons (Not implemented)
  - `dnde` : Differential flux of the test source (  $\text{ph cm}^{-2} \text{ s}^{-1} \text{ MeV}^{-1}$  )
- **hdu\_scan** (*str*) – Name of the FITS HDU with the scan data
- **hdu\_energies** (*str*) – Name of the FITS HDU with the energy binning and normalization data



- **irow** (*int* or *None*) – If none, then this assumes that there is a single row in the scan data table Otherwise, this specifies which row of the table to use

**Returns** *castro*

**Return type** *CastroData*

**classmethod** **create\_from\_flux\_points** (*txtfile*)

Create a Castro data object from a text file containing a sequence of differential flux points.

**classmethod** **create\_from\_sedfile** (*fitsfile*, *norm\_type*='eflux')

Create a CastroData object from an SED fits file

**Parameters**

- **fitsfile** (*str*) – Name of the fits file
- **norm\_type** (*str*) – Type of normalization to use, options are:
  - norm : Normalization w.r.t. to test source
  - flux : Flux of the test source (  $\text{ph cm}^{-2} \text{s}^{-1}$  )
  - eflux: Energy Flux of the test source (  $\text{MeV cm}^{-2} \text{s}^{-1}$  )
  - npred: Number of predicted photons (Not implemented)
  - dnnde : Differential flux of the test source (  $\text{ph cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$  )

**Returns** *castro*

**Return type** *CastroData*

**classmethod** **create\_from\_stack** (*shape*, *components*, *ylims*, *weights*=None)

Combine the log-likelihoods from a number of components.

**Parameters**

- **shape** (*tuple*) – The shape of the return array
- **components** (*[CastroData\_Base]*) – The components to be stacked
- **weights** (*array-like*) –

**Returns** *castro*

**Return type** *CastroData*

**classmethod** **create\_from\_tables** (*norm\_type*='eflux', *tab\_s*='SCANDATA',  
*tab\_e*='EBOUNDS')

Create a CastroData object from two tables

**Parameters**

- **norm\_type** (*str*) – Type of normalization to use. Valid options are:
  - norm : Normalization w.r.t. to test source
  - flux : Flux of the test source (  $\text{ph cm}^{-2} \text{s}^{-1}$  )
  - eflux: Energy Flux of the test source (  $\text{MeV cm}^{-2} \text{s}^{-1}$  )
  - npred: Number of predicted photons (Not implemented)
  - dnnde : Differential flux of the test source (  $\text{ph cm}^{-2} \text{s}^{-1} \text{MeV}^{-1}$  )
- **tab\_s** (*str*) – table scan data
- **tab\_e** (*str*) – table energy binning and normalization data

**Returns** `castro`

**Return type** `CastroData`

**classmethod** `create_from_yamlfile` (*yamlfile*)

Create a Castro data object from a yaml file contains the likelihood data.

**create\_functor** (*specType*, *initPars=None*, *scale=1000.0*)

Create a functor object that computes normalizations in a sequence of energy bins for a given spectral model.

**Parameters**

- **specType** (*str*) – The type of spectrum to use. This can be a string corresponding to the spectral model class name or a `SpectralFunction` object.
- **initPars** (*ndarray*) – Arrays of parameter values with which the spectral function will be initialized.
- **scale** (*float*) – The ‘pivot energy’ or energy scale to use for the spectrum

**Returns** `fn` – A functor object.

**Return type** `SEDFunctor`

**nE**

Return the number of energy bins. This is also the number of x-axis bins.

**refSpec**

Return a `ReferenceSpec` with the spectral data

**spectrum\_loglike** (*specType*, *params*, *scale=1000.0*)

return the log-likelihood for a particular spectrum

**Parameters**

- **specTypes** (*str*) – The type of spectrum to try
- **params** (*array-like*) – The spectral parameters
- **scale** (*float*) – The energy scale or ‘pivot’ energy

**test\_spectra** (*spec\_types=None*)

Test different spectral types against the SED represented by this `CastroData`.

**Parameters** **spec\_types** (*[str, ...]*) – List of spectral types to try

**Returns**

**retDict** – A dictionary of dictionaries. The top level dictionary is keyed by `spec_type`. The sub-dictionaries each contain:

- **"Function"** : `SpectralFunction`
- **"Result"** : tuple with the output of `scipy.optimize.fmin`
- **"Spectrum"** : `ndarray` with best-fit spectral values
- **"ScaleEnergy"** : float, the ‘pivot energy’ value
- **"TS"** : float, the TS for the best-fit spectrum

**Return type** `dict`

**x\_edges** ()

**class** `fermipy.castro.CastroData_Base` (*norm\_vals, nll\_vals, nll\_offsets, norm\_type*)

Bases: `object`

This class wraps the data needed to make a “Castro” plot, namely the log-likelihood as a function of normalization.

In this case the x-axes and y-axes are generic Sub-classes can implement particular axes choices (e.g., EFlux v. Energy)

**TS\_spectrum** (*spec\_vals*)

Calculate and the TS for a given set of spectral values.

**build\_lnl\_fn** (*normv, nllv*)

**build\_scandata\_table** ()

Build an `astropy.table.Table` object from these data.

**chi2\_vals** (*x*)

Compute the difference in the log-likelihood between the MLE in each energy bin and the normalization predicted by a global best-fit model. This array can be summed to get a goodness-of-fit chi2 for the model.

**Parameters** *x* (`ndarray`) – An array of normalizations derived from a global fit to all energy bins.

**Returns** `chi2_vals` – An array of chi2 values for each energy bin.

**Return type** `ndarray`

**derivative** (*x, der=1*)

Return the derivate of the log-like summed over the energy bins

**Parameters**

- *x* (`ndarray`) – Array of N x M values
- *der* (`int`) – Order of the derivate

**Returns** `der_val` – Array of negative log-likelihood values.

**Return type** `ndarray`

**fitNorm\_v2** (*specVals*)

Fit the normalization given a set of spectral values that define a spectral shape.

This version uses `scipy.optimize.fmin`.

**Parameters**

- **specVals** (*an array of (nebin values that define a spectral shape)*) –
- **xlims** (*fit limits*) –

**Returns** `norm` – Best-fit normalization value

**Return type** `float`

**fitNormalization** (*specVals, xlims*)

Fit the normalization given a set of spectral values that define a spectral shape

This version is faster, and solves for the root of the derivatvie

**Parameters**

- **specVals** (*an array of (nebin values that define a spectral shape)*) –

- **xlims** (*fit limits*) –
- **the best-fit normalization value** (*returns*) –

**fit\_spectrum** (*specFunc, initPars, freePars=None*)

Fit for the free parameters of a spectral function

#### Parameters

- **specFunc** (*SpectralFunction*) – The Spectral Function
- **initPars** (*ndarray*) – The initial values of the parameters
- **freePars** (*ndarray*) – Boolean array indicating which parameters should be free in the fit.

#### Returns

- **params** (*ndarray*) – Best-fit parameters.
- **spec\_vals** (*ndarray*) – The values of the best-fit spectral model in each energy bin.
- **ts\_spec** (*float*) – The TS of the best-fit spectrum
- **chi2\_vals** (*ndarray*) – Array of chi-squared values for each energy bin.
- **chi2\_spec** (*float*) – Global chi-squared value for the sum of all energy bins.
- **pval\_spec** (*float*) – p-value of chi-squared for the best-fit spectrum.

**fn\_mles** ()

returns the summed likelihood at the maximum likelihood estimate

Note that simply sums the maximum likelihood values at each bin, and does not impose any sort of constrain between bins

**getIntervals** (*alpha*)

Evaluate the two-sided intervals corresponding to a C.L. of (1-alpha)%.

**Parameters** **alpha** (*float*) – limit confidence level.

#### Returns

- **limit\_vals\_hi** (*ndarray*) – An array of lower limit values.
- **limit\_vals\_lo** (*ndarray*) – An array of upper limit values.

**getLimits** (*alpha, upper=True*)

Evaluate the limits corresponding to a C.L. of (1-alpha)%.

#### Parameters

- **alpha** (*float*) – limit confidence level.
- **upper** (*bool*) – upper or lower limits.
- **an array of values, one for each energy bin** (*returns*) –

**mles** ()

return the maximum likelihood estimates for each of the energy bins

**nll\_null**

Return the negative log-likelihood for the null-hypothesis

**nll\_offsets**

Return the offsets in the negative log-likelihoods for each bin

**norm\_derivative** (*spec, norm*)

**norm\_type**

Return the normalization type flag

**nx**

Return the number of profiles

**ny**

Return the number of profiles

**static stack\_nll** (*shape, components, ylimits, weights=None*)

Combine the log-likelihoods from a number of components.

#### Parameters

- **shape** (*tuple*) – The shape of the return array
- **components** (*CastroData\_Base*) – The components to be stacked
- **weights** (*array-like*) –

#### Returns

- **norm\_vals** (*numpy.ndarray*) – N X M array of Normalization values
- **nll\_vals** (*numpy.ndarray*) – N X M array of log-likelihood values
- **nll\_offsets** (*numpy.ndarray*) – N array of maximum log-likelihood values in each bin

**ts\_vals** ()

returns test statistic values for each energy bin

**x\_edges** ()

**class** fermipy.castro.**Interpolator** (*x, y*)

Bases: *object*

Helper class for interpolating a 1-D function from a set of tabulated values.

Safely deals with overflows and underflows

**derivative** (*x, der=1*)

return the derivative a an array of input values

x : the inputs der : the order of derivative

**x**

return the x values used to construct the split

**xmax**

return the maximum value over which the spline is defined

**xmin**

return the minimum value over which the spline is defined

**y**

return the y values used to construct the split

**class** fermipy.castro.**LnLFn** (*x, y, norm\_type=0*)

Bases: *object*

Helper class for interpolating a 1-D log-likelihood function from a set of tabulated values.

**TS** ()

return the Test Statistic

**fn\_mle** ()

return the function value at the maximum likelihood estimate

**getDeltaLogLike** (*dlnl*, *upper=True*)

Find the point at which the log-likelihood changes by a given value with respect to its value at the MLE.

**getInterval** (*alpha*)

Evaluate the interval corresponding to a C.L. of (1-alpha)%.

**Parameters** *alpha* (*limit confidence level.*)–

**getLimit** (*alpha*, *upper=True*)

Evaluate the limits corresponding to a C.L. of (1-alpha)%.

**Parameters**

- **alpha** (*limit confidence level.*)–
- **upper** (*upper or lower limits.*)–

**interp**

return the underlying Interpolator object

**mle** ()

return the maximum likelihood estimate

This will return the cached value, if it exists

**norm\_type**

Return a string specifying the quantity used for the normalization. This isn't actually used in this class, but it is carried so that the class is self-describing. The possible values are open-ended.

**class** fermipy.castro.**ReferenceSpec** (*emin*, *emax*, *ref\_dnde*, *ref\_flux*, *ref\_eflux*, *ref\_npred*,  
*eref=None*)

Bases: `object`

This class encapsulates data for a reference spectrum.

**Parameters**

- **ne** (*int*) – Number of energy bins
- **ebins** (*ndarray*) – Array of bin edges.
- **emin** (*ndarray*) – Array of lower bin edges.
- **emax** (*ndarray*) – Array of upper bin edges.
- **bin\_widths** (*ndarray*) – Array of energy bin widths.
- **eref** (*ndarray*) – Array of reference energies. Typically these are the geometric mean of the energy bins
- **ref\_dnde** (*ndarray*) – Array of differential photon flux values.
- **ref\_flux** (*ndarray*) – Array of integral photon flux values.
- **ref\_eflux** (*ndarray*) – Array of integral energy flux values.
- **ref\_npred** (*ndarray*) – Array of predicted number of photons in each energy bin.

**bin\_widths**

**build\_ebound\_table** ()

Build and return an EBOUNDS table with the encapsulated data.

**classmethod** **create\_from\_table** (*tab\_e*)

**Parameters** *tab\_e* (*Table*) – EBOUNDS table.

**create\_functor** (*specType*, *normType*, *initPars=None*, *scale=1000.0*)

Create a functor object that computes normalizations in a sequence of energy bins for a given spectral model.

#### Parameters

- **specType** (*str*) – The type of spectrum to use. This can be a string corresponding to the spectral model class name or a *SpectralFunction* object.
- **normType** (*The type of normalization to use*) –
- **initPars** (*ndarray*) – Arrays of parameter values with which the spectral function will be initialized.
- **scale** (*float*) – The ‘pivot energy’ or energy scale to use for the spectrum

**Returns** **fn** – A functor object.

**Return type** *SEDFunctor*

**ebins**

**emax**

**emin**

**eref**

**log\_ebins**

**nE**

**ref\_dnde**

**ref\_eflux**

return the energy flux values

**ref\_flux**

return the flux values

**ref\_npred**

return the number of predicted events

**class** `fermipy.castro.SpecData` (*ref\_spec*, *norm*, *norm\_err*)

Bases: *fermipy.castro.ReferenceSpec*

This class encapsulates spectral analysis results (best-fit normalizations, errors, etc.), energy binning, and reference spectrum definition.

#### Parameters

- **norm** (*ndarray*) –
- **norm\_err** (*ndarray*) –
- **flux** (*ndarray*) – Array of integral photon flux values.
- **eflux** (*ndarray*) – Array of integral energy flux values.
- **dnde** (*ndarray*) – Differential flux values
- **dnde\_err** (*ndarray*) – Uncertainties on differential flux values
- **e2dnde** (*ndarray*) – Differential flux values scaled by  $E^2$
- **e2dnde\_err** (*ndarray*) – Uncertainties on differential flux values scaled by  $E^2$

**build\_spec\_table** ()

```
classmethod create_from_table(tab)
```

```
dnde
```

```
dnde_err
```

```
e2dnde
```

```
e2dnde_err
```

```
eflux
```

```
flux
```

```
norm
```

```
norm_err
```

```
class fermipy.castro.TSCube(tmap, normmap, tscube, normcube, norm_vals, nll_vals, refSpec,  
                             norm_type)
```

Bases: `object`

A class wrapping a TSCube, which is a collection of CastroData objects for a set of directions.

This class wraps a combination of:

- Pixel data,
- Pixel x Energy bin data,
- Pixel x Energy Bin x Normalization scan point data

```
castroData_from_ipix(ipix, colwise=False)
```

Build a CastroData object for a particular pixel

```
castroData_from_pix_xy(xy, colwise=False)
```

Build a CastroData object for a particular pixel

```
classmethod create_from_fits(fitsfile, norm_type='flux')
```

Build a TSCube object from a fits file created by gttscube :param fitsfile: Path to the tscube FITS file. :type fitsfile: str :param norm\_type: String specifying the quantity used for the normalization :type norm\_type: str

```
find_and_refine_peaks(threshold, min_separation=1.0, use_cumul=False)
```

Run a simple peak-finding algorithm, and fit the peaks to paraboloids to extract their positions and error ellipses.

#### Parameters

- **threshold** (*float*) – Peak threshold in TS.
- **min\_separation** (*float*) – Radius of region size in degrees. Sets the minimum allowable separation between peaks.
- **use\_cumul** (*bool*) – If true, used the cumulative TS map (i.e., the TS summed over the energy bins) instead of the TS Map from the fit to and index=2 powerlaw.

**Returns** **peaks** – List of dictionaries containing the location and amplitude of each peak. Output of `find_peaks`

**Return type** `list`

```
find_sources(threshold, min_separation=1.0, use_cumul=False, output_peaks=False, out-  
             put_castro=False, output_specInfo=False, output_src_dicts=False, out-  
             put_srcs=False)
```



**nE**  
return the number of energy bins

**nN**  
return the number of sample points in each energy bin

**normcube**  
return the Cube of the normalization value per pixel / energy bin

**normmap**  
return the Map of the Best-fit normalization value

**nvals**  
Return the number of values in the tscube

**refSpec**  
Return the Spectral Data object

**test\_spectra\_of\_peak** (*peak, spec\_types=None*)  
Test different spectral types against the SED represented by the CastroData corresponding to a single pixel in this TSCube :param spec\_types: List of spectral types to try :type spec\_types: [str,...]

**Returns**

- **castro** (*CastroData*) – The castro data object for the pixel corresponding to the peak
- **test\_dict** (*dict*) – The dictionary returned by *test\_spectra*

**ts\_cumul**  
return the Map of the cumulative TestStatistic value per pixel (summed over energy bin)

**tscube**  
return the Cube of the TestStatistic value per pixel / energy bin

**tmap**  
return the Map of the TestStatistic value

`fermipy.castro.build_source_dict (src_name, peak_dict, spec_dict, spec_type)`

`fermipy.castro.convert_sed_cols (tab)`  
Cast SED column names to lowercase.

## fermipy.tsmap module

**class** `fermipy.tsmap.TSCubeGenerator`

Bases: `object`

**tscube** (*prefix=*”, *\*\*kwargs*)

Generate a spatial TS map for a source component with properties defined by the `model` argument. This method uses the `gttscube` ST application for source fitting and will simultaneously fit the test source normalization as well as the normalizations of any background components that are currently free. The output of this method is a dictionary containing *Map* objects with the TS and amplitude of the best-fit test source. By default this method will also save maps to FITS files and render them as image files.

### Parameters

- **prefix** (*str*) – Optional string that will be prepended to all output files (FITS and rendered images).
- **model** (*dict*) – Dictionary defining the properties of the test source.
- **do\_sed** (*bool*) – Compute the energy bin-by-bin fits.

- **nnorm** (*int*) – Number of points in the likelihood v. normalization scan.
- **norm\_sigma** (*float*) – Number of sigma to use for the scan range.
- **tol** (*float*) – Criteria for fit convergence (estimated vertical distance to min < tol ).
- **tol\_type** (*int*) – Absolute (0) or relative (1) criteria for convergence.
- **max\_iter** (*int*) – Maximum number of iterations for the Newton's method fitter
- **remake\_test\_source** (*bool*) – If true, recomputes the test source image (otherwise just shifts it)
- **st\_scan\_level** (*int*) –
- **make\_plots** (*bool*) – Write image files.
- **write\_fits** (*bool*) – Write a FITS file with the results of the analysis.

**Returns** **maps** – A dictionary containing the [Map](#) objects for TS and source amplitude.

**Return type** [dict](#)

**class** `fermipy.tsmap.TSMapGenerator`

Bases: [object](#)

Mixin class for [GTAnalysis](#) that generates TS maps.

**tsmap** (*prefix="*, *\*\*kwargs*)

Generate a spatial TS map for a source component with properties defined by the `model` argument. The TS map will have the same geometry as the ROI. The output of this method is a dictionary containing [Map](#) objects with the TS and amplitude of the best-fit test source. By default this method will also save maps to FITS files and render them as image files.

This method uses a simplified likelihood fitting implementation that only fits for the normalization of the test source. Before running this method it is recommended to first optimize the ROI model (e.g. by running [optimize\(\)](#)).

**Parameters**

- **prefix** (*str*) – Optional string that will be prepended to all output files.
- **{options}** –

**Returns** **tsmap** – A dictionary containing the [Map](#) objects for TS and source amplitude.

**Return type** [dict](#)

`fermipy.tsmap.cash` (*counts*, *model*)

Compute the Poisson log-likelihood function.

`fermipy.tsmap.convert_tscube` (*infile*, *outfile*)

`fermipy.tsmap.convert_tscube_old` (*infile*, *outfile*)

Convert between old and new TSCube formats.

`fermipy.tsmap.extract_array` (*array\_large*, *array\_small*, *position*)

`fermipy.tsmap.extract_images_from_tscube` (*infile*, *outfile*)

Extract data from table HDUs in TSCube file and convert them to FITS images

`fermipy.tsmap.extract_large_array` (*array\_large*, *array\_small*, *position*)

`fermipy.tsmap.extract_small_array` (*array\_small*, *array\_large*, *position*)

`fermipy.tsmap.f_cash` (*x*, *counts*, *bkg*, *model*)

Wrapper for cash statistics, that defines the model function.

**Parameters**

- **x** (*float*) – Model amplitude.
- **counts** (*ndarray*) – Count map slice, where model is defined.
- **bkg** (*ndarray*) – Background map slice, where model is defined.
- **model** (*ndarray*) – Source template (multiplied with exposure).

`fermipy.tsmap.f_cash_sum(x, counts, bkg, model, bkg_sum=0, model_sum=0)`

`fermipy.tsmap.poisson_log_like(counts, model)`

Compute the Poisson log-likelihood function for the given counts and model arrays.

`fermipy.tsmap.truncate_array(array1, array2, position)`

Truncate array1 by finding the overlap with array2 when the array1 center is located at the given position in array2.

**fermipy.residmap module**

**class** `fermipy.residmap.ResidMapGenerator`

Bases: `object`

Mixin class for *GTAnalysis* that generates spatial residual maps from the difference of data and model maps smoothed with a user-defined spatial/spectral template. The map of residual significance can be interpreted in the same way as a TS map (the likelihood of a source at the given location).

**residmap** (*prefix=""*, *\*\*kwargs*)

Generate 2-D spatial residual maps using the current ROI model and the convolution kernel defined with the `model` argument.

**Parameters**

- **prefix** (*str*) – String that will be prefixed to the output residual map files.
- **{options}** –

**Returns** `maps` – A dictionary containing the Map objects for the residual significance and amplitude.

**Return type** `dict`

`fermipy.residmap.convolve_map(m, k, cpix, threshold=0.001, imin=0, imax=None, wmap=None)`

Perform an energy-dependent convolution on a sequence of 2-D spatial maps.

**Parameters**

- **m** (*ndarray*) – 3-D map containing a sequence of 2-D spatial maps. First dimension should be energy.
- **k** (*ndarray*) – 3-D map containing a sequence of convolution kernels (PSF) for each slice in m. This map should have the same dimension as m.
- **cpix** (*list*) – Indices of kernel reference pixel in the two spatial dimensions.
- **threshold** (*float*) – Kernel amplitude
- **imin** (*int*) – Minimum index in energy dimension.
- **imax** (*int*) – Maximum index in energy dimension.
- **wmap** (*ndarray*) – 3-D map containing a sequence of 2-D spatial maps of weights. First dimension should be energy. This map should have the same dimension as m.

```
fermipy.residmap.convolve_map_hpx(m, k, cpix, threshold=0.001, imin=0, imax=None,
                                   wmap=None)
```

Perform an energy-dependent convolution on a sequence of 2-D spatial maps.

#### Parameters

- **m** (`ndarray`) – 2-D map containing a sequence of 1-D HEALPix maps. First dimension should be energy.
- **k** (`ndarray`) – 2-D map containing a sequence of convolution kernels (PSF) for each slice in m. This map should have the same dimension as m.
- **threshold** (`float`) – Kernel amplitude
- **imin** (`int`) – Minimum index in energy dimension.
- **imax** (`int`) – Maximum index in energy dimension.
- **wmap** (`ndarray`) – 2-D map containing a sequence of 1-D HEALPix maps of weights. First dimension should be energy. This map should have the same dimension as m.

```
fermipy.residmap.convolve_map_hpx_gauss(m, sigmas, imin=0, imax=None, wmap=None)
```

Perform an energy-dependent convolution on a sequence of 2-D spatial maps.

#### Parameters

- **m** (`HpxMap`) – 2-D map containing a sequence of 1-D HEALPix maps. First dimension should be energy.
- **sigmas** (`ndarray`) – 1-D map containing a sequence gaussian widths for smoothing
- **imin** (`int`) – Minimum index in energy dimension.
- **imax** (`int`) – Maximum index in energy dimension.
- **wmap** (`ndarray`) – 2-D map containing a sequence of 1-D HEALPix maps of weights. First dimension should be energy. This map should have the same dimension as m.

```
fermipy.residmap.get_source_kernel(gta, name, kernel=None)
```

Get the PDF for the given source.

```
fermipy.residmap.poisson_lnl(nc, mu)
```

## fermipy.lightcurve module

```
class fermipy.lightcurve.LightCurve
```

Bases: `object`

```
lightcurve(name, **kwargs)
```

Generate a lightcurve for the named source. The function will complete the basic analysis steps for each bin and perform a likelihood fit for each bin. Extracted values (along with errors) are Integral Flux, spectral model, Spectral index, TS value, pred. # of photons. Note: successful calculation of TS:subscript:var requires at least one free background parameter and a previously optimized ROI model.

#### Parameters

- **name** (`str`) – source name
- **{options}** –

**Returns** `LightCurve` – Dictionary containing output of the LC analysis

**Return type** `dict`

```
fermipy.lightcurve.calcTS_var(loglike, loglike_const, flux_err, flux_const, systematic,
                             fit_success)
```

## Module contents

```
fermipy.get_git_version_fp()
```

Get the version string of the ST release.

```
fermipy.get_st_version()
```

Get the version string of the ST release.

```
fermipy.test(package=None, test_path=None, args=None, plugins=None, verbose=False,
             pastebin=None, remote_data=False, pep8=False, pdb=False, coverage=False,
             open_files=False, **kwargs)
```

Run the tests using `py.test`. A proper set of arguments is constructed and passed to `pytest.main`.

### Parameters

- **package** (*str*, *optional*) – The name of a specific package to test, e.g. ‘io.fits’ or ‘utils’. If nothing is specified all default tests are run.
- **test\_path** (*str*, *optional*) – Specify location to test by path. May be a single file or directory. Must be specified absolutely or relative to the calling directory.
- **args** (*str*, *optional*) – Additional arguments to be passed to `pytest.main` in the `args` keyword argument.
- **plugins** (*list*, *optional*) – Plugins to be passed to `pytest.main` in the `plugins` keyword argument.
- **verbose** (*bool*, *optional*) – Convenience option to turn on verbose output from `py.test`. Passing `True` is the same as specifying ‘-v’ in `args`.
- **pastebin** (*{‘failed’, ‘all’, None}*, *optional*) – Convenience option for turning on `py.test` pastebin output. Set to ‘failed’ to upload info for failed tests, or ‘all’ to upload info for all tests.
- **remote\_data** (*bool*, *optional*) – Controls whether to run tests marked with `@remote_data`. These tests use online data and are not run by default. Set to `True` to run these tests.
- **pep8** (*bool*, *optional*) – Turn on PEP8 checking via the `pytest-pep8` plugin and disable normal tests. Same as specifying ‘--pep8 -k pep8’ in `args`.
- **pdb** (*bool*, *optional*) – Turn on PDB post-mortem analysis for failing tests. Same as specifying ‘--pdb’ in `args`.
- **coverage** (*bool*, *optional*) – Generate a test coverage report. The result will be placed in the directory `htmlcov`.
- **open\_files** (*bool*, *optional*) – Fail when any tests leave files open. Off by default, because this adds extra run time to the test suite. Works only on platforms with a working `lsof` command.
- **parallel** (*int*, *optional*) – When provided, run the tests in parallel on the specified number of CPUs. If `parallel` is negative, it will use all the cores on the machine. Requires the `pytest-xdist` plugin installed. Only available when using Astropy 0.3 or later.
- **kwargs** – Any additional keywords passed into this function will be passed on to the astropy test runner. This allows use of test-related functionality implemented in later versions of astropy without explicitly updating the package template.

### 1.3.11 fermipy.jobs subpackage

The `fermipy.jobs` sub-package is a light-weight, largely standalone, package to manage data analysis pipelines. It allows the user to build up increasingly complex analysis pipelines from single applications that are callable either from inside python or from the unix command line.

#### Subpackage contents

##### Link objects

The basic building block of an analysis pipeline is a `Link` object. In general a `Link` is a single application that can be called from the command line.

The `fermipy.jobs` package implements five types of `Link` objects, and the idea is that users can make sub-classes to perform the steps of their analysis.

Every link sub-class has a small required header block, for example:

```
class AnalyzeROI(Link):
    """Small class that wraps an analysis script.

    This particular script does baseline fitting of an ROI.
    """
    appname = 'fermipy-analyze-roi'
    linkname_default = 'analyze-roi'
    usage = '%s [options]' % (appname)
    description = "Run analysis of a single ROI"

    default_options = dict(config=defaults.common['config'],
                           roi_baseline=defaults.common['roi_baseline'],
                           make_plots=defaults.common['make_plots'])

    __doc__ += Link.construct_docstring(default_options)
```

The various pieces of the header are:

- `appname` This is the unix command that will invoke this link.
- `linkname_default` This is the default name that links of this type will be given when then are put into analysis pipeline.
- `usage`, `description` These are passed to the argument parser and used to build the help string.
- `default_options` This is the set of options and default values for this link
- The `__doc__ += Link.construct_docstring(default_options)` line ensures that the default options will be included in the class's docstring.

##### Link sub-classes

There are five types of `Link` sub-classes implemented here.

- `Link`

This is the sub-class to use for a user-defined function. In this case in addition to providing the header material above, the sub-class will need to implement the `run_analysis()` to perform that function.

```
def run_analysis(self, argv):
    """Run this analysis"""
    args = self._parser.parse_args(argv)

    do_stuff
```

- Gtlink

This is the sub-class to use to invoke a Fermi ScienceTools gt-tool, such as gtsrcmaps or gtexcube2. In this case the user only needs to provide the header content to make the options they want available to the interface.

- AppLink

This is the sub-class to use to invoke a pre-existing unix command. In this case the user only needs to provide the header content to make the options they want available to the interface.

- ScatterGather

This is the sub-class to use to send a set of similar jobs to a computing batch farm. In this case the user needs to provide the standard header content and a couple of additional things. Here is an example:

```
class AnalyzeROI_SG(ScatterGather):
    """Small class to generate configurations for the `AnalyzeROI`
    ↪class.

    This loops over all the targets defined in the target list.
    """
    appname = 'fermipy-analyze-roi-sg'
    usage = "%s [options]" % (appname)
    description = "Run analyses on a series of ROIs"
    clientclass = AnalyzeROI

    job_time = 1500

    default_options = dict(ttype=defaults.common['ttype'],
                           targetlist=defaults.common['targetlist'],
                           config=defaults.common['config'],
                           roi_baseline=defaults.common['roi_baseline'],
                           make_plots=defaults.common['make_plots'])

    __doc__ += Link.construct_docstring(default_options)

    def build_job_configs(self, args):
        """Hook to build job configurations
        """
        job_configs = {}

        ttype = args['ttype']

        do_stuff

        return job_configs
```

The job\_time **class parameter** should be an estimate of the time the average job managed by this **class will** take. That **is** used to decided which batch farm resources to use to run the job, **and** how often to check **from job\_** ↪**completion**.

(continues on next page)

(continued from previous page)

The user defined function `build_job_configs()` function should build a dictionary of dictionaries that contains the parameters to use for each instance of the command that will run. E.g., if you want to analyze a set of 3 ROIs, using different config files and making different roi\_baseline output files, `build_job_configs` should return a dictionary of 3 dictionaries, something like this:

.. code-block:: python

```
job_configs = {"ROI_000000" : {config="ROI_000000/config.yaml",
                               roi_baseline="baseline",
                               make_plts=True},
               "ROI_000000" : {config="ROI_000000/config.yaml",
                               roi_baseline="baseline",
                               make_plts=True},
               "ROI_000000" : {config="ROI_000000/config.yaml",
                               roi_baseline="baseline",
                               make_plts=True}}
```

- Chain

This is the sub-class to use to run multiple Link objects in sequence.

For Chain sub-classes, in addition to the standard header material, the user should profile a `map_arguments()` method that builds up the chain and sets the options of the component Link objects using the `_set_link()` method. Here is an example:

```
def _map_arguments(self, input_dict):
    """Map from the top-level arguments to the arguments provided to
    the individual links """

    config_yaml = input_dict['config']
    config_dict = load_yaml(config_yaml)

    data = config_dict.get('data')
    comp = config_dict.get('comp')
    sourcekeys = config_dict.get('sourcekeys')

    mktimefilter = config_dict.get('mktimefilter')

    self._set_link('expcube2', Gtexpcube2wcs_SG,
                  comp=comp, data=data,
                  mktimefilter=mktimefilter)

    self._set_link('exphpsun', Gtexphpsun_SG,
                  comp=comp, data=data,
                  mktimefilter=mktimefilter)

    self._set_link('sunttemp', Gtsunttemp_SG,
                  comp=comp, data=data,
                  mktimefilter=mktimefilter,
                  sourcekeys=sourcekeys)
```



## Using Links and sub-classes in python

The main aspect of the `Link` python interface are:

- Building the `Link` and setting the parameters. By way of example we will build a `Link` of type `AnalyzeROI` and configure it do a standard analysis of the ROI using the file 'config.yaml' write the resulting ROI snapshot to 'baseline' and make the standard validation plots.

```
link = AnalyzeROI.create()
link.update_args(dict(config='config.yaml',
                      roi_baseline='baseline',
                      make_plots=True))
```

- Seeing the equivalent command line task

```
link.formatted_command()
```

- Running the `Link`:

```
link.run()
```

- Seeing the status of the `Link`:

```
link.check_job_status()
```

- Seeing the jobs associated to this `Link`:

```
link.jobs
```

- Setting the arguments used to run this `Link`:

```
link.update_args(dict=(option_name=option_value,
                       option_name2=option_value2,
                       ...))
```

## Using fermipy.jobs to analyze multiple ROIS

The `fermipy.jobs` sub-package includes a few scripts and tools that can be used to parallelize standard analysis of region of interest as well as both positive and negative control tests.

### Overview

This package implements an analysis pipeline to perform a standard analysis on multiple ROIs. This involves a lot of bookkeeping and loops over various things. It is probably easiest to first describe this with a bit of pseudo-code that represents the various analysis steps.

The various loop variable are:

- rosters

The list of all lists of targets to analyze. This might seem a bit like overkill, but it is a way to allow you to define multiple versions of the same target, e.g., to test different models.

- targets

The list of all the analysis targets. This is generated by merging all the targets from the input rosters.

- target.profiles

The list of all the spatial profiles to analyze for a particular target. This is generated by finding all the versions of a target from all the input rosters.

- sims

This is of all the simulation scenarios to analyze. This is provided by the user.

- first, last

The first and last seeds to use the random number genreator (for simulations), or the first and last random directions to use, (for random direction control studies).

```
# Initialization, prepare the analysis directories and build the list of targets
PrepareTargets(rosters)

# Data analysis

# Loop over targets
for target in targets:
    AnalyzeROI(target)

    for profile in target.profiles:
        AnalyzeSED(target, profile)
        PlotCastro(target, profile)

# Simulation analysis

# Loop over simulation scenarios
for sim in sims:

    # Loop over targets
    for target in targets:
        CopyBaseROI(sim, target)

        for profile in target.profiles:
            SimulateROI(sim, target, profile) # This loops over simulation seeds and
            ↳ produces SEDS
            CollectSED(sim, target, profile)

# Random direction control analysis

# Loop over targets
for target in targets:
    CopyBaseROI(target)
    RandomDirGen(target)

    for profile in target.profiles:
        for seed in range(first, last)
            AnalyzeSED(target, profile, seed)

        CollectSED('random', target, profile)
```

## Master Configuration File

fermipy.jobs uses [YAML](#) files to read and write its configuration in a persistent format. The configuration file has a hierarchical structure that groups parameters into dictionaries that are keyed to a section name.

```
:caption: Sample Configuration

ttype: dSphs
rosters : ['test']
spatial_models: ['point']

sim_defaults:
  seed : 0
  nsims : 20
  profile : ['point']

sims:
  'null' : {}
  'pl2_1em9' : {}

random: {}

data_plotting:
  plot-castro : {}
```

Options at the top level apply to all parts of the analysis pipeline

Listing 6: Sample *top level* Configuration

```
# Top level
ttype : 'dSphs'
rosters : ['test']
spatial_models: ['point']
```

- `ttype`: str Target tpye. This is used for bookkeeping mainly, to give the name of the top-level directory, and to call out specific configuration files.
- `rosters`: list List of rosters of targets to analyze. Each roster represents a self-consistent set of targets. Different versions of the same target can be on several different rosters. But no target should appear on a single roster more than once.
- `spatial_models`: : list List of types of spatial model to use when fitting the DM. Options are \* `point` : A point source

**Note:** If multiple rosters include the same target and profile, that target will only be analyzed once, and those results will be re-used when combining each roster.

## Simulation configuration

The `sim_defaults`, `sims` and `random` sections can be used to define analysis configurations for control studies with simulations and random sky directions.

Listing 7: Sample *simulation* Configuration

```
sim_defaults:
  seed : 0
  nsims : 20
  profile : point

sims:
  'null' : {}
  'pl2_1em9' : {}

random: {}
```

- **sim\_defaults** : dict This is a dictionary of the parameters to use for simulations. This can be overridden for specific type of simulation.
  - **seed** [int] Random number seed to use for the first simulation
  - **nsims** [int] Number of simulations
  - **profile** [str] Name of the spatial profile to use for simulations. This must match a profile defined in the roster for each target. The ‘alias\_dict’ file can be used to remap longer profile names, or to define a common name for all the profiles in a roster.

- **sims** : dict This is a dictionary of the simulation scenarios to consider, and of any option overrides for some of those scenarios.

Each defined simulation needs a ‘config/sim\_{sim\_name}.yaml’ to define the injected source to use for that simulation.

- **random**: dict This is a dictionary of the options to use for random sky direction control studies.

## Plotting configuration

Listing 8: Sample *plotting* Configuration

```
data_plotting:
  plot-castro : {}
```

- **data\_plotting** : dict

Dictionaries of which types of plots to make for data, simulations and random direction controls. These dictionaries can be used to override the default set of channels for any particular set of plots.

The various plot types are:

- **plot-castro** : SED plots of a particular target, assuming a particular spatial profile.

## Additional Configuration files

In addition to the master configuration file, the pipeline needs a few additional files.

## Fermipy Analysis Configuration Yaml

This is simply a template of the *fermipy* configuration file to be used for the baseline analysis and SED fitting in each ROI. Details of the syntax and options are [here](#) \_ The actual direction and name of the target source in this file

will be over written for each target.

### Profile Alias Configuration Yaml

This is an optional small file that remaps the target profile names to shorter names (without underscores in them). Removing the underscores helps keep the file name fields more logical, and fermipy.jobs generally uses underscores as a field separator. This also keeps file names shorter, and allows us to use roster with a mixed set of profile versions to do simulations. Here is an example:

```
ackermann2016_photoj_0.6_nfw : ack2016
geringer-sameth2015_nfw : gs2015
```

### Simulation Scenario Configuration Yaml

This file specifies the signal to inject in the analysis (if any). Here is an example, note that everything inside the ‘injected\_source’ tag is in the format that *fermipy* expects to see source definitions.

```
# For positive control tests we with injected source.
# In this case it is a powerlaw spectrum
injected_source:
  name : testpl
  source_model :
    SpatialModel : PointSource
    SpectrumType : Powerlaw
  Prefactor :
    value : 1e-9
  index :
    value: 2.
  scale :
    value : 1000.
```

For null simulations, you should include the ‘injected\_source’ tag, but leave it blank

```
# For positive control tests we with injected source.
# In this case it is a DM annihilation spectrum.
injected_source:
```

### Random Direction Control Sample Configuration Yaml

The file define how we select random directions for the random direction control studies. Here is an example:

```
# These are the parameters for the random direction selection
# The algorithm picks points on a grid

# File key for the first direction
seed : 0
# Number of directions to select
nsims : 20

# Step size between grid points (in deg)
step_x : 1.0
step_y : 1.0
```

(continues on next page)

(continued from previous page)

```
# Max distance from ROI center (in deg)
max_x : 3.0
max_y : 3.0
```

## Preparing the analysis areas

The initial setup can be done either by using the `PrepareTargets` link directly from python, or by running the `fermipy-prepare-targets` executable. This will produce a number of analysis directories and populate them with the needed configuration files.

```
link = PrepareTargets()
link.update_args(dict(ttype=dSphs,
                      rosters=['dsph_roster.yaml'],
                      spatial_models=['point'],
                      sims=['null', 'random', 'pl2_1em9']))
link.run()
```

```
fermipy-prepare-targets --ttype dSphs --rosters dsph_roster.yaml --spatial_
↪models point --sims random --sims pl2_1em9 --sims null
```

- Additional Arguments
  - `alias_dict` [None] Optional path to a file that remaps the target profile name to shorter names.

## Baseline target analysis

The first step of the analysis chain is to perform a baseline re-optimization of each ROI. This is done by using `AnalyzeROI_SG` to run the `AnalyzeROI` link on each ROI in the target list generated by `PrepareTargets`. This can be done directly from python, or from the shell using the `fermipy-analyze-roi-sg` executable.

```
link = AnalyzeROI_SG()
link.update_args(dict(ttype=dSphs,
                      targetlist='dSphs/target_list.yaml'))
link.run()

.. code-block:: shell

fermipy-analyze-roi-sg --ttype dSphs --targetlist dSphs/target_list.yaml --config_
↪config.yaml
```

- Additional Arguments
  - `config` ['config.yaml'] Name of the fermipy configuration file to use.
  - `roi_baseline` ['fit\_baseline'] Prefix to use for the output files from the baseline fit to the ROI
  - `make_plots` [False] Produce the standard plots for an ROI analysis.

## Target SED analysis

The next step of the analysis chain is to perform extract the SED each spatial profile for each target. This is done by using `AnalyzeSED_SG` to run the `AnalyzeSED` link on each ROI in the target list. This uses the baseline fits as

a starting point for the SED fits. This can be done directly from python, or from the shell using the `fermipy-analyze-sed-sg` executable.

```
link = AnalyzeSED_SG()
link.update_args(dict(ttype=dSphs,
                      targetlist='dSphs/target_list.yaml'))
link.run()

.. code-block:: shell

fermipy-analyze-sed-sg --ttype dSphs --targetlist dSphs/target_list.yaml --config_
↪config.yaml
```

- Additional Arguments

- `config` ['config.yaml'] Name of the fermipy configuration file to use.
- `roi_baseline` ['fit\_baseline'] Prefix to use for the output files from the baseline fit to the ROI
- `make_plots` [False] Produce the standard plots for a SED analysis.
- `non_null_src` [False] If set to True, the analysis will zero out the source before computing the SED. This is needed for positive control simulations.
- `skydirs` [None] Optional file with a set of directions to build SEDs for. This is used from random direction control samples.

## Simulated realizations of ROI analysis

This module provides tools to perform simulated realizations of the ROIs. This is done by copying the baseline ROI, using it as a starting point, and simulating realizations of the analysis by throwing Poisson fluctuations on the expected models counts of the ROI and then fitting those simulated data. These simulations are done for each target and can optionally include injecting a signal source. This can be done directly from python, or from the shell using executables. Here is an example of how to generate negative control (“null”) simulations. This requires having ‘config/sim\_null.yaml’ consist of just a single empty tag ‘injected\_source’. To run positive control sample you would just change “null” to, for example “pl2\_1em9”, where ‘config/sim\_pl2\_1em9.yaml’ is the yaml file with the spectral model described above.

```
# Copy the base line ROI
copy_link = CopyBaseROI_SG()
copy_link.update_args(dict(ttype=dSphs,
                           targetlist='dSphs_sim/sim_null/target_list.yaml',
                           sim='null'))
copy_link.run()

# Run simulations of the ROI
sim_link = SimulateROI_SG()
sim_link.update_args(dict(ttype=dSphs,
                           targetlist='dSphs_sim/sim_null/target_list.yaml',
                           sim='null'))
sim_link.run()

# Collect the results of the simulations
col_link = CollectSED_SG()
col_link.update_args(dict(ttype=dSphs,
                           targetlist='dSphs_sim/sim_null/target_list.yaml',
                           sim='null'))
col_link.run()
```

```
fermipy-copy-base-roi-sg --ttype dSphs --targetlist dSphs_sim/sim_null/  
↪target_list.yaml --sim null  
fermipy-simulate-roi-sg --ttype dSphs --targetlist dSphs_sim/sim_null/target_  
↪list.yaml --sim null  
fermipy-collect-sed-sg --ttype dSphs --targetlist dSphs_sim/sim_null/target_  
↪list.yaml --sim null
```

- Additional Arguments

- extracopy [] Extra files to copy from baseline fit directory.
- config ['config.yaml'] Name of the fermipy configuration file to use.
- roi\_baseline ['fit\_baseline'] Prefix to use for the output files from the baseline fit to the ROI
- non\_null\_src [False] If set to True, the analysis will zero out the source before computing the SED. This is needed for positive control simulations.
- do\_find\_src [False] Do an additional setup of source finding in the ROI.
- sim\_profile ['default'] Name of the profile to use to produce the simulations
- nsims [20] Number of simulations to run
- seed [0] Starting random number seed. Also used as in bookkeeping.
- nsims\_job [0] Number of simulations per job. 0 means to run all the simulations in a single job.

## Random Direction Control Studies

This module also provides tools to perform analyses of random directions in the ROI as a control sample. This done by copying the baseline ROI, using it as a starting point, and then picked directions away from the center of the ROI and treating them as the target. Here is an example of how to generate random direction control simulations. Defined by having 'config/sim\_null.yaml' consist of just a single empty tag 'injected\_source'. To run positive control sample you would just change "null" to, for example "pl2\_1em9", where 'config/sim\_pl2\_1em9.yaml' is the yaml file with the spectral model described above.

```
# Copy the base line ROI  
copy_link = CopyBaseROI_SG()  
copy_link.update_args(dict(ttype=dSphs,  
                           targetlist='dSphs_sim/sim_random/target_random.  
↪yaml',  
                           sim='random'))  
copy_link.run()  
  
# Make a set of random directions  
dir_link = RandomDirGen_SG()  
dir_link.update_args(dict(ttype=dSphs,  
                           targetlist='dSphs_sim/sim_random/target_list.yaml',  
                           sim='random',  
                           rand_config='config/random_dSphs.yaml'))  
dir_link.run()  
  
# Construct the SED for each random direction  
sed_link = AnalyzeSED_SG()  
sed_link.update_args(dict(ttype=dSphs,  
                           targetlist='dSphs_sim/sim_random/target_list.yaml',  
                           skydirs='skydirs.yaml'))  
sed_link.run()
```

(continues on next page)



(continued from previous page)

```
# Collect the results for the random directions
col_link = CollectSED_SG()
col_link.update_args(dict(ttype=dSphs,
                          targetlist='dSphs_sim/sim_random/target_list.yaml',
                          sim='random'))
col_link.run()
```

```
fermipy-copy-base-roi-sg --ttype dSphs --targetlist dSphs_sim/sim_random/
↪target_list.yaml --sim random
fermipy-random-dir-gen-sg --ttype dSphs --targetlist dSphs_sim/sim_random/
↪target_list.yaml --sim random --rand_config config/random_dSphs.yaml
fermipy-analyze-sed-sg --ttype dSphs --targetlist dSphs_sim/sim_random/
↪target_list.yaml --skydirs skydirs.yaml
fermipy-collect-sed-sg --ttype dSphs --targetlist dSphs_sim/sim_random/
↪target_list.yaml --sim random
```

- Additional Arguments

- extracopy [] Extra files to copy from baseline fit directory.
- config ['config.yaml'] Name of the fermipy configuration file to use.
- roi\_baseline ['fit\_baseline'] Prefix to use for the output files from the baseline fit to the ROI
- non\_null\_src [False] If set to True, the analysis will zero out the source before computing the SED. This is needed for positive control simulations.
- do\_find\_src [False] Do an additional setup of source finding in the ROI.
- write\_full [False] Write a full description of all the collected SED results
- write\_summary [False]


## Plotting Results

The module also includes code to plot the SED for each target. Note that this can also be done with the `make_plots=True` option in `AnalyzeSED_SG`.

```
link = PlotCastro_SG()
link.update_args(dict(ttype=dSphs,
                      targetlist='dSphs/target_list.yaml'))
link.run()
```

```
fermipy-plot-castro-sg --ttype dSphs --targetlist dSphs/target_list.yaml
```

One of the resulting plots would look something like this:



## Module contents

### Link class and trivial sub-classes

**class** `fermipy.jobs.link.Link`(\*\*kwargs)

Bases: `object`

A wrapper for a command line application.

This class keeps track for the arguments to pass to the application as well as input and output files.

This can be used either with other `Link` objects to build a `Chain`, or as standalone wrapper to pass configuration to the application.

Derived classes will need to override the `appname` and `linkname`-default class parameters.

#### Parameters

- **appname** (*str*) – Name of the application run by this `Link`
- **linkname\_default** (*str*) – Default name for `Link` of this type
- **default\_options** (*dict*) – Dictionary with options, defaults, helpstring and types for the parameters associated with the `Link`
- **default\_file\_args** (*dict*) – Dictionary specifying if particular parameters are associated with input or output files.
- **linkname** (*str*) – Name of this `Link`, used as a key to find it in a `Chain`.

- **link\_prefix** (*str*) – Optional prefix for this *Link*, used to distinguish between similar *Link* objects on different *Chain* objects.
- **args** (*dict*) – Up-to-date dictionary with the arguments that will be passed to the application
- **\_options** (*dict*) – Dictionary with the options that we are allowed to set and default values
- **files** (*FileDict*) – Object that keeps track of input and output files
- **jobs** (*OrderedDict*) – Dictionary mapping keys to *JobDetails*. This contains information about all the batch jobs associated to this *Link*

**appname** = 'dummy'

**arg\_names**

Return the list of arg names

**check\_input\_files** (*return\_found=True, return\_missing=True*)

Check if input files exist.

**Parameters**

- **return\_found** (*list*) – A list with the paths of the files that were found.
- **return\_missing** (*list*) – A list with the paths of the files that were missing.

**Returns**

- **found** (*list*) – List of the found files, if requested, otherwise *None*
- **missing** (*list*) – List of the missing files, if requested, otherwise *None*

**check\_job\_status** (*key='\_\_top\_\_', fail\_running=False, fail\_pending=False, force\_check=False*)

Check the status of a particular job

By default this checks the status of the top-level job, but can be made to drill into the sub-jobs.

**Parameters**

- **key** (*str*) – Key associated to the job in question
- **fail\_running** (*bool*) – If True, consider running jobs as failed
- **fail\_pending** (*bool*) – If True, consider pending jobs as failed
- **force\_check** (*bool*) – Drill into status of individual jobs' instead of using top level job only

**Returns** *status* – Job status flag

**Return type** *JobStatus*

**check\_jobs\_status** (*fail\_running=False, fail\_pending=False*)

Check the status of all the jobs run from this link and return a status flag that summarizes that.

**Parameters**

- **fail\_running** (*bool*) – If True, consider running jobs as failed
- **fail\_pending** (*bool*) – If True, consider pending jobs as failed

**Returns** *status* – Job status flag that summarizes the status of all the jobs,

**Return type** *JobStatus*

**check\_output\_files** (*return\_found=True, return\_missing=True*)

Check if output files exist.

**Parameters**

- **return\_found** (*list*) – A list with the paths of the files that were found.
- **return\_missing** (*list*) – A list with the paths of the files that were missing.

**Returns**

- **found** (*list*) – List of the found files, if requested, otherwise `None`
- **missing** (*list*) – List of the missing files, if requested, otherwise `None`

**clean\_jobs** (*recursive=False*)

Clean out all of the jobs associated to this link.

For sub-classes, if recursive is True this also clean jobs from any internal [Link](#)

**clear\_jobs** (*recursive=True*)

Clear the self.jobs dictionary that contains information about jobs associated with this [Link](#).

For sub-classes, if recursive is True this also clean jobs from any internal [Link](#)

**command\_template** ()

Build and return a string that can be used as a template invoking this chain from the command line.

The actual command can be obtained by using `self.command_template().format(**self.args)`

**static construct\_docstring** (*options*)

Construct a docstring for a set of options

**classmethod create** (*\*\*kwargs*)

Build and return a [Link](#)

**default\_file\_args** = {}

**default\_options** = {}

**description** = 'Link to run dummy'

**formatted\_command** ()

Build and return the formatted command for this [Link](#).

This is exactly the command as called from the Unix command line.

**full\_linkname**

Return the linkname with the prefix attached This is useful to distinguish between links on different Chain objects.

**get\_failed\_jobs** (*fail\_running=False, fail\_pending=False*)

Return a dictionary with the subset of jobs that are marked as failed

**Parameters**

- **fail\_running** (*bool*) – If True, consider running jobs as failed
- **fail\_pending** (*bool*) – If True, consider pending jobs as failed

**Returns** **failed\_jobs** – Dictionary mapping from job key to `JobDetails` for the failed jobs.

**Return type** `dict`

**get\_jobs** (*recursive=True*)

Return a dictionary with all the jobs

For sub-classes, if recursive is True this will include jobs from any internal [Link](#)

**linkname\_default** = 'dummy'

**classmethod main** ()

Hook to run this [Link](#) from the command line

**missing\_input\_files** ()

Make and return a dictionary of the missing input files.

This returns a dictionary mapping filepath to list of [Link](#) that use the file as input.

**missing\_output\_files** ()

Make and return a dictionary of the missing output files.

This returns a dictionary mapping filepath to list of links that produce the file as output.

**print\_summary** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, indent=", recurse\_level=2*)

Print a summary of the activity done by this [Link](#).

#### Parameters

- **stream** (*file*) – Stream to print to, must have ‘write’ method.
- **indent** (*str*) – Indentation at start of line
- **recurse\_level** (*int*) – Number of recursion levels to print

**classmethod register\_class** ()

Register this class in the LinkFactory

**run** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, dry\_run=False, stage\_files=True, resubmit\_failed=False*)

Runs this [Link](#).

This version is intended to be overwritten by sub-classes so as to provide a single function that behaves the same for all version of [Link](#)

#### Parameters

- **stream** (*file*) – Stream that this [Link](#) will print to, Must have ‘write’ function
- **dry\_run** (*bool*) – Print command but do not run it.
- **stage\_files** (*bool*) – Copy files to and from scratch staging area.
- **resubmit\_failed** (*bool*) – Flag for sub-classes to resubmit failed jobs.

**run\_analysis** (*argv*)

Implemented by sub-classes to run a particular analysis

**run\_command** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, dry\_run=False*)

Runs the command for this link. This method can be overridden by sub-classes to invoke a different command

#### Parameters

- **stream** (*file*) – Stream that this [Link](#) will print to, Must have ‘write’ function
- **dry\_run** (*bool*) – Print command but do not run it

**Returns code** – Return code from sub-process

Return type `int`

**run\_with\_log** (*dry\_run=False, stage\_files=True, resubmit\_failed=False*)

Runs this link with output sent to a pre-defined logfile

Parameters

- **dry\_run** (*bool*) – Print command but do not run it.
- **stage\_files** (*bool*) – Copy files to and from scratch staging area.
- **resubmit\_failed** (*bool*) – Flag for sub-classes to resubmit failed jobs.

**topkey** = `'__top__'`

**update\_args** (*override\_args*)

Update the argument used to invoke the application

Note that this will also update the dictionary of input and output files.

Parameters **override\_args** (*dict*) – Dictionary of arguments to override the current values

**usage** = `'dummy [options]'`

Utilities to chain together a series of ScienceTools apps

**class** `fermipy.jobs.gtlink.Gtlink` (*\*\*kwargs*)

Bases: `fermipy.jobs.link.Link`

A wrapper for a single ScienceTools application

This class keeps track for the arguments to pass to the application as well as input and output files.

This can be used either with other `Link` to build a `Chain`, or as as standalone wrapper to pass configuration to the application.

See help for `chain.Link` for additional details

**appname** = `'dummy'`

**command\_template** ()

Build and return a string that can be used as a template invoking this chain from the command line.

The actual command can be obtained by using `self.command_template().format(**self.args)`

**description** = `'Link to run dummy'`

**get\_gtapp** ()

Returns a `GtApp` object that will run this `Link`

**linkname\_default** = `'dummy'`

**run\_analysis** (*argv*)

Implemented by sub-classes to run a particular analysis

**run\_command** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, dry\_run=False*)

Runs the command for this link. This method can be overridden by sub-classes to invoke a different command

Parameters

- **stream** (*file*) – Must have ‘write’ function
- **dry\_run** (*bool*) – Print command but do not run it

**update\_args** (*override\_args*)

Update the argument used to invoke the application

See help for `chain.Link` for details

This calls the base class function then fills the parameters of the `GtApp` object

**usage** = 'dummy [options]'

`fermipy.jobs.gtlink.build_gtapp` (*appname*, *dry\_run*, *\*\*kwargs*)

Build an object that can run ScienceTools application

#### Parameters

- **appname** (*str*) – Name of the application (e.g., `gtbin`)
- **dry\_run** (*bool*) – Print command but do not run it
- **kwargs** (*arguments used to invoke the application*) –
- **GtApp.GtApp** object that will run the application in question  
(Returns) –

`fermipy.jobs.gtlink.extract_parameters` (*pil*, *keys=None*)

Extract and return parameter names and values from a `pil` object

#### Parameters

- **pil** (*Pil* object) –
- **keys** (*list*) – List of parameter names, if `None`, extract all parameters

**Returns** `out_dict` – Dictionary with parameter name, value pairs

**Return type** `dict`

`fermipy.jobs.gtlink.run_gtapp` (*gtapp*, *stream*, *dry\_run*, *\*\*kwargs*)

Runs one on the ScienceTools apps

Taken from `fermipy.gtanalysis.run_gtapp` by Matt Wood

#### Parameters

- **gtapp** (`GtApp.GtApp` object) – The application (e.g., `gtbin`)
- **stream** (*stream object*) – Must have ‘write’ function
- **dry\_run** (*bool*) – Print command but do not run it
- **kwargs** (*arguments used to invoke the application*) –

`fermipy.jobs.gtlink.update_gtapp` (*gtapp*, *\*\*kwargs*)

Update the parameters of the object that can run ScienceTools applications

#### Parameters

- **gtapp** (`GtApp.GtApp`) – Object that will run the application in question
- **kwargs** (*arguments used to invoke the application*) –

**class** `fermipy.jobs.app_link.AppLink` (*\*\*kwargs*)

Bases: `fermipy.jobs.link.Link`

A wrapper for a single fermipy application

This class keeps track for the arguments to pass to the application as well as input and output files.

This can be used either with other `Link` to build a `Chain`, or as a standalone wrapper to pass configuration to the application.

See help for `Link` for additional details

```
appname = 'dummy'
description = 'Link to run dummy'
linkname_default = 'dummy'
run_analysis (argv)
    Implemented by sub-classes to run a particular analysis
usage = 'dummy [options]'
```

## ScatterGather class

```
class fermipy.jobs.scatter_gather.ScatterGather (link, **kwargs)
```

Bases: `fermipy.jobs.link.Link`

Class to dispatch several jobs in parallel and collect and merge the results.

Sub-classes will need to generate configuration for the jobs that they launch.

### Parameters

- **clientclass** (*type*) – Type of `Link` object managed by this class.
- **job\_time** (*int*) – Estimated maximum time it takes to run a job This is used to manage batch farm scheduling and checking for completion.

```
appname = 'dummy-sg'
```

```
build_job_configs (args)
```

Hook to build job configurations

Sub-class implementation should return:

**job\_configs** [dict] Dictionary of dictionaries passed to parallel jobs

```
check_status (stream=<_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>,
              check_once=False, fail_pending=False, fail_running=False, no_wait=False,
              do_print=True, write_status=False)
```

Loop to check on the status of all the jobs in job dict.

### Parameters

- **stream** (*file*) – Stream that this function will print to, Must have 'write' function.
- **check\_once** (*bool*) – Check status once and exit loop.
- **fail\_pending** (*bool*) – If True, consider pending jobs as failed
- **fail\_running** (*bool*) – If True, consider running jobs as failed
- **no\_wait** (*bool*) – Do not sleep before checking jobs.
- **do\_print** (*bool*) – Print summary stats.
- **write\_status** (*bool*) – Write the status the to log file.

**Returns** **status\_vect** – Vector that summarize the number of jobs in various states.

**Return type** `JobStatusVector`

```
clean_jobs (recursive=False)
```

Clean up all the jobs associated with this object.

If recursive is True this also clean jobs dispatch by this object.



**clear\_jobs** (*recursive=True*)

Clear the self.jobs dictionary that contains information about jobs associated with this *ScatterGather*

If recursive is True this will include jobs from all internal *Link*

**clientclass** = None

**classmethod create** (*\*\*kwargs*)

Build and return a *ScatterGather* object

**default\_options** = {}

**default\_options\_base** = {'action': ('run', 'Action to perform', <class 'str'>), 'check

**default\_prefix\_logfile** = 'scatter'

**description** = 'Run multiple analyses'

**get\_jobs** (*recursive=True*)

Return a dictionary with all the jobs

If recursive is True this will include jobs from all internal *Link*

**job\_time** = 1500

**classmethod main** ()

Hook for command line interface to sub-classes

**print\_failed** (*stream=<\_io.TextIOWrapper name='<stderr>' mode='w' encoding='UTF-8'>*)

Print list of the failed jobs

**print\_summary** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, indent="", recurse\_level=2*)

Print a summary of the activity done by this *Link*.

#### Parameters

- **stream** (*file*) – Stream to print to
- **indent** (*str*) – Indentation at start of line
- **recurse\_level** (*int*) – Number of recursion levels to print

**print\_update** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, job\_stats=None*)

Print an update about the current number of jobs running

**resubmit** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, fail\_running=False, resubmit\_failed=False*)

Function to resubmit failed jobs and collect results

#### Parameters

- **stream** (*file*) – Stream that this function will print to, Must have 'write' function.
- **fail\_running** (*bool*) – If True, consider running jobs as failed
- **resubmit\_failed** (*bool*) – Resubmit failed jobs.

**Returns** *status\_vect* – Vector that summarize the number of jobs in various states.

**Return type** *JobStatusVector*

**run** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, dry\_run=False, stage\_files=True, resubmit\_failed=True*)

Runs this *Link*.

This version is intended to be overwritten by sub-classes so as to provide a single function that behaves the same for all version of `Link`

#### Parameters

- **stream** (*file*) – Stream that this `Link` will print to, Must have ‘write’ function
- **dry\_run** (*bool*) – Print command but do not run it.
- **stage\_files** (*bool*) – Copy files to and from scratch staging area.
- **resubmit\_failed** (*bool*) – Flag for sub-classes to resubmit failed jobs.

#### **run\_analysis** (*argv*)

Implemented by sub-classes to run a particular analysis

#### **run\_jobs** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, resubmit\_failed=False*)

Function to dispatch jobs and collect results

#### Parameters

- **stream** (*file*) – Stream that this function will print to, Must have ‘write’ function.
- **resubmit\_failed** (*bool*) – Resubmit failed jobs.

**Returns** `status_vect` – Vector that summarize the number of jobs in various states.

**Return type** `JobStatusVector`

#### **scatter\_link**

Return the `Link` object used the scatter phase of processing

#### **update\_args** (*override\_args*)

Update the arguments used to invoke the application

Note that this will also update the dictionary of input and output files

**Parameters** `override_args` (*dict*) – dictionary of arguments to override the current values

**usage** = 'dummy-sg [options]'

## Chain class

### **class** `fermipy.jobs.chain.Chain` (*\*\*kwargs*)

Bases: `fermipy.jobs.link.Link`

An object tying together a series of applications into a single application.

This class keep track of the arguments to pass to the applications as well as input and output files.

Note that this class is itself a `Link`. This allows you to write a python module that implements a chain and also has a `__main__` function to allow it to be called from the shell.

#### **check\_links\_status** (*fail\_running=False, fail\_pending=False*)

“Check the status of all the jobs run from the `Link` objects in this `Chain` and return a status flag that summarizes that.

#### Parameters

- **fail\_running** (*bool*) – If True, consider running jobs as failed
- **fail\_pending** (*bool*) – If True, consider pending jobs as failed

**Returns** `status` – Job status flag that summarizes the status of all the jobs,

**Return type** `JobStatus`

**clear\_jobs** (*recursive=True*)

Clear a dictionary with all the jobs

If recursive is True this will include jobs from all internal `Link`

**get\_jobs** (*recursive=True*)

Return a dictionary with all the jobs

If recursive is True this will include jobs from all internal `Link`

**linknames**

Return the name of the `Link` objects owned by this `Chain`

**links**

Return the `OrderedDict` of `Link` objects owned by this `Chain`

**load\_config** (*configfile*)

Read a config file for the top-level arguments

**classmethod main** ()

Hook to run this `Chain` from the command line

**missing\_input\_files** ()

Make and return a dictionary of the missing input files.

This returns a dictionary mapping filepath to list of `Link` that use the file as input.

**missing\_output\_files** ()

Make and return a dictionary of the missing output files.

This returns a dictionary mapping filepath to list of links that produce the file as output.

**print\_status** (*indent="", recurse=False*)

Print a summary of the job status for each `Link` in this `Chain`

**print\_summary** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, indent="", recurse\_level=2*)

Print a summary of the activity done by this `Chain`.

**Parameters**

- **stream** (*file*) – Stream to print to, must have ‘write’ method.
- **indent** (*str*) – Indentation at start of line
- **recurse\_level** (*int*) – Number of recursion levels to print

**run** (*stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, dry\_run=False, stage\_files=True, resubmit\_failed=False*)

Runs this `Chain`.

**Parameters**

- **stream** (*file*) – Stream that this `Link` will print to, Must have ‘write’ function
- **dry\_run** (*bool*) – Print command but do not run it.
- **stage\_files** (*bool*) – Copy files to and from scratch staging area.
- **resubmit\_failed** (*bool*) – Flag for sub-classes to resubmit failed jobs.

**run\_analysis** (*argv*)

Implemented by sub-classes to run a particular analysis

**update\_args** (*override\_args*)

Update the argument used to invoke the application

Note that this will also update the dictionary of input and output files.

**Parameters** **override\_args** (*dict*) – dictionary passed to the links

## High-level analysis classes

These are `Link` sub-classes that implement *fermipy* analyses, or perform tasks related to *fermipy* analyses, such as plotting or collecting results for a set of simulations.

**class** `fermipy.jobs.target_analysis.AnalyzeROI` (*\*\*kwargs*)

Bases: `fermipy.jobs.link.Link`

Small class that wraps an analysis script.

This particular script does baseline fitting of an ROI.

### Parameters

- **config** (*<class 'str'>*) – Path to fermipy config file. [config.yaml]
- **make\_plots** (*<class 'bool'>*) – Make plots [False]
- **roi\_baseline** (*<class 'str'>*) – Key for roi baseline file. [fit\_baseline]

**appname** = 'fermipy-analyze-roi'

**default\_options** = {'config': ('config.yaml', 'Path to fermipy config file.', <class 'str'>), 'roi\_baseline': ('fit\_baseline', 'Key for roi baseline file.', <class 'str'>), 'make\_plots': (False, 'Make plots.', <class 'bool'>)}

**description** = 'Run analysis of a single ROI'

**linkname\_default** = 'analyze-roi'

**run\_analysis** (*argv*)

Run this analysis

**usage** = 'fermipy-analyze-roi [options]'

**class** `fermipy.jobs.target_analysis.AnalyzeSED` (*\*\*kwargs*)

Bases: `fermipy.jobs.link.Link`

Small class to wrap an analysis script.

This particular script fits an SED for a target source with respect to the baseline ROI model.

### Parameters

- **config** (*<class 'str'>*) – Path to fermipy config file. [config.yaml]
- **roi\_baseline** (*<class 'str'>*) – Key for roi baseline file. [fit\_baseline]
- **profiles** (*<class 'list'>*) – List of profiles to analyze [[]]
- **non\_null\_src** (*<class 'bool'>*) – Zero out test source [False]
- **make\_plots** (*<class 'bool'>*) – Make plots [False]
- **skydirs** (*<class 'str'>*) – Yaml file with blank sky directions. [None]

**appname** = 'fermipy-analyze-sed'

**default\_options** = {'config': ('config.yaml', 'Path to fermipy config file.', <class 'str'>), 'roi\_baseline': ('fit\_baseline', 'Key for roi baseline file.', <class 'str'>), 'profiles': ([], 'List of profiles to analyze.', <class 'list'>), 'non\_null\_src': (False, 'Zero out test source.', <class 'bool'>), 'make\_plots': (False, 'Make plots.', <class 'bool'>), 'skydirs': (None, 'Yaml file with blank sky directions.', <class 'str'>)}

```

description = 'Extract the SED for a single target'
linkname_default = 'analyze-sed'
run_analysis(argv)
    Run this analysis
usage = 'fermipy-analyze-sed [options]'

```

**class** fermipy.jobs.target\_collect.CollectSED(\*\*kwargs)  
Bases: *fermipy.jobs.link.Link*

Small class to collect SED results from a series of simulations.

**Parameters**

- **summaryfile** (<class 'str'>) – Path to file with results summaries. [None]
- **outfile** (<class 'str'>) – Path to output file. [None]
- **sed\_file** (<class 'str'>) – Path to SED file. [None]
- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **nsims** (<class 'int'>) – Number of simulations to run. [20]
- **dry\_run** (<class 'bool'>) – Print commands but do not run them. [False]
- **enumbins** (<class 'int'>) – Number of energy bins [12]
- **seed** (<class 'int'>) – Seed number for first simulation. [0]

```

appname = 'fermipy-collect-sed'
collist = [{'unit': 'MeV', 'name': 'e_min'}, {'unit': 'MeV', 'name': 'e_ref'}, {'unit': 'MeV', 'name': 'e_max'}]
default_options = {'config': ('config.yaml', 'Path to fermipy config file.', <class 'str'>)}
description = 'Collect SED results from simulations'
linkname_default = 'collect-sed'
run_analysis(argv)
    Run this analysis
usage = 'fermipy-collect-sed [options]'

```

**class** fermipy.jobs.target\_sim.CopyBaseROI(\*\*kwargs)  
Bases: *fermipy.jobs.link.Link*

**Small class to copy a baseline ROI to a simulation area** This is useful for parallelizing analysis using the fermipy.jobs module.

**Parameters**

- **sim** (<class 'str'>) – Name of the simulation scenario. [None]
- **extracopy** (<class 'list'>) – Extra files to copy [[]]
- **ttype** (<class 'str'>) – Type of target being analyzed. [None]
- **target** (<class 'str'>) – Name of analysis target. [None]
- **roi\_baseline** (<class 'str'>) – Key for roi baseline file. [fit\_baseline]

```

appname = 'fermipy-copy-base-roi'

```

```
classmethod copy_analysis_files(orig_dir, dest_dir, copyfiles)
    Copy a list of files from orig_dir to dest_dir

classmethod copy_target_dir(orig_dir, dest_dir, roi_baseline, extracopy)
    Create and populate directoris for target analysis

copyfiles = ['srcmap_*.fits', 'ccube.fits', 'ccube_*.fits']

default_options = {'extracopy': ([], 'Extra files to copy', <class 'list'>), 'roi_base

description = 'Copy a baseline ROI to a simulation area'

linkname_default = 'copy-base-roi'

run_analysis(argv)
    Run this analysis

usage = 'fermipy-copy-base-roi [options]'

class fermipy.jobs.target_sim.RandomDirGen(**kwargs)
    Bases: fermipy.jobs.link.Link

    Small class to generate random sky directions inside an ROI This is useful for parallelizing analysis using
    the fermipy.jobs module.
```

#### Parameters

- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **outfile** (<class 'str'>) – Path to output file. [None]
- **rand\_config** (<class 'str'>) – Path to config file for generation random sky dirs [None]

```
appname = 'fermipy-random-dir-gen'

default_options = {'config': ('config.yaml', 'Path to fermipy config file.', <class '

description = 'Generate random sky directions in an ROI'

linkname_default = 'random-dir-gen'

run_analysis(argv)
    Run this analysis

usage = 'fermipy-random-dir-gen [options]'

class fermipy.jobs.target_sim.SimulateROI(**kwargs)
    Bases: fermipy.jobs.link.Link
```

Small class wrap an analysis script. This is useful for parallelizing analysis using the fermipy.jobs module.

#### Parameters

- **profiles** (<class 'list'>) – List of profiles to analyze [[]]
- **non\_null\_src** (<class 'bool'>) – Zero out test source [False]
- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **nsims** (<class 'int'>) – Number of simulations to run. [20]
- **roi\_baseline** (<class 'str'>) – Key for roi baseline file. [fit\_baseline]
- **sim\_profile** (<class 'str'>) – Name of the profile to use for simulation. [default]

- **do\_find\_src** (<class 'bool'>) – Add source finding step to simulated realizations [False]
- **seed** (<class 'int'>) – Seed number for first simulation. [0]
- **sim** (<class 'str'>) – Name of the simulation scenario. [None]

**appname** = 'fermipy-simulate-roi'

**default\_options** = {'config': ('config.yaml', 'Path to fermipy config file.', <class 'str'>), 'outfile': ('', 'Path to output file.', <class 'str'>), 'infile': ('', 'Path to input file.', <class 'str'>), 'make\_plots': (False, 'Make plots.', <class 'bool'>), 'targetlist': ('', 'Path to the target list.', <class 'str'>), 'roi\_baseline': ('', 'Key for roi baseline file.', <class 'str'>), 'ttype': ('', 'Type of target being analyzed.', <class 'str'>)}.

**description** = 'Run simulated analysis of a single ROI'

**linkname\_default** = 'simulate-roi'

**run\_analysis** (argv)

Run this analysis

**usage** = 'fermipy-simulate-roi [options]'

**class** fermipy.jobs.target\_plotting.PlotCastro (\*\*kwargs)

Bases: [fermipy.jobs.link.Link](#)

Small class to plot an SED as a ‘Castro’ plot.

#### Parameters

- **outfile** (<class 'str'>) – Path to output file. [None]
- **infile** (<class 'str'>) – Path to input file. [None]

**appname** = 'fermipy-plot-castro'

**default\_options** = {'infile': (None, 'Path to input file.', <class 'str'>), 'outfile': ('', 'Path to output file.', <class 'str'>), 'make\_plots': (False, 'Make plots.', <class 'bool'>), 'targetlist': ('', 'Path to the target list.', <class 'str'>), 'roi\_baseline': ('', 'Key for roi baseline file.', <class 'str'>), 'ttype': ('', 'Type of target being analyzed.', <class 'str'>)}.

**description** = 'Plot likelihood v. flux normalization and energy'

**linkname\_default** = 'plot-castro'

**run\_analysis** (argv)

Run this analysis

**usage** = 'fermipy-plot-castro [options]'

## High-level analysis job dispatch

These are ScatterGather sub-classes that invoke the Link sub-classes listed above.

**class** fermipy.jobs.target\_analysis.AnalyzeROI\_SG (link, \*\*kwargs)

Bases: [fermipy.jobs.scatter\\_gather.ScatterGather](#)

Small class to generate configurations for the [AnalyzeROI](#) class.

This loops over all the targets defined in the target list.

#### Parameters

- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **make\_plots** (<class 'bool'>) – Make plots [False]
- **targetlist** (<class 'str'>) – Path to the target list. [None]
- **roi\_baseline** (<class 'str'>) – Key for roi baseline file. [fit\_baseline]
- **ttype** (<class 'str'>) – Type of target being analyzed. [None]

```
appname = 'fermipy-analyze-roi-sg'
build_job_configs(args)
    Hook to build job configurations

clientclass
    alias of AnalyzeROI

default_options = {'config': ('config.yaml', 'Path to fermipy config file.', <class '
description = 'Run analyses on a series of ROIs'
job_time = 1500
usage = 'fermipy-analyze-roi-sg [options]'
```

**class** fermipy.jobs.target\_analysis.**AnalyzeSED\_SG**(link, \*\*kwargs)  
Bases: *fermipy.jobs.scatter\_gather.ScatterGather*  
Small class to generate configurations for this script  
This loops over all the targets defined in the target list, and over all the profiles defined for each target.

**Parameters**

- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **targetlist** (<class 'str'>) – Path to the target list. [None]
- **roi\_baseline** (<class 'str'>) – Key for roi baseline file. [fit\_baseline]
- **non\_null\_src** (<class 'bool'>) – Zero out test source [False]
- **make\_plots** (<class 'bool'>) – Make plots [False]
- **skydirs** (<class 'str'>) – Yaml file with blank sky directions. [None]
- **ttype** (<class 'str'>) – Type of target being analyzed. [None]

```
appname = 'fermipy-analyze-sed-sg'
build_job_configs(args)
    Hook to build job configurations

clientclass
    alias of AnalyzeSED

default_options = {'config': ('config.yaml', 'Path to fermipy config file.', <class '
description = 'Run analyses on a series of ROIs'
job_time = 1500
usage = 'fermipy-analyze-sed-sg [options]'
```

**class** fermipy.jobs.target\_collect.**CollectSED\_SG**(link, \*\*kwargs)  
Bases: *fermipy.jobs.scatter\_gather.ScatterGather*  
Small class to generate configurations for *CollectSED*  
This loops over all the targets defined in the target list

**Parameters**

- **write\_summary** (<class 'bool'>) – Write file with summary of collected results [False]



- **targetlist** (<class 'str'>) – Path to the target list. [None]
- **ttype** (<class 'str'>) – Type of target being analyzed. [None]
- **write\_full** (<class 'bool'>) – Write file with full collected results [False]
- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **nsims** (<class 'int'>) – Number of simulations to run. [20]
- **seed** (<class 'int'>) – Seed number for first simulation. [0]
- **sim** (<class 'str'>) – Name of the simulation scenario. [None]

**appname** = 'fermipy-collect-sed-sg'

**build\_job\_configs** (*args*)

Hook to build job configurations

**clientclass**

alias of *CollectSED*

**default\_options** = {'config': ('config.yaml', 'Path to fermipy config file.', <class 'str'>),

**description** = 'Collect SED data from a set of simulations for a series of ROIs'

**job\_time** = 120

**usage** = 'fermipy-collect-sed-sg [options]'

**class** fermipy.jobs.target\_sim.**CopyBaseROI\_SG** (*link*, **\*\*kwargs**)

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

**Small class to generate configurations for this script** This adds the following arguments:

#### Parameters

- **sim** (<class 'str'>) – Name of the simulation scenario. [None]
- **extracopy** (<class 'list'>) – Extra files to copy [[]]
- **targetlist** (<class 'str'>) – Path to the target list. [None]
- **ttype** (<class 'str'>) – Type of target being analyzed. [None]
- **roi\_baseline** (<class 'str'>) – Key for roi baseline file. [fit\_baseline]

**appname** = 'fermipy-copy-base-roi-sg'

**build\_job\_configs** (*args*)

Hook to build job configurations

**clientclass**

alias of *CopyBaseROI*

**default\_options** = {'extracopy': ([], 'Extra files to copy', <class 'list'>), 'roi\_base

**description** = 'Run analyses on a series of ROIs'

**job\_time** = 60

**usage** = 'fermipy-copy-base-roi-sg [options]'

**class** fermipy.jobs.target\_sim.**RandomDirGen\_SG** (*link*, **\*\*kwargs**)

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

**Small class to generate configurations for this script** This adds the following arguments:

**Parameters**

- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **sim** (<class 'str'>) – Name of the simulation scenario. [None]
- **targetlist** (<class 'str'>) – Path to the target list. [None]
- **ttype** (<class 'str'>) – Type of target being analyzed. [None]
- **rand\_config** (<class 'str'>) – Path to config file for generation random sky dirs [None]

**appname** = 'fermipy-random-dir-gen-sg'

**build\_job\_configs** (*args*)

Hook to build job configurations

**clientclass**

alias of *RandomDirGen*

**default\_options** = {'config': ('config.yaml', 'Path to fermipy config file.', <class 'str'>),

**description** = 'Run analyses on a series of ROIs'

**job\_time** = 60

**usage** = 'fermipy-random-dir-gen-sg [options]'

**class** fermipy.jobs.target\_sim.**SimulateROI\_SG** (*link*, *\*\*kwargs*)

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

**Small class to generate configurations for this script** This adds the following arguments:

**Parameters**

- **targetlist** (<class 'str'>) – Path to the target list. [None]
- **ttype** (<class 'str'>) – Type of target being analyzed. [None]
- **non\_null\_src** (<class 'bool'>) – Zero out test source [False]
- **config** (<class 'str'>) – Path to fermipy config file. [config.yaml]
- **nsims\_job** (<class 'int'>) – Number of simulations to run per job. [0]
- **nsims** (<class 'int'>) – Number of simulations to run. [20]
- **roi\_baseline** (<class 'str'>) – Key for roi baseline file. [fit\_baseline]
- **sim\_profile** (<class 'str'>) – Name of the profile to use for simulation. [default]
- **do\_find\_src** (<class 'bool'>) – Add source finding step to simulated realizations [False]
- **seed** (<class 'int'>) – Seed number for first simulation. [0]
- **sim** (<class 'str'>) – Name of the simulation scenario. [None]

**appname** = 'fermipy-simulate-roi-sg'

**build\_job\_configs** (*args*)

Hook to build job configurations

**clientclass**

alias of *SimulateROI*

```

default_options = {'config': ('config.yaml', 'Path to fermipy config file.', <class 'str'>),
description = 'Run analyses on a series of ROIs'
job_time = 1500
usage = 'fermipy-simulate-roi-sg [options]'

class fermipy.jobs.target_plotting.PlotCastro_SG(link, **kwargs)
    Bases: fermipy.jobs.scatter_gather.ScatterGather
    Small class to generate configurations for the PlotCastro class.
        This loops over all the targets defined in the target list.

    Parameters
        • targetlist (<class 'str'>) – Path to the target list. [None]
        • tttype (<class 'str'>) – Type of target being analyzed. [None]

    appname = 'fermipy-plot-castro-sg'
    build_job_configs(args)
        Hook to build job configurations

    clientclass
        alias of PlotCastro

    default_options = {'targetlist': (None, 'Path to the target list.', <class 'str'>), '
description = 'Make castro plots for set of targets'
job_time = 60
usage = 'fermipy-plot-castro-sg [options]'

```

## Batch and System Interfaces

Abstract interface for interactions with system for launching jobs.

```

class fermipy.jobs.sys_interface.SysInterface(**kwargs)
    Bases: object
    Base class to handle job dispatching interface

    classmethod check_job(job_details)
        Check the status of a specific job

    clean_jobs(link, job_dict=None, clean_all=False)
        Clean up all the jobs associated with this link.

        Returns a JobStatus enum

    dispatch_job(link, key, job_archive, stream=<_io.TextIOWrapper name='<stdout>' mode='w'
        encoding='UTF-8'>)
        Function to dispatch a single job

```

### Parameters

- **link** (*Link*) – Link object that sends the job
- **key** (*str*) – Key used to identify this particular job
- **job\_archive** (*JobArchive*) – Archive used to keep track of jobs

- **JobDetails object** (*Returns*) –

**dispatch\_job\_hook** (*link, key, job\_config, logfile, stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Hook to dispatch a single job

**string\_exited** = 'Exited with exit code'

**string\_successful** = 'Successfully completed'

C'tor

**submit\_jobs** (*link, job\_dict=None, job\_archive=None, stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Run the Link with all of the items job\_dict as input.

If job\_dict is None, the job\_dict will be take from link.jobs

Returns a JobStatus enum

`fermipy.jobs.sys_interface.check_log` (*logfile, exited='Exited with exit code', successful='Successfully completed'*)

Check a log file to determine status of LSF job

Often logfile doesn't exist because the job hasn't begun to run. It is unclear what you want to do in that case...

#### Parameters

- **logfile** (*str*) – String with path to logfile
- **exited** (*str*) – Value to check for in existing logfile for exit with failure
- **successful** (*str*) – Value to check for in existing logfile for success
- **str, one of 'Pending', 'Running', 'Done', 'Failed'** (*Returns*) –

`fermipy.jobs.sys_interface.clean_job` (*logfile, outfiles, dry\_run=False*)

Removes log file and files created by failed jobs.

If dry\_run is True, print name of files to be removed, but do not remove them.

`fermipy.jobs.sys_interface.remove_file` (*filepath, dry\_run=False*)

Remove the file at filepath

Catches exception if the file does not exist.

If dry\_run is True, print name of file to be removed, but do not remove it.

Implementation of ScatterGather class for dealing with LSF batch jobs

**class** `fermipy.jobs.native_impl.NativeInterface` (*\*\*kwargs*)

Bases: `fermipy.jobs.sys_interface.SysInterface`

Implmention of ScatterGather that uses the native system

**dispatch\_job\_hook** (*link, key, job\_config, logfile, stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Send a single job to be executed

#### Parameters

- **link** (`fermipy.jobs.chain.Link`) – The link used to invoke the command we are running
- **key** (*str*) – A string that identifies this particular instance of the job
- **job\_config** (*dict*) – A dictionary with the arguments for the job. Used with the `self._command_template` job template

- **logfile** (*str*) – The logfile for this job, may be used to check for success/ failure

**string\_exited** = 'Exited with exit code'

**string\_successful** = 'Successfully completed'

**submit\_jobs** (*link*, *job\_dict=None*, *job\_archive=None*, *stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)  
Submit all the jobs in *job\_dict*

**fermipy.jobs.native\_impl.get\_native\_default\_args()**

Get the correct set of batch jobs arguments.

Implementation of ScatterGather interface class for dealing with LSF batch jobs at SLAC

**class** **fermipy.jobs.slac\_impl.SlacInterface** (*\*\*kwargs*)

Bases: *fermipy.jobs.sys\_interface.SysInterface*

Implmention of ScatterGather that uses LSF

**dispatch\_job\_hook** (*link*, *key*, *job\_config*, *logfile*, *stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)

Send a single job to the LSF batch

#### Parameters

- **link** (*fermipy.jobs.chain.Link*) – The link used to invoke the command we are running
- **key** (*str*) – A string that identifies this particular instance of the job
- **job\_config** (*dict*) – A dictionary with the arguments for the job. Used with the *self.\_command\_template* job template
- **logfile** (*str*) – The logfile for this job, may be used to check for success/ failure

**string\_exited** = 'Exited with exit code'

**string\_successful** = 'Successfully completed'

**submit\_jobs** (*link*, *job\_dict=None*, *job\_archive=None*, *stream=<\_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>*)  
Submit all the jobs in *job\_dict*

**fermipy.jobs.slac\_impl.build\_bsub\_command** (*command\_template*, *lsf\_args*)

Build and return a lsf batch command template

The structure will be **'bsub -s <key> <value> <command\_template>'** where *<key>* and *<value>* refer to items in *lsf\_args*

**fermipy.jobs.slac\_impl.get\_lsf\_status()**

Count and print the number of jobs in various LSF states

**fermipy.jobs.slac\_impl.get\_slac\_default\_args** (*job\_time=1500*)

Create a batch job interface object.

**Parameters** **job\_time** (*int*) – Expected max length of the job, in seconds. This is used to select the batch queue and set the *job\_check\_sleep* parameter that sets how often we check for job completion.

**fermipy.jobs.slac\_impl.make\_gpfs\_path** (*path*)

Make a gpfs version of a file path. This just puts /gpfs at the beginning instead of /nfs

**fermipy.jobs.slac\_impl.make\_nfs\_path** (*path*)

Make a nfs version of a file path. This just puts /nfs at the beginning instead of /gpfs

Factory module to return the default interace to the batch farm

```
fermipy.jobs.batch.get_batch_job_args(job_time=1500)
```

Get the correct set of batch jobs arguments.

**Parameters** `job_time` (*int*) – Expected max length of the job, in seconds. This is used to select the batch queue and set the `job_check_sleep` parameter that sets how often we check for job completion.

**Returns** `job_args` – Dictionary of arguments used to submit a batch job

**Return type** `dict`

```
fermipy.jobs.batch.get_batch_job_interface(job_time=1500)
```

Create a batch job interface object.

**Parameters** `job_time` (*int*) – Expected max length of the job, in seconds. This is used to select the batch queue and set the `job_check_sleep` parameter that sets how often we check for job completion.

**Returns** `job_interfact` – Object that manages interactions with batch farm

**Return type** `SysInterface`

## File Archive module

Classes and utilites to keep track of files associated to an analysis.

The main class is *FileArchive*, which keep track of all the files associated to an analysis.

The *FileHandle* helper class encapsulates information on a particular file.

```
class fermipy.jobs.file_archive.FileArchive(**kwargs)
```

Bases: `object`

Class that keeps track of the status of files used in an analysis

### Parameters

- **table\_file** (*str*) – Path to the file used to persist this *FileArchive*
- **table** (`astropy.table.Table`) – Persistent representation of this *FileArchive*
- **cache** (`OrderedDict`) – Transient representation of this *FileArchive*
- **base\_path** (*str*) – Base file path for all files in this *FileArchive*

### base\_path

Return the base file path for all files in this *FileArchive*

```
classmethod build_archive(**kwargs)
```

Return the singleton *FileArchive* instance, building it if needed

### cache

Return the transiet representation of this *FileArchive*

```
classmethod get_archive()
```

Return the singleton *FileArchive* instance

```
get_file_ids(file_list, creator=None, status=0, file_dict=None)
```

Get or create a list of file ids based on file names

### Parameters

- **file\_list** (*list*) – The paths to the file

- **creator** (*int*) – A unique key for the job that created these files
- **status** (*FileStatus*) – Enumeration giving current status of files
- **file\_dict** (*FileDict*) – Mask giving flags set on this file
- **list of integers** (*Returns*) –

**get\_file\_paths** (*id\_list*)

Get a list of file paths based of a set of ids

#### Parameters

- **id\_list** (*list*) – List of integer file keys
- **list of file paths** (*Returns*) –

**get\_handle** (*filepath*)

Get the *FileHandle* object associated to a particular file

**register\_file** (*filepath, creator, status=0, flags=0*)

Register a file in the archive.

If the file already exists, this raises a *KeyError*

#### Parameters

- **filepath** (*str*) – The path to the file
- **creator** (*int*) – A unique key for the job that created this file
- **status** (*FileStatus*) – Enumeration giving current status of file
- **flags** (*FileFlags*) – Enumeration giving flags set on this file
- **FileHandle** (*Returns*) –

**table**

Return the persistent representation of this *FileArchive*

**table\_file**

Return the path to the file used to persist this *FileArchive*

**update\_file** (*filepath, creator, status*)

Update a file in the archive

If the file does not exists, this raises a *KeyError*

#### Parameters

- **filepath** (*str*) – The path to the file
- **creator** (*int*) – A unique key for the job that created this file
- **status** (*FileStatus*) – Enumeration giving current status of file
- **FileHandle** (*Returns*) –

**update\_file\_status** ()

Update the status of all the files in the archive

**write\_table\_file** (*table\_file=None*)

Write the table to self.\_table\_file

**class** fermipy.jobs.file\_archive.**FileDict** (*\*\*kwargs*)

Bases: *object*

Small class to keep track of files used & created by a link.

### Parameters

- **file\_args** (*dict*) – Dictionary mapping argument to *FileFlags* enum
- **file\_dict** (*dict*) – Dictionary mapping file path to *FileFlags* enum

### **chain\_input\_files**

Return a list of the input files needed by this chain.

For *Link* sub-classes this will return only those files that were not created by any internal *Link*

### **chain\_output\_files**

Return a list of the all the output files produced by this link.

For *Link* sub-classes this will return only those files that were not marked as internal files or marked for removal.

### **gzip\_files**

Return a list of the files compressed by this link.

This returns all files that were explicitly marked for compression.

### **input\_files**

Return a list of the input files needed by this link.

For *Link* sub-classes this will return the union of all the input files of each internal *Link*.

That is to say this will include files produced by one *Link* in a *Chain* and used as input to another *Link* in the *Chain*

### **input\_files\_to\_stage**

Return a list of the input files needed by this link.

For *Link* sub-classes this will return the union of all the input files of each internal *Link*.

That is to say this will include files produced by one *Link* in a *Chain* and used as input to another *Link* in the *Chain*

### **internal\_files**

Return a list of the intermediate files produced by this link.

This returns all files that were explicitly marked as internal files.

### **items()**

Return iterator over self.file\_dict

### **latch\_file\_info** (*args*)

Extract the file paths from a set of arguments

### **output\_files**

Return a list of the output files produced by this link.

For *Link* sub-classes this will return the union of all the output files of each internal *Link*.

That is to say this will include files produced by one *Link* in a *Chain* and used as input to another *Link* in the *Chain*

### **output\_files\_to\_stage**

Return a list of the input files needed by this link.

For *Link* sub-classes this will return the union of all the input files of each internal *Link*.

That is to say this will include files produced by one *Link* in a *Chain* and used as input to another *Link* in the *Chain*



```
print_chain_summary (stream=<_io.TextIOWrapper          name='<stdout>'          mode='w'
                     encoding='UTF-8'>, indent="")
```

Print a summary of the files in this file dict.

This version uses chain\_input\_files and chain\_output\_files to count the input and output files.

```
print_summary (stream=<_io.TextIOWrapper name='<stdout>' mode='w' encoding='UTF-8'>, in-
               dent="")
```

Print a summary of the files in this file dict.

This version explicitly counts the union of all input and output files.

```
temp_files
```

Return a list of the temporary files produced by this link.

This returns all files that were explicitly marked for removal.

```
update (file_dict)
```

Update self with values from a dictionary mapping file path [str] to *FileFlags* enum

```
class fermipy.jobs.file_archive.FileFlags
```

Bases: *object*

Bit masks to indicate file types

```
gz_mask = 8
```

```
in_ch_mask = 23
```

```
in_stage_mask = 33
```

```
input_mask = 1
```

```
internal_mask = 16
```

```
no_flags = 0
```

```
out_ch_mask = 22
```

```
out_stage_mask = 34
```

```
output_mask = 2
```

```
rm_mask = 4
```

```
rmint_mask = 20
```

```
stageable = 32
```

```
class fermipy.jobs.file_archive.FileHandle (**kwargs)
```

Bases: *object*

Class to keep track of information about a file file.

#### Parameters

- **key** (*int*) – Unique id for this particular file
- **creator** (*int*) – Unique id for the job that created this file
- **timestamp** (*int*) – File creation time cast as an int
- **status** (*FileStatus*) – Enum giving current status of file
- **flags** (*FileFlags*) – Mask giving flags set on this file
- **path** (*str*) – Path to file

**append\_to\_table** (*table*)

Add this instance as a row on a `astropy.table.Table`

**check\_status** (*basepath=None*)

Check on the status of this particular file

**classmethod create\_from\_row** (*table\_row*)

Build and return a `FileHandle` from an `astropy.table.Row`

**classmethod make\_dict** (*table*)

Build and return a dict of `FileHandle` from an `astropy.table.Table`

The dictionary is keyed by `FileHandle.key`, which is a unique integer for each file

**static make\_table** (*file\_dict*)

Build and return an `astropy.table.Table` to store `FileHandle`

**update\_table\_row** (*table, row\_idx*)

Update the values in an `astropy.table.Table` for this instances

**class** `fermipy.jobs.file_archive.FileStageManager` (*scratchdir, workdir*)

Bases: `object`

Small class to deal with staging files to and from a scratch area

**construct\_scratch\_path** (*dirname, basename*)

Construct and return a path in the scratch area.

This will be `<self.scratchdir>/<dirname>/<basename>`

**static copy\_from\_scratch** (*file\_mapping, dry\_run=True*)

Copy output files from scratch area

**static copy\_to\_scratch** (*file\_mapping, dry\_run=True*)

Copy input files to scratch area

**get\_scratch\_path** (*local\_file*)

Construct and return a path in the scratch area from a local file.

**static make\_scratch\_dirs** (*file\_mapping, dry\_run=True*)

Make any directories need in the scratch area

**map\_files** (*local\_files*)

Build a dictionary mapping local paths to scratch paths.

#### Parameters

- **local\_files** (*list*) – List of filenames to be mapped to scratch area
- **dict** (*Returns*) – Mapping `local_file` : fullpath of scratch file

**split\_local\_path** (*local\_file*)

Split the local path into a directory name and a file name

If `local_file` is in `self.workdir` or a subdirectory of it, the directory will consist of the relative path from `workdir`.

If `local_file` is not in `self.workdir`, directory will be empty.

Returns (`dirname`, `basename`)

**class** `fermipy.jobs.file_archive.FileStatus`

Bases: `object`

Enumeration of file status types

```

exists = 2
expected = 1
missing = 3
no_file = 0
superseded = 4
temp_removed = 5

fermipy.jobs.file_archive.get_timestamp()
    Get the current time as an integer

fermipy.jobs.file_archive.get_unique_match(table, colname, value)
    Get the row matching value for a particular column. If exactly one row matches, return index of that row,
    Otherwise raise KeyError.

fermipy.jobs.file_archive.main_browse()
    Entry point for command line use for browsing a FileArchive

```

## Job Archive module

Classes and utilites to keep track the various jobs that are running in an analysis pipeline.

The main class is *JobArchive*, which keep track of all the jobs associated to an analysis.

The *JobDetails* helper class encapsulates information on a instance of running a job.

```
class fermipy.jobs.job_archive.JobArchive (**kwargs)
```

Bases: *object*

Class that keeps of all the jobs associated to an analysis.

### Parameters

- **table\_file** (*str*) – Path to the file used to persist this *JobArchive*
- **table** (*astropy.table.Table*) – Persistent representation of this *JobArchive*
- **table\_ids** (*astropy.table.Table*) – Ancillary table with information about file ids
- **file\_archive** (*FileArchive*) – Archive with infomation about all this files used and produced by this analysis

```
classmethod build_archive (**kwargs)
```

Return the singleton *JobArchive* instance, building it if needed

```
classmethod build_temp_job_archive ()
```

Build and return a *JobArchive* using default locations of persistent files.

### cache

Return the transiet representation of this *JobArchive*

### file\_archive

Return the *FileArchive* with infomation about all the files used and produced by this analysis

```
classmethod get_archive ()
```

Return the singleton *JobArchive* instance

```
get_details (jobname, jobkey)
```

Get the *JobDetails* associated to a particular job instance

```
make_job_details (row_idx)
    Create a JobDetails from an astropy.table.Row

register_job (job_details)
    Register a job in this JobArchive

register_job_from_link (link, key, **kwargs)
    Register a job in the JobArchive from a Link object

register_jobs (job_dict)
    Register a bunch of jobs in this archive

remove_jobs (mask)
    Mark all jobs that match a mask as 'removed'

table
    Return the persistent representation of this JobArchive

table_file
    Return the path to the file used to persist this JobArchive

table_ids
    Return the persistent representation of the ancillary info of this JobArchive

update_job (job_details)
    Update a job in the JobArchive

update_job_status (checker_func)
    Update the status of all the jobs in the archive

write_table_file (job_table_file=None, file_table_file=None)
    Write the table to self._table_file

class fermipy.jobs.job_archive.JobDetails (**kwargs)
    Bases: object
```

A simple structure to keep track of the details of each of the sub-process jobs.

#### Parameters

- **dbkey** (*int*) – A unique key to identify this job
- **jobname** (*str*) – A name used to identify this job
- **jobkey** (*str*) – A string to identify this instance of the job
- **appname** (*str*) – The executable invoked to run the job
- **logfile** (*str*) – The logfile for this job, may be used to check for success/ failure
- **job\_config** (*dict*) – A dictionary with the arguments for the job
- **parent\_id** (*int*) – Unique key identifying the parent job
- **infile\_ids** (*list of int*) – Keys to identify input files to this job
- **outfile\_ids** (*list of int*) – Keys to identify output files from this job
- **rmfile\_ids** (*list of int*) – Keys to identify temporary files removed by this job
- **intfile\_ids** (*list of int*) – Keys to identify internal files
- **status** (*int*) – Current job status, one of the enums above

```
append_to_tables (table, table_ids)
    Add this instance as a row on a astropy.table.Table
```

**check\_status\_logfile** (*checker\_func*)

Check on the status of this particular job using the logfile

**classmethod create\_from\_row** (*table\_row*)

Create a *JobDetails* from an *astropy.table.Row*

**fullkey**

Return the fullkey for this job fullkey = <jobkey>@<jobname>

**get\_file\_ids** (*file\_archive, creator=None, status=0*)

Fill the file id arrays from the file lists

#### Parameters

- **file\_archive** (*FileArchive*) – Used to look up file ids
- **creator** (*int*) – A unique key for the job that created these file
- **status** (*FileStatus*) – Enumeration giving current status thse files

**get\_file\_paths** (*file\_archive, file\_id\_array*)

Get the full paths of the files used by this object from the the id arrays

#### Parameters

- **file\_archive** (*FileArchive*) – Used to look up file ids
- **file\_id\_array** (*numpy.array*) – Array that remaps the file indexes

**classmethod make\_dict** (*table*)

Build a dictionary map int to *JobDetails* from an *astropy.table.Table*

**static make\_fullkey** (*jobname, jobkey='\_\_top\_\_'*)

Combine jobname and jobkey to make a unique key fullkey = <jobkey>@<jobname>

**static make\_tables** (*job\_dict*)

Build and return an *astropy.table.Table* to store `JobDetails

**static split\_fullkey** (*fullkey*)

Split fullkey to make extract jobname, jobkey fullkey = <jobkey>@<jobname>

**topkey** = `'__top__'`

**update\_table\_row** (*table, row\_idx*)

Add this instance as a row on a *astropy.table.Table*

**class** fermipy.jobs.job\_archive.**JobStatus**

Bases: *object*

Enumeration of job status types

**done** = 5

**failed** = 6

**no\_job** = -1

**not\_ready** = 1

**partial\_failed** = 7

**pending** = 3

**ready** = 2

**removed** = 8

**running** = 4

```
unknown = 0
```

**class** fermipy.jobs.job\_archive.**JobStatusVector**  
Bases: `object`

Vector that counts the status of jobs and returns an overall status flag based on those

**get\_status()**  
Return an overall status based on the number of jobs in various states.

**n\_done**  
Return the number of successfully completed jobs

**n\_failed**  
Return the number of failed jobs

**n\_pending**  
Return the number jobs submitted to batch, but not yet running

**n\_running**  
Return the number of running jobs

**n\_total**  
Return the total number of jobs

**n\_waiting**  
Return the number of jobs in various waiting states

**reset()**  
Reset the counters

fermipy.jobs.job\_archive.**main\_browse()**  
Entry point for command line use for browsing a JobArchive

### 1.3.12 fermipy.diffuse subpackage

The fermipy.diffuse sub-package is a collection of standalone utilities that allow the user to parallelize the data and template preparation for all-sky analysis.

The tools described here perform a number of functions:

- Making binned counts maps and expousre maps over the whole sky.
- Managing model components for all-sky analysis; including both diffuse emission and point source contributions. This includes make spatial-spectral templates and expected counts maps for various components.
- Building intergrated models for a collection of model components.
- Fitting those models.

#### Overview

This package implements an analysis pipeline prepare data and templates for analysis. This involves a lot of bookkeeping and loops over various things. It is probably easiest to first describe this with a bit of pseudo-code that represents the various analysis steps.

The various loop variables are:

- Input data files  
For practical reasons, the input photon event files (FT1) files are split into monthly files. In the binning step of the analysis we loop over those files.

- binning components

We split the data into several “binning components” and make separate binned counts maps for each component. A binning component is defined by energy range and data sub-selection (such as PSF event type and zenith angle cuts).

- Diffuse model components

The set of all the model components that represent diffuse emission, such as contributions for cosmic ray interactions with

- Catalog model components

The set of all the catalog sources (both point sources and extended source), merged into a few distinct contributions.

- Diffuse emission model definitions

A set of user defined models that merge the various model components with specific spectral models.

```
# Data Binning, prepare the analysis directories and precompute the DM spectra

# First we loop over all the input input files and split up the
# data by binning component and bin the data using the command
# fermipy-split-and-bin-sg, which is equivalent to:
for file in input_data_files:
    fermipy-split-and-bin(file)

# Then we loop over the binning components and coadd the binned
# data from all the input files using the command
# fermipy-coadd-split-sf, which is equivalent to:
for comp in binning_components:
    fermipy-coadd-split(comp)

# We also loop over the binning components and compute the
# exposure maps for each binning component using the command
# fermipy-gtexpcube2-sg, which is equivalent to:
for comp in binned_components:
    gtexpcube2(comp)

# We loop over the diffuse components that come from GALProp
# templates and refactor them using the command
# fermipy-sum-ring-gasmaps-sg, which is equivalent to
for galprop_comp in diffuse_galprop_components:
    fermipy-coadd(galprop_comp)

# We do a triple loop over all of the diffuse components, all the
# binning components and all the energy bins and convolve the
# emission template with the instrument response using the command
# fermipy-srcmaps-diffuse-sg, which is equivalent to
for diffuse_comp in diffuse_components:
    for binning_comp in binned_components:
        for energy in energy_bins:
            fermipy-srcmap-diffuse(diffuse_comp, binning_comp, energy)

# We then do a double loop over all the diffuse components and all
# the binning components and stack the template maps into single
# files using the command
# fermipy-vstack-diffuse-sg, which is equivalent to
for diffuse_comp in diffuse_components:
```

(continues on next page)

(continued from previous page)

```

    for binning_comp in binned_components:
        fermipy-vstack-diffuse(diffuse_comp, binning_comp)

# We then do a double loop over source catalogs and binning
# components and compute the templates for each source using the
# command
# fermipy-srcmaps-catalog-sg, which is equivalent to
    for catalog in catalogs:
        for binning_comp in binned_components:
            fermipy-srcmaps-catalog(catalog, binning_comp)

# We then loop over the catalog components (essentially
# sub-sets of catalog sources that we want to merge)
# and merge those sources into templates using the command
# fermipy-merge-srcmaps-sg, which is equivalent to
    for catalog_comp in catalog_components:
        for binning_comp in binned_components:
            fermipy-merge-srcmaps(catalog_comp, binning_comp)

# At this point we have a library to template maps for all the
# emission components that we have defined.
# Now we want to define specific models. We do this
# using the commands
# fermipy-init-model and fermipy-assemble-model-sg, which is equivalent to
    for model in models:
        fermipy-assemble-model(model)

# At this point we, for each model under consideration we have an
# analysis directory that is set up for fermipy

```

## Configuration

This section describes the configuration management scheme used within the `fermipy.diffuse` package and documents the configuration parameters that can be set in the configuration file.

Analysis classes in the `dmpipe` package all inherit from the `fermipy.jobs.Link` class, which allow user to invoke the class either interactively within python or from the unix command line.

From the command line

```
$ fermipy-srcmaps-diffuse-sg --comp config/binning.yaml --data config/dataset_source.
↪yaml --library models/library.yaml
```

From python there are a number of ways to do it, we recommend this:

```

from fermipy.diffuse.gt_srcmap_partial import SrcmapsDiffuse_SG
link = SrcmapsDiffuse_SG( )
link.update_args(dict(comp='config/binning.yaml', data='config/dataset_source.yaml',
↪library='models/library.yaml'))
link.run()

```

## Top Level Configuration

We use a yaml file to define the top-level analysis parameters.



Listing 9: Sample *top level* Configuration

```

# The binning components
comp : config/binning.yaml
# The dataset
data : config/dataset_source.yaml
# Library with the fitting components
library : models/library.yaml
# Yaml file with the list of models to prepare
models : models/modellist.yaml
# Input FT1 file
ft1file : P8_P305_8years_source_zmax105.lst
# HEALPix order for counts cubes
hpx_order_ccube : 9
# HEALPix order for exposure cubes
hpx_order_expcube : 6
# HEALPix order fitting models
hpx_order_fitting : 7
# Build the XML files for the diffuse emission model components
make_diffuse_comp_xml : True
# Build the XML files for the catalog source model components
make_catalog_comp_xml : True
# Name of the directory for the merged GALProp gasmaps
merged_gasmap_dir : merged_gasmap
# Number of catalog sources per batch job
catalog_nsrc : 500

```

## Binning Configuration

We use a yaml file to define the binning components.

Listing 10: Sample *binning* Configuration

```

coordsys : 'GAL'
E0:
  log_emin : 1.5
  log_emax : 2.0
  numbins : 2
  zmax : 80.
  psf_types :
    PSF3 :
      hpx_order : 5
E1:
  log_emin : 2.0
  log_emax : 2.5
  numbins : 2
  zmax : 90.
  psf_types :
    PSF23 :
      hpx_order : 6
E2:
  log_emin : 2.5
  log_emax : 3.0
  numbins : 3
  zmax : 100.
  psf_types :

```

(continues on next page)

(continued from previous page)

```

        PSF123 :
            hpx_order : 8
E3:
    log_emin : 3.0
    log_emax : 6.0
    enumbins : 9
    zmax : 105.
    psf_types :
        PSF0123 :
            hpx_order : 9

```

- **coordsys** ['GAL' or 'CEL'] Coordinate system to use
- **log\_emin, log\_emax: float** Energy bin boundries in log10(MeV)
- **enumbins: int** Number of energy bins for this binning component
- **zmax** [float] Maximum zenith angle (in degrees) for this binning component
- **psf\_types: dict** Sub-dictionary of binning components by PSF event type, PSF3 means PSF event type 3 events only. PSF0123 means all four PSF event types.
- **hpx\_order: int** HEALPix order to use for binning. The more familiar nside parameter is  $nside = 2^{**}order$

## Dataset Configuration

We use a yaml file to define the data set we are using. The example below specifies using a pre-defined 8 year dataset, selecting the “SOURCE” event class and using the V2 version of the corresponding IRFs (specifically P8R3\_SOURCE\_V2).

Listing 11: Sample *dataset* Configuration

```

basedir : '/gpfs/slac/kipac/fs1/u/dmcat/data/flight/diffuse_dev'
data_pass : 'P8'
data_ver : 'P305'
evclass : 'source'
data_time : '8years'
irf_ver : 'V2'

```

The basedir parameter should point at the analysis directory. For the most part the other parameter are using to make the names of the various files produced by the pipeline. The evclass parameter defines the event selection, and the IRF version is defined by a combination of the data\_ver, evclass and irf\_ver parameters.

## GALProp Rings Configuration

We use a yaml file to define the how we combine GALProp emission templates. The example below specifies how to construct as series of ‘merged\_CO’ rings by combining GALProp intensity template predictions.

Listing 12: Sample *GALProp rings* Configuration

```

galprop_run : 56_LRYusifovXCO5z6R30_QRPD_150_rc_Rs8
ring_limits : [1, 2, 3, 4, 6, 8, 9, 10, 11, 12, 13, 15]
diffuse_comp_dict :
    merged_CO : ['pi0_decay_H2R', 'bremss_H2R']
remove_rings : ['merged_CO_7']

```

- **galprop\_run** [string] Define the GALProp run to use for this component. This is used to make the filenames for input template maps.
- **ring\_limits** [list of int] This specifies how to combine the GALProp rings into a smaller set of rings.
- **diffuse\_comp\_dict** [dict] This specifies how to make GALProp components into merged components for the diffuse analysis
- **remove\_rings: list of str** This allow use to remove certain rings from the model

## Catalog Component Configuration

We use a yaml file to define the how we split up the catalog source components. The example below specifies using the FL8Y source list, and to split out the faint sources (i.e., those with the Signif\_Avg value less that 100.), and the extended source, and to keep all the remaining sources (i.e., the bright, pointlike, sources) as individual sources.

Listing 13: Sample *catalog component* Configuration

```
catalog_name : FL8Y
catalog_file : /nfs/slac/kipac/fs1/u/dmcat/ancil/catalogs/official/4FGLp/gll_psc_
→8year_v4.fit
catalog_extdir : /nfs/slac/kipac/fs1/u/dmcat/ancil/catalogs/official/extended/
→Extended_archive_v18
catalog_type : FL8Y
rules_dict :
  faint :
    cuts :
      - { cut_var: Signif_Avg, max_val : 100. }
      - mask_extended
  extended :
    cuts :
      - select_extended
  remainder :
    merge : False
```

## Model Component Library

We use a yaml file to define a “library” of model components. The comprises a set of named emission components, and a set one or more versions for each named component. Here is an example library definition file.

Listing 14: Sample *Model Component Library* Configuration

```
# Catalog Components
FL8Y :
  model_type : catalog
  versions : [v00]
# Diffuse Components
galprop_rings :
  model_type : galprop_rings
  versions : [p8-ref_IC_thin, p8-ref_HI_150, p8-ref_CO_300_mom, p8-ref_dnm_300hp]
dnm_merged:
  model_type : MapCubeSource
  versions : ['like_4y_300K']
gll-iem :
  model_type : MapCubeSource
  versions : [v06]
```

(continues on next page)

(continued from previous page)

```

loopI :
  model_type : MapCubeSource
  versions : [haslam]
bubbles :
  model_type : MapCubeSource
  versions : [v00, v01]
iso_map :
  model_type : MapCubeSource
  versions : [P8R3_SOURCE_V2]
patches :
  model_type : MapCubeSource
  versions : [v09]
  selection_dependent : True
  no_psf : True
  edisp_disable : True
unresolved :
  model_type : MapCubeSource
  versions : [strong]
sun-ic :
  model_type : MapCubeSource
  versions : [v2r0, P8R3-v2r0]
  moving : True
  edisp_disable : True
sun-disk :
  model_type : MapCubeSource
  versions : [v3r1, P8R3-v3r1]
  moving : True
  edisp_disable : True
moon :
  model_type : MapCubeSource
  versions : [v3r2, P8R3-v3r2]
  moving : True
  edisp_disable : True

```

- **model\_type:** ‘MapCubeSource’ or ‘catalog’ or ‘galprop\_rings’ or ‘SpatialMap’ Specifies how this model should be constructed. See more below in the versions parameters.
- **versions: list of str** Specifies different versions of this model component. How this string is used depend on the model type. for ‘MapCubeSource’ and ‘SpatialMap’ sources it is used to construct the expected filename for the intensity template. For ‘catalog’ and ‘galprop\_rings’ it is used to construct the filename for the yaml file that defines the sub-components for that component.
- **moving:** bool If true, then will use source-specific livetime cubes to constuct source templates for each zenith angle cut.
- **selection\_dependent :** bool If true, then will used different source templates for each binning component.
- **no\_psf :** bool Turns of PSF convolution for this source. Useful for data-driven components.
- **edisp\_disable :** bool Turns off energy dispersion for the source. Useful for data-driven components.

## Spectral Model Configuration

We use a yaml file to define the spectral models and default parameters. This file is simply a dictionary mapping names to sub-dictionaries defining spectral models and default model parameters.

## Model Defintion

We use a yaml file to define each overall model, which combine library components and spectral models.

Listing 15: Sample *Model Definition* Configuration

```
library : models/library.yaml
spectral_models : models/spectral_models.yaml
sources :
  galprop_rings_p8-ref_IC_thin :
    model_type : galprop_rings
    version : p8-ref_IC_150
    SpectrumType :
      default : Constant_Correction
  galprop_rings_p8-ref_HI_300:
    model_type : galprop_rings
    version : p8-ref_HI_300
    SpectrumType :
      default : Powerlaw_Correction
      merged_HI_2_p8-ref_HI_300 : BinByBin_5
      merged_HI_3_p8-ref_HI_300 : BinByBin_5
      merged_HI_4_p8-ref_HI_300 : BinByBin_9
      merged_HI_5_p8-ref_HI_300 : BinByBin_9
      merged_HI_6_p8-ref_HI_300 : BinByBin_9
      merged_HI_8_p8-ref_HI_300 : BinByBin_5
      merged_HI_9_p8-ref_HI_300 : BinByBin_5
  galprop_rings_p8-ref_CO_300:
    model_type : galprop_rings
    version : p8-ref_CO_300_mom
    SpectrumType :
      default : Powerlaw_Correction
      merged_CO_2_p8-ref_CO_300_mom : BinByBin_5
      merged_CO_3_p8-ref_CO_300_mom : BinByBin_5
      merged_CO_4_p8-ref_CO_300_mom : BinByBin_9
      merged_CO_5_p8-ref_CO_300_mom : BinByBin_9
      merged_CO_6_p8-ref_CO_300_mom : BinByBin_9
      merged_CO_8_p8-ref_CO_300_mom : BinByBin_5
      merged_CO_9_p8-ref_CO_300_mom : BinByBin_5
  dnm_merged :
    version : like_4y_300K
    SpectrumType : BinByBin_5
  iso_map :
    version : P8R3_SOURCE_V2
    SpectrumType : Iso
  sun-disk :
    version : v3r1
    SpectrumType : Constant_Correction
    edisp_disable : True
  sun-ic :
    version : v2r0
    SpectrumType : Constant_Correction
    edisp_disable : True
  moon :
    version : v3r2
    SpectrumType : Constant_Correction
    edisp_disable : True
  patches :
    version : v09
```

(continues on next page)

(continued from previous page)

```

    SpectrumType : Patches
    edisp_disable : True
    unresolved :
        version : strong
        SpectrumType : Constant_Correction
    FL8Y :
        model_type : Catalog
        version : v00
        SpectrumType :
            default : Constant_Correction
            FL8Y_v00_remain : Catalog
            FL8Y_v00_faint : BinByBin_9

```

- **model\_type**: ‘MapCubeSource’ or ‘catalog’ or ‘galprop\_rings’ or ‘SpatialMap’ Specifies how this model should be constructed. See more below.
- **version**: **str** Specifies version of this model component.
- **edisp\_disable**: **bool** Turns off energy dispersion for the source. Useful for data-driven components. Needed for model XML file construction.
- **SpectrumType**: **str** or **dictionary** This specifies the Spectrum type to use for this model component. For ‘catalog’ and ‘galprop\_rings’ model types it can be a dictionary mapping model sub-components to spectrum types. Note that the spectrum types should be defined in the spectral model configuration described above.

## Examples

### Module contents

#### Configuration, binning, default options, etc...

Small helper class to represent the binning used for a single component of a summed likelihood in diffuse analysis

**class** fermipy.diffuse.binning.**Component** (*\*\*kwargs*)

Bases: `object`

Small helper class to represent the binning used for a single component of a summed likelihood in diffuse analysis

#### Parameters

- **log\_emin** (*float*) – Log base 10 of minimum energy for this component
- **log\_emax** (*float*) – Log base 10 of maximum energy for this component
- **enumbins** (*int*) – Number of energy bins for this component
- **zmax** (*float*) – Maximum zenith angle cube for this component in degrees
- **mktimefilters** (*list*) – Filters for gmtime.
- **hpx\_order** (*int*) – HEALPix order to use for this component
- **coordsys** (*str*) – Coordinate system, ‘CEL’ or ‘GAL’

**classmethod** **build\_from\_energy\_dict** (*ebin\_name, input\_dict*)

Build a list of components from a dictionary for a single energy range

**classmethod** **build\_from\_yamlfile** (*yamlfile*)

Build a list of components from a yaml file

**classmethod build\_from\_yamlstr** (*yamlstr*)

Build a list of components from a yaml string

**emax**

Maximum energy for this component

**emin**

Minimum energy for this component

**evtype**

Event type bit mask for this component

**make\_key** (*format\_str*)

Make a key to identify this component

*format\_str* is formatted using object `__dict__`

Analysis framework for all-sky diffuse emission fitting

Handle the naming conventions for composite likelihood analysis

**class** `fermipy.diffuse.name_policy.NameFactory` (*\*\*kwargs*)

Bases: `object`

Helper class to define file names and keys consistently.

**angprofile** (*\*\*kwargs*)

return the file name for sun or moon angular profiles

**angprofile\_format** = `'templates/profile_{sourcekey}.fits'`

**bexpcube** (*\*\*kwargs*)

return the name of a binned exposure cube file

**bexpcube\_format** = `'bexp_cubes/bexpcube_{dataset}_{mktime}_{component}_{coordsys}_{irf_v`

**bexpcube\_moon** (*\*\*kwargs*)

return the name of a binned exposure cube file

**bexpcube\_sun** (*\*\*kwargs*)

return the name of a binned exposure cube file

**bexpcubemoon\_format** = `'bexp_cubes/bexpcube_{dataset}_{mktime}_{component}_{irf_ver}_moon`

**bexpcubesun\_format** = `'bexp_cubes/bexpcube_{dataset}_{mktime}_{component}_{irf_ver}_sun`

**catalog\_split\_yaml** (*\*\*kwargs*)

return the name of a catalog split yaml file

**catalog\_split\_yaml\_format** = `'models/catalog_{sourcekey}.yaml'`

**ccube** (*\*\*kwargs*)

return the name of a counts cube file

**ccube\_format** = `'counts_cubes/ccube_{dataset}_{mktime}_{component}_{coordsys}.fits'`

**comp\_srcmdl\_xml** (*\*\*kwargs*)

return the name of a source model file

**comp\_srcmdl\_xml\_format** = `'analysis/model_{modelkey}/srcmdl_{modelkey}_{component}.xml'`

**component** (*\*\*kwargs*)

Return a key that specifies data the sub-selection

**component\_format** = `'{zcut}_{ebin}_{psftype}'`

**dataset** (*\*\*kwargs*)  
Return a key that specifies the data selection

**dataset\_format** = '{data\_pass}\_{data\_ver}\_{data\_time}\_{evclass}'

**diffuse\_template** (*\*\*kwargs*)  
return the file name for other diffuse map templates

**diffuse\_template\_format** = 'templates/template\_{sourcekey}.fits'

**evclassmask** (*evclass\_str*)  
Get the bitmask for a particular event class

**ft1file** (*\*\*kwargs*)  
return the name of the input ft1 file list

**ft1file\_format** = '{dataset}\_{zcut}.lst'

**ft2file** (*\*\*kwargs*)  
return the name of the input ft2 file list

**ft2file\_format** = 'ft2\_files/ft2\_{data\_time}.lst'

**fullpath** (*\*\*kwargs*)  
Return a full path name for a given file

**fullpath\_format** = '{basedir}/{localpath}'

**galprop\_gasmap** (*\*\*kwargs*)  
return the file name for Galprop input gasmaps

**galprop\_gasmap\_format** = 'gasmap/{sourcekey}\_{projtype}\_{galprop\_run}.gz'

**galprop\_ringkey** (*\*\*kwargs*)  
return the sourcekey for galprop input maps : specifies the component and ring

**galprop\_ringkey\_format** = '{source\_name}\_{ringkey}'

**galprop\_rings\_yaml** (*\*\*kwargs*)  
return the name of a galprop rings merging yaml file

**galprop\_rings\_yaml\_format** = 'models/galprop\_rings\_{galkey}.yaml'

**galprop\_sourcekey** (*\*\*kwargs*)  
return the sourcekey for merged galprop maps : specifies the merged component and merging scheme

**galprop\_sourcekey\_format** = '{source\_name}\_{galpropkey}'

**generic** (*input\_string, \*\*kwargs*)  
return a generic filename for a given dataset and component

**irf\_ver** (*\*\*kwargs*)  
Get the name of the IRF version

**irfs** (*\*\*kwargs*)  
Get the name of IFRs associated with a particular dataset

**ltcube** (*\*\*kwargs*)  
return the name of a livetime cube file

**ltcube\_format** = 'lt\_cubes/ltcube\_{data\_time}\_{mktime}\_{zcut}.fits'

**ltcube\_moon** (*\*\*kwargs*)  
return the name of a livetime cube file



```

ltcube_sun (**kwargs)
    return the name of a livetime cube file

ltcubemoon_format = 'sunmoon/ltcube_{data_time}_{mktime}_{zcut}_moon.fits'

ltcubesun_format = 'sunmoon/ltcube_{data_time}_{mktime}_{zcut}_sun.fits'

make_filenames (**kwargs)
    Make a dictionary of filenames for various types

master_srcmdl_xml (**kwargs)
    return the name of a source model file

master_srcmdl_xml_format = 'analysis/model_{modelkey}/srcmdl_{modelkey}_master.xml'

mcube (**kwargs)
    return the name of a model cube file

mcube_format = 'model_cubes/mcube_{sourcekey}_{dataset}_{mktime}_{component}_{coordsys}'

merged_gasmap (**kwargs)
    return the file name for Galprop merged gasmaps

merged_gasmap_format = 'merged_gasmaps/{sourcekey}_{projtype}.fits'

merged_sourcekey (**kwargs)
    return the sourcekey for merged sets of point sources : specifies the catalog and merging rule

merged_sourcekey_format = '{catalog}_{rulekey}'

merged_srcmaps (**kwargs)
    return the name of a source map file

merged_srcmaps_format = 'analysis/model_{modelkey}/srcmaps_{dataset}_{mktime}_{component}'

mktime (**kwargs)
    return the name of a selected events ft1file

mktime_format = 'counts_cubes/mktime_{dataset}_{mktime}_{component}.fits'

model_yaml (**kwargs)
    return the name of a model yaml file

model_yaml_format = 'models/model_{modelkey}.yaml'

nested_srcmdl_xml (**kwargs)
    return the file name for source model xml files of nested sources

nested_srcmdl_xml_format = 'srcmdls/{sourcekey}_sources.xml'

residual_cr (**kwargs)
    Return the name of the residual CR analysis output files

residual_cr_format = 'residual_cr/residual_cr_{dataset}_{mktime}_{component}_{coordsys}'

select (**kwargs)
    return the name of a selected events ft1file

select_format = 'counts_cubes/select_{dataset}_{component}.fits'

sourcekey (**kwargs)
    Return a key that specifies the name and version of a source or component

sourcekey_format = '{source_name}_{source_ver}'

spectral_template (**kwargs)
    return the file name for spectral templates

```

```
spectral_template_format = 'templates/spectral_{sourcekey}.txt'

srcmaps (**kwargs)
    return the name of a source map file

srcmaps_format = 'srcmaps/srcmaps_{sourcekey}_{dataset}_{mtime}_{component}_{coordsys}'

srcmdl_xml (**kwargs)
    return the file name for source model xml files

srcmdl_xml_format = 'srcmdls/{sourcekey}.xml'

stamp (**kwargs)
    Return the path for a stamp file for a scatter gather job

stamp_format = 'stamps/{linkname}.stamp'

template_sunmoon (**kwargs)
    return the file name for sun or moon template files

templatesunmoon_format = 'templates/template_{sourcekey}_{zcut}.fits'

update_base_dict (yamlfile)
    Update the values in baseline dictionary used to resolve names
```

## Utilities and tools

Classes and utilities that manage spectral model specific to diffuse analyses

```
class fermipy.diffuse.spectral.SpectralLibrary (spectral_dict)
    Bases: object

    A small helper class that serves as an alias dictionary for spectral models

    classmethod create_from_yaml (yamlfile)
        Create the dictionary for a yaml file

    classmethod create_from_yamlstr (yamlstr)
        Create the dictionary for a yaml file

    update (spectral_dict)
        Update the dictionary
```

Small helper class to represent the selection of mktime filters used in the analysis

```
class fermipy.diffuse.timefilter.MktimeFilterDict (aliases, selections)
    Bases: object

    Small helper class toselection of mktime filters used in the analysis

    static build_from_yamlfile (yamlfile)
        Build a list of components from a yaml file

    items ()
        Return the iterator over key, value pairs

    keys ()
        Return the iterator over keys

    values ()
        Return the iterator over values
```

Classes and utilities that create fermipy source objects

**class** `fermipy.diffuse.source_factory.SourceFactory`

Bases: `object`

Small helper class to build and keep track of sources

**add\_sources** (*source\_info\_dict*)

Add all of the sources in *source\_info\_dict* to this factory

**static build\_catalog** (*\*\*kwargs*)

Build a `fermipy.catalog.Catalog` object

**Parameters**

- **catalog\_type** (*str*) – Specifies catalog type, options include 2FHL | 3FGL | 4FGLP
- **catalog\_file** (*str*) – FITS file with catalog tables
- **catalog\_extdir** (*str*) – Path to directory with extended source templates

**classmethod copy\_selected\_sources** (*roi, source\_names*)

Build and return a `fermipy.roi_model.ROIModel` object by copying selected sources from another such object

**static make\_fermipy\_roi\_model\_from\_catalogs** (*cataloglist*)

Build and return a `fermipy.roi_model.ROIModel` object from a list of `fermipy.catalog.Catalog` objects

**classmethod make\_roi** (*sources=None*)

Build and return a `fermipy.roi_model.ROIModel` object from a dict with information about the sources

**source\_info\_dict**

Return the dictionary of *source\_info* objects used to build sources

**sources**

Return the dictionary of sources

`fermipy.diffuse.source_factory.make_catalog_sources` (*catalog\_roi\_model,*  
*source\_names*)

Construct and return dictionary of sources that are a subset of sources in *catalog\_roi\_model*.

**Parameters**

- **catalog\_roi\_model** (dict or `fermipy.roi_model.ROIModel`) – Input set of sources
- **source\_names** (*list*) – Names of sources to extract
- **dict mapping source\_name to fermipy.roi\_model.Source object**  
(Returns)–

`fermipy.diffuse.source_factory.make_composite_source` (*name, spectrum*)

Construct and return a `fermipy.roi_model.CompositeSource` object

`fermipy.diffuse.source_factory.make_isotropic_source` (*name, Spectrum\_Filename,*  
*spectrum*)

Construct and return a `fermipy.roi_model.IsoSource` object

`fermipy.diffuse.source_factory.make_mapcube_source` (*name, Spatial\_Filename, spec-*  
*trum*)

Construct and return a `fermipy.roi_model.MapCubeSource` object

`fermipy.diffuse.source_factory.make_point_source` (*name, src\_dict*)

Construct and return a `fermipy.roi_model.Source` object

`fermipy.diffuse.source_factory.make_sources(comp_key, comp_dict)`

Make dictionary mapping component keys to a source or set of sources

#### Parameters

- **comp\_key** (*str*) – Key used to access sources
- **comp\_dict** (*dict*) – Information used to build sources
- **OrderedDict** mapping **comp\_key** to **fermipy.roi\_model.Source** (*return*) –

`fermipy.diffuse.source_factory.make_spatialmap_source(name, Spatial_Filename, spectrum)`

Construct and return a *fermipy.roi\_model.Source* object

Prepare data for diffuse all-sky analysis

`fermipy.diffuse.utils.create_inputlist(arglist)`

Read lines from a file and makes a list of file names.

Removes whitespace and lines that start with ‘#’ Recursively read all files with the extension ‘.lst’

`fermipy.diffuse.utils.readlines(arg)`

Read lines from a file into a list.

Removes whitespace and lines that start with ‘#’

## Helper classes to manage model building

**class** `fermipy.diffuse.model_component.ModelComponentInfo(**kwargs)`

Bases: `object`

Information about a model component

#### Parameters

- **source\_name** (*str*) – The name given to the component, e.g., loop\_I or moon
- **source\_ver** (*str*) – Key to identify the model version of the source, e.g., v00
- **sourcekey** (*str*) – Key that identifies this component, e.g., loop\_I\_v00 or moon\_v00
- **model\_type** (*str*) – Type of model, ‘MapCubeSource’ | ‘IsoSource’ | ‘Composite-Source’ | ‘Catalog’ | ‘PointSource’
- **srcmdl\_name** (*str*) – Name of the xml file with the xml just for this component
- **moving** (*bool*) – Flag for moving sources (i.e., the sun and moon)
- **selection\_dependent** (*bool*) – Flag for selection dependent sources (i.e., the residual cosmic ray model)
- **no\_psf** (*bool*) – Flag to indicate that we do not smear this component with the PSF
- **components** (*dict*) – Sub-dictionary of *ModelComponentInfo* objects for moving and selection\_dependent sources
- **comp\_key** (*str*) – Component key for this component of moving and selection\_dependent sources

**add\_component\_info** (*compinfo*)

Add sub-component specific information to a particular data selection

**Parameters** **compinfo** (*ModelComponentInfo* object) – Sub-component being added

**clone\_and\_merge\_sub** (*key*)

Clones self and merges clone with sub-component specific information

#### Parameters

- **key** (*str*) – Key specifying which sub-component
- **ModelComponentInfo object** (*Returns*) –

**get\_component\_info** (*comp*)

Return the information about sub-component specific to a particular data selection

#### Parameters

- **comp** (*binning.Component object*) – Specifies the sub-component
- **ModelComponentInfo object** (*Returns*) –

**update** (*\*\*kwargs*)

Update data members from keyword arguments

**class** `fermipy.diffuse.model_component.CatalogInfo` (*\*\*kwargs*)

Bases: `object`

Information about a source catalog

#### Parameters

- **catalog\_name** (*str*) – The name given to the merged component, e.g., merged\_CO or merged\_HI
- **catalog\_file** (*str*) – Fits file with catalog data
- **catalog\_extdir** (*str*) – Directory with extended source templates
- **catalog\_type** (*str*) – Identifies the format of the catalog fits file: e.g., ‘3FGL’ or ‘4FGLP’
- **catalog** (*fermipy.catalog.Catalog*) – Catalog object
- **roi\_model** (*fermipy.roi\_model.ROIModel*) – Fermipy object describing all the catalog sources
- **srcmdl\_name** (*str*) – Name of xml file with the catalog source model

**update** (*\*\*kwargs*)

Update data members from keyword arguments

**class** `fermipy.diffuse.model_component.GalpropMergedRingInfo` (*\*\*kwargs*)

Bases: `object`

Information about a set of Merged Galprop Rings

#### Parameters

- **source\_name** (*str*) – The name given to the merged component, e.g., merged\_CO or merged\_HI
- **ring** (*int*) – The index of the merged ring
- **sourcekey** (*str*) – Key that identifies this component, e.g., merged\_CO\_1, or merged\_HI\_3
- **galkey** (*str*) – Key that identifies how to merge the galprop rings, e.g., ‘ref’
- **galprop\_run** (*str*) – Key that identifies the galprop run used to make the input rings
- **files** (*str*) – List of files of the input gasmap files

- **merged\_gasmap** (*str*) – Filename for the merged gasmap

**update** (*\*\*kwargs*)

Update data members from keyword arguments

**class** fermipy.diffuse.model\_component.**ModelComponentInfo** (*\*\*kwargs*)

Bases: *object*

Information about a model component

#### Parameters

- **source\_name** (*str*) – The name given to the component, e.g., loop\_I or moon
- **source\_ver** (*str*) – Key to indentify the model version of the source, e.g., v00
- **sourcekey** (*str*) – Key that identifies this component, e.g., loop\_I\_v00 or moon\_v00
- **model\_type** (*str*) – Type of model, ‘MapCubeSource’ | ‘IsoSource’ | ‘Composite-Source’ | ‘Catalog’ | ‘PointSource’
- **srcmdl\_name** (*str*) – Name of the xml file with the xml just for this component
- **moving** (*bool*) – Flag for moving sources (i.e., the sun and moon)
- **selection\_dependent** (*bool*) – Flag for selection dependent sources (i.e., the residual cosmic ray model)
- **no\_psf** (*bool*) – Flag to indicate that we do not smear this component with the PSF
- **components** (*dict*) – Sub-dictionary of *ModelComponentInfo* objects for moving and selection\_dependent sources
- **comp\_key** (*str*) – Component key for this component of moving and selection\_dependent sources

**add\_component\_info** (*compinfo*)

Add sub-component specific information to a particular data selection

**Parameters** **compinfo** (*ModelComponentInfo* object) – Sub-component being added

**clone\_and\_merge\_sub** (*key*)

Clones self and merges clone with sub-component specific information

#### Parameters

- **key** (*str*) – Key specifying which sub-component
- **ModelComponentInfo** *object* (*Returns*) –

**get\_component\_info** (*comp*)

Return the information about sub-component specific to a particular data selection

#### Parameters

- **comp** (*binning.Component* object) – Specifies the sub-component
- **ModelComponentInfo** *object* (*Returns*) –

**update** (*\*\*kwargs*)

Update data members from keyword arguments

**class** fermipy.diffuse.model\_component.**IsoComponentInfo** (*\*\*kwargs*)

Bases: *fermipy.diffuse.model\_component.ModelComponentInfo*

Information about a model component represented by a IsoSource

**Parameters** **Spectral\_Filename** (*str*) – Name of the template file for the spatial model

**class** fermipy.diffuse.model\_component.**PointSourceInfo** (\*\*kwargs)

Bases: *fermipy.diffuse.model\_component.ModelComponentInfo*

Information about a model component represented by a PointSource

**class** fermipy.diffuse.model\_component.**CompositeSourceInfo** (\*\*kwargs)

Bases: *fermipy.diffuse.model\_component.ModelComponentInfo*

Information about a model component represented by a CompositeSource

#### Parameters

- **source\_names** (*list*) – The names of the nested sources
- **catalog\_info** (*model\_component.CatalogInfo* or *None*) – Information about the catalog containing the nested sources
- **roi\_model** (*fermipy.roi\_model.ROIModel*) – Fermipy object describing the nested sources

**class** fermipy.diffuse.model\_component.**CatalogSourcesInfo** (\*\*kwargs)

Bases: *fermipy.diffuse.model\_component.ModelComponentInfo*

Information about a model component consisting of sources from a catalog

#### Parameters

- **source\_names** (*list*) – The names of the nested sources
- **catalog\_info** (*model\_component.CatalogInfo* or *None*) – Information about the catalog containing the nested sources
- **roi\_model** (*fermipy.roi\_model.ROIModel*) – Fermipy object describing the nested sources

**class** fermipy.diffuse.diffuse\_src\_manager.**GalpropMapManager** (\*\*kwargs)

Bases: *object*

Small helper class to keep track of Galprop gasmaps

This keeps track of two types of dictionaries. Both are keyed by: key = {source\_name}\_{ring}\_{galkey}

Where: {source\_name} is something like ‘merged\_C0’ {ring} is the ring index {galkey} is a key specifying which version of galprop rings to use.

The two dictionaries are: ring\_dict[key] = model\_component.GalpropMergedRingInfo diffuse\_comp\_info\_dict[key] ] model\_component.ModelComponentInfo

The dictionaries are defined in files called. models/galprop\_rings\_{galkey}.yaml

**diffuse\_comp\_info\_dicts** (*galkey*)

Return the components info dictionary for a particular galprop key

**galkeys** ()

Return the list of galprop keys used

**make\_diffuse\_comp\_info** (*merged\_name, galkey*)

Make the information about a single merged component

#### Parameters

- **merged\_name** (*str*) – The name of the merged component
- **galkey** (*str*) – A short key identifying the galprop parameters
- **Model\_component.ModelComponentInfo** (*Returns*) –

**make\_diffuse\_comp\_info\_dict** (*galkey*)

Make a dictionary mapping from merged component to information about that component

**Parameters** **galkey** (*str*) – A short key identifying the galprop parameters

**make\_merged\_name** (*source\_name*, *galkey*, *fullpath*)

Make the name of a gasmap file for a set of merged rings

**Parameters**

- **source\_name** (*str*) – The galprop component, used to define path to gasmap files
- **galkey** (*str*) – A short key identifying the galprop parameters
- **fullpath** (*bool*) – Return the full path name

**make\_ring\_dict** (*galkey*)

Make a dictionary mapping the merged component names to list of template files

**Parameters**

- **galkey** (*str*) – Unique key for this ring dictionary
- **model\_component.GalpropMergedRingInfo** (*Returns*) –

**make\_ring\_filelist** (*sourcekeys*, *rings*, *galprop\_run*)

Make a list of all the template files for a merged component

**Parameters**

- **sourcekeys** (*list-like of str*) – The names of the components to merge
- **rings** (*list-like of int*) – The indices of the rings to merge
- **galprop\_run** (*str*) – String identifying the galprop parameters

**make\_ring\_filename** (*source\_name*, *ring*, *galprop\_run*)

Make the name of a gasmap file for a single ring

**Parameters**

- **source\_name** (*str*) – The galprop component, used to define path to gasmap files
- **ring** (*int*) – The ring index
- **galprop\_run** (*str*) – String identifying the galprop parameters

**make\_xml\_name** (*source\_name*, *galkey*, *fullpath*)

Make the name of an xml file for a model definition for a set of merged rings

**Parameters**

- **source\_name** (*str*) – The galprop component, used to define path to gasmap files
- **galkey** (*str*) – A short key identifying the galprop parameters
- **fullpath** (*bool*) – Return the full path name

**merged\_components** (*galkey*)

Return the set of merged components for a particular galprop key

**read\_galprop\_rings\_yaml** (*galkey*)

Read the yaml file for a particular galprop key

**ring\_dict** (*galkey*)

Return the ring dictionary for a particular galprop key



```
class fermipy.diffuse.diffuse_src_manager.DiffuseModelManager (**kwargs)
```

Bases: `object`

Small helper class to keep track of diffuse component templates

This keeps track of the 'diffuse component information' dictionary

This keyed by: `key = {source_name}_{source_ver}` Where: `{source_name}` is something like 'loopI' `{source_ver}` is something like v00

The dictionary is `diffuse_comp_info_dict[key] -> model_component.ModelComponentInfo`

Note that some components ( those that represent moving sources or are selection dependent ) will have a sub-dictionary of `diffuse_comp_info_dict` object for each sub-component

The components are defined in a file called `config/diffuse_components.yaml`

```
diffuse_comp_info (sourcekey)
```

Return the Component info associated to a particular key

```
make_diffuse_comp_info (source_name, source_ver, diffuse_dict, components=None,
                        comp_key=None)
```

Make a dictionary mapping the merged component names to list of template files

#### Parameters

- **source\_name** (*str*) – Name of the source
- **source\_ver** (*str*) – Key identifying the version of the source
- **diffuse\_dict** (*dict*) – Information about this component
- **comp\_key** (*str*) – Used when we need to keep track of sub-components, i.e., for moving and selection dependent sources.
- **model\_component.ModelComponentInfo** **or** (*Returns*) –
- **model\_component.IsoComponentInfo** –

```
make_diffuse_comp_info_dict (diffuse_sources, components)
```

Make a dictionary mapping from diffuse component to information about that component

#### Parameters

- **diffuse\_sources** (*dict*) – Dictionary with diffuse source definitions
- **components** (*dict*) – Dictionary with event selection definitions, needed for selection dependent diffuse components

**Returns** **ret\_dict** – Dictionary mapping `sourcekey` to `model_component.ModelComponentInfo`

**Return type** `dict`

```
make_template_name (model_type, sourcekey)
```

Make the name of a template file for particular component

#### Parameters

- **model\_type** (*str*) – Type of model to use for this component
- **sourcekey** (*str*) – Key to identify this component
- **filename** **or** **None** **if component does not require a template file** (*Returns*) –

```
make_xml_name (sourcekey)
```

Make the name of an xml file for a model definition of a single component

**Parameters** **sourcekey** (*str*) – Key to identify this component

**static read\_diffuse\_component\_yaml** (*yamlfile*)

Read the yaml file for the diffuse components

**sourcekeys** ()

Return the list of source keys

**class** `fermipy.diffuse.catalog_src_manager.CatalogSourceManager` (*\*\*kwargs*)

Bases: `object`

Small helper class to keep track of how we deal with catalog sources

This keeps track of two dictionaries

One of the dictionaries is keyed by catalog name, and contains information about complete catalogs `catalog_comp_info_dicts[catalog_name] : model_component.CatalogInfo`

The other dictionary is keyed by `[[catalog_name]_{split_ver}][{split_key}]` Where: `{catalog_name}` is something like '3FGL' `{split_ver}` is something like 'v00' and specifies how to divide sources in the catalog `{split_key}` refers to a specific sub-selection of sources

`split_comp_info_dicts[splitkey] : model_component.ModelComponentInfo`

**build\_catalog\_info** (*catalog\_info*)

Build a CatalogInfo object

**catalog\_comp\_info\_dict** (*catkey*)

Return the roi\_model for an entire catalog

**catalog\_components** (*catalog\_name, split\_ver*)

Return the set of merged components for a particular split key

**catalogs** ()

Return the list of full catalogs used

**make\_catalog\_comp\_info** (*full\_cat\_info, split\_key, rule\_key, rule\_val, sources*)

Make the information about a single merged component

#### Parameters

- **full\_cat\_info** (`_model_component.CatalogInfo`) – Information about the full catalog
- **split\_key** (*str*) – Key identifying the version of the splitting used
- **rule\_key** (*str*) – Key identifying the specific rule for this component
- **rule\_val** (*list*) – List of the cuts used to define this component
- **sources** (*list*) – List of the names of the sources in this component
- **CompositeSourceInfo** or **CatalogSourcesInfo** (*Returns*) –

**make\_catalog\_comp\_info\_dict** (*catalog\_sources*)

Make the information about the catalog components

**Parameters** **catalog\_sources** (*dict*) – Dictionary with catalog source definitions

#### Returns

- **catalog\_ret\_dict** (*dict*) – Dictionary mapping `catalog_name` to `model_component.CatalogInfo`
- **split\_ret\_dict** (*dict*) – Dictionary mapping `sourcekey` to `model_component.ModelComponentInfo`

```

read_catalog_info_yaml (splitkey)
    Read the yaml file for a particular split key

split_comp_info (catalog_name, split_ver, split_key)
    Return the info for a particular split key

split_comp_info_dict (catalog_name, split_ver)
    Return the information about a particular scheme for how to handle catalog sources

splitkeys ()
    Return the list of catalog split keys used

class fermipy.diffuse.model_manager.ModelComponent (**kwargs)
    Bases: object

    Small helper class to tie a ModelComponentInfo to a spectrum

class fermipy.diffuse.model_manager.ModelInfo (**kwargs)
    Bases: object

    Small helper class to keep track of a single fitting model

    component_names
        Return the list of name of the components

    edisp_disable_list ()
        Return the list of source for which energy dispersion should be turned off

    items ()
        Return the key, value pairs of model components

    make_model_rois (components, name_factory)
        Make the fermipy roi_model objects for each of a set of binning components

    make_srcmap_manifest (components, name_factory)
        Build a yaml file that specifies how to make the srcmap files for a particular model

    Parameters
        • components (list) – The binning components used in this analysis
        • name_factory (NameFactory) – Object that handles naming conventions
        • a dictionary that contains information about where to find the (Returns) –
        • maps for each component of the model (source) –

class fermipy.diffuse.model_manager.ModelManager (**kwargs)
    Bases: object

    Small helper class to create fitting models and manager XML files for fermipy

    This class contains a ‘library’, which is a dictionary of all the source components:
    specifically it maps:

    sourcekey : model_component.ModelComponentInfo

    csm
        Return the CatalogSourceManager

    dmm
        Return the DiffuseModelManager

```

**static get\_sub\_comp\_info** (*source\_info*, *comp*)

Build and return information about a sub-component for a particular selection

**gmm**

Return the GalpropMapManager

**make\_fermipy\_config\_yaml** (*modelkey*, *components*, *data*, *\*\*kwargs*)

Build a fermipy top-level yaml configuration file

#### Parameters

- **modelkey** (*str*) – Key used to identify this particular model
- **components** (*list*) – The binning components used in this analysis
- **data** (*str*) – Path to file containing dataset definition

**make\_library** (*diffuse\_yaml*, *catalog\_yaml*, *binning\_yaml*)

Build up the library of all the components

#### Parameters

- **diffuse\_yaml** (*str*) – Name of the yaml file with the library of diffuse component definitions
- **catalog\_yaml** (*str*) – Name of the yaml file width the library of catalog split definitions
- **binning\_yaml** (*str*) – Name of the yaml file with the binning definitions

**make\_model\_info** (*modelkey*)

Build a dictionary with the information for a particular model.

#### Parameters

- **modelkey** (*str*) – Key used to identify this particular model
- **ModelInfo** (*Return*) –

**make\_srcmap\_manifest** (*modelkey*, *components*, *data*)

Build a yaml file that specifies how to make the srcmap files for a particular model

#### Parameters

- **modelkey** (*str*) – Key used to identify this particular model
- **components** (*list*) – The binning components used in this analysis
- **data** (*str*) – Path to file containing dataset definition

**read\_model\_yaml** (*modelkey*)

Read the yaml file for the diffuse components

## Trivial Link Sub-classes

**class** fermipy.diffuse.job\_library.Gtlink\_select (*\*\*kwargs*)

Bases: *fermipy.jobs.gtlink.Gtlink*

Small wrapper to run gtselect :param zmax: Maximum zenith angle [degrees] [100.0] :type zmax: <class 'float'>  
:param emax: Maximum energy [MeV] [100000.0] :type emax: <class 'float'> :param emin: Minimum energy [MeV] [100.0] :type emin: <class 'float'> :param evtype: Event type selections [None] :type evtype: <class 'int'> :param pfiles: PFILES directory [None] :type pfiles: <class 'str'> :param evclass: Event Class [None] :type evclass: <class 'int'> :param outfile: Output file [None] :type outfile: <class 'str'> :param infile: Input file [None] :type infile: <class 'str'>

```

    appname = 'gtselect'
    default_file_args = {'infile': 1, 'outfile': 2}
    default_options = {'emax': (100000.0, 'Maximum energy [MeV]', <class 'float'>), 'emin':
    description = 'Link to run gtselect'
    linkname_default = 'gtselect'
    usage = 'gtselect [options]'

class fermipy.diffuse.job_library.Gtlink_bin(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtbin :param emax: Maximum energy [MeV] [100000.0] :type emax: <class 'float'>
    :param emin: Minimum energy [MeV] [100.0] :type emin: <class 'float'> :param hpx_order: HEALPIX order
    parameter [6] :type hpx_order: <class 'int'> :param coordsys: Coordinate system [GAL] :type coordsys: <class
    'str'> :param algorithm: Binning algorithm [HEALPIX] :type algorithm: <class 'str'> :param evfile: Input FT1
    eventfile [None] :type evfile: <class 'str'> :param pfiles: PFILES directory [None] :type pfiles: <class 'str'>
    :param outfile: Output file [None] :type outfile: <class 'str'> :param enumbins: Number of energy bins [16]
    :type enumbins: <class 'int'>

    appname = 'gtbin'
    default_file_args = {'evfile': 33, 'outfile': 34}
    default_options = {'algorithm': ('HEALPIX', 'Binning algorithm', <class 'str'>), 'coo
    description = 'Link to run gtbin'
    linkname_default = 'gtbin'
    usage = 'gtbin [options]'

class fermipy.diffuse.job_library.Gtlink_expcube2(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtexpcube2 :param cmap: Input counts cube file [None] :type cmap: <class 'str'> :param
    evttype: Event type selections [None] :type evttype: <class 'int'> :param hpx_order: HEALPIX order parameter
    [6] :type hpx_order: <class 'int'> :param irfs: Instrument response functions [CALDB] :type irfs: <class 'str'>
    :param coordsys: Coordinate system [GAL] :type coordsys: <class 'str'> :param outfile: Output file [None]
    :type outfile: <class 'str'> :param infile: Input livetime cube file [None] :type infile: <class 'str'>

    appname = 'gtexpcube2'
    default_file_args = {'cmap': 1, 'infile': 1, 'outfile': 2}
    default_options = {'cmap': (None, 'Input counts cube file', <class 'str'>), 'coordsys
    description = 'Link to run gtexpcube2'
    linkname_default = 'gtexpcube2'
    usage = 'gtexpcube2 [options]'

class fermipy.diffuse.job_library.Gtlink_scrmaps(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtscrmaps :param bexpmap: Input binned exposure map file [None] :type bexpmap: <class
    'str'> :param expcube: Input Livetime cube file [None] :type expcube: <class 'str'> :param irfs: Instrument
    response functions [CALDB] :type irfs: <class 'str'> :param srcmdl: Input source model xml file [None] :type
    srcmdl: <class 'str'> :param outfile: Output file [None] :type outfile: <class 'str'> :param cmap: Input counts
    cube file [None] :type cmap: <class 'str'>

    appname = 'gtscrmaps'

```

```
default_file_args = {'bexpmap': 1, 'cmap': 1, 'expcube': 1, 'outfile': 2, 'srcmdl': 1}
default_options = {'bexpmap': (None, 'Input binned exposure map file', <class 'str'>)}
description = 'Link to run gtscrm maps'
linkname_default = 'gtscrm maps'
usage = 'gtscrm maps [options]'

class fermipy.diffuse.job_library.Gtlink_ltsum(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtltsun :param infile1: Livetime cube 1 or list of files [None] :type infile1: <class 'str'>
    :param outfile: Output file [None] :type outfile: <class 'str'> :param infile2: Livetime cube 2 [None] :type
    infile2: <class 'str'>

    appname = 'gtltsun'
    default_file_args = {'infile1': 1, 'outfile': 2}
    default_options = {'infile1': (None, 'Livetime cube 1 or list of files', <class 'str'>)}
    description = 'Link to run gtltsun'
    linkname_default = 'gtltsun'
    usage = 'gtltsun [options]'

class fermipy.diffuse.job_library.Gtlink_mktime(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtmktime :param pfiles: PFILES directory [None] :type pfiles: <class 'str'> :param roicut:
    Apply ROI-based zenith angle cut [False] :type roicut: <class 'bool'> :param filter: Filter expression [None]
    :type filter: <class 'str'> :param evfile: Input FT1 File [None] :type evfile: <class 'str'> :param scfile: Input
    FT2 file [None] :type scfile: <class 'str'> :param outfile: Output FT1 File [None] :type outfile: <class 'str'>

    appname = 'gtmktime'
    default_file_args = {'evfile': 33, 'outfile': 34, 'scfile': 33}
    default_options = {'evfile': (None, 'Input FT1 File', <class 'str'>), 'filter': (None, 'Filter expression', <class 'str'>)}
    description = 'Link to run gtmktime'
    linkname_default = 'gtmktime'
    usage = 'gtmktime [options]'

class fermipy.diffuse.job_library.Gtlink_ltcube(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtlcube :param zmax: Maximum zenith angle [105] :type zmax: <class 'float'> :param
    scfile: Input FT2 file [None] :type scfile: <class 'str'> :param evfile: Input FT1 File [None] :type evfile: <class
    'str'> :param binsz: Pixel size (degrees) [1.0] :type binsz: <class 'float'> :param pfiles: PFILES directory
    [None] :type pfiles: <class 'str'> :param dcostheta: Step size in cos(theta) [0.025] :type dcostheta: <class
    'float'> :param phibins: Number of phi bins [0] :type phibins: <class 'int'> :param outfile: Output Livetime
    cube File [None] :type outfile: <class 'str'> :param zmin: Minimum zenith angle [0] :type zmin: <class 'float'>

    appname = 'gtltcube'
    default_file_args = {'evfile': 33, 'outfile': 34, 'scfile': 33}
    default_options = {'binsz': (1.0, 'Pixel size (degrees)', <class 'float'>), 'dcostheta': (0.025, 'Step size in cos(theta)', <class 'float'>)}
    description = 'Link to run gtlcube'
```

```

linkname_default = 'gtltcube'

usage = 'gtltcube [options]'

class fermipy.diffuse.solar.Gtlink_expcube2_wcs(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtexpcube2 :param emin: Start energy (MeV) of first bin [100.0] :type emin: <class 'float'> :param evtype: Event type selections [None] :type evtype: <class 'int'> :param yref: Second coordinate of image center in degrees (DEC or GLAT) [0.0] :type yref: <class 'float'> :param xref: First coordinate of image center in degrees (RA or GLON) [0.0] :type xref: <class 'float'> :param outfile: Output file [None] :type outfile: <class 'str'> :param infile: Input livetime cube file [None] :type infile: <class 'str'> :param axisrot: Rotation angle of image axis, in degrees [0.0] :type axisrot: <class 'float'> :param emax: Stop energy (MeV) of last bin [1000000.0] :type emax: <class 'float'> :param cmap: Input counts cube template [none] :type cmap: <class 'str'> :param nxpix: Size of the X axis in pixels [1440] :type nxpix: <class 'int'> :param coordsys: Coordinate system [GAL] :type coordsys: <class 'str'> :param enumbins: Number of logarithmically-spaced energy bins [12] :type enumbins: <class 'int'> :param binsz: Image scale (in degrees/pixel) [0.25] :type binsz: <class 'float'> :param proj: Projection method e.g. AITARCICARIGLSIMERINCPISINISTGITAN [CAR] :type proj: <class 'str'> :param irfs: Instrument response functions [CALDB] :type irfs: <class 'str'> :param nyxpix: Size of the Y axis in pixels [720] :type nyxpix: <class 'int'>

    appname = 'gtexpcube2'

    default_file_args = {'cmap': 1, 'infile': 1, 'outfile': 2}

    default_options = {'axisrot': (0.0, 'Rotation angle of image axis, in degrees', <class 'float'>),

    description = 'Link to run gtexpcube2'

    linkname_default = 'gtexpcube2'

    usage = 'gtexpcube2 [options]'

class fermipy.diffuse.solar.Gtlink_exphpsun(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtexphpsun :param emax: Stop energy (MeV) of last bin [1000000.0] :type emax: <class 'float'> :param emin: Start energy (MeV) of first bin [100.0] :type emin: <class 'float'> :param evtype: Event type selection [3] :type evtype: <class 'int'> :param outfile: Output file [None] :type outfile: <class 'str'> :param binsz: Image scale (in degrees/pixel) [1.0] :type binsz: <class 'float'> :param irfs: Instrument response functions [CALDB] :type irfs: <class 'str'> :param enumbins: Number of logarithmically-spaced energy bins [12] :type enumbins: <class 'int'> :param infile: Input livetime cube file [None] :type infile: <class 'str'>

    appname = 'gtexphpsun'

    default_file_args = {'infile': 1, 'outfile': 2}

    default_options = {'binsz': (1.0, 'Image scale (in degrees/pixel)', <class 'float'>),

    description = 'Link to run gtexphpsun'

    linkname_default = 'gtexphpsun'

    usage = 'gtexphpsun [options]'

class fermipy.diffuse.solar.Gtlink_suntemp(**kwargs)
    Bases: fermipy.jobs.gtlink.Gtlink

    Small wrapper to run gtsuntemp :param emin: Start energy (MeV) of first bin [100.0] :type emin: <class 'float'> :param evtype: Event type selection [3] :type evtype: <class 'int'> :param yref: Second coordinate of image center in degrees (DEC or GLAT) [0.0] :type yref: <class 'float'> :param expsun: Exposure binned in healpix and solar angles [None] :type expsun: <class 'str'> :param xref: First coordinate of image center in degrees (RA or GLON) [0.0] :type xref: <class 'float'> :param outfile: Output file [None] :type outfile: <class 'str'>

```

```
:param axisrot: Rotation angle of image axis, in degrees [0.0] :type axisrot: <class 'float'> :param emax: Stop
energy (MeV) of last bin [1000000.0] :type emax: <class 'float'> :param cmap: Counts map file [none] :type
cmap: <class 'str'> :param nxpix: Size of the X axis in pixels [1440] :type nxpix: <class 'int'> :param co-
ordsys: Coordinate system (CEL - celestial, GAL -galactic) [GAL] :type coordsys: <class 'str'> :param sun-
prof: Fits file containing solar intensity profile [None] :type sunprof: <class 'str'> :param enumbins: Number
of logarithmically-spaced energy bins [12] :type enumbins: <class 'int'> :param binsz: Image scale (in de-
grees/pixel) [0.25] :type binsz: <class 'float'> :param avgexp: Binned exposure [None] :type avgexp: <class
'str'> :param proj: Projection method e.g. AITARCICARIGLSIMERINCPISINISTGITAN [CAR] :type proj:
<class 'str'> :param irfs: Instrument response functions [CALDB] :type irfs: <class 'str'> :param nypix: Size
of the Y axis in pixels [720] :type nypix: <class 'int'>

appname = 'gtsuntemp'

default_file_args = {'avgexp': 1, 'expsun': 1, 'outfile': 2, 'sunprof': 1}

default_options = {'avgexp': (None, 'Binned exposure', <class 'str'>), 'axisrot': (0

description = 'Link to run gtsuntemp'

linkname_default = 'gtsuntemp'

usage = 'gtsuntemp [options]'

class fermipy.diffuse.job_library.Link_FermipyCoadd(**kwargs)
    Bases: fermipy.jobs.app_link.AppLink

    Small wrapper to run fermipy-coadd :param args: List of input files [[]] :type args: <class 'list'> :param output:
    Output file [None] :type output: <class 'str'>

    appname = 'fermipy-coadd'

    default_file_args = {'args': 1, 'output': 2}

    default_options = {'args': ([], 'List of input files', <class 'list'>), 'output': (N

    description = 'Link to run fermipy-coadd'

    linkname_default = 'coadd'

    usage = 'fermipy-coadd [options]'

class fermipy.diffuse.job_library.Link_FermipyGatherSrcmaps(**kwargs)
    Bases: fermipy.jobs.app_link.AppLink

    Small wrapper to run fermipy-gather-srcmaps :param rm: Remove input files [False] :type rm: <class 'bool'>
    :param args: List of input files [[]] :type args: <class 'list'> :param clobber: Overwrite output [False] :type clob-
    ber: <class 'bool'> :param output: Output file name [None] :type output: <class 'str'> :param gzip: Compress
    output [False] :type gzip: <class 'bool'>

    appname = 'fermipy-gather-srcmaps'

    default_file_args = {'args': 1, 'output': 2}

    default_options = {'args': ([], 'List of input files', <class 'list'>), 'clobber': (

    description = 'Link to run fermipy-gather-srcmaps'

    linkname_default = 'gather-srcmaps'

    usage = 'fermipy-gather-srcmaps [options]'

class fermipy.diffuse.job_library.Link_FermipyVstack(**kwargs)
    Bases: fermipy.jobs.app_link.AppLink

    Small wrapper to run fermipy-vstack :param rm: Remove input files [False] :type rm: <class 'bool'> :param
    args: List of input files [[]] :type args: <class 'list'> :param hdu: Name of HDU to stack [None] :type hdu:
```



<class 'str'> :param gzip: Compress output [False] :type gzip: <class 'bool'> :param output: Output file name [None] :type output: <class 'str'> :param clobber: Overwrite output [False] :type clobber: <class 'bool'>

**appname** = 'fermipy-vstack'

**default\_file\_args** = {'args': 1, 'output': 2}

**default\_options** = {'args': ([], 'List of input files', <class 'list'>), 'clobber': (

**description** = 'Link to run fermipy-vstack'

**linkname\_default** = 'vstack'

**usage** = 'fermipy-vstack [options]'

**class** fermipy.diffuse.job\_library.Link\_FermipyHealview(\*\*kwargs)

Bases: *fermipy.jobs.app\_link.AppLink*

Small wrapper to run fermipy-healview :param extension: FITS HDU with HEALPix map [None] :type extension: <class 'str'> :param zscale: Scaling for color scale [log] :type zscale: <class 'str'> :param output: Output file name [None] :type output: <class 'str'> :param input: Input file [None] :type input: <class 'str'>

**appname** = 'fermipy-healview'

**default\_file\_args** = {'args': 1, 'output': 2}

**default\_options** = {'extension': (None, 'FITS HDU with HEALPix map', <class 'str'>), '

**description** = 'Link to run fermipy-healview'

**linkname\_default** = 'fermipy-healview'

**usage** = 'fermipy-healview [options]'

## Standalone Analysis Links

**class** fermipy.diffuse.gt\_merge\_srcmaps.GtMergeSrcmaps(\*\*kwargs)

Bases: *fermipy.jobs.link.Link*

Small class to merge source maps for composite sources.

This is useful for parallelizing source map creation.

### Parameters

- **outxml** (<class 'str'>) – Output source model xml file [None]
- **merged** (<class 'str'>) – Name of merged source [None]
- **srcmaps** (<class 'str'>) – Input source maps file [None]
- **bexpmap** (<class 'str'>) – Input binned exposure map file [None]
- **expcube** (<class 'str'>) – Input Livetime cube file [None]
- **gzip** (<class 'bool'>) – Compress output file [False]
- **irfs** (<class 'str'>) – Instrument response functions [CALDB]
- **outfile** (<class 'str'>) – Output file [None]
- **srcmdl** (<class 'str'>) – Input source model xml file [None]

**NULL\_MODEL** = 'srcmdls/null.xml'

**appname** = 'fermipy-merge-srcmaps'

```
default_file_args = {'bexpmap': 1, 'cmap': 1, 'expcube': 1, 'outfile': 2, 'outxml': 1}
default_options = {'bexpmap': (None, 'Input binned exposure map file', <class 'str'>)}
description = 'Merge source maps from a set of sources'
linkname_default = 'merge-srcmaps'
run_analysis(argv)
    Run this analysis
usage = 'fermipy-merge-srcmaps [options]'
```

```
class fermipy.diffuse.gt_srcmap_partial.GtSrcmapsDiffuse(**kwargs)
    Bases: fermipy.jobs.link.Link
```

**Small class to create srcmaps for only once source in a model**, and optionally for only some of the energy layers.

This is useful for parallelizing source map creation.

#### Parameters

- **kmin** (*<class 'int'>*) – Minimum Energy Bin [0]
- **kmax** (*<class 'int'>*) – Maximum Energy Bin [-1]
- **cmap** (*<class 'str'>*) – Input counts cube file [None]
- **bexpmap** (*<class 'str'>*) – Input binned exposure map file [None]
- **source** (*<class 'str'>*) – Input source [None]
- **expcube** (*<class 'str'>*) – Input Livetime cube file [None]
- **gzip** (*<class 'bool'>*) – Compress output file [False]
- **irfs** (*<class 'str'>*) – Instrument response functions [CALDB]
- **no\_psf** (*<class 'bool'>*) – Do not apply PSF smearing [False]
- **outfile** (*<class 'str'>*) – Output file [None]
- **srcmdl** (*<class 'str'>*) – Input source model xml file [None]

```
NULL_MODEL = 'srcmdls/null.xml'
appname = 'fermipy-srcmaps-diffuse'
default_file_args = {'bexpmap': 1, 'cmap': 1, 'expcube': 1, 'outfile': 2, 'srcmdl': 1}
default_options = {'bexpmap': (None, 'Input binned exposure map file', <class 'str'>)}
description = 'Run gtsrcmaps for one or more energy planes for a single source'
linkname_default = 'srcmaps-diffuse'
run_analysis(argv)
    Run this analysis
usage = 'fermipy-srcmaps-diffuse [options]'
```

```
class fermipy.diffuse.gt_srcmaps_catalog.GtSrcmapsCatalog(**kwargs)
    Bases: fermipy.jobs.link.Link
```

**Small class to create and write srcmaps for all the catalog sources**, once source at a time.

This is useful for creating source maps for all the sources in a catalog

**Parameters**

- **srcmax** (<class 'int'>) – Index of last source [-1]
- **cmap** (<class 'str'>) – Input counts cube file [None]
- **srcmin** (<class 'int'>) – Index of first source [0]
- **bexpmap** (<class 'str'>) – Input binned exposure map file [None]
- **expcube** (<class 'str'>) – Input Livetime cube file [None]
- **gzip** (<class 'bool'>) – Compress output file [False]
- **irfs** (<class 'str'>) – Instrument response functions [CALDB]
- **outfile** (<class 'str'>) – Output file [None]
- **srcmdl** (<class 'str'>) – Input source model xml file [None]

```
NULL_MODEL = 'srcmdls/null.xml'
```

```
appname = 'fermipy-srcmaps-catalog'
```

```
default_file_args = {'bexpmap': 1, 'cmap': 1, 'expcube': 1, 'outfile': 2, 'srcmdl': 1}
```

```
default_options = {'bexpmap': (None, 'Input binned exposure map file', <class 'str'>)}
```

```
description = 'Run gtsrcmaps for for all the sources in a catalog'
```

```
linkname_default = 'srcmaps-catalog'
```

```
run_analysis (argv)
```

```
    Run this analysis
```

```
usage = 'fermipy-srcmaps-catalog [options]'
```

```
class fermipy.diffuse.gt_assemble_model.InitModel (**kwargs)
```

```
    Bases: fermipy.jobs.link.Link
```

```
    Small class to preprate files fermipy analysis.
```

```
    Specifically this create the srcmap_manifest and fermipy_config_yaml files
```

```
appname = 'fermipy-init-model'
```

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
```

```
description = 'Initialize model fitting directory'
```

```
linkname_default = 'init-model'
```

```
run_analysis (argv)
```

```
    Build the manifest for all the models
```

```
usage = 'fermipy-init-model [options]'
```

```
class fermipy.diffuse.gt_assemble_model.AssembleModel (**kwargs)
```

```
    Bases: fermipy.jobs.link.Link
```

```
    Small class to assemple source map files for fermipy analysis.
```

```
    This is useful for re-merging after parallelizing source map creation.
```

```
static append_hdus (hdulist, srcmap_file, source_names, hpx_order)
```

```
    Append HEALPix maps to a list
```

**Parameters**

- **hdulist** (*list*) – The list being appended to
- **srcmap\_file** (*str*) – Path to the file containing the HDUs
- **source\_names** (*list of str*) – Names of the sources to extract from srcmap\_file
- **hpx\_order** (*int*) – Maximum order for maps

**appname** = 'fermipy-assemble-model'

**static assemble\_component** (*compname, compinfo, hpx\_order*)

Assemble the source map file for one binning component

#### Parameters

- **compname** (*str*) – The key for this component (e.g., E0\_PSF3)
- **compinfo** (*dict*) – Information about this component
- **hpx\_order** (*int*) – Maximum order for maps

**static copy\_ccube** (*ccube, outsrcmap, hpx\_order*)

Copy a counts cube into outsrcmap file reducing the HEALPix order to hpx\_order if needed.

**default\_options** = {'compname': (None, 'Component name.', <class 'str'>), 'hpx\_order':

**description** = 'Assemble sourcemaps for model fitting'

**linkname\_default** = 'assemble-model'

**static open\_outsrcmap** (*outsrcmap*)

Open and return the outsrcmap file in append mode

**run\_analysis** (*argv*)

Assemble the source map file for one binning component FIXME

**usage** = 'fermipy-assemble-model [options]'

**class** fermipy.diffuse.residual\_cr.**ResidualCR** (\*\*kwargs)

Bases: [fermipy.jobs.link.Link](#)

Small class to analyze the residual cosmic-ray contamination.

#### Parameters

- **ccube\_clean** (<class 'str'>) – Input counts cube for clean event class. [None]
- **ccube\_dirty** (<class 'str'>) – Input counts cube for dirty event class. [None]
- **hpx\_order** (<class 'int'>) – HEALPIX order parameter [6]
- **bexpcube\_clean** (<class 'str'>) – Input exposure cube for clean event class. [None]
- **sigma** (<class 'float'>) – Width of gaussian to smooth output maps [degrees] [3.0]
- **full\_output** (<class 'bool'>) – Include diagnostic output [False]
- **mask\_factor** (<class 'float'>) – Pixel selection factor for output mask [2.0]
- **select\_factor** (<class 'float'>) – Pixel selection factor for Aeff Correction [5.0]
- **bexpcube\_dirty** (<class 'str'>) – Input exposure cube for dirty event class. [None]
- **outfile** (<class 'str'>) – Output file [None]
- **clobber** (<class 'bool'>) – Overwrite files [False]

```

appname = 'fermipy-residual-cr'
default_file_args = {'bexpcube_clean': 1, 'bexpcube_dirty': 1, 'ccube_clean': 1, 'c
default_options = {'bexpcube_clean': (None, 'Input exposure cube for clean event clas
description = 'Compute the residual cosmic-ray contamination'
linkname_default = 'residual-cr'
run_analysis(argv)
    Run this analysis
usage = 'fermipy-residual-cr [options]'

```

### Batch job dispatch classes

```
class fermipy.diffuse.job_library.Gtexpcube2_SG(link, **kwargs)
```

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for *Gtlink\_expcube2*

#### Parameters

- **hpx\_order\_max** (<class 'int'>) – Maximum HEALPIX order for exposure cubes. [6]
- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-gtexpcube2-sg'
```

```
build_job_configs(args)
    Hook to build job configurations
```

```
clientclass
    alias of Gtlink_expcube2
```

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning
```

```
description = 'Submit gtexpube2 jobs in parallel'
```

```
job_time = 300
```

```
usage = 'fermipy-gtexpcube2-sg [options]'
```

```
class fermipy.diffuse.job_library.Gtltsum_SG(link, **kwargs)
```

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for *Gtlink\_ltsum*

#### Parameters

- **ft1file** (<class 'str'>) – Input FT1 file [None]
- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-gtltsum-sg'
```

```
build_job_configs(args)
    Hook to build job configurations
```

```
clientclass
    alias of Gtlink_ltsum

default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
description = 'Submit gtltsum jobs in parallel'
job_time = 300
usage = 'fermipy-gtltsum-sg [options]'
```

**class** fermipy.diffuse.solar.Gtexpcube2wcs\_SG(*link*, *\*\*kwargs*)  
Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for gtexphpsun

**Parameters**

- **binsz** (<class 'float'>) – Image scale (in degrees/pixel) [1.0]
- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **mktimefilter** (<class 'str'>) – Key for gtmktime selection [None]
- **nxpix** (<class 'int'>) – Size of the X axis in pixels [360]
- **nypix** (<class 'int'>) – Size of the Y axis in pixels [180]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-gtexpcube2wcs-sg'

build_job_configs(args)
    Hook to build job configurations

clientclass
    alias of Gtlink_expcube2_wcs

default_options = {'binsz': (1.0, 'Image scale (in degrees/pixel)', <class 'float'>)},
description = 'Submit gtexpcube2 jobs in parallel'
job_time = 300
usage = 'fermipy-gtexpcube2wcs-sg [options]'
```

**class** fermipy.diffuse.solar.Gtexphpsun\_SG(*link*, *\*\*kwargs*)  
Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for gtexphpsun

**Parameters**

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **mktimefilter** (<class 'str'>) – Key for gtmktime selection [None]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-gtexphpsun-sg'

build_job_configs(args)
    Hook to build job configurations

clientclass
    alias of Gtlink_exphpsun
```

```

default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning
description = 'Submit gtexphpsun jobs in parallel'
job_time = 300
usage = 'fermipy-gtexphpsun-sg [options]'

class fermipy.diffuse.solar.Gtsuntemp_SG(link, **kwargs)
    Bases: fermipy.jobs.scatter_gather.ScatterGather
    Small class to generate configurations for gtsuntemp

    Parameters
        • sourcekeys (<class 'list'>) – Keys for sources to make template for [None]
        • data (<class 'str'>) – Path to yaml file defining dataset. [config/dataset_source.yaml]
        • mktimefilter (<class 'str'>) – Key for gtmktime selection [None]
        • comp (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

    appname = 'fermipy-gtsuntemp-sg'

    build_job_configs(args)
        Hook to build job configurations

    clientclass
        alias of Gtlink_suntemp

    default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning
    description = 'Submit gtsuntemp jobs in parallel'
    job_time = 300
    usage = 'fermipy-gtsuntemp-sg [options]'

class fermipy.diffuse.gt_coadd_split.CoaddSplit_SG(link, **kwargs)
    Bases: fermipy.jobs.scatter_gather.ScatterGather
    Small class to generate configurations for fermipy-coadd

    Parameters
        • ft1file (<class 'str'>) – Input FT1 file [None]
        • data (<class 'str'>) – Path to yaml file defining dataset. [config/dataset_source.yaml]
        • comp (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

    appname = 'fermipy-coadd-split-sg'

    build_job_configs(args)
        Hook to build job configurations

    clientclass
        alias of fermipy.diffuse.job_library.Link_FermipyCoadd

    default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning
    description = 'Submit fermipy-coadd-split- jobs in parallel'
    job_time = 300
    usage = 'fermipy-coadd-split-sg [options]'

```

```
class fermipy.diffuse.job_library.GatherSrcmaps_SG(link, **kwargs)
```

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for *Link\_FermipyGatherSrcmaps*

**Parameters**

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **library** (<class 'str'>) – Path to yaml file defining model components. [models/library.yaml]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-gather-srcmaps-sg'
```

```
build_job_configs(args)
```

Hook to build job configurations

```
clientclass
```

alias of *Link\_FermipyGatherSrcmaps*

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
```

```
description = 'Submit fermipy-gather-srcmaps jobs in parallel'
```

```
job_time = 300
```

```
usage = 'fermipy-gather-srcmaps-sg [options]'
```

```
class fermipy.diffuse.job_library.Vstack_SG(link, **kwargs)
```

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for *Link\_FermipyVstack* to merge source maps

**Parameters**

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **library** (<class 'str'>) – Path to yaml file defining model components. [models/library.yaml]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-vstack-sg'
```

```
build_job_configs(args)
```

Hook to build job configurations

```
clientclass
```

alias of *Link\_FermipyVstack*

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
```

```
description = 'Submit fermipy-vstack jobs in parallel'
```

```
job_time = 300
```

```
usage = 'fermipy-vstack-sg [options]'
```

```
class fermipy.diffuse.job_library.Healview_SG(link, **kwargs)
```

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for *Link\_FermipyHealview*



**Parameters**

- **data** (`<class 'str'>`) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **library** (`<class 'str'>`) – Path to yaml file defining model components. [models/library.yaml]
- **comp** (`<class 'str'>`) – Path to yaml file defining binning. [config/binning.yaml]

**appname** = 'fermipy-healviw-sg'

**build\_job\_configs** (*args*)

Hook to build job configurations

**clientclass**

alias of *Link\_FermipyHealview*

**default\_options** = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}

**description** = 'Submit fermipy-healviw jobs in parallel'

**job\_time** = 60

**usage** = 'fermipy-healviw-sg [options]'

**class** fermipy.diffuse.job\_library.SumRings\_SG(*link*, *\*\*kwargs*)

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for *Link\_FermipyCoadd* to sum galprop ring gasmaps

**Parameters**

- **outdir** (`<class 'str'>`) – Output directory [None]
- **library** (`<class 'str'>`) – Path to yaml file defining model components. [models/library.yaml]

**appname** = 'fermipy-sum-rings-sg'

**build\_job\_configs** (*args*)

Hook to build job configurations

**clientclass**

alias of *Link\_FermipyCoadd*

**default\_options** = {'library': ('models/library.yaml', 'Path to yaml file defining model components')}

**description** = 'Submit fermipy-coadd jobs in parallel to sum GALProp rings'

**job\_time** = 300

**usage** = 'fermipy-sum-rings-sg [options]'

**class** fermipy.diffuse.job\_library.SumRings\_SG(*link*, *\*\*kwargs*)

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for *Link\_FermipyCoadd* to sum galprop ring gasmaps

**Parameters**

- **outdir** (`<class 'str'>`) – Output directory [None]
- **library** (`<class 'str'>`) – Path to yaml file defining model components. [models/library.yaml]

```
appname = 'fermipy-sum-rings-sg'
build_job_configs(args)
    Hook to build job configurations

clientclass
    alias of Link_FermipyCoadd

default_options = {'library': ('models/library.yaml', 'Path to yaml file defining mod
description = 'Submit fermipy-coadd jobs in parallel to sum GALProp rings'
job_time = 300
usage = 'fermipy-sum-rings-sg [options]'
```

**class** fermipy.diffuse.residual\_cr.**ResidualCR\_SG**(*link*, *\*\*kwargs*)  
Bases: *fermipy.jobs.scatter\_gather.ScatterGather*  
Small class to generate configurations for this script

**Parameters**

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **dirty** (<class 'str'>) – Dirty event class [source]
- **mktimefilter** (<class 'str'>) – Key for gtmktime selection [None]
- **hpx\_order** (<class 'int'>) – HEALPIX order parameter [6]
- **sigma** (<class 'float'>) – Width of gaussian to smooth output maps [degrees] [3.0]
- **full\_output** (<class 'bool'>) – Include diagnostic output [False]
- **mask\_factor** (<class 'float'>) – Pixel selection factor for output mask [2.0]
- **select\_factor** (<class 'float'>) – Pixel selection factor for Aeff Correction [5.0]
- **clean** (<class 'str'>) – Clean event class [ultracleanveto]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-residual-cr-sg'
build_job_configs(args)
    Hook to build job configurations

clientclass
    alias of ResidualCR

default_options = {'clean': ('ultracleanveto', 'Clean event class', <class 'str'>), '
description = 'Compute the residual cosmic-ray contamination'
job_time = 300
usage = 'fermipy-residual-cr-sg [options]'
```

**class** fermipy.diffuse.gt\_merge\_srcmaps.**MergeSrcmaps\_SG**(*link*, *\*\*kwargs*)  
Bases: *fermipy.jobs.scatter\_gather.ScatterGather*  
Small class to generate configurations for *GtMergeSrcmaps*

**Parameters**

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **library** (<class 'str'>) – Path to yaml file defining model components. [models/library.yaml]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```

appname = 'fermipy-merge-srcmaps-sg'
build_job_configs (args)
    Hook to build job configurations
clientclass
    alias of GtMergeSrcmaps
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning
description = 'Merge diffuse maps for all-sky analysis'
job_time = 300
usage = 'fermipy-merge-srcmaps-sg [options]'
class fermipy.diffuse.gt_srcmap_partial.SrcmapsDiffuse_SG(link, **kwargs)
    Bases: fermipy.jobs.scatter_gather.ScatterGather
    Small class to generate configurations for GtSrcmapsDiffuse

    Parameters
        • data (<class 'str'>) – Path to yaml file defining dataset. [config/dataset_source.yaml]
        • library (<class 'str'>) – Path to yaml file defining model components. [models/library.yaml]
        • make_xml (<class 'bool'>) – Write xml files needed to make source maps [True]
        • comp (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

appname = 'fermipy-srcmaps-diffuse-sg'
build_job_configs (args)
    Hook to build job configurations
clientclass
    alias of GtSrcmapsDiffuse
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning
description = 'Run gtsrcmaps for diffuse sources'
job_time = 1500
usage = 'fermipy-srcmaps-diffuse-sg [options]'
class fermipy.diffuse.gt_srcmaps_catalog.SrcmapsCatalog_SG(link, **kwargs)
    Bases: fermipy.jobs.scatter_gather.ScatterGather
    Small class to generate configurations for gtsrcmaps for catalog sources

    Parameters
        • library (<class 'str'>) – Path to yaml file defining model components. [models/library.yaml]

```

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **make\_xml** (<class 'bool'>) – Make XML files. [True]
- **nsrc** (<class 'int'>) – Number of sources per job [500]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

**appname** = 'fermipy-srcmaps-catalog-sg'

**build\_job\_configs** (*args*)  
Hook to build job configurations

**clientclass**  
alias of *GtSrcmapsCatalog*

**default\_options** = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}

**description** = 'Run gtsrcmaps for catalog sources'

**job\_time** = 1500

**usage** = 'fermipy-srcmaps-catalog-sg [options]'

**class** fermipy.diffuse.gt\_assemble\_model.**AssembleModel\_SG**(*link*, **\*\*kwargs**)

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for this script

#### Parameters

- **--compname** (*binning component definition yaml file*) –
- **--data** (*dataset definition yaml file*) –
- **--models** (*model definition yaml file*) –
- **args** (*Names of models to assemble source maps for*) –

**appname** = 'fermipy-assemble-model-sg'

**build\_job\_configs** (*args*)  
Hook to build job configurations

**clientclass**  
alias of *AssembleModel*

**default\_options** = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}

**description** = 'Copy source maps from the library to a analysis directory'

**job\_time** = 300

**usage** = 'fermipy-assemble-model-sg [options]'

**class** fermipy.diffuse.residual\_cr.**ResidualCR\_SG**(*link*, **\*\*kwargs**)

Bases: *fermipy.jobs.scatter\_gather.ScatterGather*

Small class to generate configurations for this script

#### Parameters

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **dirty** (<class 'str'>) – Dirty event class [source]
- **mktimefilter** (<class 'str'>) – Key for gtmtime selection [None]

- **hpx\_order** (*<class 'int'>*) – HEALPIX order parameter [6]
- **sigma** (*<class 'float'>*) – Width of gaussian to smooth output maps [degrees] [3.0]
- **full\_output** (*<class 'bool'>*) – Include diagnostic output [False]
- **mask\_factor** (*<class 'float'>*) – Pixel selection factor for output mask [2.0]
- **select\_factor** (*<class 'float'>*) – Pixel selection factor for Aeff Correction [5.0]
- **clean** (*<class 'str'>*) – Clean event class [ultracleanveto]
- **comp** (*<class 'str'>*) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-residual-cr-sg'
```

**build\_job\_configs** (*args*)

## Hook to build job configurations

**clientclass**alias of *ResidualCR*

```
default_options = {'clean': ('ultracleanveto', 'Clean event class', <class 'str'>), 'c
```

```
description = 'Compute the residual cosmic-ray contamination'
```

```
job_time = 300
```

```
usage = 'fermipy-residual-cr-sg [options]'
```

```
class fermipy.diffuse.gt_split_and_bin.SplitAndBin_SG(link, **kwargs)
```

Bases: `fermipy.jobs.scatter_gather.ScatterGather`

### Small class to generate configurations for SplitAndBin

## Parameters

- **ft1file** (*<class 'str'>*) – Input FT1 file [None]
- **hpx\_order\_max** (*<class 'int'>*) – Maximum HEALPIX order for binning counts data. [9]
- **data** (*<class 'str'>*) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **scratch** (*<class 'str'>*) – Path to scratch area [None]
- **comp** (*<class 'str'>*) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-split-and-bin-sg'
```

**build\_job\_configs** (*args*)

## Hook to build job configurations

**clientclass**alias of *SplitAndBin*

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning
```

```
description = 'Prepare data for diffuse all-sky analysis'
```

```
job time = 1500
```

```
usage = 'fermipy-split-and-bin-sg [options]'
```

**class** `fermipy.diffuse.gt_split_and_mktime.SplitAndMktime_SG` (*link*, *\*\*kwargs*)

Bases: `fermipy.jobs.scatter_gather.ScatterGather`

Small class to generate configurations for SplitAndMktime

#### Parameters

- **ft1file** (`<class 'str'>`) – Path to list of input FT1 files [P8\_P305\_8years\_source\_zmax105.lst]
- **scratch** (`<class 'str'>`) – Path to scratch area. [None]
- **hpx\_order\_max** (`<class 'int'>`) – Maximum HEALPIX order for binning counts data. [9]
- **do\_ltsum** (`<class 'bool'>`) – Run gtlsum on inputs [False]
- **dry\_run** (`<class 'bool'>`) – Print commands but do not run them [False]
- **data** (`<class 'str'>`) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **ft2file** (`<class 'str'>`) – Path to list of input FT2 files [ft2\_8years.lst]
- **comp** (`<class 'str'>`) – Path to yaml file defining binning. [config/binning.yaml]

**appname** = 'fermipy-split-and-mktime-sg'

**build\_job\_configs** (*args*)

Hook to build job configurations

**clientclass**

alias of `SplitAndMktime`

**default\_options** = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}

**description** = 'Prepare data for diffuse all-sky analysis'

**job\_time** = 1500

**usage** = 'fermipy-split-and-mktime-sg [options]'

## Analysis chain classes

**class** `fermipy.diffuse.gt_coadd_split.CoaddSplit` (*\*\*kwargs*)

Bases: `fermipy.jobs.chain.Chain`

Small class to merge counts cubes for a series of binning components

This chain consists multiple Link objects:

**coadd-EBIN-ZCUT-FILTER-EVTYPE** [`_Link_FermipyCoadd`] Link to coadd data of a particular type.

#### Parameters

- **dry\_run** (`<class 'bool'>`) – Print commands but do not run them [False]
- **nfiles** (`<class 'int'>`) – Number of input files [96]
- **do\_ltsum** (`<class 'bool'>`) – Sum livetime cube files [False]
- **data** (`<class 'str'>`) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **comp** (`<class 'str'>`) – Path to yaml file defining binning. [config/binning.yaml]

```

appname = 'fermipy-coadd-split'
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
description = 'Merge a set of counts cube files'
linkname_default = 'coadd-split'
usage = 'fermipy-coadd-split [options]'

```

```
class fermipy.diffuse.gt_split_and_bin.SplitAndBin(**kwargs)
```

Bases: [fermipy.jobs.chain.Chain](#)

Small class to split and bin data according to some user-provided specification

This chain consists multiple Link objects:

**select-energy-EBIN-ZCUT** [Gtlink\_select] Initial splitting by energy bin and zenith angle cut

**select-type-EBIN-ZCUT-FILTER-TYPE** [Gtlink\_select] Refinement of selection from event types

**bin-EBIN-ZCUT-FILTER-TYPE** [Gtlink\_bin] Final binning of the data for each event type

#### Parameters

- **ft1file** (<class 'str'>) – Input FT1 file [None]
- **scratch** (<class 'str'>) – Scratch area [None]
- **hpx\_order\_max** (<class 'int'>) – Maximum HEALPIX order for binning counts data. [9]
- **outdir** (<class 'str'>) – Base name for output files [counts\_cubes\_cr]
- **pfiles** (<class 'str'>) – Directory for .par files [None]
- **evclass** (<class 'int'>) – Event class bit mask [128]
- **outkey** (<class 'str'>) – Key for this particular output file [None]
- **dry\_run** (<class 'bool'>) – Print commands but do not run them [False]
- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```

appname = 'fermipy-split-and-bin'
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
description = 'Run gtselect and gtbin together'
linkname_default = 'split-and-bin'
usage = 'fermipy-split-and-bin [options]'

```

```
class fermipy.diffuse.gt_split_and_bin.SplitAndBinChain(**kwargs)
```

Bases: [fermipy.jobs.chain.Chain](#)

Chain to run split and bin and then make exposure cubes

This chain consists of:

**split-and-bin** [[SplitAndBin\\_SG](#)] Chain to make the binned counts maps for each input file

**coadd-split** [CoaddSplit\_SG] Link to co-add the binned counts maps files

**expcube2** [Gtexpcube2\_SG] Link to make the corresponding binned exposure maps

#### Parameters

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **scratch** (<class 'str'>) – Path to scratch area. [None]
- **dry\_run** (<class 'bool'>) – Print commands but do not run them [False]
- **ft1file** (<class 'str'>) – Path to list of input FT1 files [P8\_P305\_8years\_source\_zmax105.lst]
- **hpx\_order\_ccube** (<class 'int'>) – Maximum HEALPIX order for binning counts data. [9]
- **hpx\_order\_expcube** (<class 'int'>) – Maximum HEALPIX order for exposure cubes. [6]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-split-and-bin-chain'
```

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
```

```
description = 'Run split-and-bin, coadd-split and exposure'
```

```
linkname_default = 'split-and-bin-chain'
```

```
usage = 'fermipy-split-and-bin-chain [options]'
```

```
class fermipy.diffuse.gt_split_and_mktime.SplitAndMktime(**kwargs)
```

Bases: *fermipy.jobs.chain.Chain*

Small class to split, apply mktime and bin data according to some user-provided specification

This chain consists multiple Link objects:

**select-energy-EBIN-ZCUT** [Gtlink\_select] Initial splitting by energy bin and zenith angle cut

**mktime-EBIN-ZCUT-FILTER** [Gtlink\_mktime] Application of gtmktime filter for zenith angle cut

**ltcube-EBIN-ZCUT-FILTER** [Gtlink\_ltcube] Computation of livetime cube for zenith angle cut

**select-type-EBIN-ZCUT-FILTER-TYPE** [Gtlink\_select] Refinement of selection from event types

**bin-EBIN-ZCUT-FILTER-TYPE** [Gtlink\_bin] Final binning of the data for each event type

#### Parameters

- **ft1file** (<class 'str'>) – Path to list of input FT1 files [P8\_P305\_8years\_source\_zmax105.lst]
- **scratch** (<class 'str'>) – Scratch area [None]
- **hpx\_order\_max** (<class 'int'>) – Maximum HEALPIX order for binning counts data. [9]
- **outdir** (<class 'str'>) – Output directory [counts\_cubes]



- **do\_ltsum** (<class 'bool'>) – Sum livetime cube files [False]
- **pfiles** (<class 'str'>) – Directory for .par files [None]
- **evclass** (<class 'int'>) – Event class bit mask [128]
- **outkey** (<class 'str'>) – Key for this particular output file [None]
- **dry\_run** (<class 'bool'>) – Print commands but do not run them [False]
- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **ft2file** (<class 'str'>) – Path to list of input FT2 files [ft2\_8years.lst]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-split-and-mktime'
```

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
```

```
description = 'Run gtselect and gtbin together'
```

```
linkname_default = 'split-and-mktime'
```

```
usage = 'fermipy-split-and-mktime [options]'
```

```
class fermipy.diffuse.gt_split_and_mktime.SplitAndMktimeChain(**kwargs)
```

Bases: [fermipy.jobs.chain.Chain](#)

Chain to run split and mktime and then make livetime and exposure cubes

This chain consists of:

**split-and-mktime** [SplitAndMkTime\_SG] Chain to make the binned counts maps for each input file

**coadd-split** [CoaddSplit\_SG] Link to co-add the binned counts maps files

**ltsum** [Gtltsum\_SG] Link to co-add the livetime cube files

**expcube2** [Gtexpcube2\_SG] Link to make the corresponding binned exposure maps

#### Parameters

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **scratch** (<class 'str'>) – Path to scratch area. [None]
- **hpx\_order\_ccube** (<class 'int'>) – Maximum HEALPIX order for binning counts data. [9]
- **do\_ltsum** (<class 'bool'>) – Run gtltsum on inputs [False]
- **dry\_run** (<class 'bool'>) – Print commands but do not run them [False]
- **ft1file** (<class 'str'>) – Path to list of input FT1 files [P8\_P305\_8years\_source\_zmax105.lst]
- **ft2file** (<class 'str'>) – Path to list of input FT2 files [ft2\_8years.lst]
- **hpx\_order\_expcube** (<class 'int'>) – Maximum HEALPIX order for exposure cubes. [6]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-split-and-mktime-chain'
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
description = 'Run split-and-mktime, coadd-split and exposure'
linkname_default = 'split-and-mktime-chain'
usage = 'fermipy-split-and-mktime-chain [options]'
```

```
class fermipy.diffuse.diffuse_analysis.DiffuseCompChain(**kwargs)
```

Bases: *fermipy.jobs.chain.Chain*

Chain to build srcmaps for diffuse components

This chain consists of:

**sum-rings** [SumRings\_SG] Merge GALProp gas maps by type and ring

**srcmaps-diffuse** [SrcmapsDiffuse\_SG] Compute diffuse component source maps in parallel

**vstack-diffuse** [Vstack\_SG] Combine diffuse component source maps

#### Parameters

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **library** (<class 'str'>) – Path to yaml file defining model components. [models/library.yaml]
- **make\_xml** (<class 'bool'>) – Make XML files. [True]
- **dry\_run** (<class 'bool'>) – Print commands but do not run them [False]
- **outdir** (<class 'str'>) – Output directory [None]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-diffuse-comp-chain'
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
description = 'Run diffuse component analysis'
linkname_default = 'diffuse-comp'
usage = 'fermipy-diffuse-comp-chain [options]'
```

```
class fermipy.diffuse.diffuse_analysis.CatalogCompChain(**kwargs)
```

Bases: *fermipy.jobs.chain.Chain*

Small class to build srcmaps for catalog components

This chain consists of:

**srcmaps-catalog** [SrcmapsCatalog\_SG] Build source maps for all catalog sources in parallel

**gather-srcmaps** [GatherSrcmaps\_SG] Gather source maps into

**merge-srcmaps** [MergeSrcmaps\_SG] Compute source maps for merged sources

#### Parameters

- **data** (<class 'str'>) – Path to yaml file defining dataset. [config/dataset\_source.yaml]
- **make\_xml** (<class 'bool'>) – Make XML files for diffuse components [False]

- **nsrc** (<class 'int'>) – Number of sources per job [500]
- **dry\_run** (<class 'bool'>) – Print commands but do not run them [False]
- **library** (<class 'str'>) – Path to yaml file defining model components. [models/library.yaml]
- **comp** (<class 'str'>) – Path to yaml file defining binning. [config/binning.yaml]

```
appname = 'fermipy-catalog-comp-chain'
```

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
```

```
description = 'Run catalog component analysis'
```

```
linkname_default = 'catalog-comp'
```

```
usage = 'fermipy-catalog-comp-chain [options]'
```

```
class fermipy.diffuse.gt_assemble_model.AssembleModelChain(**kwargs)
```

Bases: *fermipy.jobs.chain.Chain*

Small class to split, apply mktime and bin data according to some user-provided specification

```
appname = 'fermipy-assemble-model-chain'
```

```
default_options = {'comp': ('config/binning.yaml', 'Path to yaml file defining binning')}
```

```
description = 'Run init-model and assemble-model'
```

```
linkname_default = 'assemble-model-chain'
```

```
usage = 'fermipy-assemble-model-chain [options]'
```

```
class fermipy.diffuse.diffuse_analysis.DiffuseAnalysisChain(**kwargs)
```

Bases: *fermipy.jobs.chain.Chain*

Chain to define diffuse all-sky analysis

This chain consists of:

**prepare** [*SplitAndBinChain*] Bin the data and make the exposure maps

**diffuse-comp** [*DiffuseCompChain*] Make source maps for diffuse components

**catalog-comp** [*CatalogCompChain*] Make source maps for catalog components

**assemble-model** [*AssembleModelChain*] Assemble the models for fitting

#### Parameters

- **dry\_run** (<class 'bool'>) – Print commands but do not run them [False]
- **config** (<class 'str'>) – Config yaml file [None]

```
appname = 'fermipy-diffuse-analysis'
```

```
default_options = {'config': (None, 'Config yaml file', <class 'str'>), 'dry_run': (False, 'Print commands but do not run them')}
```

```
description = 'Run diffuse analysis chain'
```

```
linkname_default = 'diffuse'
```

```
usage = 'fermipy-diffuse-analysis [options]'
```

```
class fermipy.diffuse.residual_cr.ResidualCRChain(**kwargs)
    Bases: fermipy.jobs.chain.Chain

    Chain to preform analysis of residual cosmic-ray contamination

    This chain consists of:

    split-and-mktime [SplitAndMktimeChain] Chain to bin up the data and make exposure cubes
    residual-cr [ResidualCR] Residual CR analysis

    Parameters config (<class 'str'>) – Config yaml file [None]

    appname = 'fermipy-residual-cr-chain'
    default_options = {'config': (None, 'Config yaml file', <class 'str'>)}
    description = 'Run residual cosmic ray analysis'
    linkname_default = 'residual-cr-chain'
    usage = 'fermipy-residual-cr-chain [options]'

class fermipy.diffuse.solar.SunMoonChain(**kwargs)
    Bases: fermipy.jobs.chain.Chain

    Chain to construct sun and moon templates

    This chain consists of:

    exphpsun [Gtexphpsun_SG] Build the sun-centered exposure cubes
    suntemp [Gtsuntemp_SG] Build the templates

    appname = 'fermipy-sunmoon-chain'
    default_options = {'config': (None, 'Config yaml file', <class 'str'>)}
    description = 'Run sun and moon template construction'
    linkname_default = 'summoon'
    usage = 'fermipy-sunmoon-chain [options]'
```

### 1.3.13 Changelog

This page is a changelog for releases of Fermipy. You can also browse releases on [Github](#).

#### 0.19.0 (03/25/2020)

- Switch installation procedure and to using fermitools-data for diffuse emission models
- Update docs to reflect changers in intallation procedure
- Added new version of 4FGL catalog
- Updated automatic testing to work with 4FGL and new diffuse emisison models

### 0.18.1 (03/10/2020)

- Changes to improve automated builds for testing
- Added documentation for fermipy.jobs and fermipy.diffuse modules
- Some changes to support different size pixels in different components
- Added gtpsf and gtdrm support to gtanalysis

### 0.18.0 (10/18/2019)

- Added tools to use new version of energy dispersion from fermitools.
- Changed travis testing and conda scripts to work with conda release of fermitools.

### 0.17.4 (3/13/2019)

- Including 4FGL, interstellar emission model and isotropic templates files.
- Changing catalog.py to use 4FGL catalog
- Minor fixes to target\_collect.py, lightcurve.py and gta.simulate()

### 0.17.3 (7/12/2018)

- Added fitting code to fermipy.diffuse module
- Improved fermipy.jobs to deal with analyses with multiple components
- Added capability to plot global minimum in castro plots
- Added spectra for dark matter decay to DMFitFunction
- Added code to split simulations into smaller batch jobs
- Added fixed shape lightcurve to correct TS\_var computation

### 0.17.2 (5/30/2018)

- Added lots of documentation for the fermipy.jobs module.
- Minor changes to the fermipy.jobs module to work with the dark matter analysis pipeline (dmpipe).

### 0.17.1 (5/23/2018)

- Patch release to get versioning working with GitHub release system.

### 0.17.0 (5/22/2018)

- The LogParabola, PowerLawSuperExponential and Dark Matter SEDs have been added to the sensitivity.py script.
- There are a lot of additions to perform a stacking analysis. This can be applied for instance for the search of dark matter with a stacking analysis of Milky Way dSphs, Galaxy Clusters or other galaxies.
- It contains scripts to send jobs to SLAC Batch Farm and collect the results.

- It includes scripts and functions to perform all sky fits.
- It also fixes a few issues with glon and glat in the localization (#225), and the wrong orientation of residual and TS maps (#216)

### 0.16.0 (12/27/2017)

- Improvements and refactoring in the internals of the `lightcurve` method (see #156, #157, #160, #161, #162). Resolve fit stability issues that were arising when the source of interest was not significantly detected in a given time bin. Added options to speed up source map calculation by rescaling source maps (enabled with `use_scaled_srcmap=True`) and split the `lightcurve` calculation across N cores (enabled with `multithread=True` and `nthread=N`). Add calculation of `TS_var` to test for variability using method from the 2FGL.
- Updates to validation tools. Added MeritSkimmer script (`fermipy-merit-skimmer`) for skimming ROOT merit tuples either locally or on xrootd.

### 0.15.0 (09/05/2017)

- Bug fix related to restoring analysis state for phased analysis (scaled exposure).
- Many improvements and feature additions to sensitivity tools (see e.g. #148, #149, and #152).
- Various updates to support DM pipeline package (#146).
- Improve robustness of algorithms for extracting peak and uncertainty ellipse from 2D likelihood surface.
- Added `curvature` method for testing a source for spectral curvature.
- Added `fix_shape` option to `extension` and `localize` to fix spectral shape parameters. Spectral shape parameters of the source of interest are now free by default when localizing or fitting extension.

### 0.14.0 (03/28/2017)

- Refactoring and improvements in `localize` and `extension` (see #124). Cleanup of columns in `localize`. Add new columns for 1-sigma errors projected in CEL and GAL coordinates as well as associated covariance and correlation matrices. Add positional errors when running `extension` with `fit_position=True`.
- Add `free_radius` option to `localize`, `extension`, and `sed`. This can be used to free background sources within a certain distance of the analyzed source.
- Relocalize point-source hypothesis when testing extension of extended sources.
- Improve speed and accuracy of source map calculation (see #123). Exposures are now extracted directly from the exposure map.
- Write analysis configuration to `CONFIG` header keyword of all FITS output files.
- Add `jobs` and `diffuse` submodules (see #120 and #122). These contain functionality for performing all-sky diffuse analysis and setting up automated analysis pipelines. More detailed documentation on these features to be provided in a future release.

### 0.13.0 (01/16/2017)

- Rewrite `LTCube` class to add support for fast LT cube generation. The `gtlike.use_local_ltcube` option can be used to enable the python-based LT cube calculation in lieu of `gtltcube`.

- Bug fixes and improvements to lightcurve method (see #102). Python-based LT cube generation is now enabled by default resulting in much faster execution time when generating light curves over long time spans.
- Add `fit_position` option to `extension` that can be used to enable a joint fit of extension and position.
- New scheme for auto-generating parameter docstrings.
- Add new `set_source_morphology` method to update the spatial model of a source at runtime.
- Major refactoring of `extension` and `localize` (see #106 and #110).
- Pulled in many new modules and scripts for diffuse all-sky analysis (see #105).

### 0.12.0 (11/20/2016)

- Add support for phased analysis (#87). `gtlike.expscale` and `gtlike.src_expscale` can be used to apply a constant exposure correction to a whole component or individual sources within a component. See *Phased Analysis* for examples.
- Add script and tools for calculating flux sensitivity (#88 and #95). The `fermipy-flux-sensitivity` script evaluates both the differential and integral flux sensitivity for a given TS threshold and minimum number of detected counts. See *Sensitivity Tools* for examples.
- Add `fermipy-healview` script for generating images of healpix maps and cubes.
- Improvements to HPX-related classes and utilities.
- Refactoring in `irfs` module to support development of new validation tools.
- Improvements to configuration handling to allow parameter validation when updating configuration at runtime.
- Add lightcurve method (#80). See *Light Curves* for documentation.
- Change convention for flux arrays in source object. Values and uncertainties are now stored in separate arrays (e.g. `flux` and `flux_err`).
- Add *Docker-based installation* instructions. This can be used to run the RHEL6 SLAC ST builds on any machine that supports Docker (e.g. OSX Yosemite or later).
- Adopt changes to column name conventions in SED format. All column names are now lowercase.

### 0.11.0 (08/24/2016)

- Add support for weighted likelihood fits (supported in ST 11-03-00 or later). Weights maps can be specified with the `wmap` parameter in `gtlike`.
- Implemented performance improvements in `tsmap` including switching to newton's method for step-size calculation and masking of empty pixels (see #79).
- Ongoing development and refactoring of classes for dealing with `CastroData` (binned likelihood profiles).
- Added `reload_sources` method for faster recomputation of source maps.
- Fixed sign error in localization plotting method that gave wrong orientation for error ellipse..
- Refactored classes in `spectrum` and simplified interface for doing spectral fits (see #69).
- Added `DMFitFunction` spectral model class in `spectrum` (see #66). This uses the same lookup tables as the ST `DMFitFunction` class but provides a pure python implementation which can be used independently of the STs.

### 0.10.0 (07/03/2016)

- Implement support for more spectral models (DMFitFunction, EblAtten, FileFunction, Gaussian).
- New options (`outdir_regex` and `workdir_regex`) for fine-grained control over input/output file staging.
- Add `offset_roi_edge` to source dictionary. Defined as the distance from the source position to the edge of the ROI ( $< 0$  = inside the ROI,  $> 0$  = outside the ROI).
- Add new variables in `fit` output (`edm`, `fit_status`).
- Add new package scripts (`fermipy-collect-sources`, `fermipy-cluster-sources`).
- Various refactoring and improvements in code for dealing with castro data.
- Add `MODEL_FLUX` and `PARAMS` HDUs to SED FITS file. Many new elements added SED output dictionary.
- Support NEWTON fitter with the same interface as MINUIT and NEWMINUIT. Running `fit` with `optimizer = NEWTON` will use the NEWTON fitter where applicable (only free norms) and MINUIT otherwise. The `optimizer` argument to `sed`, `extension`, and `localize` can be used to override the default optimizer at runtime. Note that the NEWTON fitter is only supported by ST releases *after* 11-01-01.

### 0.9.0 (05/25/2016)

- Bug fixes and various refactoring in TSCube and CastroData. Classes for reading and manipulating bin-by-bin likelihoods are now moved to the `castro` module.
- Rationalized naming conventions for energy-related variables. Properties and method arguments with units of the logarithm of the energy now consistently contain `log` in the name.
  - `energies` now returns bin energies in MeV (previously it returned logarithmic energies). `log_energies` can be used to access logarithmic bin energies.
  - Changed `erange` parameter to `log_bounds` in the methods that accept an energy range.
  - Changed the units of `emin`, `ectr`, and `emax` in the sed output dictionary to MeV.
- Add more columns to the FITS source catalog file generated by `write_roi`. All float and string values in the source dictionary are now automatically included in the FITS file. Parameter values, errors, and names are written to the `param_values`, `param_errors`, and `param_names` vector columns.
- Add package script for dispatching batch jobs to LSF (`fermipy-dispatch`).
- Fixed some bugs related to handling of unicode strings.

### 0.8.0 (05/18/2016)

- Added new variables to source dictionary:
  - Likelihood scan of source normalization (`dloglike_scan`, `eflux_scan`, `flux_scan`).
  - Source localization errors (`pos_sigma`, `pos_sigma_semimajor`, `pos_sigma_semiminor`, `pos_r68`, `pos_r95`, `pos_r99`, `pos_angle`). These are automatically filled when running `localize` or `find_sources`.
- Removed camel-case in some source variable names.
- Add `cacheft1` option to `data` disable caching FT1 files. Cacheing is still enabled by default.
- Support FITS file format for preliminary releases of the 4FGL catalog.
- Add `__future__` statements throughout to ensure forward-compatibility with python3.



- Reorganize utility modules including those for manipulation of WCS and healpix images.
- Various improvements and refactoring in `localize`. This method now moved to the `sourcefind` module.
- Add new global parameter `llscan_pts` in `gtlike` to define the number of likelihood evaluation points.
- Write output of `sed` to a FITS file in the Likelihood SED format. More information about the Likelihood SED format is available on this [page](#).
- Write ROI model to a FITS file when calling `write_roi`. This file contains a BINTABLE with one row per source and uses the same column names as the 3FGL catalog file to describe spectral parameterizations. Note that this file currently only contains a subset of the information available in the numpy output file.
- Reorganize classes and methods in `sed` for manipulating and fitting bin-by-bin likelihoods. Spectral functions moved to a dedicated `spectrum` module.
- Write return dictionary to a numpy file in `residmap` and `tmap`.



## CHAPTER 2

---

Indices and tables

---



### f

- [fermipy](#), 113
- [fermipy.castro](#), 100
- [fermipy.config](#), 59
- [fermipy.defaults](#), 60
- [fermipy.diffuse](#), 162
  - [fermipy.diffuse.binning](#), 162
  - [fermipy.diffuse.defaults](#), 163
  - [fermipy.diffuse.name\\_policy](#), 163
  - [fermipy.diffuse.source\\_factory](#), 166
  - [fermipy.diffuse.spectral](#), 166
  - [fermipy.diffuse.timefilter](#), 166
  - [fermipy.diffuse.utils](#), 168
- [fermipy.jobs](#), 126
  - [fermipy.jobs.batch](#), 146
  - [fermipy.jobs.file\\_archive](#), 146
  - [fermipy.jobs.gtlink](#), 130
  - [fermipy.jobs.job\\_archive](#), 151
  - [fermipy.jobs.native\\_impl](#), 144
  - [fermipy.jobs.slac\\_impl](#), 145
  - [fermipy.jobs.sys\\_interface](#), 143
- [fermipy.lightcurve](#), 112
- [fermipy.logger](#), 75
- [fermipy.plotting](#), 90
- [fermipy.residmap](#), 111
- [fermipy.roi\\_model](#), 75
- [fermipy.sed](#), 92
- [fermipy.skymap](#), 96
- [fermipy.sourcefind](#), 92
- [fermipy.spectrum](#), 93
- [fermipy.tsmmap](#), 109
- [fermipy.utils](#), 82



## A

- `add_component_info()` (fermipy.diffuse.model\_component.ModelComponentInfo method), 168, 170
- `add_gauss_prior()` (fermipy.gtanalysis.GTAnalysis method), 60
- `add_name()` (fermipy.roi\_model.Model method), 76
- `add_option()` (fermipy.config.ConfigSchema method), 59
- `add_section()` (fermipy.config.ConfigSchema method), 59
- `add_source()` (fermipy.gtanalysis.GTAnalysis method), 60
- `add_sources()` (fermipy.diffuse.source\_factory.SourceFactory method), 167
- `add_sources_from_roi()` (fermipy.gtanalysis.GTAnalysis method), 60
- `add_to_table()` (fermipy.roi\_model.Model method), 76
- `AnalysisPlotter` (class in fermipy.plotting), 90
- `AnalyzeROI` (class in fermipy.jobs.target\_analysis), 136
- `AnalyzeROI_SG` (class in fermipy.jobs.target\_analysis), 139
- `AnalyzeSED` (class in fermipy.jobs.target\_analysis), 136
- `AnalyzeSED_SG` (class in fermipy.jobs.target\_analysis), 140
- `angle_to_cartesian()` (in module fermipy.utils), 82
- `angprofile()` (fermipy.diffuse.name\_policy.NameFactory method), 163
- `angprofile_format` (fermipy.diffuse.name\_policy.NameFactory attribute), 163
- `ann_channel_names` (fermipy.spectrum.DMFitFunction attribute), 93
- `annotate()` (in module fermipy.plotting), 91
- `annotate_name()` (in module fermipy.plotting), 91
- `append_hdus()` (fermipy.diffuse.gt\_assemble\_model.AssembleModel static method), 183
- `append_to_table()` (fermipy.jobs.file\_archive.FileHandle method), 149
- `append_to_tables()` (fermipy.jobs.job\_archive.JobDetails method), 152
- `AppLink` (class in fermipy.jobs.app\_link), 131
- `apply_minmax_selection()` (in module fermipy.utils), 82
- `appname` (fermipy.diffuse.diffuse\_analysis.CatalogCompChain attribute), 199
- `appname` (fermipy.diffuse.diffuse\_analysis.DiffuseAnalysisChain attribute), 199
- `appname` (fermipy.diffuse.diffuse\_analysis.DiffuseCompChain attribute), 198
- `appname` (fermipy.diffuse.gt\_assemble\_model.AssembleModel attribute), 184
- `appname` (fermipy.diffuse.gt\_assemble\_model.AssembleModel\_SG attribute), 192
- `appname` (fermipy.diffuse.gt\_assemble\_model.AssembleModelChain attribute), 199
- `appname` (fermipy.diffuse.gt\_assemble\_model.InitModel attribute), 183
- `appname` (fermipy.diffuse.gt\_coadd\_split.CoaddSplit attribute), 195
- `appname` (fermipy.diffuse.gt\_coadd\_split.CoaddSplit\_SG attribute), 187
- `appname` (fermipy.diffuse.gt\_merge\_srcmaps.GtMergeSrcmaps attribute), 181
- `appname` (fermipy.diffuse.gt\_merge\_srcmaps.MergeSrcmaps\_SG attribute), 191
- `appname` (fermipy.diffuse.gt\_split\_and\_bin.SplitAndBin attribute), 195
- `appname` (fermipy.diffuse.gt\_split\_and\_bin.SplitAndBin\_SG attribute), 193

[appname \(fermipy.diffuse.gt\\_split\\_and\\_bin.SplitAndBinChain attribute\), 196](#)  
[appname \(fermipy.diffuse.gt\\_split\\_and\\_mktime.SplitAndMktime attribute\), 197](#)  
[appname \(fermipy.diffuse.gt\\_split\\_and\\_mktime.SplitAndMktime\\_SG attribute\), 194](#)  
[appname \(fermipy.diffuse.gt\\_split\\_and\\_mktime.SplitAndMktimeChain attribute\), 197](#)  
[appname \(fermipy.diffuse.gt\\_srcmap\\_partial.GtSrcmapsDiffuse attribute\), 182](#)  
[appname \(fermipy.diffuse.gt\\_srcmap\\_partial.SrcmapsDiffuse\\_SG attribute\), 191](#)  
[appname \(fermipy.diffuse.gt\\_srcmaps\\_catalog.GtSrcmapsCatalog attribute\), 183](#)  
[appname \(fermipy.diffuse.gt\\_srcmaps\\_catalog.SrcmapsCatalog\\_SG attribute\), 192](#)  
[appname \(fermipy.diffuse.job\\_library.GatherSrcmaps\\_SG attribute\), 188](#)  
[appname \(fermipy.diffuse.job\\_library.Gtexpcube2\\_SG attribute\), 185](#)  
[appname \(fermipy.diffuse.job\\_library.Gtlink\\_bin attribute\), 177](#)  
[appname \(fermipy.diffuse.job\\_library.Gtlink\\_expcube2 attribute\), 177](#)  
[appname \(fermipy.diffuse.job\\_library.Gtlink\\_ltcube attribute\), 178](#)  
[appname \(fermipy.diffuse.job\\_library.Gtlink\\_ltsun attribute\), 178](#)  
[appname \(fermipy.diffuse.job\\_library.Gtlink\\_mktime attribute\), 178](#)  
[appname \(fermipy.diffuse.job\\_library.Gtlink\\_scrmaps attribute\), 177](#)  
[appname \(fermipy.diffuse.job\\_library.Gtlink\\_select attribute\), 176](#)  
[appname \(fermipy.diffuse.job\\_library.Gtltsum\\_SG attribute\), 185](#)  
[appname \(fermipy.diffuse.job\\_library.Healview\\_SG attribute\), 189](#)  
[appname \(fermipy.diffuse.job\\_library.Link\\_FermipyCoadd attribute\), 180](#)  
[appname \(fermipy.diffuse.job\\_library.Link\\_FermipyGatherSrcmaps attribute\), 180](#)  
[appname \(fermipy.diffuse.job\\_library.Link\\_FermipyHealview attribute\), 181](#)  
[appname \(fermipy.diffuse.job\\_library.Link\\_FermipyVstack attribute\), 181](#)  
[appname \(fermipy.diffuse.job\\_library.SumRings\\_SG attribute\), 189](#)  
[appname \(fermipy.diffuse.job\\_library.Vstack\\_SG attribute\), 188](#)  
[appname \(fermipy.diffuse.residual\\_cr.ResidualCR attribute\), 184](#)  
[appname \(fermipy.diffuse.residual\\_cr.ResidualCR\\_SG attribute\), 190, 193](#)  
[appname \(fermipy.diffuse.residual\\_cr.ResidualCRChain attribute\), 200](#)  
[appname \(fermipy.diffuse.solar.Gtexpcube2wcs\\_SG attribute\), 186](#)  
[appname \(fermipy.diffuse.solar.Gtexphpsun\\_SG attribute\), 186](#)  
[appname \(fermipy.diffuse.solar.Gtlink\\_expcube2\\_wcs attribute\), 179](#)  
[appname \(fermipy.diffuse.solar.Gtlink\\_exphpsun attribute\), 179](#)  
[appname \(fermipy.diffuse.solar.Gtlink\\_sunttemp attribute\), 180](#)  
[appname \(fermipy.diffuse.solar.Gtsunttemp\\_SG attribute\), 187](#)  
[appname \(fermipy.diffuse.solar.SunMoonChain attribute\), 200](#)  
[appname \(fermipy.jobs.app\\_link.AppLink attribute\), 132](#)  
[appname \(fermipy.jobs.gtlink.Gtlink attribute\), 130](#)  
[appname \(fermipy.jobs.link.Link attribute\), 127](#)  
[appname \(fermipy.jobs.scatter\\_gather.ScatterGather attribute\), 132](#)  
[appname \(fermipy.jobs.target\\_analysis.AnalyzeROI attribute\), 136](#)  
[appname \(fermipy.jobs.target\\_analysis.AnalyzeROI\\_SG attribute\), 140](#)  
[appname \(fermipy.jobs.target\\_analysis.AnalyzeSED attribute\), 136](#)  
[appname \(fermipy.jobs.target\\_analysis.AnalyzeSED\\_SG attribute\), 140](#)  
[appname \(fermipy.jobs.target\\_collect.CollectSED attribute\), 137](#)  
[appname \(fermipy.jobs.target\\_collect.CollectSED\\_SG attribute\), 141](#)  
[appname \(fermipy.jobs.target\\_plotting.PlotCastro attribute\), 139](#)  
[appname \(fermipy.jobs.target\\_plotting.PlotCastro\\_SG attribute\), 143](#)  
[appname \(fermipy.jobs.target\\_sim.CopyBaseROI attribute\), 137](#)  
[appname \(fermipy.jobs.target\\_sim.CopyBaseROI\\_SG attribute\), 141](#)  
[appname \(fermipy.jobs.target\\_sim.RandomDirGen attribute\), 138](#)  
[appname \(fermipy.jobs.target\\_sim.RandomDirGen\\_SG attribute\), 142](#)  
[appname \(fermipy.jobs.target\\_sim.SimulateROI attribute\), 139](#)  
[appname \(fermipy.jobs.target\\_sim.SimulateROI\\_SG attribute\), 142](#)  
[arg\\_names \(fermipy.jobs.link.Link attribute\), 127](#)  
[arg\\_to\\_list\(\) \(in module fermipy.utils\), 82](#)  
[assemble\\_component\(\) \(fermipy.diffuse.gt\\_assemble\\_model.AssembleModel static method\), 184](#)



AssembleModel	(class in <i>fer-</i>	162
<i>mipy.diffuse.gt_assemble_model</i> ), 183		
AssembleModel_SG	(class in <i>fer-</i>	<i>mipy.diffuse.timefilter.MktimeFilterDict</i> static
<i>mipy.diffuse.gt_assemble_model</i> ), 192		method), 166
AssembleModelChain	(class in <i>fer-</i>	<i>build_from_yamlstr()</i> ( <i>fer-</i>
<i>mipy.diffuse.gt_assemble_model</i> ), 199		<i>mipy.diffuse.binning.Component</i> class method),
assoc ( <i>fermipy.roi_model.Model</i> attribute), 76		162
associations ( <i>fermipy.roi_model.Source</i> attribute), 80		<i>build_gtapp()</i> (in module <i>fermipy.jobs.gtlink</i> ), 131
		<i>build_job_configs()</i> ( <i>fer-</i>
		<i>mipy.diffuse.gt_assemble_model.AssembleModel_SG</i>
		method), 192
<b>B</b>		
base_path ( <i>fermipy.jobs.file_archive.FileArchive</i> at-		<i>build_job_configs()</i> ( <i>fer-</i>
tribute), 146		<i>mipy.diffuse.gt_coadd_split.CoaddSplit_SG</i>
bexpcube() ( <i>fermipy.diffuse.name_policy.NameFactory</i>		method), 187
method), 163		
bexpcube_format	( <i>fer-</i>	<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.diffuse.name_policy.NameFactory</i> at-		<i>mipy.diffuse.gt_merge_srcmaps.MergeSrcmaps_SG</i>
tribute), 163		method), 191
bexpcube_moon()	( <i>fer-</i>	<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.diffuse.name_policy.NameFactory</i>		<i>mipy.diffuse.gt_split_and_bin.SplitAndBin_SG</i>
method), 163		method), 193
bexpcube_sun()	( <i>fer-</i>	<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.diffuse.name_policy.NameFactory</i>		<i>mipy.diffuse.gt_split_and_mktime.SplitAndMktime_SG</i>
method), 163		method), 194
bexpcubemoon_format	( <i>fer-</i>	<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.diffuse.name_policy.NameFactory</i> at-		<i>mipy.diffuse.gt_srcmap_partial.SrcmapsDiffuse_SG</i>
tribute), 163		method), 191
bexpcubesun_format	( <i>fer-</i>	<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.diffuse.name_policy.NameFactory</i> at-		<i>mipy.diffuse.gt_srcmaps_catalog.SrcmapsCatalog_SG</i>
tribute), 163		method), 192
bin_widths ( <i>fermipy.castro.ReferenceSpec</i> attribute), 106		<i>build_job_configs()</i> ( <i>fer-</i>
		<i>mipy.diffuse.job_library.GatherSrcmaps_SG</i>
		method), 188
bowtie() ( <i>fermipy.gtanalysis.GTAnalysis</i> method), 61		<i>build_job_configs()</i> ( <i>fer-</i>
<i>build_archive()</i> ( <i>fer-</i>		<i>mipy.diffuse.job_library.Gtexpcube2_SG</i>
<i>mipy.jobs.file_archive.FileArchive</i> class		method), 185
method), 146		
<i>build_archive()</i> ( <i>fer-</i>		<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.jobs.job_archive.JobArchive</i> class		<i>mipy.diffuse.job_library.Gtiltsum_SG</i> method),
method), 151		185
<i>build_bsub_command()</i> (in module <i>fer-</i>		<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.jobs.slac_impl</i> ), 145		<i>mipy.diffuse.job_library.Healview_SG</i> method),
		189
<i>build_catalog()</i> ( <i>fer-</i>		<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.diffuse.source_factory.SourceFactory</i>		<i>mipy.diffuse.job_library.SumRings_SG</i>
static method), 167		method), 189, 190
<i>build_catalog_info()</i> ( <i>fer-</i>		<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.diffuse.catalog_src_manager.CatalogSourceManager</i>		<i>mipy.diffuse.job_library.Vstack_SG</i> method),
method), 174		188
<i>build_ebound_table()</i> ( <i>fer-</i>		<i>build_job_configs()</i> ( <i>fer-</i>
<i>mipy.castro.ReferenceSpec</i> method), 106		<i>mipy.diffuse.residual_cr.ResidualCR_SG</i>
<i>build_from_energy_dict()</i> ( <i>fer-</i>		method), 190, 193
<i>mipy.diffuse.binning.Component</i> class method),		<i>build_job_configs()</i> ( <i>fer-</i>
162		<i>mipy.diffuse.solar.Gtexpcube2wcs_SG</i> method),
<i>build_from_yamlfile()</i> ( <i>fer-</i>		186
<i>mipy.diffuse.binning.Component</i> class method),		<i>build_job_configs()</i> ( <i>fer-</i>

*mipy.diffuse.solar.Gtexphsun\_SG* method), 186  
*build\_job\_configs()* (*fermipy.diffuse.solar.Gtsuntemp\_SG* method), 187  
*build\_job\_configs()* (*fermipy.jobs.scatter\_gather.ScatterGather* method), 132  
*build\_job\_configs()* (*fermipy.jobs.target\_analysis.AnalyzeROI\_SG* method), 140  
*build\_job\_configs()* (*fermipy.jobs.target\_analysis.AnalyzeSED\_SG* method), 140  
*build\_job\_configs()* (*fermipy.jobs.target\_collect.CollectSED\_SG* method), 141  
*build\_job\_configs()* (*fermipy.jobs.target\_plotting.PlotCastro\_SG* method), 143  
*build\_job\_configs()* (*fermipy.jobs.target\_sim.CopyBaseROI\_SG* method), 141  
*build\_job\_configs()* (*fermipy.jobs.target\_sim.RandomDirGen\_SG* method), 142  
*build\_job\_configs()* (*fermipy.jobs.target\_sim.SimulateROI\_SG* method), 142  
*build\_lnl\_fn()* (*fermipy.castro.CastroData\_Base* method), 103  
*build\_scandata\_table()* (*fermipy.castro.CastroData\_Base* method), 103  
*build\_source\_dict()* (in module *fermipy.castro*), 109  
*build\_spec\_table()* (*fermipy.castro.SpecData* method), 107  
*build\_temp\_job\_archive()* (*fermipy.jobs.job\_archive.JobArchive* class method), 151

**C**  
*cache* (*fermipy.jobs.file\_archive.FileArchive* attribute), 146  
*cache* (*fermipy.jobs.job\_archive.JobArchive* attribute), 151  
*calcTS\_var()* (in module *fermipy.lightcurve*), 112  
*cash()* (in module *fermipy.tsmmap*), 110  
*cast\_args()* (in module *fermipy.spectrum*), 96  
*cast\_config()* (in module *fermipy.config*), 59  
*cast\_params()* (in module *fermipy.spectrum*), 96  
*CastroData* (class in *fermipy.castro*), 100  
*CastroData\_Base* (class in *fermipy.castro*), 102  
*castroData\_from\_ipix()* (*fermipy.castro.TSCube* method), 108  
*castroData\_from\_pix\_xy()* (*fermipy.castro.TSCube* method), 108  
*catalog\_comp\_info\_dict()* (*fermipy.diffuse.catalog\_src\_manager.CatalogSourceManager* method), 174  
*catalog\_components()* (*fermipy.diffuse.catalog\_src\_manager.CatalogSourceManager* method), 174  
*catalog\_split\_yaml()* (*fermipy.diffuse.name\_policy.NameFactory* method), 163  
*catalog\_split\_yaml\_format* (*fermipy.diffuse.name\_policy.NameFactory* attribute), 163  
*CatalogCompChain* (class in *fermipy.diffuse.diffuse\_analysis*), 198  
*CatalogInfo* (class in *fermipy.diffuse.model\_component*), 169  
*catalogs()* (*fermipy.diffuse.catalog\_src\_manager.CatalogSourceManager* method), 174  
*CatalogSourceManager* (class in *fermipy.diffuse.catalog\_src\_manager*), 174  
*CatalogSourcesInfo* (class in *fermipy.diffuse.model\_component*), 171  
*ccube()* (*fermipy.diffuse.name\_policy.NameFactory* method), 163  
*ccube\_format* (*fermipy.diffuse.name\_policy.NameFactory* attribute), 163  
*center\_to\_edge()* (in module *fermipy.utils*), 82  
*Chain* (class in *fermipy.jobs.chain*), 134  
*chain\_input\_files* (*fermipy.jobs.file\_archive.FileDict* attribute), 148  
*chain\_output\_files* (*fermipy.jobs.file\_archive.FileDict* attribute), 148  
*chan* (*fermipy.spectrum.DMFitFunction* attribute), 93  
*chan\_code* (*fermipy.spectrum.DMFitFunction* attribute), 93  
*channel\_index\_mapping* (*fermipy.spectrum.DMFitFunction* attribute), 93  
*channel\_name\_mapping* (*fermipy.spectrum.DMFitFunction* attribute), 93  
*channel\_rev\_map* (*fermipy.spectrum.DMFitFunction* attribute), 93  
*channel\_shortcode\_mapping* (*fermipy.spectrum.DMFitFunction* attribute), 94  
*channels()* (*fermipy.spectrum.DMFitFunction* static method), 94

`check_cuts()` (*fermipy.roi\_model.Model* method), 76  
`check_input_files()` (*fermipy.jobs.link.Link* method), 127  
`check_job()` (*fermipy.jobs.sys\_interface.SysInterface* class method), 143  
`check_job_status()` (*fermipy.jobs.link.Link* method), 127  
`check_jobs_status()` (*fermipy.jobs.link.Link* method), 127  
`check_links_status()` (*fermipy.jobs.chain.Chain* method), 134  
`check_log()` (in module *fermipy.jobs.sys\_interface*), 144  
`check_output_files()` (*fermipy.jobs.link.Link* method), 127  
`check_status()` (*fermipy.jobs.file\_archive.FileHandle* method), 150  
`check_status()` (*fermipy.jobs.scatter\_gather.ScatterGather* method), 132  
`check_status_logfile()` (*fermipy.jobs.job\_archive.JobDetails* method), 152  
`chi2_vals()` (*fermipy.castro.CastroData\_Base* method), 103  
`clean_job()` (in module *fermipy.jobs.sys\_interface*), 144  
`clean_jobs()` (*fermipy.jobs.link.Link* method), 128  
`clean_jobs()` (*fermipy.jobs.scatter\_gather.ScatterGather* method), 132  
`clean_jobs()` (*fermipy.jobs.sys\_interface.SysInterface* method), 143  
`cleanup()` (*fermipy.gtanalysis.GTAnalysis* method), 61  
`clear()` (*fermipy.roi\_model.ROIModel* method), 77  
`clear_jobs()` (*fermipy.jobs.chain.Chain* method), 135  
`clear_jobs()` (*fermipy.jobs.link.Link* method), 128  
`clear_jobs()` (*fermipy.jobs.scatter\_gather.ScatterGather* method), 132  
`clientclass` (*fermipy.diffuse.gt\_assemble\_model.AssembleModel\_SG* attribute), 192  
`clientclass` (*fermipy.diffuse.gt\_coadd\_split.CoaddSplit\_SG* attribute), 187  
`clientclass` (*fermipy.diffuse.gt\_merge\_srcmaps.MergeSrcmaps\_SG* attribute), 191  
`clientclass` (*fermipy.diffuse.gt\_split\_and\_bin.SplitAndBin\_SG* attribute), 193  
`clientclass` (*fermipy.diffuse.gt\_split\_and\_mktime.SplitAndMktime\_SG* attribute), 194  
`clientclass` (*fermipy.diffuse.gt\_srcmap\_partial.SrcmapsDiffuse\_SG* attribute), 191  
`clientclass` (*fermipy.diffuse.gt\_srcmaps\_catalog.SrcmapsCatalog\_SG* attribute), 192  
`clientclass` (*fermipy.diffuse.job\_library.GatherSrcmaps\_SG* attribute), 188  
`clientclass` (*fermipy.diffuse.job\_library.Gtexpcube2\_SG* attribute), 185  
`clientclass` (*fermipy.diffuse.job\_library.Gtltsun\_SG* attribute), 185  
`clientclass` (*fermipy.diffuse.job\_library.Healview\_SG* attribute), 189  
`clientclass` (*fermipy.diffuse.job\_library.SumRings\_SG* attribute), 189, 190  
`clientclass` (*fermipy.diffuse.job\_library.Vstack\_SG* attribute), 188  
`clientclass` (*fermipy.diffuse.residual\_cr.ResidualCR\_SG* attribute), 190, 193  
`clientclass` (*fermipy.diffuse.solar.Gtexpcube2wcs\_SG* attribute), 186  
`clientclass` (*fermipy.diffuse.solar.Gtexphpsun\_SG* attribute), 186  
`clientclass` (*fermipy.diffuse.solar.Gtsuntemp\_SG* attribute), 187  
`clientclass` (*fermipy.jobs.scatter\_gather.ScatterGather* attribute), 133  
`clientclass` (*fermipy.jobs.target\_analysis.AnalyzeROI\_SG* attribute), 140  
`clientclass` (*fermipy.jobs.target\_analysis.AnalyzeSED\_SG* attribute), 140  
`clientclass` (*fermipy.jobs.target\_collect.CollectSED\_SG* attribute), 141  
`clientclass` (*fermipy.jobs.target\_plotting.PlotCastro\_SG* attribute), 143  
`clientclass` (*fermipy.jobs.target\_sim.CopyBaseROI\_SG* attribute), 141  
`clientclass` (*fermipy.jobs.target\_sim.RandomDirGen\_SG* attribute), 142  
`clientclass` (*fermipy.jobs.target\_sim.SimulateROI\_SG* attribute), 142  
`clone()` (*fermipy.gtanalysis.GTAnalysis* method), 61  
`clone_and_merge_sub()` (*fermipy.diffuse.model\_component.ModelComponentInfo* method), 168, 170  
`fermipy.logger.StreamLogger` method), 75  
`coadd_maps()` (in module *fermipy.skymap*), 100  
`CoaddSplit` (class in *fermipy.diffuse.gt\_coadd\_split*), 194  
`CoaddSplit_SG` (class in *fermipy.diffuse.gt\_coadd\_split*), 187  
`CollectDirs` (in module *fermipy.utils*), 82  
`CollectSED` (class in *fermipy.jobs.target\_collect*), 137  
`CollectSED_SG` (class in *fermipy.jobs.target\_collect*), 140  
`CollectSED` (class in *fermipy.jobs.target\_collect*), 137  
`compile()` (*fermipy.jobs.gmlink.Gmlink*

*method*), 130  
`command_template()` (*fermipy.jobs.link.Link*  
*method*), 128  
`comp_srcmdl_xml()` (*fer-*  
*mipy.diffuse.name\_policy.NameFactory*  
*method*), 163  
`comp_srcmdl_xml_format` (*fer-*  
*mipy.diffuse.name\_policy.NameFactory* *at-*  
*tribute*), 163  
`Component` (*class in fermipy.diffuse.binning*), 162  
`component()` (*fermipy.diffuse.name\_policy.NameFactory*  
*method*), 163  
`component_format` (*fer-*  
*mipy.diffuse.name\_policy.NameFactory* *at-*  
*tribute*), 163  
`component_names` (*fer-*  
*mipy.diffuse.model\_manager.ModelInfo* *at-*  
*tribute*), 175  
`components` (*fermipy.gtanalysis.GTAnalysis* *attribute*),  
61  
`CompositeSource` (*class in fermipy.roi\_model*), 75  
`CompositeSourceInfo` (*class in fer-*  
*mipy.diffuse.model\_component*), 171  
`compute_drm()` (*fermipy.gtanalysis.GTAnalysis*  
*method*), 61  
`compute_psf()` (*fermipy.gtanalysis.GTAnalysis*  
*method*), 61  
`compute_srcprob()` (*fermipy.gtanalysis.GTAnalysis*  
*method*), 61  
`config` (*fermipy.config.Configurable* *attribute*), 59  
`config` (*fermipy.gtanalysis.GTAnalysis* *attribute*), 61  
`configdir` (*fermipy.config.Configurable* *attribute*), 59  
`configdir` (*fermipy.gtanalysis.GTAnalysis* *attribute*),  
61  
`ConfigManager` (*class in fermipy.config*), 59  
`ConfigSchema` (*class in fermipy.config*), 59  
`Configurable` (*class in fermipy.config*), 59  
`configure()` (*fermipy.config.Configurable* *method*),  
59  
`configure()` (*fermipy.gtanalysis.GTAnalysis*  
*method*), 61  
`configure()` (*fermipy.logger.Logger* *static method*),  
75  
`constrain_norms()` (*fermipy.gtanalysis.GTAnalysis*  
*method*), 61  
`construct_docstring()` (*fermipy.jobs.link.Link*  
*static method*), 128  
`construct_scratch_path()` (*fer-*  
*mipy.jobs.file\_archive.FileStageManager*  
*method*), 150  
`convert_sed_cols()` (*in module fermipy.castro*),  
109  
`convert_to_cached_wcs()` (*fer-*  
*mipy.skymap.HpxMap* *method*), 97  
`convert_tscube()` (*in module fermipy.tsmmap*), 110  
`convert_tscube_old()` (*in module fermipy.tsmmap*),  
110  
`convolve2d_disk()` (*in module fermipy.utils*), 82  
`convolve2d_gauss()` (*in module fermipy.utils*), 82  
`convolve_map()` (*in module fermipy.residmap*), 111  
`convolve_map_hpx()` (*in module fermipy.residmap*),  
111  
`convolve_map_hpx_gauss()` (*in module fer-*  
*mipy.residmap*), 112  
`copy_analysis_files()` (*fer-*  
*mipy.jobs.target\_sim.CopyBaseROI* *class*  
*method*), 137  
`copy_ccube()` (*fermipy.diffuse.gt\_assemble\_model.AssembleModel*  
*static method*), 184  
`copy_from_scratch()` (*fer-*  
*mipy.jobs.file\_archive.FileStageManager*  
*static method*), 150  
`copy_selected_sources()` (*fer-*  
*mipy.diffuse.source\_factory.SourceFactory*  
*class method*), 167  
`copy_source()` (*fermipy.roi\_model.ROIModel*  
*method*), 77  
`copy_target_dir()` (*fer-*  
*mipy.jobs.target\_sim.CopyBaseROI* *class*  
*method*), 138  
`copy_to_scratch()` (*fer-*  
*mipy.jobs.file\_archive.FileStageManager*  
*static method*), 150  
`CopyBaseROI` (*class in fermipy.jobs.target\_sim*), 137  
`CopyBaseROI_SG` (*class in fermipy.jobs.target\_sim*),  
141  
`copyfiles` (*fermipy.jobs.target\_sim.CopyBaseROI* *at-*  
*tribute*), 138  
`counts` (*fermipy.skymap.Map\_Base* *attribute*), 99  
`counts_map()` (*fermipy.gtanalysis.GTAnalysis*  
*method*), 61  
`cov_to_correlation()` (*in module fermipy.utils*),  
83  
`create()` (*fermipy.config.ConfigManager* *class*  
*method*), 59  
`create()` (*fermipy.gtanalysis.GTAnalysis* *class*  
*method*), 61  
`create()` (*fermipy.jobs.link.Link* *class method*), 128  
`create()` (*fermipy.jobs.scatter\_gather.ScatterGather*  
*class method*), 133  
`create()` (*fermipy.roi\_model.ROIModel* *class*  
*method*), 77  
`create()` (*fermipy.skymap.Map* *class method*), 98  
`create_config()` (*fermipy.config.ConfigSchema*  
*method*), 59  
`create_default_config()` (*in module fer-*  
*mipy.config*), 59  
`create_dict()` (*in module fermipy.utils*), 83



`create_diffuse_srcs()` (*fermipy.roi\_model.ROIModel* method), 77  
`create_eflux_funcor()` (*fermipy.spectrum.SpectralFunction* class method), 95  
`create_flux_funcor()` (*fermipy.spectrum.SpectralFunction* class method), 95  
`create_from_dict()` (*fermipy.roi\_model.Model* static method), 76  
`create_from_dict()` (*fermipy.roi\_model.Source* class method), 80  
`create_from_eflux()` (*fermipy.spectrum.SpectralFunction* class method), 95  
`create_from_fits()` (*fermipy.castro.CastroData* class method), 100  
`create_from_fits()` (*fermipy.castro.TSCube* class method), 108  
`create_from_fits()` (*fermipy.plotting.ROIPlotter* class method), 90  
`create_from_fits()` (*fermipy.skymap.HpxMap* class method), 97  
`create_from_fits()` (*fermipy.skymap.Map* class method), 98  
`create_from_flux()` (*fermipy.spectrum.SpectralFunction* class method), 95  
`create_from_flux_points()` (*fermipy.castro.CastroData* class method), 101  
`create_from_hdu()` (*fermipy.skymap.HpxMap* class method), 97  
`create_from_hdu()` (*fermipy.skymap.Map* class method), 98  
`create_from_hdulist()` (*fermipy.skymap.HpxMap* class method), 97  
`create_from_position()` (*fermipy.roi\_model.ROIModel* class method), 78  
`create_from_roi_data()` (*fermipy.roi\_model.ROIModel* class method), 78  
`create_from_row()` (*fermipy.jobs.file\_archive.FileHandle* class method), 150  
`create_from_row()` (*fermipy.jobs.job\_archive.JobDetails* class method), 153  
`create_from_sedfile()` (*fermipy.castro.CastroData* class method), 101  
`create_from_source()` (*fermipy.roi\_model.ROIModel* class method), 78  
`create_from_stack()` (*fermipy.castro.CastroData* class method), 101  
`create_from_table()` (*fermipy.castro.ReferenceSpec* class method), 106  
`create_from_table()` (*fermipy.castro.SpecData* class method), 107  
`create_from_tables()` (*fermipy.castro.CastroData* class method), 101  
`create_from_xml()` (*fermipy.roi\_model.Source* static method), 80  
`create_from_xmlfile()` (*fermipy.roi\_model.Source* class method), 81  
`create_from_yaml()` (*fermipy.diffuse.spectral.SpectralLibrary* class method), 166  
`create_from_yamlfile()` (*fermipy.castro.CastroData* class method), 102  
`create_from_yamlstr()` (*fermipy.diffuse.spectral.SpectralLibrary* class method), 166  
`create_funcor()` (*fermipy.castro.CastroData* method), 102  
`create_funcor()` (*fermipy.castro.ReferenceSpec* method), 106  
`create_funcor()` (*fermipy.spectrum.SpectralFunction* class method), 96  
`create_hpx_disk_region_string()` (in module *fermipy.utils*), 83  
`create_image_hdu()` (*fermipy.skymap.HpxMap* method), 97  
`create_image_hdu()` (*fermipy.skymap.Map* method), 98  
`create_inputlist()` (in module *fermipy.diffuse.utils*), 168  
`create_kernel_function_lookup()` (in module *fermipy.utils*), 83  
`create_model_name()` (in module *fermipy.utils*), 83  
`create_param_table()` (*fermipy.roi\_model.ROIModel* method), 78  
`create_primary_hdu()` (*fermipy.skymap.Map* method), 98  
`create_radial_spline()` (in module *fermipy.utils*), 83  
`create_roi_from_ft1()` (*fermipy.roi\_model.ROIModel* class method), 78  
`create_roi_table()` (*fermipy.gtanalysis.GTAnalysis* method), 62  
`create_source()` (*fermipy.roi\_model.ROIModel* method), 78  
`create_source_name()` (in module *fermipy.utils*), 83  
`create_source_table()` (*fer-*

*mipy.roi\_model.ROIModel* method), 78  
*create\_source\_table()* (in module *fer-*  
*mipy.roi\_model*), 81  
*create\_table()* (*fermipy.roi\_model.ROIModel*  
method), 78  
*create\_xml\_element()* (in module *fermipy.utils*),  
83  
*csm* (*fermipy.diffuse.model\_manager.ModelManager* at-  
tribute), 175  
*curvature()* (*fermipy.gtanalysis.GTAnalysis*  
method), 62

## D

*data* (*fermipy.plotting.ROIPlotter* attribute), 90  
*data* (*fermipy.roi\_model.Model* attribute), 76  
*data* (*fermipy.roi\_model.Source* attribute), 81  
*data* (*fermipy.skymap.Map\_Base* attribute), 99  
*dataset()* (*fermipy.diffuse.name\_policy.NameFactory*  
method), 163  
*dataset\_format* (*fer-*  
*mipy.diffuse.name\_policy.NameFactory* at-  
tribute), 164  
*decay* (*fermipy.spectrum.DMFitFunction* attribute), 94  
*decay\_channel\_names* (*fer-*  
*mipy.spectrum.DMFitFunction* attribute),  
94  
*default\_file\_args* (*fer-*  
*mipy.diffuse.gt\_merge\_srcmaps.GtMergeSrcmaps*  
attribute), 181  
*default\_file\_args* (*fer-*  
*mipy.diffuse.gt\_srcmap\_partial.GtSrcmapsDiffuse*  
attribute), 182  
*default\_file\_args* (*fer-*  
*mipy.diffuse.gt\_srcmaps\_catalog.GtSrcmapsCatalog*  
attribute), 183  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Gtlink\_bin* attribute),  
177  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Gtlink\_expcube2*  
attribute), 177  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Gtlink\_ltcube*  
attribute), 178  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Gtlink\_ltsun*  
attribute), 178  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Gtlink\_mktime*  
attribute), 178  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Gtlink\_scrmaps*  
attribute), 177

*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Gtlink\_select* at-  
tribute), 177  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Link\_FermipyCoadd*  
attribute), 180  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Link\_FermipyGatherSrcmaps*  
attribute), 180  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Link\_FermipyHealview*  
attribute), 181  
*default\_file\_args* (*fer-*  
*mipy.diffuse.job\_library.Link\_FermipyVstack*  
attribute), 181  
*default\_file\_args* (*fer-*  
*mipy.diffuse.residual\_cr.ResidualCR* attribute),  
185  
*default\_file\_args* (*fer-*  
*mipy.diffuse.solar.Gtlink\_expcube2\_wcs* at-  
tribute), 179  
*default\_file\_args* (*fer-*  
*mipy.diffuse.solar.Gtlink\_exphpsun* attribute),  
179  
*default\_file\_args* (*fer-*  
*mipy.diffuse.solar.Gtlink\_suntemp* attribute),  
180  
*default\_file\_args* (*fermipy.jobs.link.Link* at-  
tribute), 128  
*default\_options* (*fer-*  
*mipy.diffuse.diffuse\_analysis.CatalogCompChain*  
attribute), 199  
*default\_options* (*fer-*  
*mipy.diffuse.diffuse\_analysis.DiffuseAnalysisChain*  
attribute), 199  
*default\_options* (*fer-*  
*mipy.diffuse.diffuse\_analysis.DiffuseCompChain*  
attribute), 198  
*default\_options* (*fer-*  
*mipy.diffuse.gt\_assemble\_model.AssembleModel*  
attribute), 184  
*default\_options* (*fer-*  
*mipy.diffuse.gt\_assemble\_model.AssembleModel\_SG*  
attribute), 192  
*default\_options* (*fer-*  
*mipy.diffuse.gt\_assemble\_model.AssembleModelChain*  
attribute), 199  
*default\_options* (*fer-*  
*mipy.diffuse.gt\_assemble\_model.InitModel*  
attribute), 183  
*default\_options* (*fer-*  
*mipy.diffuse.gt\_coadd\_split.CoaddSplit* at-  
tribute), 195  
*default\_options* (*fer-*

<i>mipy.diffuse.gt_coadd_split.CoaddSplit_SG</i> attribute), 187		<i>mipy.diffuse.job_library.Gtlink_ltsum</i> attribute), 178	
default_options (fer-	<i>mipy.diffuse.gt_merge_srcmaps.GtMergeSrcmaps</i> attribute), 182	default_options (fer-	<i>mipy.diffuse.job_library.Gtlink_mktime</i> attribute), 178
default_options (fer-	<i>mipy.diffuse.gt_merge_srcmaps.MergeSrcmaps_SG</i> attribute), 191	default_options (fer-	<i>mipy.diffuse.job_library.Gtlink_scrmaps</i> attribute), 178
default_options (fer-	<i>mipy.diffuse.gt_split_and_bin.SplitAndBin</i> attribute), 195	default_options (fer-	<i>mipy.diffuse.job_library.Gtlink_select</i> attribute), 177
default_options (fer-	<i>mipy.diffuse.gt_split_and_bin.SplitAndBin_SG</i> attribute), 193	default_options (fer-	<i>mipy.diffuse.job_library.Gtltsum_SG</i> attribute), 186
default_options (fer-	<i>mipy.diffuse.gt_split_and_bin.SplitAndBinChain</i> attribute), 196	default_options (fer-	<i>mipy.diffuse.job_library.Healview_SG</i> attribute), 189
default_options (fer-	<i>mipy.diffuse.gt_split_and_mktime.SplitAndMktime</i> attribute), 197	default_options (fer-	<i>mipy.diffuse.job_library.Link_FermipyCoadd</i> attribute), 180
default_options (fer-	<i>mipy.diffuse.gt_split_and_mktime.SplitAndMktime_SG</i> attribute), 194	default_options (fer-	<i>mipy.diffuse.job_library.Link_FermipyGatherSrcmaps</i> attribute), 180
default_options (fer-	<i>mipy.diffuse.gt_split_and_mktime.SplitAndMktimeChain</i> attribute), 198	default_options (fer-	<i>mipy.diffuse.job_library.Link_FermipyHealview</i> attribute), 181
default_options (fer-	<i>mipy.diffuse.gt_srcmap_partial.GtSrcmapsDiffuse</i> attribute), 182	default_options (fer-	<i>mipy.diffuse.job_library.Link_FermipyVstack</i> attribute), 181
default_options (fer-	<i>mipy.diffuse.gt_srcmap_partial.SrcmapsDiffuse_SG</i> attribute), 191	default_options (fer-	<i>mipy.diffuse.job_library.SumRings_SG</i> attribute), 189, 190
default_options (fer-	<i>mipy.diffuse.gt_srcmaps_catalog.GtSrcmapsCatalog</i> attribute), 183	default_options (fer-	<i>mipy.diffuse.job_library.Vstack_SG</i> attribute), 188
default_options (fer-	<i>mipy.diffuse.gt_srcmaps_catalog.SrcmapsCatalog_SG</i> attribute), 192	default_options (fer-	<i>mipy.diffuse.residual_cr.ResidualCR</i> attribute), 185
default_options (fer-	<i>mipy.diffuse.job_library.GatherSrcmaps_SG</i> attribute), 188	default_options (fer-	<i>mipy.diffuse.residual_cr.ResidualCR_SG</i> attribute), 190, 193
default_options (fer-	<i>mipy.diffuse.job_library.Gtexpcube2_SG</i> attribute), 185	default_options (fer-	<i>mipy.diffuse.residual_cr.ResidualCRChain</i> attribute), 200
default_options (fer-	<i>mipy.diffuse.job_library.Gtlink_bin</i> attribute), 177	default_options (fer-	<i>mipy.diffuse.solar.Gtexpcube2wcs_SG</i> attribute), 186
default_options (fer-	<i>mipy.diffuse.job_library.Gtlink_expcube2</i> attribute), 177	default_options (fer-	<i>mipy.diffuse.solar.Gtexphpsun_SG</i> attribute), 186
default_options (fer-	<i>mipy.diffuse.job_library.Gtlink_ltcube</i> attribute), 178	default_options (fer-	<i>mipy.diffuse.solar.Gtlink_expcube2_wcs</i> attribute), 179
default_options (fer-		default_options (fer-	

<code>mipy.diffuse.solar.Gtlink_exphpsun</code> attribute), 179	139	
<code>default_options</code> ( <code>fermipy.diffuse.solar.Gtlink_suntemp</code> attribute), 180	<code>default_options</code> ( <code>mipy.jobs.target_sim.SimulateROI_SG</code> attribute), 142	(fer-tribute), 142
<code>default_options</code> ( <code>mipy.diffuse.solar.Gtsuntemp_SG</code> attribute), 187	<code>default_options_base</code> ( <code>mipy.jobs.scatter_gather.ScatterGather</code> attribute), 133	(fer-tribute), 133
<code>default_options</code> ( <code>mipy.diffuse.solar.SunMoonChain</code> attribute), 200	<code>default_prefix_logfile</code> ( <code>mipy.jobs.scatter_gather.ScatterGather</code> attribute), 133	(fer-tribute), 133
<code>default_options</code> ( <code>fermipy.jobs.link.Link</code> attribute), 128	<code>defaults</code> ( <code>fermipy.gtanalysis.GTAnalysis</code> attribute), 62	<code>defaults</code> ( <code>fermipy.plotting.AnalysisPlotter</code> attribute), 90
<code>default_options</code> ( <code>mipy.jobs.scatter_gather.ScatterGather</code> attribute), 133	<code>defaults</code> ( <code>fermipy.plotting.ROIPlotter</code> attribute), 91	<code>defaults</code> ( <code>fermipy.roi_model.ROIModel</code> attribute), 78
<code>default_options</code> ( <code>mipy.jobs.target_analysis.AnalyzeROI</code> attribute), 136	<code>delete_source()</code> ( <code>fermipy.gtanalysis.GTAnalysis</code> method), 62	<code>delete_sources()</code> ( <code>fermipy.gtanalysis.GTAnalysis</code> method), 62
<code>default_options</code> ( <code>mipy.jobs.target_analysis.AnalyzeROI_SG</code> attribute), 140	<code>delete_sources()</code> ( <code>fermipy.roi_model.ROIModel</code> method), 78	<code>delete_workdir()</code> ( <code>fermipy.gtanalysis.GTAnalysis</code> method), 62
<code>default_options</code> ( <code>mipy.jobs.target_analysis.AnalyzeSED</code> attribute), 136	<code>derivative()</code> ( <code>fermipy.castro.CastroData_Base</code> method), 103	<code>derivative()</code> ( <code>fermipy.castro.Interpolator</code> method), 105
<code>default_options</code> ( <code>mipy.jobs.target_analysis.AnalyzeSED_SG</code> attribute), 140	<code>description</code> ( <code>fermipy.diffuse.diffuse_analysis.CatalogCompChain</code> attribute), 199	<code>description</code> ( <code>fermipy.diffuse.diffuse_analysis.DiffuseAnalysisChain</code> attribute), 199
<code>default_options</code> ( <code>mipy.jobs.target_collect.CollectSED</code> attribute), 137	<code>description</code> ( <code>fermipy.diffuse.diffuse_analysis.DiffuseCompChain</code> attribute), 198	<code>description</code> ( <code>fermipy.diffuse.gt_assemble_model.AssembleModel</code> attribute), 184
<code>default_options</code> ( <code>mipy.jobs.target_collect.CollectSED_SG</code> attribute), 141	<code>description</code> ( <code>fermipy.diffuse.gt_assemble_model.AssembleModel_SG</code> attribute), 192	<code>description</code> ( <code>fermipy.diffuse.gt_assemble_model.AssembleModelChain</code> attribute), 199
<code>default_options</code> ( <code>mipy.jobs.target_plotting.PlotCastro</code> attribute), 139	<code>description</code> ( <code>fermipy.diffuse.gt_assemble_model.InitModel</code> attribute), 183	<code>description</code> ( <code>fermipy.diffuse.gt_coadd_split.CoaddSplit</code> attribute), 195
<code>default_options</code> ( <code>mipy.jobs.target_plotting.PlotCastro_SG</code> attribute), 143	<code>description</code> ( <code>fermipy.diffuse.gt_coadd_split.CoaddSplit_SG</code> attribute), 187	<code>description</code> ( <code>fermipy.diffuse.gt_merge_srcmaps.GtMergeSrcmaps</code> attribute), 182
<code>default_options</code> ( <code>mipy.jobs.target_sim.CopyBaseROI</code> attribute), 138	<code>description</code> ( <code>fermipy.diffuse.gt_merge_srcmaps.MergeSrcmaps_SG</code> attribute), 191	<code>description</code> ( <code>fermipy.diffuse.gt_split_and_bin.SplitAndBin</code> attribute), 195
<code>default_options</code> ( <code>mipy.jobs.target_sim.CopyBaseROI_SG</code> attribute), 141	<code>description</code> ( <code>fermipy.diffuse.gt_split_and_bin.SplitAndBin_SG</code> attribute), 193	<code>description</code> ( <code>fermipy.diffuse.gt_split_and_bin.SplitAndBinChain</code> attribute), 193
<code>default_options</code> ( <code>mipy.jobs.target_sim.RandomDirGen</code> attribute), 138		
<code>default_options</code> ( <code>mipy.jobs.target_sim.RandomDirGen_SG</code> attribute), 142		
<code>default_options</code> ( <code>mipy.jobs.target_sim.SimulateROI</code> attribute), 139		



[attribute](#)), 196  
[description \(fermipy.diffuse.gt\\_split\\_and\\_mktime.SplitAndMktime attribute\)](#), 197  
[description \(fermipy.diffuse.gt\\_split\\_and\\_mktime.SplitAndMktime\\_SGn attribute\)](#), 194  
[description \(fermipy.diffuse.gt\\_split\\_and\\_mktime.SplitAndMktimeChain attribute\)](#), 198  
[description \(fermipy.diffuse.gt\\_srcmap\\_partial.GtSrcmapDiffuse attribute\)](#), 182  
[description \(fermipy.diffuse.gt\\_srcmap\\_partial.SrcmapsDiffuse attribute\)](#), 191  
[description \(fermipy.diffuse.gt\\_srcmaps\\_catalog.GtSrcmapsCatalog attribute\)](#), 183  
[description \(fermipy.diffuse.gt\\_srcmaps\\_catalog.SrcmapsCatalog attribute\)](#), 192  
[description \(fermipy.diffuse.job\\_library.GatherSrcmaps attribute\)](#), 188  
[description \(fermipy.diffuse.job\\_library.Gtexpcube2\\_SG attribute\)](#), 185  
[description \(fermipy.diffuse.job\\_library.Gtlink\\_bin attribute\)](#), 177  
[description \(fermipy.diffuse.job\\_library.Gtlink\\_expcube2 attribute\)](#), 177  
[description \(fermipy.diffuse.job\\_library.Gtlink\\_ltcube attribute\)](#), 178  
[description \(fermipy.diffuse.job\\_library.Gtlink\\_ltsun attribute\)](#), 178  
[description \(fermipy.diffuse.job\\_library.Gtlink\\_mktime attribute\)](#), 178  
[description \(fermipy.diffuse.job\\_library.Gtlink\\_scrmaps attribute\)](#), 178  
[description \(fermipy.diffuse.job\\_library.Gtlink\\_select attribute\)](#), 177  
[description \(fermipy.diffuse.job\\_library.Gtltsun\\_SG attribute\)](#), 186  
[description \(fermipy.diffuse.job\\_library.Healview\\_SG attribute\)](#), 189  
[description \(fermipy.diffuse.job\\_library.Link\\_FermipyCoadd attribute\)](#), 180  
[description \(fermipy.diffuse.job\\_library.Link\\_FermipyGatherSrcmaps attribute\)](#), 180  
[description \(fermipy.diffuse.job\\_library.Link\\_FermipyHealview attribute\)](#), 181  
[description \(fermipy.diffuse.job\\_library.Link\\_FermipyVstack attribute\)](#), 181  
[description \(fermipy.diffuse.job\\_library.SumRings\\_SG attribute\)](#), 189, 190  
[description \(fermipy.diffuse.job\\_library.Vstack\\_SG attribute\)](#), 188  
[description \(fermipy.diffuse.residual\\_cr.ResidualCR attribute\)](#), 185  
[description \(fermipy.diffuse.residual\\_cr.ResidualCR\\_SG attribute\)](#), 190, 193  
[description \(fermipy.diffuse.residual\\_cr.ResidualCRChain attribute\)](#), 200  
[description \(fermipy.diffuse.solar.Gtexpcube2wcs\\_SG attribute\)](#), 186  
[description \(fermipy.diffuse.solar.Gtexphpsun\\_SG attribute\)](#), 187  
[description \(fermipy.diffuse.solar.Gtlink\\_expcube2\\_wcs attribute\)](#), 179  
[description \(fermipy.diffuse.solar.Gtlink\\_exphpsun attribute\)](#), 179  
[description \(fermipy.diffuse.solar.Gtlink\\_suntemp attribute\)](#), 180  
[description \(fermipy.diffuse.solar.Gtsuntemp\\_SG attribute\)](#), 187  
[description \(fermipy.diffuse.solar.SunMoonChain attribute\)](#), 200  
[description \(fermipy.jobs.app\\_link.AppLink attribute\)](#), 132  
[description \(fermipy.jobs.gtlink.Gtlink attribute\)](#), 130  
[description \(fermipy.jobs.link.Link attribute\)](#), 128  
[description \(fermipy.jobs.scatter\\_gather.ScatterGather attribute\)](#), 133  
[description \(fermipy.jobs.target\\_analysis.AnalyzeROI attribute\)](#), 136  
[description \(fermipy.jobs.target\\_analysis.AnalyzeROI\\_SG attribute\)](#), 140  
[description \(fermipy.jobs.target\\_analysis.AnalyzeSED attribute\)](#), 136  
[description \(fermipy.jobs.target\\_analysis.AnalyzeSED\\_SG attribute\)](#), 140  
[description \(fermipy.jobs.target\\_collect.CollectSED attribute\)](#), 137  
[description \(fermipy.jobs.target\\_collect.CollectSED\\_SG attribute\)](#), 141  
[description \(fermipy.jobs.target\\_plotting.PlotCastro attribute\)](#), 139  
[description \(fermipy.jobs.target\\_plotting.PlotCastro\\_SG attribute\)](#), 143  
[description \(fermipy.jobs.target\\_sim.CopyBaseROI attribute\)](#), 138  
[description \(fermipy.jobs.target\\_sim.CopyBaseROI\\_SG attribute\)](#), 141  
[description \(fermipy.jobs.target\\_sim.RandomDirGen attribute\)](#), 138  
[description \(fermipy.jobs.target\\_sim.RandomDirGen\\_SG attribute\)](#), 142  
[description \(fermipy.jobs.target\\_sim.SimulateROI attribute\)](#), 139  
[description \(fermipy.jobs.target\\_sim.SimulateROI\\_SG attribute\)](#), 143  
[diffuse \(fermipy.roi\\_model.CompositeSource attribute\)](#), 75  
[diffuse \(fermipy.roi\\_model.IsoSource attribute\)](#), 75  
[diffuse \(fermipy.roi\\_model.MapCubeSource attribute\)](#), 75

- tribute), 76
- diffuse (*fermipy.roi\_model.Source* attribute), 81
- diffuse\_comp\_info() (*fermipy.diffuse.diffuse\_src\_manager.DiffuseModelManager* method), 173
- diffuse\_comp\_info\_dicts() (*fermipy.diffuse.diffuse\_src\_manager.GalpropMapManager* method), 171
- diffuse\_sources (*fermipy.roi\_model.ROIModel* attribute), 78
- diffuse\_template() (*fermipy.diffuse.name\_policy.NameFactory* method), 164
- diffuse\_template\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164
- DiffuseAnalysisChain (class in *fermipy.diffuse.diffuse\_analysis*), 199
- DiffuseCompChain (class in *fermipy.diffuse.diffuse\_analysis*), 198
- DiffuseModelManager (class in *fermipy.diffuse.diffuse\_src\_manager*), 172
- dispatch\_job() (*fermipy.jobs.sys\_interface.SysInterface* method), 143
- dispatch\_job\_hook() (*fermipy.jobs.native\_impl.NativeInterface* method), 144
- dispatch\_job\_hook() (*fermipy.jobs.slac\_impl.SlacInterface* method), 145
- dispatch\_job\_hook() (*fermipy.jobs.sys\_interface.SysInterface* method), 144
- DMFitFunction (class in *fermipy.spectrum*), 93
- dmm (*fermipy.diffuse.model\_manager.ModelManager* attribute), 175
- dnde (*fermipy.castro.SpecData* attribute), 108
- dnde() (*fermipy.spectrum.SpectralFunction* method), 96
- dnde\_deriv() (*fermipy.spectrum.SpectralFunction* method), 96
- dnde\_err (*fermipy.castro.SpecData* attribute), 108
- done (*fermipy.jobs.job\_archive.JobStatus* attribute), 153
- dot\_prod() (in module *fermipy.utils*), 83
- draw\_circle() (*fermipy.plotting.ROIPlotter* method), 91
- E**
- e2dnde (*fermipy.castro.SpecData* attribute), 108
- e2dnde() (*fermipy.spectrum.SpectralFunction* method), 96
- e2dnde\_deriv() (*fermipy.spectrum.SpectralFunction* method), 96
- e2dnde\_err (*fermipy.castro.SpecData* attribute), 108
- ebins (*fermipy.castro.ReferenceSpec* attribute), 107
- edge\_to\_center() (in module *fermipy.utils*), 83
- edge\_to\_width() (in module *fermipy.utils*), 83
- edisp\_disable\_list() (*fermipy.diffuse.model\_manager.ModelInfo* method), 175
- ednde() (*fermipy.spectrum.SpectralFunction* method), 96
- ednde\_deriv() (*fermipy.spectrum.SpectralFunction* method), 96
- eflux (*fermipy.castro.SpecData* attribute), 108
- eflux() (*fermipy.spectrum.SpectralFunction* method), 96
- ellipse\_to\_cov() (in module *fermipy.utils*), 83
- emax (*fermipy.castro.ReferenceSpec* attribute), 107
- emax (*fermipy.diffuse.binning.Component* attribute), 163
- emax (*fermipy.spectrum.SEDFuncor* attribute), 95
- emin (*fermipy.castro.ReferenceSpec* attribute), 107
- emin (*fermipy.diffuse.binning.Component* attribute), 163
- emin (*fermipy.spectrum.SEDFuncor* attribute), 95
- energies (*fermipy.gtanalysis.GTAnalysis* attribute), 62
- enumbins (*fermipy.gtanalysis.GTAnalysis* attribute), 62
- eq2gal() (in module *fermipy.utils*), 83
- eref (*fermipy.castro.ReferenceSpec* attribute), 107
- eval\_dnde() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_dnde\_deriv() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_e2dnde() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_e2dnde\_deriv() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_ednde() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_ednde\_deriv() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_eflux() (*fermipy.spectrum.PowerLaw* class method), 95
- eval\_eflux() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_flux() (*fermipy.spectrum.PowerLaw* static method), 95
- eval\_flux() (*fermipy.spectrum.SpectralFunction* class method), 96
- eval\_norm() (*fermipy.spectrum.PowerLaw* class method), 95
- eval\_radial\_kernel() (in module *fermipy.utils*), 83
- evclassmask() (*fermipy.spectrum.SpectralFunction* method), 96

- mipy.diffuse.name\_policy.NameFactory method*), 164
- evtype* (*fermipy.diffuse.binning.Component* attribute), 163
- exists* (*fermipy.jobs.file\_archive.FileStatus* attribute), 150
- expanded\_counts\_map*() (*fermipy.skymap.HpxMap* method), 97
- expected* (*fermipy.jobs.file\_archive.FileStatus* attribute), 151
- explicit\_counts\_map*() (*fermipy.skymap.HpxMap* method), 97
- extdir* (*fermipy.roi\_model.ROIModel* attribute), 78
- extend\_array*() (in module *fermipy.utils*), 83
- extended* (*fermipy.roi\_model.Source* attribute), 81
- extension*() (*fermipy.gtanalysis.GTAnalysis* method), 63
- ExtensionPlotter* (class in *fermipy.plotting*), 90
- extra\_params* (*fermipy.spectrum.SpectralFunction* attribute), 96
- extract\_array*() (in module *fermipy.tsmmap*), 110
- extract\_images\_from\_tscube*() (in module *fermipy.tsmmap*), 110
- extract\_large\_array*() (in module *fermipy.tsmmap*), 110
- extract\_parameters*() (in module *fermipy.jobs.gtlink*), 131
- extract\_small\_array*() (in module *fermipy.tsmmap*), 110
- ## F
- f\_cash*() (in module *fermipy.tsmmap*), 110
- f\_cash\_sum*() (in module *fermipy.tsmmap*), 111
- failed* (*fermipy.jobs.job\_archive.JobStatus* attribute), 153
- fermipy* (module), 113
- fermipy.castro* (module), 100
- fermipy.config* (module), 59
- fermipy.defaults* (module), 60
- fermipy.diffuse* (module), 162
- fermipy.diffuse.binning* (module), 162
- fermipy.diffuse.defaults* (module), 163
- fermipy.diffuse.name\_policy* (module), 163
- fermipy.diffuse.source\_factory* (module), 166
- fermipy.diffuse.spectral* (module), 166
- fermipy.diffuse.timefilter* (module), 166
- fermipy.diffuse.utils* (module), 168
- fermipy.jobs* (module), 126
- fermipy.jobs.batch* (module), 146
- fermipy.jobs.file\_archive* (module), 146
- fermipy.jobs.gtlink* (module), 130
- fermipy.jobs.job\_archive* (module), 151
- fermipy.jobs.native\_impl* (module), 144
- fermipy.jobs.slac\_impl* (module), 145
- fermipy.jobs.sys\_interface* (module), 143
- fermipy.lightcurve* (module), 112
- fermipy.logger* (module), 75
- fermipy.plotting* (module), 90
- fermipy.residmap* (module), 111
- fermipy.roi\_model* (module), 75
- fermipy.sed* (module), 92
- fermipy.skymap* (module), 96
- fermipy.sourcefind* (module), 92
- fermipy.spectrum* (module), 93
- fermipy.tsmmap* (module), 109
- fermipy.utils* (module), 82
- file\_archive* (*fermipy.jobs.job\_archive.JobArchive* attribute), 151
- FileArchive* (class in *fermipy.jobs.file\_archive*), 146
- FileDict* (class in *fermipy.jobs.file\_archive*), 147
- FileFlags* (class in *fermipy.jobs.file\_archive*), 149
- filefunction* (*fermipy.roi\_model.IsoSource* attribute), 75
- FileHandle* (class in *fermipy.jobs.file\_archive*), 149
- files* (*fermipy.gtanalysis.GTAnalysis* attribute), 63
- FileStageManager* (class in *fermipy.jobs.file\_archive*), 150
- FileStatus* (class in *fermipy.jobs.file\_archive*), 150
- find\_and\_refine\_peaks*() (*fermipy.castro.TSCube* method), 108
- find\_function\_root*() (in module *fermipy.utils*), 83
- find\_rows\_by\_string*() (in module *fermipy.utils*), 84
- find\_sources*() (*fermipy.castro.TSCube* method), 108
- find\_sources*() (*fermipy.gtanalysis.GTAnalysis* method), 63
- find\_sources*() (*fermipy.sourcefind.SourceFind* method), 92
- fit*() (*fermipy.gtanalysis.GTAnalysis* method), 63
- fit\_correlation*() (*fermipy.gtanalysis.GTAnalysis* method), 64
- fit\_parabola*() (in module *fermipy.utils*), 84
- fit\_spectrum*() (*fermipy.castro.CastroData\_Base* method), 104
- fitNorm\_v2*() (*fermipy.castro.CastroData\_Base* method), 103
- fitNormalization*() (*fermipy.castro.CastroData\_Base* method), 103
- fits\_reccarray\_to\_dict*() (in module *fermipy.utils*), 84
- flush*() (*fermipy.logger.StreamLogger* method), 75
- flux* (*fermipy.castro.SpecData* attribute), 108
- flux*() (*fermipy.spectrum.SpectralFunction* method), 96
- fn\_mle*() (*fermipy.castro.LnLFn* method), 105

`fn_mles()` (*fermipy.castro.CastroData\_Base* method), 104  
`format_filename()` (in module *fermipy.utils*), 84  
`formatted_command()` (*fermipy.jobs.link.Link* method), 128  
`free_index()` (*fermipy.gtanalysis.GTAnalysis* method), 64  
`free_norm()` (*fermipy.gtanalysis.GTAnalysis* method), 64  
`free_parameter()` (*fermipy.gtanalysis.GTAnalysis* method), 64  
`free_shape()` (*fermipy.gtanalysis.GTAnalysis* method), 64  
`free_source()` (*fermipy.gtanalysis.GTAnalysis* method), 64  
`free_sources()` (*fermipy.gtanalysis.GTAnalysis* method), 64  
`free_sources_by_name()` (*fermipy.gtanalysis.GTAnalysis* method), 65  
`ft1file()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`ft1file_format` (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164  
`ft2file()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`ft2file_format` (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164  
`full_linkname` (*fermipy.jobs.link.Link* attribute), 128  
`fullkey` (*fermipy.jobs.job\_archive.JobDetails* attribute), 153  
`fullpath()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`fullpath_format` (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164

## G

`gal2eq()` (in module *fermipy.utils*), 84  
`galkeys()` (*fermipy.diffuse.diffuse\_src\_manager.GalpropMapManager* method), 171  
`galprop_gasmap()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`galprop_gasmap_format` (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164  
`galprop_ringkey()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`galprop_ringkey_format` (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164  
`galprop_rings_yaml()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`galprop_rings_yaml_format` (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164  
`galprop_sourcekey()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`galprop_sourcekey_format` (*fermipy.diffuse.name\_policy.NameFactory* attribute), 164  
`GalpropMapManager` (class in *fermipy.diffuse.diffuse\_src\_manager*), 171  
`GalpropMergedRingInfo` (class in *fermipy.diffuse.model\_component*), 169  
`GatherSrcmaps_SG` (class in *fermipy.diffuse.job\_library*), 187  
`generate_model()` (*fermipy.gtanalysis.GTAnalysis* method), 65  
`generic()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`geom` (*fermipy.gtanalysis.GTAnalysis* attribute), 65  
`geom` (*fermipy.plotting.ImagePlotter* attribute), 90  
`geom` (*fermipy.plotting.ROIPlotter* attribute), 91  
`geom` (*fermipy.roi\_model.ROIModel* attribute), 78  
`get_archive()` (*fermipy.jobs.file\_archive.FileArchive* class method), 146  
`get_archive()` (*fermipy.jobs.job\_archive.JobArchive* class method), 151  
`get_batch_job_args()` (in module *fermipy.jobs.batch*), 146  
`get_batch_job_interface()` (in module *fermipy.jobs.batch*), 146  
`get_bounded_slice()` (in module *fermipy.utils*), 84  
`get_catalog_dict()` (*fermipy.roi\_model.Model* method), 76  
`get_component_info()` (*fermipy.diffuse.model\_component.ModelComponentInfo* method), 169, 170  
`get_config()` (*fermipy.config.Configurable* class method), 59  
`get_config()` (*fermipy.gtanalysis.GTAnalysis* class method), 65  
`get_data_projection()` (*fermipy.plotting.ROIPlotter* static method), 91  
`get_details()` (*fermipy.jobs.job\_archive.JobArchive* method), 151  
`get_dist_to_edge()` (in module *fermipy.roi\_model*), 81  
`get_failed_jobs()` (*fermipy.jobs.link.Link* method), 128



[get\\_file\\_ids\(\)](#) (*fermipy.jobs.file\_archive.FileArchive* method), 146  
[get\\_file\\_ids\(\)](#) (*fermipy.jobs.job\_archive.JobDetails* method), 153  
[get\\_file\\_paths\(\)](#) (*fermipy.jobs.file\_archive.FileArchive* method), 147  
[get\\_file\\_paths\(\)](#) (*fermipy.jobs.job\_archive.JobDetails* method), 153  
[get\\_free\\_param\\_vector\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 65  
[get\\_free\\_source\\_params\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 65  
[get\\_git\\_version\\_fp\(\)](#) (in module *fermipy*), 113  
[get\\_gtapp\(\)](#) (*fermipy.jobs.gtlink.Gtlink* method), 130  
[get\\_handle\(\)](#) (*fermipy.jobs.file\_archive.FileArchive* method), 147  
[get\\_jobs\(\)](#) (*fermipy.jobs.chain.Chain* method), 135  
[get\\_jobs\(\)](#) (*fermipy.jobs.link.Link* method), 128  
[get\\_jobs\(\)](#) (*fermipy.jobs.scatter\_gather.ScatterGather* method), 133  
[get\\_linear\\_dist\(\)](#) (in module *fermipy.roi\_model*), 81  
[get\\_lsf\\_status\(\)](#) (in module *fermipy.jobs.slac\_impl*), 145  
[get\\_map\\_values\(\)](#) (*fermipy.skymap.HpxMap* method), 97  
[get\\_map\\_values\(\)](#) (*fermipy.skymap.Map* method), 98  
[get\\_map\\_values\(\)](#) (*fermipy.skymap.Map\_Base* method), 99  
[get\\_native\\_default\\_args\(\)](#) (in module *fermipy.jobs.native\_impl*), 145  
[get\\_nearby\\_sources\(\)](#) (*fermipy.roi\_model.ROIModel* method), 78  
[get\\_norm\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 65  
[get\\_norm\(\)](#) (*fermipy.roi\_model.Model* method), 76  
[get\\_parameter\\_limits\(\)](#) (in module *fermipy.utils*), 84  
[get\\_params\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 66  
[get\\_pixel\\_indices\(\)](#) (*fermipy.skymap.HpxMap* method), 97  
[get\\_pixel\\_indices\(\)](#) (*fermipy.skymap.Map* method), 98  
[get\\_pixel\\_indices\(\)](#) (*fermipy.skymap.Map\_Base* method), 99  
[get\\_pixel\\_skydirs\(\)](#) (*fermipy.skymap.HpxMap* method), 97  
[get\\_pixel\\_skydirs\(\)](#) (*fermipy.skymap.Map* method), 99  
[get\\_pixel\\_skydirs\(\)](#) (*fermipy.skymap.Map\_Base* method), 100  
[get\\_region\\_mask\(\)](#) (in module *fermipy.utils*), 85  
[get\\_scratch\\_path\(\)](#) (*fermipy.jobs.file\_archive.FileStageManager* method), 150  
[get\\_skydir\\_distance\\_mask\(\)](#) (in module *fermipy.roi\_model*), 81  
[get\\_slac\\_default\\_args\(\)](#) (in module *fermipy.jobs.slac\_impl*), 145  
[get\\_source\\_by\\_name\(\)](#) (*fermipy.roi\_model.ROIModel* method), 78  
[get\\_source\\_dnde\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 66  
[get\\_source\\_kernel\(\)](#) (in module *fermipy.residmap*), 112  
[get\\_source\\_name\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 66  
[get\\_source\\_params\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 66  
[get\\_sources\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 66  
[get\\_sources\(\)](#) (*fermipy.roi\_model.ROIModel* method), 78  
[get\\_sources\\_by\\_name\(\)](#) (*fermipy.roi\_model.ROIModel* method), 79  
[get\\_sources\\_by\\_position\(\)](#) (*fermipy.roi\_model.ROIModel* method), 79  
[get\\_sources\\_by\\_property\(\)](#) (*fermipy.roi\_model.ROIModel* method), 79  
[get\\_src\\_model\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 66  
[get\\_st\\_version\(\)](#) (in module *fermipy*), 113  
[get\\_status\(\)](#) (*fermipy.jobs.job\_archive.JobStatusVector* method), 154  
[get\\_sub\\_comp\\_info\(\)](#) (*fermipy.diffuse.model\_manager.ModelManager* static method), 175  
[get\\_timestamp\(\)](#) (in module *fermipy.jobs.file\_archive*), 151  
[get\\_true\\_params\\_dict\(\)](#) (in module *fermipy.roi\_model*), 82  
[get\\_unique\\_match\(\)](#) (in module *fermipy.jobs.file\_archive*), 151  
[get\\_xerr\(\)](#) (in module *fermipy.plotting*), 91  
[get\\_ylimits\(\)](#) (*fermipy.plotting.SEDPlotter* static method), 91  
[getDeltaLogLike\(\)](#) (*fermipy.castro.LnLFn* method), 105  
[getInterval\(\)](#) (*fermipy.castro.LnLFn* method), 106  
[getIntervals\(\)](#) (*fermipy.castro.CastroData\_Base* method), 104  
[getLimit\(\)](#) (*fermipy.castro.LnLFn* method), 106

`getLimits()` (*fermipy.castro.CastroData\_Base* method), 104  
`gmm` (*fermipy.diffuse.model\_manager.ModelManager* attribute), 176  
`GTAnalysis` (class in *fermipy.gtanalysis*), 60  
`Gtexpcube2_SG` (class in *fermipy.diffuse.job\_library*), 185  
`Gtexpcube2wcs_SG` (class in *fermipy.diffuse.solar*), 186  
`Gtexphpsun_SG` (class in *fermipy.diffuse.solar*), 186  
`Gtlink` (class in *fermipy.jobs.gtlink*), 130  
`Gtlink_bin` (class in *fermipy.diffuse.job\_library*), 177  
`Gtlink_expcube2` (class in *fermipy.diffuse.job\_library*), 177  
`Gtlink_expcube2_wcs` (class in *fermipy.diffuse.solar*), 179  
`Gtlink_exphpsun` (class in *fermipy.diffuse.solar*), 179  
`Gtlink_ltcube` (class in *fermipy.diffuse.job\_library*), 178  
`Gtlink_ltsum` (class in *fermipy.diffuse.job\_library*), 178  
`Gtlink_mktime` (class in *fermipy.diffuse.job\_library*), 178  
`Gtlink_scrmaps` (class in *fermipy.diffuse.job\_library*), 177  
`Gtlink_select` (class in *fermipy.diffuse.job\_library*), 176  
`Gtlink_sunttemp` (class in *fermipy.diffuse.solar*), 179  
`Gtltsum_SG` (class in *fermipy.diffuse.job\_library*), 185  
`GtMergeSrcmaps` (class in *fermipy.diffuse.gt\_merge\_srcmaps*), 181  
`GtSrcmapsCatalog` (class in *fermipy.diffuse.gt\_srcmaps\_catalog*), 182  
`GtSrcmapsDiffuse` (class in *fermipy.diffuse.gt\_srcmap\_partial*), 182  
`Gtsunttemp_SG` (class in *fermipy.diffuse.solar*), 187  
`gz_mask` (*fermipy.jobs.file\_archive.FileFlags* attribute), 149  
`gzip_files` (*fermipy.jobs.file\_archive.FileDict* attribute), 148

## H

`has_source()` (*fermipy.roi\_model.ROIModel* method), 79  
`Healview_SG` (class in *fermipy.diffuse.job\_library*), 188  
`hpx` (*fermipy.skymap.HpxMap* attribute), 97  
`HpxMap` (class in *fermipy.skymap*), 96

## I

`ImagePlotter` (class in *fermipy.plotting*), 90  
`in_ch_mask` (*fermipy.jobs.file\_archive.FileFlags* attribute), 149

`in_stage_mask` (*fermipy.jobs.file\_archive.FileFlags* attribute), 149  
`init_matplotlib_backend()` (in module *fermipy.utils*), 85  
`InitModel` (class in *fermipy.diffuse.gt\_assemble\_model*), 183  
`input_files` (*fermipy.jobs.file\_archive.FileDict* attribute), 148  
`input_files_to_stage` (*fermipy.jobs.file\_archive.FileDict* attribute), 148  
`input_mask` (*fermipy.jobs.file\_archive.FileFlags* attribute), 149  
`internal_files` (*fermipy.jobs.file\_archive.FileDict* attribute), 148  
`internal_mask` (*fermipy.jobs.file\_archive.FileFlags* attribute), 149  
`interp` (*fermipy.castro.LnLFn* attribute), 106  
`interpolate()` (*fermipy.skymap.HpxMap* method), 97  
`interpolate()` (*fermipy.skymap.Map* method), 99  
`interpolate()` (*fermipy.skymap.Map\_Base* method), 100  
`interpolate_at_skydir()` (*fermipy.skymap.Map* method), 99  
`interpolate_function_min()` (in module *fermipy.utils*), 85  
`Interpolator` (class in *fermipy.castro*), 105  
`ipix_swap_axes()` (*fermipy.skymap.Map* method), 99  
`ipix_to_xypix()` (*fermipy.skymap.Map* method), 99  
`irf_ver()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`irfs()` (*fermipy.diffuse.name\_policy.NameFactory* method), 164  
`is_fits_file()` (in module *fermipy.utils*), 85  
`is_free` (*fermipy.roi\_model.Model* attribute), 76  
`IsoComponentInfo` (class in *fermipy.diffuse.model\_component*), 170  
`IsoSource` (class in *fermipy.roi\_model*), 75  
`isstr()` (in module *fermipy.utils*), 85  
`items()` (*fermipy.config.ConfigSchema* method), 59  
`items()` (*fermipy.diffuse.model\_manager.ModelInfo* method), 175  
`items()` (*fermipy.diffuse.timefilter.MktimeFilterDict* method), 166  
`items()` (*fermipy.jobs.file\_archive.FileDict* method), 148  
`items()` (*fermipy.roi\_model.Model* method), 76

## J

`job_time` (*fermipy.diffuse.gt\_assemble\_model.AssembleModel\_SG* attribute), 192

`job_time` (`fermipy.diffuse.gt_coadd_split.CoaddSplit_SG` **K**  
`attribute`), 187  
`job_time` (`fermipy.diffuse.gt_merge_srcmaps.MergeSrcmaps_SG` **K**  
`attribute`), 191  
`job_time` (`fermipy.diffuse.gt_split_and_bin.SplitAndBin_SG` **K**  
`attribute`), 193  
`job_time` (`fermipy.diffuse.gt_split_and_mktime.SplitAndMktime_SG` **K**  
`attribute`), 194  
`job_time` (`fermipy.diffuse.gt_srcmap_partial.SrcmapsDiffuse_SG` **K**  
`attribute`), 191  
`job_time` (`fermipy.diffuse.gt_srcmaps_catalog.SrcmapsCatalog_SG` **K**  
`attribute`), 192  
`job_time` (`fermipy.diffuse.job_library.GatherSrcmaps_SG` **K**  
`attribute`), 188  
`job_time` (`fermipy.diffuse.job_library.Gtexpcube2_SG` **K**  
`attribute`), 185  
`job_time` (`fermipy.diffuse.job_library.Giltsum_SG` **K**  
`attribute`), 186  
`job_time` (`fermipy.diffuse.job_library.Healview_SG` **K**  
`attribute`), 189  
`job_time` (`fermipy.diffuse.job_library.SumRings_SG` **K**  
`attribute`), 189, 190  
`job_time` (`fermipy.diffuse.job_library.Vstack_SG` **K**  
`attribute`), 188  
`job_time` (`fermipy.diffuse.residual_cr.ResidualCR_SG` **K**  
`attribute`), 190, 193  
`job_time` (`fermipy.diffuse.solar.Gtexpcube2wcs_SG` **K**  
`attribute`), 186  
`job_time` (`fermipy.diffuse.solar.Gtexphpsun_SG` **K**  
`attribute`), 187  
`job_time` (`fermipy.diffuse.solar.Gtsuntemp_SG` **K**  
`attribute`), 187  
`job_time` (`fermipy.jobs.scatter_gather.ScatterGather` **K**  
`attribute`), 133  
`job_time` (`fermipy.jobs.target_analysis.AnalyzeROI_SG` **K**  
`attribute`), 140  
`job_time` (`fermipy.jobs.target_analysis.AnalyzeSED_SG` **K**  
`attribute`), 140  
`job_time` (`fermipy.jobs.target_collect.CollectSED_SG` **K**  
`attribute`), 141  
`job_time` (`fermipy.jobs.target_plotting.PlotCastro_SG` **K**  
`attribute`), 143  
`job_time` (`fermipy.jobs.target_sim.CopyBaseROI_SG` **K**  
`attribute`), 141  
`job_time` (`fermipy.jobs.target_sim.RandomDirGen_SG` **K**  
`attribute`), 142  
`job_time` (`fermipy.jobs.target_sim.SimulateROI_SG` **K**  
`attribute`), 143  
`JobArchive` (class in `fermipy.jobs.job_archive`), 151  
`JobDetails` (class in `fermipy.jobs.job_archive`), 152  
`JobStatus` (class in `fermipy.jobs.job_archive`), 153  
`JobStatusVector` (class in `fermipy.jobs.job_archive`), 154  
`join_strings()` (in module `fermipy.utils`), 85  
`keys()` (`fermipy.diffuse.timefilter.MktimeFilterDict`  
`method`), 166  
`latch_file_info()` (`fermipy.jobs.file_archive.FileDict`  
`method`), 148  
`LightCurve` (class in `fermipy.lightcurve`), 112  
`lightcurve()` (`fermipy.gtanalysis.GTAnalysis`  
`method`), 66  
`lightcurve()` (`fermipy.lightcurve.LightCurve`  
`method`), 112  
`like` (`fermipy.gtanalysis.GTAnalysis` `attribute`), 66  
`Link` (class in `fermipy.jobs.link`), 126  
`Link_FermipyCoadd` (class in `fermipy.diffuse.job_library`), 180  
`Link_FermipyGatherSrcmaps` (class in `fermipy.diffuse.job_library`), 180  
`Link_FermipyHealview` (class in `fermipy.diffuse.job_library`), 181  
`Link_FermipyVstack` (class in `fermipy.diffuse.job_library`), 180  
`linkname_default` (`fermipy.diffuse.diffuse_analysis.CatalogCompChain`  
`attribute`), 199  
`linkname_default` (`fermipy.diffuse.diffuse_analysis.DiffuseAnalysisChain`  
`attribute`), 199  
`linkname_default` (`fermipy.diffuse.diffuse_analysis.DiffuseCompChain`  
`attribute`), 198  
`linkname_default` (`fermipy.diffuse.gt_assemble_model.AssembleModel`  
`attribute`), 184  
`linkname_default` (`fermipy.diffuse.gt_assemble_model.AssembleModelChain`  
`attribute`), 199  
`linkname_default` (`fermipy.diffuse.gt_assemble_model.InitModel`  
`attribute`), 183  
`linkname_default` (`fermipy.diffuse.gt_coadd_split.CoaddSplit` `at-`  
`tribute`), 195  
`linkname_default` (`fermipy.diffuse.gt_merge_srcmaps.GtMergeSrcmaps`  
`attribute`), 182  
`linkname_default` (`fermipy.diffuse.gt_split_and_bin.SplitAndBin`  
`attribute`), 195  
`linkname_default` (`fermipy.diffuse.gt_split_and_bin.SplitAndBinChain`  
`attribute`), 196

linkname_default mipy.diffuse.gt_split_and_mktime.SplitAndMktime attribute), 197	(fer- linkname_default mipy.diffuse.solar.Gtlink_exphpsun attribute), 179
linkname_default mipy.diffuse.gt_split_and_mktime.SplitAndMktimeChain attribute), 198	(fer- linkname_default mipy.diffuse.solar.Gtlink_suntemp attribute), 180
linkname_default mipy.diffuse.gt_srcmap_partial.GtSrcmapsDiffuse attribute), 182	(fer- linkname_default mipy.diffuse.solar.SunMoonChain attribute), 200
linkname_default mipy.diffuse.gt_srcmaps_catalog.GtSrcmapsCatalog attribute), 183	(fermipy.jobs.app_link.AppLink attribute), 132
linkname_default mipy.diffuse.job_library.Gtlink_bin attribute), 177	(fermipy.jobs.gtlink.Gtlink attribute), 130
linkname_default mipy.diffuse.job_library.Gtlink_expcube2 attribute), 177	(fermipy.jobs.link.Link attribute), 129
linkname_default mipy.diffuse.job_library.Gtlink_ltcube attribute), 178	(fer- linkname_default mipy.jobs.target_analysis.AnalyzeROI attribute), 136
linkname_default mipy.diffuse.job_library.Gtlink_ltsum attribute), 178	(fer- linkname_default mipy.jobs.target_analysis.AnalyzeSED attribute), 137
linkname_default mipy.diffuse.job_library.Gtlink_mktime attribute), 178	(fer- linkname_default mipy.jobs.target_collect.CollectSED attribute), 137
linkname_default mipy.diffuse.job_library.Gtlink_scrmaps attribute), 178	(fer- linkname_default mipy.jobs.target_plotting.PlotCastro attribute), 139
linkname_default mipy.diffuse.job_library.Gtlink_select attribute), 177	(fer- linkname_default mipy.jobs.target_sim.CopyBaseROI attribute), 138
linkname_default mipy.diffuse.job_library.Link_FermipyCoadd attribute), 180	(fer- linkname_default mipy.jobs.target_sim.RandomDirGen attribute), 138
linkname_default mipy.diffuse.job_library.Link_FermipyGatherSrcmaps attribute), 180	(fer- linkname_default mipy.jobs.target_sim.SimulateROI attribute), 139
linkname_default mipy.diffuse.job_library.Link_FermipyHealview attribute), 181	linknames (fermipy.jobs.chain.Chain attribute), 135
linkname_default mipy.diffuse.job_library.Link_FermipyVstack attribute), 181	LnLFn (class in fermipy.castro), 105
linkname_default mipy.diffuse.residual_cr.ResidualCR attribute), 185	load() (fermipy.config.ConfigManager static method), 59
linkname_default mipy.diffuse.residual_cr.ResidualCRChain attribute), 200	load() (fermipy.roi_model.ROIModel method), 79
linkname_default mipy.diffuse.solar.Gtlink_expcube2_wcs attribute), 179	load_bluered_cmap() (in module fermipy.plotting), 91
	load_config() (fermipy.jobs.chain.Chain method), 135
	load_data() (in module fermipy.utils), 85
	load_diffuse_srcs() (fer- mipy.roi_model.ROIModel method), 79
	load_ds9_cmap() (in module fermipy.plotting), 91
	load_existing_catalog() (fer- mipy.roi_model.ROIModel method), 79
	load_fits_catalog() (fer- mipy.roi_model.ROIModel method), 79



`load_npy()` (in module `fermipy.utils`), 85  
`load_parameters_from_yaml()` (`fermipy.gtanalysis.GTAnalysis` method), 66  
`load_roi()` (`fermipy.gtanalysis.GTAnalysis` method), 67  
`load_source()` (`fermipy.roi_model.ROIModel` method), 79  
`load_sources()` (`fermipy.roi_model.ROIModel` method), 80  
`load_xml()` (`fermipy.gtanalysis.GTAnalysis` method), 67  
`load_xml()` (`fermipy.roi_model.ROIModel` method), 80  
`load_xml_elements()` (in module `fermipy.utils`), 85  
`load_yaml()` (in module `fermipy.utils`), 85  
`localize()` (`fermipy.gtanalysis.GTAnalysis` method), 67  
`localize()` (`fermipy.sourcefind.SourceFind` method), 93  
`lock_parameter()` (`fermipy.gtanalysis.GTAnalysis` method), 67  
`lock_source()` (`fermipy.gtanalysis.GTAnalysis` method), 67  
`log_ebins` (`fermipy.castro.ReferenceSpec` attribute), 107  
`log_energies` (`fermipy.gtanalysis.GTAnalysis` attribute), 67  
`log_level()` (in module `fermipy.logger`), 75  
`log_params` (`fermipy.spectrum.SpectralFunction` attribute), 96  
`log_to_params()` (`fermipy.spectrum.PLEXPcutoff` static method), 94  
`log_to_params()` (`fermipy.spectrum.PLSuperExpCutoff` static method), 94  
`loge_bounds` (`fermipy.gtanalysis.GTAnalysis` attribute), 67  
`Logger` (class in `fermipy.logger`), 75  
`logger` (`fermipy.gtanalysis.GTAnalysis` attribute), 67  
`loglevel` (`fermipy.gtanalysis.GTAnalysis` attribute), 68  
`LogParabola` (class in `fermipy.spectrum`), 94  
`lonlat_to_xyz()` (in module `fermipy.utils`), 85  
`ltcube()` (`fermipy.diffuse.name_policy.NameFactory` method), 164  
`ltcube_format` (`fermipy.diffuse.name_policy.NameFactory` attribute), 164  
`ltcube_moon()` (`fermipy.diffuse.name_policy.NameFactory` method), 164  
`ltcube_sun()` (`fermipy.diffuse.name_policy.NameFactory` method), 164  
`ltcubemoon_format` (`fermipy.diffuse.name_policy.NameFactory` attribute), 165  
`ltcubesun_format` (`fermipy.diffuse.name_policy.NameFactory` attribute), 165

## M

`main()` (`fermipy.jobs.chain.Chain` class method), 135  
`main()` (`fermipy.jobs.link.Link` class method), 129  
`main()` (`fermipy.jobs.scatter_gather.ScatterGather` class method), 133  
`main_browse()` (in module `fermipy.jobs.file_archive`), 151  
`main_browse()` (in module `fermipy.jobs.job_archive`), 154  
`make_attrs_class()` (in module `fermipy.defaults`), 60  
`make_catalog_comp_info()` (`fermipy.diffuse.catalog_src_manager.CatalogSourceManager` method), 174  
`make_catalog_comp_info_dict()` (`fermipy.diffuse.catalog_src_manager.CatalogSourceManager` method), 174  
`make_catalog_sources()` (in module `fermipy.diffuse.source_factory`), 167  
`make_cdisk_kernel()` (in module `fermipy.utils`), 85  
`make_cgauss_kernel()` (in module `fermipy.utils`), 85  
`make_coadd_hpx()` (in module `fermipy.skymap`), 100  
`make_coadd_map()` (in module `fermipy.skymap`), 100  
`make_coadd_wcs()` (in module `fermipy.skymap`), 100  
`make_composite_source()` (in module `fermipy.diffuse.source_factory`), 167  
`make_counts_spectrum_plot()` (in module `fermipy.plotting`), 92  
`make_cube_slice()` (in module `fermipy.plotting`), 92  
`make_default_dict()` (in module `fermipy.defaults`), 60  
`make_default_tuple()` (in module `fermipy.defaults`), 60  
`make_dict()` (`fermipy.jobs.file_archive.FileHandle` class method), 150  
`make_dict()` (`fermipy.jobs.job_archive.JobDetails` class method), 153  
`make_diffuse_comp_info()` (`fermipy.diffuse.diffuse_src_manager.DiffuseModelManager` method), 173  
`make_diffuse_comp_info()` (`fermipy.diffuse.diffuse_src_manager.GalpropMapManager` method), 171  
`make_diffuse_comp_info_dict()` (`fermipy.diffuse.diffuse_src_manager.DiffuseModelManager` method), 173  
`make_diffuse_comp_info_dict()` (`fermipy.diffuse.diffuse_src_manager.GalpropMapManager` method), 173

`method`), 171  
`make_disk_kernel()` (in module `fermipy.utils`), 85  
`make_extension_plots()` (`fermipy.plotting.AnalysisPlotter` method), 90  
`make_fermipy_config_yaml()` (`fermipy.diffuse.model_manager.ModelManager` method), 176  
`make_fermipy_roi_model_from_catalogs()` (`fermipy.diffuse.source_factory.SourceFactory` static method), 167  
`make_filenames()` (`fermipy.diffuse.name_policy.NameFactory` method), 165  
`make_fullkey()` (`fermipy.jobs.job_archive.JobDetails` static method), 153  
`make_gaussian_kernel()` (in module `fermipy.utils`), 86  
`make_gpfs_path()` (in module `fermipy.jobs.slac_impl`), 145  
`make_isotropic_source()` (in module `fermipy.diffuse.source_factory`), 167  
`make_job_details()` (`fermipy.jobs.job_archive.JobArchive` method), 151  
`make_key()` (`fermipy.diffuse.binning.Component` method), 163  
`make_library()` (`fermipy.diffuse.model_manager.ModelManager` method), 176  
`make_localization_plots()` (`fermipy.plotting.AnalysisPlotter` method), 90  
`make_mapcube_source()` (in module `fermipy.diffuse.source_factory`), 167  
`make_merged_name()` (`fermipy.diffuse.diffuse_src_manager.GalpropMapManager` method), 172  
`make_model_info()` (`fermipy.diffuse.model_manager.ModelManager` method), 176  
`make_model_rois()` (`fermipy.diffuse.model_manager.ModelInfo` method), 175  
`make_nfs_path()` (in module `fermipy.jobs.slac_impl`), 145  
`make_pixel_distance()` (in module `fermipy.utils`), 86  
`make_plots()` (`fermipy.gtanalysis.GTAnalysis` method), 68  
`make_point_source()` (in module `fermipy.diffuse.source_factory`), 167  
`make_psf_kernel()` (in module `fermipy.utils`), 86  
`make_radial_kernel()` (in module `fermipy.utils`), 86  
`make_residmap_plots()` (`fermipy.plotting.AnalysisPlotter` method), 90  
`make_ring_dict()` (`fermipy.diffuse.diffuse_src_manager.GalpropMapManager` method), 172  
`make_ring_filelist()` (`fermipy.diffuse.diffuse_src_manager.GalpropMapManager` method), 172  
`make_ring_filename()` (`fermipy.diffuse.diffuse_src_manager.GalpropMapManager` method), 172  
`make_roi()` (`fermipy.diffuse.source_factory.SourceFactory` class method), 167  
`make_roi_plots()` (`fermipy.plotting.AnalysisPlotter` method), 90  
`make_scratch_dirs()` (`fermipy.jobs.file_archive.FileStageManager` static method), 150  
`make_sed_plots()` (`fermipy.plotting.AnalysisPlotter` method), 90  
`make_sources()` (in module `fermipy.diffuse.source_factory`), 167  
`make_spatialmap_source()` (in module `fermipy.diffuse.source_factory`), 168  
`make_srcmap_manifest()` (`fermipy.diffuse.model_manager.ModelInfo` method), 175  
`make_srcmap_manifest()` (`fermipy.diffuse.model_manager.ModelManager` method), 176  
`make_table()` (`fermipy.jobs.file_archive.FileHandle` static method), 150  
`make_tables()` (`fermipy.jobs.job_archive.JobDetails` static method), 153  
`make_template()` (`fermipy.gtanalysis.GTAnalysis` method), 68  
`make_template_name()` (`fermipy.diffuse.diffuse_src_manager.DiffuseModelManager` method), 173  
`make_tsmmap_plots()` (`fermipy.plotting.AnalysisPlotter` method), 90  
`make_wcs_from_hpx()` (`fermipy.skymap.HpxMap` method), 98  
`make_xml_name()` (`fermipy.diffuse.diffuse_src_manager.DiffuseModelManager` method), 173  
`make_xml_name()` (`fermipy.diffuse.diffuse_src_manager.GalpropMapManager` method), 172  
`Map` (class in `fermipy.skymap`), 98  
`map` (`fermipy.plotting.ROIPlotter` attribute), 91  
`Map_Base` (class in `fermipy.skymap`), 99  
`map_files()` (`fermipy.jobs.file_archive.FileStageManager` method), 150

mapcube (*fermipy.roi\_model.MapCubeSource* attribute), 76  
 MapCubeSource (class in *fermipy.roi\_model*), 75  
 master\_srcmdl\_xml () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 master\_srcmdl\_xml\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 match\_regex\_list () (in module *fermipy.utils*), 86  
 match\_source () (*fermipy.roi\_model.ROIModel* method), 80  
 mcube () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 mcube\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 memoize () (in module *fermipy.utils*), 86  
 merge\_dict () (in module *fermipy.utils*), 86  
 merge\_list\_of\_dicts () (in module *fermipy.utils*), 86  
 merged\_components () (*fermipy.diffuse.diffuse\_src\_manager.GalpropMapManager* method), 172  
 merged\_gasmap () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 merged\_gasmap\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 merged\_sourcekey () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 merged\_sourcekey\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 merged\_srcmaps () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 merged\_srcmaps\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 MergeSrcmaps\_SG (class in *fermipy.diffuse.gt\_merge\_srcmaps*), 190  
 met\_to\_mjd () (in module *fermipy.utils*), 86  
 missing (*fermipy.jobs.file\_archive.FileStatus* attribute), 151  
 missing\_input\_files () (*fermipy.jobs.chain.Chain* method), 135  
 missing\_input\_files () (*fermipy.jobs.link.Link* method), 129  
 missing\_output\_files () (*fermipy.jobs.chain.Chain* method), 135  
 missing\_output\_files () (*fermipy.jobs.link.Link* method), 129  
 mkdir () (in module *fermipy.utils*), 86  
 mktime () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 mktime\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 MktimeFilterDict (class in *fermipy.diffuse.timefilter*), 166  
 mle () (*fermipy.castro.LnLFn* method), 106  
 mles () (*fermipy.castro.CastroData\_Base* method), 104  
 Model (class in *fermipy.roi\_model*), 76  
 model\_counts\_map () (*fermipy.gtanalysis.GTAnalysis* method), 68  
 model\_counts\_spectrum () (*fermipy.gtanalysis.GTAnalysis* method), 68  
 model\_yaml () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 model\_yaml\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 ModelComponent (class in *fermipy.diffuse.model\_manager*), 175  
 ModelComponentInfo (class in *fermipy.diffuse.model\_component*), 168, 170  
 ModelInfo (class in *fermipy.diffuse.model\_manager*), 175  
 ModelManager (class in *fermipy.diffuse.model\_manager*), 175

## N

n\_done (*fermipy.jobs.job\_archive.JobStatusVector* attribute), 154  
 n\_failed (*fermipy.jobs.job\_archive.JobStatusVector* attribute), 154  
 n\_pending (*fermipy.jobs.job\_archive.JobStatusVector* attribute), 154  
 n\_running (*fermipy.jobs.job\_archive.JobStatusVector* attribute), 154  
 n\_total (*fermipy.jobs.job\_archive.JobStatusVector* attribute), 154  
 n\_waiting (*fermipy.jobs.job\_archive.JobStatusVector* attribute), 154  
 name (*fermipy.roi\_model.Model* attribute), 76  
 NameFactory (class in *fermipy.diffuse.name\_policy*), 163  
 names (*fermipy.roi\_model.Model* attribute), 76  
 NativeInterface (class in *fermipy.jobs.native\_impl*), 144  
 nE (*fermipy.castro.CastroData* attribute), 102  
 nE (*fermipy.castro.ReferenceSpec* attribute), 107  
 nE (*fermipy.castro.TSCube* attribute), 108  
 nested\_sources (*fermipy.roi\_model.CompositeSource* attribute), 75

nested\_srcmdl\_xml() (fermipy.diffuse.name\_policy.NameFactory method), 165  
 nested\_srcmdl\_xml\_format (fermipy.diffuse.name\_policy.NameFactory attribute), 165  
 nll\_null (fermipy.castro.CastroData\_Base attribute), 104  
 nll\_offsets (fermipy.castro.CastroData\_Base attribute), 104  
 nN (fermipy.castro.TSCube attribute), 109  
 no\_file (fermipy.jobs.file\_archive.FileStatus attribute), 151  
 no\_flags (fermipy.jobs.file\_archive.FileFlags attribute), 149  
 no\_job (fermipy.jobs.job\_archive.JobStatus attribute), 153  
 norm (fermipy.castro.SpecData attribute), 108  
 norm\_derivative() (fermipy.castro.CastroData\_Base method), 104  
 norm\_err (fermipy.castro.SpecData attribute), 108  
 norm\_type (fermipy.castro.CastroData\_Base attribute), 104  
 norm\_type (fermipy.castro.LnLFn attribute), 106  
 normcube (fermipy.castro.TSCube attribute), 109  
 normmap (fermipy.castro.TSCube attribute), 109  
 not\_ready (fermipy.jobs.job\_archive.JobStatus attribute), 153  
 nparam() (fermipy.spectrum.DMFitFunction static method), 94  
 nparam() (fermipy.spectrum.LogParabola static method), 94  
 nparam() (fermipy.spectrum.PLEXPcutoff static method), 94  
 nparam() (fermipy.spectrum.PLSuperExpCutoff static method), 95  
 nparam() (fermipy.spectrum.PowerLaw static method), 95  
 npix (fermipy.gtanalysis.GTAnalysis attribute), 68  
 npix (fermipy.skymap.Map attribute), 99  
 NULL\_MODEL (fermipy.diffuse.gt\_merge\_srcmaps.GtMergeSrcmaps attribute), 181  
 NULL\_MODEL (fermipy.diffuse.gt\_srcmap\_partial.GtSrcmapsDiffuse attribute), 182  
 NULL\_MODEL (fermipy.diffuse.gt\_srcmaps\_catalog.GtSrcmapsCatalog attribute), 183  
 nvals (fermipy.castro.TSCube attribute), 109  
 nx (fermipy.castro.CastroData\_Base attribute), 105  
 ny (fermipy.castro.CastroData\_Base attribute), 105  
 onesided\_cl\_to\_dlnl() (in module fermipy.utils), 86  
 onesided\_dlnl\_to\_cl() (in module fermipy.utils), 87  
 open\_outsrcmap() (fermipy.diffuse.gt\_assemble\_model.AssembleModel static method), 184  
 optimize() (fermipy.gtanalysis.GTAnalysis method), 68  
 out\_ch\_mask (fermipy.jobs.file\_archive.FileFlags attribute), 149  
 out\_stage\_mask (fermipy.jobs.file\_archive.FileFlags attribute), 149  
 outdir (fermipy.gtanalysis.GTAnalysis attribute), 69  
 output\_files (fermipy.jobs.file\_archive.FileDict attribute), 148  
 output\_files\_to\_stage (fermipy.jobs.file\_archive.FileDict attribute), 148  
 output\_mask (fermipy.jobs.file\_archive.FileFlags attribute), 149  
 overlap\_slices() (in module fermipy.utils), 87

## P

parabola() (in module fermipy.utils), 87  
 params (fermipy.roi\_model.Model attribute), 76  
 params (fermipy.spectrum.SEDFunction attribute), 95  
 params (fermipy.spectrum.SpectralFunction attribute), 96  
 params\_to\_log() (fermipy.spectrum.PLEXPcutoff static method), 94  
 params\_to\_log() (fermipy.spectrum.PLSuperExpCutoff static method), 95  
 partial\_failed (fermipy.jobs.job\_archive.JobStatus attribute), 153  
 path\_to\_xmlpath() (in module fermipy.utils), 88  
 pending (fermipy.jobs.job\_archive.JobStatus attribute), 153  
 pix\_center (fermipy.skymap.Map attribute), 99  
 pix\_size (fermipy.skymap.Map attribute), 99  
 PLEXPcutoff (class in fermipy.spectrum), 94  
 plot() (fermipy.plotting.ExtensionPlotter method), 90  
 plot() (fermipy.plotting.ImagePlotter method), 90  
 plot\_diffuse (fermipy.plotting.ROIPlotter method), 91  
 plot() (fermipy.plotting.SEDPlotter method), 91  
 plot\_catalog() (fermipy.plotting.ROIPlotter method), 91  
 plot\_error\_ellipse() (in module fermipy.plotting), 92  
 plot\_flux\_points() (fermipy.plotting.SEDPlotter static method), 91  
 plot\_lnlscan() (fermipy.plotting.SEDPlotter static method), 91  
 plot\_markers() (in module fermipy.plotting), 92



`plot_model()` (*fermipy.plotting.SEDPlotter* static method), 91  
`plot_projection()` (*fermipy.plotting.ROIPlotter* method), 91  
`plot_resid()` (*fermipy.plotting.SEDPlotter* static method), 91  
`plot_roi()` (*fermipy.plotting.ROIPlotter* method), 91  
`plot_sed()` (*fermipy.plotting.SEDPlotter* static method), 91  
`plot_sources()` (*fermipy.plotting.ROIPlotter* method), 91  
`PlotCastro` (class in *fermipy.jobs.target\_plotting*), 139  
`PlotCastro_SG` (class in *fermipy.jobs.target\_plotting*), 143  
`plotter` (*fermipy.gtanalysis.GTAnalysis* attribute), 69  
`PLSuperExpCutoff` (class in *fermipy.spectrum*), 94  
`point_sources` (*fermipy.roi\_model.ROIModel* attribute), 80  
`PointSourceInfo` (class in *fermipy.diffuse.model\_component*), 170  
`poisson_lnl()` (in module *fermipy.residmap*), 112  
`poisson_log_like()` (in module *fermipy.tsmmap*), 111  
`poly_to_parabola()` (in module *fermipy.utils*), 88  
`PowerLaw` (class in *fermipy.spectrum*), 95  
`prettify_xml()` (in module *fermipy.utils*), 88  
`print_chain_summary()` (*fermipy.jobs.file\_archive.FileDict* method), 148  
`print_config()` (*fermipy.config.Configurable* method), 59  
`print_config()` (*fermipy.gtanalysis.GTAnalysis* method), 69  
`print_failed()` (*fermipy.jobs.scatter\_gather.ScatterGather* method), 133  
`print_model()` (*fermipy.gtanalysis.GTAnalysis* method), 69  
`print_params()` (*fermipy.gtanalysis.GTAnalysis* method), 69  
`print_roi()` (*fermipy.gtanalysis.GTAnalysis* method), 69  
`print_status()` (*fermipy.jobs.chain.Chain* method), 135  
`print_summary()` (*fermipy.jobs.chain.Chain* method), 135  
`print_summary()` (*fermipy.jobs.file\_archive.FileDict* method), 149  
`print_summary()` (*fermipy.jobs.link.Link* method), 129  
`print_summary()` (*fermipy.jobs.scatter\_gather.ScatterGather* method), 133  
`print_update()` (*fermipy.jobs.scatter\_gather.ScatterGather* method), 133  
`profile()` (*fermipy.gtanalysis.GTAnalysis* method), 69  
`profile_norm()` (*fermipy.gtanalysis.GTAnalysis* method), 69  
`proj` (*fermipy.plotting.ROIPlotter* attribute), 91  
`project()` (in module *fermipy.utils*), 88  
`projtype` (*fermipy.gtanalysis.GTAnalysis* attribute), 69  
`projtype` (*fermipy.plotting.ImagePlotter* attribute), 90  
`projtype` (*fermipy.plotting.ROIPlotter* attribute), 91  
`psf_scale_fn` (*fermipy.roi\_model.Model* attribute), 76

## R

`radec` (*fermipy.roi\_model.Source* attribute), 81  
`RandomDirGen` (class in *fermipy.jobs.target\_sim*), 138  
`RandomDirGen_SG` (class in *fermipy.jobs.target\_sim*), 141  
`read_catalog_info_yaml()` (*fermipy.diffuse.catalog\_src\_manager.CatalogSourceManager* method), 174  
`read_diffuse_component_yaml()` (*fermipy.diffuse.diffuse\_src\_manager.DiffuseModelManager* static method), 174  
`read_galprop_rings_yaml()` (*fermipy.diffuse.diffuse\_src\_manager.GalpropMapManager* method), 172  
`read_map_from_fits()` (in module *fermipy.skymap*), 100  
`read_model_yaml()` (*fermipy.diffuse.model\_manager.ModelManager* method), 176  
`readlines()` (in module *fermipy.diffuse.utils*), 168  
`ready` (*fermipy.jobs.job\_archive.JobStatus* attribute), 153  
`rebin_map()` (in module *fermipy.utils*), 88  
`ref_dnde` (*fermipy.castro.ReferenceSpec* attribute), 107  
`ref_eflux` (*fermipy.castro.ReferenceSpec* attribute), 107  
`ref_flux` (*fermipy.castro.ReferenceSpec* attribute), 107  
`ref_npred` (*fermipy.castro.ReferenceSpec* attribute), 107  
`ReferenceSpec` (class in *fermipy.castro*), 106  
`refSpec` (*fermipy.castro.CastroData* attribute), 102  
`refSpec` (*fermipy.castro.TSCube* attribute), 109  
`register_class()` (*fermipy.jobs.link.Link* class method), 129  
`register_file()` (*fermipy.jobs.file\_archive.FileArchive* method), 147

```

register_job() (fermipy.jobs.job_archive.JobArchive method), 152
register_job_from_link() (fermipy.jobs.job_archive.JobArchive method), 152
register_jobs() (fermipy.jobs.job_archive.JobArchive method), 152
reload_source() (fermipy.gtanalysis.GTAnalysis method), 69
reload_sources() (fermipy.gtanalysis.GTAnalysis method), 69
remove_file() (in module fermipy.jobs.sys_interface), 144
remove_jobs() (fermipy.jobs.job_archive.JobArchive method), 152
remove_prior() (fermipy.gtanalysis.GTAnalysis method), 69
remove_priors() (fermipy.gtanalysis.GTAnalysis method), 69
removed (fermipy.jobs.job_archive.JobStatus attribute), 153
reset() (fermipy.jobs.job_archive.JobStatusVector method), 154
residmap() (fermipy.gtanalysis.GTAnalysis method), 70
residmap() (fermipy.residmap.ResidMapGenerator method), 111
ResidMapGenerator (class in fermipy.residmap), 111
residual_cr() (fermipy.diffuse.name_policy.NameFactory method), 165
residual_cr_format (fermipy.diffuse.name_policy.NameFactory attribute), 165
ResidualCR (class in fermipy.diffuse.residual_cr), 184
ResidualCR_SG (class in fermipy.diffuse.residual_cr), 190, 192
ResidualCRChain (class in fermipy.diffuse.residual_cr), 199
resolve_file_path() (in module fermipy.utils), 88
resolve_file_path_list() (in module fermipy.utils), 88
resolve_path() (in module fermipy.utils), 88
resubmit() (fermipy.jobs.scatter_gather.ScatterGather method), 133
ring_dict() (fermipy.diffuse.diffuse_src_manager.GalpropMapManager method), 172
rm_mask (fermipy.jobs.file_archive.FileFlags attribute), 149
rmint_mask (fermipy.jobs.file_archive.FileFlags attribute), 149
roi (fermipy.gtanalysis.GTAnalysis attribute), 70
ROIModel (class in fermipy.roi_model), 76
ROIPlotter (class in fermipy.plotting), 90
run() (fermipy.jobs.chain.Chain method), 135
run() (fermipy.jobs.link.Link method), 129
run() (fermipy.jobs.scatter_gather.ScatterGather method), 133
run() (fermipy.plotting.AnalysisPlotter method), 90
run_analysis() (fermipy.diffuse.gt_assemble_model.AssembleModel method), 184
run_analysis() (fermipy.diffuse.gt_assemble_model.InitModel method), 183
run_analysis() (fermipy.diffuse.gt_merge_srcmaps.GtMergeSrcmaps method), 182
run_analysis() (fermipy.diffuse.gt_srcmap_partial.GtSrcmapsDiffuse method), 182
run_analysis() (fermipy.diffuse.gt_srcmaps_catalog.GtSrcmapsCatalog method), 183
run_analysis() (fermipy.diffuse.residual_cr.ResidualCR method), 185
run_analysis() (fermipy.jobs.app_link.AppLink method), 132
run_analysis() (fermipy.jobs.chain.Chain method), 135
run_analysis() (fermipy.jobs.gtlink.Gtlink method), 130
run_analysis() (fermipy.jobs.link.Link method), 129
run_analysis() (fermipy.jobs.scatter_gather.ScatterGather method), 134
run_analysis() (fermipy.jobs.target_analysis.AnalyzeROI method), 136
run_analysis() (fermipy.jobs.target_analysis.AnalyzeSED method), 137
run_analysis() (fermipy.jobs.target_collect.CollectSED method), 137
run_analysis() (fermipy.jobs.target_plotting.PlotCastro method), 137
run_analysis() (fermipy.jobs.target_sim.CopyBaseROI method), 138
run_analysis() (fermipy.jobs.target_sim.RandomDirGen method),

```

138  
 run\_analysis() (fermipy.jobs.target\_sim.SimulateROI method), 139  
 run\_command() (fermipy.jobs.gtlink.Gtlink method), 130  
 run\_command() (fermipy.jobs.link.Link method), 129  
 run\_gtapp() (in module fermipy.jobs.gtlink), 131  
 run\_jobs() (fermipy.jobs.scatter\_gather.ScatterGather method), 134  
 run\_with\_log() (fermipy.jobs.link.Link method), 130  
 running (fermipy.jobs.job\_archive.JobStatus attribute), 153

## S

scale (fermipy.spectrum.SEDFunctor attribute), 95  
 scale (fermipy.spectrum.SpectralFunction attribute), 96  
 scale\_parameter() (fermipy.gtanalysis.GTAnalysis method), 70  
 scale\_parameter() (in module fermipy.utils), 88  
 scatter\_link (fermipy.jobs.scatter\_gather.ScatterGather attribute), 134  
 ScatterGather (class in fermipy.jobs.scatter\_gather), 132  
 schema (fermipy.config.Configurable attribute), 59  
 schema (fermipy.gtanalysis.GTAnalysis attribute), 70  
 sed (fermipy.plotting.SEDPlotter attribute), 91  
 sed() (fermipy.gtanalysis.GTAnalysis method), 70  
 sed() (fermipy.sed.SEDGenerator method), 92  
 SEDEFuxFunctor (class in fermipy.spectrum), 95  
 SEDEFuxFunctor (class in fermipy.spectrum), 95  
 SEDFunctor (class in fermipy.spectrum), 95  
 SEDGenerator (class in fermipy.sed), 92  
 SEDPlotter (class in fermipy.plotting), 91  
 select() (fermipy.diffuse.name\_policy.NameFactory method), 165  
 select\_format (fermipy.diffuse.name\_policy.NameFactory attribute), 165  
 separation() (fermipy.roi\_model.Source method), 81  
 separation\_cos\_angle() (in module fermipy.utils), 88  
 set\_channel() (fermipy.spectrum.DMFitFunction method), 94  
 set\_edisp\_flag() (fermipy.gtanalysis.GTAnalysis method), 70  
 set\_energy\_range() (fermipy.gtanalysis.GTAnalysis method), 70  
 set\_free\_param\_vector() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_geom() (fermipy.roi\_model.ROIModel method), 80  
 set\_log\_level() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_name() (fermipy.roi\_model.Model method), 76  
 set\_norm() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_norm\_bounds() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_norm\_scale() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_parameter() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_parameter\_bounds() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_parameter\_error() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_parameter\_scale() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_position() (fermipy.roi\_model.Source method), 81  
 set\_psf\_scale\_fn() (fermipy.roi\_model.Model method), 76  
 set\_radec() (fermipy.roi\_model.Source method), 81  
 set\_random\_seed() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_roi\_direction() (fermipy.roi\_model.Source method), 81  
 set\_roi\_geom() (fermipy.roi\_model.Source method), 81  
 set\_source\_dnde() (fermipy.gtanalysis.GTAnalysis method), 71  
 set\_source\_morphology() (fermipy.gtanalysis.GTAnalysis method), 72  
 set\_source\_spectrum() (fermipy.gtanalysis.GTAnalysis method), 72  
 set\_spatial\_model() (fermipy.roi\_model.Source method), 81  
 set\_spectral\_pars() (fermipy.roi\_model.Model method), 76  
 set\_weights\_map() (fermipy.gtanalysis.GTAnalysis method), 72  
 setup() (fermipy.gtanalysis.GTAnalysis method), 72  
 setup() (fermipy.logger.Logger static method), 75  
 setup\_projection\_axis() (fermipy.plotting.ROIPlotter static method), 91  
 simulate\_roi() (fermipy.gtanalysis.GTAnalysis method), 72  
 simulate\_source() (fermipy.gtanalysis.GTAnalysis method), 72  
 SimulateROI (class in fermipy.jobs.target\_sim), 138  
 SimulateROI\_SG (class in fermipy.jobs.target\_sim), 142  
 skydir (fermipy.roi\_model.ROIModel attribute), 80  
 skydir (fermipy.roi\_model.Source attribute), 81

skydir (*fermipy.skymap.Map* attribute), 99  
 SlacInterface (*class in fermipy.jobs.slac\_impl*), 145  
 Source (*class in fermipy.roi\_model*), 80  
 source\_info\_dict (*fermipy.diffuse.source\_factory.SourceFactory* attribute), 167  
 SourceFactory (*class in fermipy.diffuse.source\_factory*), 166  
 SourceFind (*class in fermipy.sourcefind*), 92  
 sourcekey () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 sourcekey\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 sourcekeys () (*fermipy.diffuse.diffuse\_src\_manager.DiffuseSrcManager* method), 174  
 sources (*fermipy.diffuse.source\_factory.SourceFactory* attribute), 167  
 sources (*fermipy.roi\_model.ROIModel* attribute), 80  
 sparse\_counts\_map () (*fermipy.skymap.HpxMap* method), 98  
 spatial\_pars (*fermipy.roi\_model.Model* attribute), 76  
 spatial\_pars\_from\_catalog () (*in module fermipy.roi\_model*), 82  
 SpecData (*class in fermipy.castro*), 107  
 spectral\_fn (*fermipy.spectrum.SEDFuncor* attribute), 95  
 spectral\_pars (*fermipy.roi\_model.Model* attribute), 76  
 spectral\_pars\_from\_catalog () (*in module fermipy.roi\_model*), 82  
 spectral\_template () (*fermipy.diffuse.name\_policy.NameFactory* method), 165  
 spectral\_template\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 165  
 SpectralFunction (*class in fermipy.spectrum*), 95  
 SpectralLibrary (*class in fermipy.diffuse.spectral*), 166  
 spectrum\_loglike () (*fermipy.castro.CastroData* method), 102  
 split\_bin\_edges () (*in module fermipy.utils*), 88  
 split\_comp\_info () (*fermipy.diffuse.catalog\_src\_manager.CatalogSourceManager* method), 175  
 split\_comp\_info\_dict () (*fermipy.diffuse.catalog\_src\_manager.CatalogSourceManager* method), 175  
 split\_fullkey () (*fermipy.jobs.job\_archive.JobDetails* static method), 153  
 split\_local\_path () (*fermipy.jobs.job\_archive.JobDetails* static method), 153  
 FileStageManager (*fermipy.jobs.file\_archive.FileStageManager* method), 150  
 SplitAndBin (*class in fermipy.diffuse.gt\_split\_and\_bin*), 195  
 SplitAndBin\_SG (*class in fermipy.diffuse.gt\_split\_and\_bin*), 193  
 SplitAndBinChain (*class in fermipy.diffuse.gt\_split\_and\_bin*), 195  
 SplitAndMktime (*class in fermipy.diffuse.gt\_split\_and\_mvertime*), 196  
 SplitAndMktime\_SG (*class in fermipy.diffuse.gt\_split\_and\_mvertime*), 193  
 SplitAndMktimeChain (*class in fermipy.diffuse.gt\_split\_and\_mvertime*), 197  
 DiffuseModelManager (*fermipy.diffuse.catalog\_src\_manager.CatalogSourceManager* method), 175  
 src\_name\_cols (*fermipy.roi\_model.ROIModel* attribute), 80  
 srcmaps () (*fermipy.diffuse.name\_policy.NameFactory* method), 166  
 srcmaps\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 166  
 SrcmapsCatalog\_SG (*class in fermipy.diffuse.gt\_srcmaps\_catalog*), 191  
 SrcmapsDiffuse\_SG (*class in fermipy.diffuse.gt\_srcmap\_partial*), 191  
 srcmdl\_xml () (*fermipy.diffuse.name\_policy.NameFactory* method), 166  
 srcmdl\_xml\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 166  
 stack\_nll () (*fermipy.castro.CastroData\_Base* static method), 105  
 stage\_input () (*fermipy.gtanalysis.GTAnalysis* method), 73  
 stage\_output () (*fermipy.gtanalysis.GTAnalysis* method), 73  
 stageable (*fermipy.jobs.file\_archive.FileFlags* attribute), 149  
 stamp () (*fermipy.diffuse.name\_policy.NameFactory* method), 166  
 stamp\_format (*fermipy.diffuse.name\_policy.NameFactory* attribute), 166  
 StreamLogger (*class in fermipy.logger*), 75  
 Manager\_exited (*fermipy.jobs.native\_impl.NativeInterface* attribute), 145  
 Manager\_exited (*fermipy.jobs.slac\_impl.SlacInterface* attribute), 145  
 string\_exited (*fermipy.jobs.sys\_interface.SysInterface* attribute), 144  
 string\_successful (*fermipy.jobs.sys\_interface.SysInterface* attribute), 144



*mipy.jobs.native\_impl.NativeInterface* attribute), 145  
 string\_successful (*fermipy.jobs.slac\_impl.SlacInterface* attribute), 145  
 string\_successful (*fermipy.jobs.sys\_interface.SysInterface* attribute), 144  
 strip\_suffix() (in module *fermipy.utils*), 88  
 submit\_jobs() (*fermipy.jobs.native\_impl.NativeInterface* method), 145  
 submit\_jobs() (*fermipy.jobs.slac\_impl.SlacInterface* method), 145  
 submit\_jobs() (*fermipy.jobs.sys\_interface.SysInterface* method), 144  
 sum\_bins() (in module *fermipy.utils*), 88  
 sum\_over\_energy() (*fermipy.skymap.HpxMap* method), 98  
 sum\_over\_energy() (*fermipy.skymap.Map* method), 99  
 sum\_over\_energy() (*fermipy.skymap.Map\_Base* method), 100  
 SumRings\_SG (class in *fermipy.diffuse.job\_library*), 189  
 SunMoonChain (class in *fermipy.diffuse.solar*), 200  
 superseded (*fermipy.jobs.file\_archive.FileStatus* attribute), 151  
 swap\_scheme() (*fermipy.skymap.HpxMap* method), 98  
 SysInterface (class in *fermipy.jobs.sys\_interface*), 143

## T

table (*fermipy.jobs.file\_archive.FileArchive* attribute), 147  
 table (*fermipy.jobs.job\_archive.JobArchive* attribute), 152  
 table\_file (*fermipy.jobs.file\_archive.FileArchive* attribute), 147  
 table\_file (*fermipy.jobs.job\_archive.JobArchive* attribute), 152  
 table\_ids (*fermipy.jobs.job\_archive.JobArchive* attribute), 152  
 temp\_files (*fermipy.jobs.file\_archive.FileDict* attribute), 149  
 temp\_removed (*fermipy.jobs.file\_archive.FileStatus* attribute), 151  
 template\_sunmoon() (*fermipy.diffuse.name\_policy.NameFactory* method), 166  
 templatesunmoon\_format (*fermipy.diffuse.name\_policy.NameFactory* at-

tribute), 166  
 test() (in module *fermipy*), 113  
 test\_spectra() (*fermipy.castro.CastroData* method), 102  
 test\_spectra\_of\_peak() (*fermipy.castro.TSCube* method), 109  
 tmax (*fermipy.gtanalysis.GTAnalysis* attribute), 73  
 tmin (*fermipy.gtanalysis.GTAnalysis* attribute), 73  
 to\_ds9() (*fermipy.roi\_model.ROIModel* method), 80  
 tolist() (in module *fermipy.utils*), 88  
 topkey (*fermipy.jobs.job\_archive.JobDetails* attribute), 153  
 topkey (*fermipy.jobs.link.Link* attribute), 130  
 truncate\_array() (in module *fermipy.tsmmap*), 111  
 truncate\_colormap() (in module *fermipy.plotting*), 92  
 TS() (*fermipy.castro.LnLFn* method), 105  
 ts\_cumul (*fermipy.castro.TSCube* attribute), 109  
 TS\_spectrum() (*fermipy.castro.CastroData\_Base* method), 103  
 ts\_vals() (*fermipy.castro.CastroData\_Base* method), 105  
 TSCube (class in *fermipy.castro*), 108  
 tscube (*fermipy.castro.TSCube* attribute), 109  
 tscube() (*fermipy.gtanalysis.GTAnalysis* method), 73  
 tscube() (*fermipy.tsmmap.TSCubeGenerator* method), 109  
 TSCubeGenerator (class in *fermipy.tsmmap*), 109  
 tsmmap (*fermipy.castro.TSCube* attribute), 109  
 tsmmap() (*fermipy.gtanalysis.GTAnalysis* method), 73  
 tsmmap() (*fermipy.tsmmap.TSMMapGenerator* method), 110  
 TSMMapGenerator (class in *fermipy.tsmmap*), 110  
 twosided\_cl\_to\_dlnl() (in module *fermipy.utils*), 89  
 twosided\_dlnl\_to\_cl() (in module *fermipy.utils*), 89

## U

ud\_grade() (*fermipy.skymap.HpxMap* method), 98  
 unicode\_representer() (in module *fermipy.utils*), 89  
 unicode\_to\_str() (in module *fermipy.utils*), 89  
 unknown (*fermipy.jobs.job\_archive.JobStatus* attribute), 153  
 unzero\_source() (*fermipy.gtanalysis.GTAnalysis* method), 74  
 update() (*fermipy.diffuse.model\_component.CatalogInfo* method), 169  
 update() (*fermipy.diffuse.model\_component.GalpropMergedRingInfo* method), 170  
 update() (*fermipy.diffuse.model\_component.ModelComponentInfo* method), 169, 170

`update()` (*fermipy.diffuse.spectral.SpectralLibrary* method), 166

`update()` (*fermipy.jobs.file\_archive.FileDict* method), 149

`update_args()` (*fermipy.jobs.chain.Chain* method), 135

`update_args()` (*fermipy.jobs.gtlink.Gtlink* method), 130

`update_args()` (*fermipy.jobs.link.Link* method), 130

`update_args()` (*fermipy.jobs.scatter\_gather.ScatterGather* method), 134

`update_base_dict()` (*fermipy.diffuse.name\_policy.NameFactory* method), 166

`update_bounds()` (in module *fermipy.utils*), 89

`update_data()` (*fermipy.roi\_model.Model* method), 76

`update_data()` (*fermipy.roi\_model.Source* method), 81

`update_file()` (*fermipy.jobs.file\_archive.FileArchive* method), 147

`update_file_status()` (*fermipy.jobs.file\_archive.FileArchive* method), 147

`update_from_schema()` (in module *fermipy.config*), 59

`update_from_source()` (*fermipy.roi\_model.Model* method), 76

`update_gtapp()` (in module *fermipy.jobs.gtlink*), 131

`update_job()` (*fermipy.jobs.job\_archive.JobArchive* method), 152

`update_job_status()` (*fermipy.jobs.job\_archive.JobArchive* method), 152

`update_keys()` (in module *fermipy.utils*), 89

`update_source()` (*fermipy.gtanalysis.GTAnalysis* method), 74

`update_spectral_pars()` (*fermipy.roi\_model.Model* method), 76

`update_table_row()` (*fermipy.jobs.file\_archive.FileHandle* method), 150

`update_table_row()` (*fermipy.jobs.job\_archive.JobDetails* method), 153

usage (*fermipy.diffuse.diffuse\_analysis.CatalogCompChain* attribute), 199

usage (*fermipy.diffuse.diffuse\_analysis.DiffuseAnalysisChain* attribute), 199

usage (*fermipy.diffuse.diffuse\_analysis.DiffuseCompChain* attribute), 198

usage (*fermipy.diffuse.gt\_assemble\_model.AssembleModel* attribute), 184

usage (*fermipy.diffuse.gt\_assemble\_model.AssembleModel\_SG* attribute), 192

usage (*fermipy.diffuse.gt\_assemble\_model.AssembleModelChain* attribute), 199

usage (*fermipy.diffuse.gt\_assemble\_model.InitModel* attribute), 183

usage (*fermipy.diffuse.gt\_coadd\_split.CoaddSplit* attribute), 195

usage (*fermipy.diffuse.gt\_coadd\_split.CoaddSplit\_SG* attribute), 187

usage (*fermipy.diffuse.gt\_merge\_srcmaps.GtMergeSrcmaps* attribute), 182

usage (*fermipy.diffuse.gt\_merge\_srcmaps.MergeSrcmaps\_SG* attribute), 191

usage (*fermipy.diffuse.gt\_split\_and\_bin.SplitAndBin* attribute), 195

usage (*fermipy.diffuse.gt\_split\_and\_bin.SplitAndBin\_SG* attribute), 193

usage (*fermipy.diffuse.gt\_split\_and\_bin.SplitAndBinChain* attribute), 196

usage (*fermipy.diffuse.gt\_split\_and\_mktime.SplitAndMktime* attribute), 197

usage (*fermipy.diffuse.gt\_split\_and\_mktime.SplitAndMktime\_SG* attribute), 194

usage (*fermipy.diffuse.gt\_split\_and\_mktime.SplitAndMktimeChain* attribute), 198

usage (*fermipy.diffuse.gt\_srcmap\_partial.GtSrcmapsDiffuse* attribute), 182

usage (*fermipy.diffuse.gt\_srcmap\_partial.SrcmapsDiffuse\_SG* attribute), 191

usage (*fermipy.diffuse.gt\_srcmaps\_catalog.GtSrcmapsCatalog* attribute), 183

usage (*fermipy.diffuse.gt\_srcmaps\_catalog.SrcmapsCatalog\_SG* attribute), 192

usage (*fermipy.diffuse.job\_library.GatherSrcmaps\_SG* attribute), 188

usage (*fermipy.diffuse.job\_library.Gtexpcube2\_SG* attribute), 185

usage (*fermipy.diffuse.job\_library.Gtlink\_bin* attribute), 177

usage (*fermipy.diffuse.job\_library.Gtlink\_expcube2* attribute), 177

usage (*fermipy.diffuse.job\_library.Gtlink\_ltcube* attribute), 179

usage (*fermipy.diffuse.job\_library.Gtlink\_ltsum* attribute), 178

usage (*fermipy.diffuse.job\_library.Gtlink\_mktime* attribute), 178

usage (*fermipy.diffuse.job\_library.Gtlink\_scrmaps* attribute), 178

usage (*fermipy.diffuse.job\_library.Gtlink\_select* attribute), 177

usage (*fermipy.diffuse.job\_library.Gtltsun\_SG* at-

- tribute), 186
- usage (*fermipy.diffuse.job\_library.Healview\_SG attribute*), 189
- usage (*fermipy.diffuse.job\_library.Link\_FermipyCoadd attribute*), 180
- usage (*fermipy.diffuse.job\_library.Link\_FermipyGatherSrcmaps attribute*), 180
- usage (*fermipy.diffuse.job\_library.Link\_FermipyHealview attribute*), 181
- usage (*fermipy.diffuse.job\_library.Link\_FermipyVstack attribute*), 181
- usage (*fermipy.diffuse.job\_library.SumRings\_SG attribute*), 189, 190
- usage (*fermipy.diffuse.job\_library.Vstack\_SG attribute*), 188
- usage (*fermipy.diffuse.residual\_cr.ResidualCR attribute*), 185
- usage (*fermipy.diffuse.residual\_cr.ResidualCR\_SG attribute*), 190, 193
- usage (*fermipy.diffuse.residual\_cr.ResidualCRChain attribute*), 200
- usage (*fermipy.diffuse.solar.Gtexpcube2wcs\_SG attribute*), 186
- usage (*fermipy.diffuse.solar.Gtexphpsun\_SG attribute*), 187
- usage (*fermipy.diffuse.solar.Gtlink\_expcube2\_wcs attribute*), 179
- usage (*fermipy.diffuse.solar.Gtlink\_exphpsun attribute*), 179
- usage (*fermipy.diffuse.solar.Gtlink\_sunttemp attribute*), 180
- usage (*fermipy.diffuse.solar.Gtsunttemp\_SG attribute*), 187
- usage (*fermipy.diffuse.solar.SunMoonChain attribute*), 200
- usage (*fermipy.jobs.app\_link.AppLink attribute*), 132
- usage (*fermipy.jobs.gtlink.Gtlink attribute*), 131
- usage (*fermipy.jobs.link.Link attribute*), 130
- usage (*fermipy.jobs.scatter\_gather.ScatterGather attribute*), 134
- usage (*fermipy.jobs.target\_analysis.AnalyzeROI attribute*), 136
- usage (*fermipy.jobs.target\_analysis.AnalyzeROI\_SG attribute*), 140
- usage (*fermipy.jobs.target\_analysis.AnalyzeSED attribute*), 137
- usage (*fermipy.jobs.target\_analysis.AnalyzeSED\_SG attribute*), 140
- usage (*fermipy.jobs.target\_collect.CollectSED attribute*), 137
- usage (*fermipy.jobs.target\_collect.CollectSED\_SG attribute*), 141
- usage (*fermipy.jobs.target\_plotting.PlotCastro attribute*), 139
- usage (*fermipy.jobs.target\_plotting.PlotCastro\_SG attribute*), 143
- usage (*fermipy.jobs.target\_sim.CopyBaseROI attribute*), 138
- usage (*fermipy.jobs.target\_sim.CopyBaseROI\_SG attribute*), 141
- usage (*fermipy.jobs.target\_sim.RandomDirGen attribute*), 138
- usage (*fermipy.jobs.target\_sim.RandomDirGen\_SG attribute*), 142
- usage (*fermipy.jobs.target\_sim.SimulateROI attribute*), 139
- usage (*fermipy.jobs.target\_sim.SimulateROI\_SG attribute*), 143
- ## V
- val\_to\_bin() (in module *fermipy.utils*), 89
- val\_to\_bin\_bounded() (in module *fermipy.utils*), 89
- val\_to\_edge() (in module *fermipy.utils*), 89
- val\_to\_pix() (in module *fermipy.utils*), 89
- validate\_config() (in module *fermipy.config*), 60
- validate\_from\_schema() (in module *fermipy.config*), 60
- validate\_option() (in module *fermipy.config*), 60
- values() (*fermipy.diffuse.timefilter.MktimeFilterDict method*), 166
- Vstack\_SG (class in *fermipy.diffuse.job\_library*), 188
- ## W
- wcs (*fermipy.skymap.Map attribute*), 99
- weight\_map() (*fermipy.gtanalysis.GTAnalysis method*), 74
- width (*fermipy.skymap.Map attribute*), 99
- workdir (*fermipy.gtanalysis.GTAnalysis attribute*), 74
- write() (*fermipy.logger.StreamLogger method*), 75
- write\_config() (*fermipy.config.Configurable method*), 59
- write\_config() (*fermipy.gtanalysis.GTAnalysis method*), 74
- write\_ds9region() (*fermipy.roi\_model.ROIModel method*), 80
- write\_fits() (*fermipy.gtanalysis.GTAnalysis method*), 74
- write\_fits() (*fermipy.roi\_model.ROIModel method*), 80
- write\_model\_map() (*fermipy.gtanalysis.GTAnalysis method*), 74
- write\_roi() (*fermipy.gtanalysis.GTAnalysis method*), 74
- write\_table\_file() (*fermipy.jobs.file\_archive.FileArchive method*), 147

[write\\_table\\_file\(\)](#) (*fermipy.jobs.job\_archive.JobArchive* method), 152  
[write\\_weight\\_map\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 74  
[write\\_xml\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 75  
[write\\_xml\(\)](#) (*fermipy.roi\_model.CompositeSource* method), 75  
[write\\_xml\(\)](#) (*fermipy.roi\_model.IsoSource* method), 75  
[write\\_xml\(\)](#) (*fermipy.roi\_model.MapCubeSource* method), 76  
[write\\_xml\(\)](#) (*fermipy.roi\_model.ROIModel* method), 80  
[write\\_xml\(\)](#) (*fermipy.roi\_model.Source* method), 81  
[write\\_yaml\(\)](#) (in module *fermipy.utils*), 89

## X

[x](#) (*fermipy.castro.Interpolator* attribute), 105  
[x\\_edges\(\)](#) (*fermipy.castro.CastroData* method), 102  
[x\\_edges\(\)](#) (*fermipy.castro.CastroData\_Base* method), 105  
[xmax](#) (*fermipy.castro.Interpolator* attribute), 105  
[xmin](#) (*fermipy.castro.Interpolator* attribute), 105  
[xmlpath\\_to\\_path\(\)](#) (in module *fermipy.utils*), 89  
[xypix\\_to\\_ipix\(\)](#) (*fermipy.skymap.Map* method), 99  
[xyz\\_to\\_lonlat\(\)](#) (in module *fermipy.utils*), 89

## Y

[y](#) (*fermipy.castro.Interpolator* attribute), 105

## Z

[zero\\_source\(\)](#) (*fermipy.gtanalysis.GTAnalysis* method), 75  
[zoom\(\)](#) (*fermipy.plotting.ROIPlotter* method), 91